

```

-- Viveka Agrawal
-- 1. SQL DDL statements --
CREATE SCHEMA IF NOT EXISTS zot_pets;
CREATE SCHEMA
SET search_path TO zot_pets;
SET
-- Use CASCADE to automatically drop dependent views and objects
DROP TABLE IF EXISTS "appointment_service" CASCADE;
DROP TABLE
DROP TABLE IF EXISTS "purchase" CASCADE;
DROP TABLE
DROP TABLE IF EXISTS "appointment" CASCADE;
DROP TABLE
DROP TABLE IF EXISTS "pet" CASCADE;
DROP TABLE
DROP TABLE IF EXISTS "service" CASCADE;
DROP TABLE
DROP TABLE IF EXISTS "product" CASCADE;
DROP TABLE
DROP TABLE IF EXISTS "groomer" CASCADE;
DROP TABLE
DROP TABLE IF EXISTS "pet_owner" CASCADE;
DROP TABLE
DROP TABLE IF EXISTS "user" CASCADE;
DROP TABLE
DROP TYPE IF EXISTS service_type_enum;
DROP TYPE
CREATE TYPE service_type_enum AS ENUM ('Bath', 'Haircut', 'Nail
Trim');
CREATE TYPE
CREATE TABLE "user" (
"user_id" SERIAL PRIMARY KEY,
"name" VARCHAR(255) NOT NULL,
"email" VARCHAR(255) NOT NULL UNIQUE,
"street" VARCHAR(255),
"city" VARCHAR(100),
"state" VARCHAR(100),
"join_date" DATE NOT NULL DEFAULT CURRENT_DATE
);
CREATE TABLE
CREATE TABLE "pet_owner" (
"user_id" INT PRIMARY KEY,
"payment_info" VARCHAR(255),
CONSTRAINT "fk_pet_owner_user"
FOREIGN KEY("user_id")
REFERENCES "user"("user_id")
ON DELETE CASCADE
);
CREATE TABLE
CREATE TABLE "groomer" (

```

```

"user_id" INT PRIMARY KEY,
"bio" TEXT,
"certification" VARCHAR(255),
"rating" NUMERIC(3, 2) CHECK ("rating" >= 0 AND "rating" <= 5),
CONSTRAINT "fk_groomer_user"
FOREIGN KEY("user_id")
REFERENCES "user"("user_id")
ON DELETE CASCADE
);
CREATE TABLE
CREATE TABLE "pet" (
"owner_id" INT NOT NULL,
"pet_id" SERIAL NOT NULL,
"name" VARCHAR(255) NOT NULL,
"species" VARCHAR(100),
"breed" VARCHAR(100),
"dob" DATE,
"notes" TEXT,
"photo_urls" VARCHAR(2048),
PRIMARY KEY ("owner_id", "pet_id"),
CONSTRAINT "fk_pet_owner"
FOREIGN KEY("owner_id")
REFERENCES "pet_owner"("user_id")
ON DELETE CASCADE
);
CREATE TABLE
CREATE TABLE "service" (
"groomer_id" INT NOT NULL,
"service_id" SERIAL NOT NULL,
"service_type" service_type_enum NOT NULL,
"description" TEXT,
"price" NUMERIC(10, 2) NOT NULL CHECK ("price" >= 0),
PRIMARY KEY ("groomer_id", "service_id"),
CONSTRAINT "fk_service_groomer"
FOREIGN KEY("groomer_id")
REFERENCES "groomer"("user_id")
ON DELETE CASCADE
);
CREATE TABLE
CREATE TABLE "product" (
"product_id" SERIAL PRIMARY KEY,
"name" VARCHAR(255) NOT NULL,
"price" NUMERIC(10, 2) NOT NULL CHECK ("price" >= 0)
);
CREATE TABLE
CREATE TABLE "appointment" (
"appointment_id" SERIAL PRIMARY KEY,
"pet_owner_id" INT NOT NULL,
"pet_id" INT NOT NULL,
"appointment_datetime" TIMESTAMP WITH TIME ZONE NOT NULL,

```

```

CONSTRAINT "fk_appointment_pet"
FOREIGN KEY("pet_owner_id", "pet_id")
REFERENCES "pet"("owner_id", "pet_id")
ON DELETE CASCADE
);
CREATE TABLE
CREATE TABLE "appointment_service" (
"appointment_id" INT NOT NULL,
"service_groomer_id" INT NOT NULL,
"service_id" INT NOT NULL,
PRIMARY KEY ("appointment_id", "service_groomer_id", "service_id"),
CONSTRAINT "fk_appointment"
FOREIGN KEY("appointment_id")
REFERENCES "appointment"("appointment_id")
ON DELETE CASCADE,
CONSTRAINT "fk_service"
FOREIGN KEY("service_groomer_id", "service_id")
REFERENCES "service"("groomer_id", "service_id")
ON DELETE CASCADE
);
CREATE TABLE
CREATE TABLE "purchase" (
"purchase_id" SERIAL PRIMARY KEY,
"pet_owner_id" INT NOT NULL,
"product_id" INT NOT NULL,
"groomer_id" INT NOT NULL,
"purchase_date" DATE NOT NULL DEFAULT CURRENT_DATE,
CONSTRAINT "fk_purchase_owner"
FOREIGN KEY("pet_owner_id")
REFERENCES "pet_owner"("user_id")
ON DELETE CASCADE,
CONSTRAINT "fk_purchase_product"
FOREIGN KEY("product_id")
REFERENCES "product"("product_id")
ON DELETE RESTRICT,
CONSTRAINT "fk_purchase_groomer"
FOREIGN KEY("groomer_id")
REFERENCES "groomer"("user_id")
ON DELETE SET NULL
);
CREATE TABLE
-- Pets table field design observations
/*

```

owner_id: This value is INT since it is a number assigned to the owner of a pet. It must be included as it can't be NULL.

pet_id: This value is SERIAL, which is an auto-number which makes each pet unique. This works with owner_id

to make sure there are no duplicate pets. It must be included as it can't be NULL.

name: This value is VARCHAR(255). Its a text field for a pet's name. It can store up to 255 characters for long names. It must be included as it can't be NULL.

species: This value is VARCHAR(100). It specifies an animal type like a dog or a cat. It can be an optional field since the species of a pet may be unknown.

breed: This value is VARCHAR(100). It specifies the breed information of a pet. It can be an optional field since the breed of a pet may be unknown.

notes: This value is TEXT to provide extra information about the pet in words. It can be an optional field used to write special facts about a pet.

dob: This value is DATE to store the birth date of a pet. It can be an optional field since some pets have unknown birthdays.

photo_urls: This value is VARCHAR(2048) as it stores multiple photo URLs. It has space for several URLs but can run out of space for pets that have many photos.

*/

-- 2. Data Loading (COPY commands) --

```
\copy zot_pets.user(user_id, name, email, street, city, state,
join_date) FROM '/Users/viv/Downloads/ZotPetsData/user.csv' WITH
(FORMAT csv, HEADER true);
```

COPY 150

```
\copy zot_pets.pet_owner(user_id, payment_info) FROM '/Users/viv/
Downloads/ZotPetsData/pet_owner.csv' WITH (FORMAT csv, HEADER true);
```

COPY 143

```
\copy zot_pets.groomer(user_id, bio, certification, rating) FROM '/
Users/viv/Downloads/ZotPetsData/groomer.csv' WITH (FORMAT csv, HEADER
true);
```

COPY 45

```
\copy zot_pets.pet(owner_id, pet_id, name, species, breed, dob, notes,
photo_urls) FROM '/Users/viv/Downloads/ZotPetsData/pet.csv' WITH
(FORMAT csv, HEADER true);
```

COPY 200

```
\copy zot_pets.service(groomer_id, service_id, service_type,
description, price) FROM '/Users/viv/Downloads/ZotPetsData/
service.csv' WITH (FORMAT csv, HEADER true);
```

COPY 250

```
\copy zot_pets.product(product_id, name, price) FROM '/Users/viv/
Downloads/ZotPetsData/product.csv' WITH (FORMAT csv, HEADER true);
```

COPY 8

```
\copy zot_pets.appointment(appointment_id, pet_owner_id, pet_id,
appointment_datetime) FROM '/Users/viv/Downloads/ZotPetsData/
appointment.csv' WITH (FORMAT csv, HEADER true);
```

COPY 400

```
\copy zot_pets.appointment_service(appointment_id, service_groomer_id,
service_id) FROM '/Users/viv/Downloads/ZotPetsData/
appointment_service.csv' WITH (FORMAT csv, HEADER true);
```

COPY 602

```
\copy zot_pets.purchase(purchase_id, pet_owner_id, product_id,
groomer_id, purchase_date) FROM '/Users/viv/Downloads/ZotPetsData/
purchase.csv' WITH (FORMAT csv, HEADER true);
```

COPY 500

-- 3. Query Answers --

-- Problem A --

-- I used subqueries to make sure to only use 1 SELECT statement

```
SELECT (SELECT COUNT(*) FROM zot_pets.user) AS number_of_users,
       (SELECT COUNT(*) FROM zot_pets.pet) AS number_of_pets,
       (SELECT COUNT(*) FROM zot_pets.appointment) AS
```

```
number_of_appointments;
```

```
number_of_users | number_of_pets | number_of_appointments
```

```
-----+-----+-----
```

```
150 | 200 | 400
```

(1 row)

-- Problem B --

-- Since 2 tables are being used, the user's id and groomer's id must be joined

```
SELECT u.name, g.rating
FROM zot_pets.user u, zot_pets.groomer g
WHERE u.user_id = g.user_id
      AND g.rating >= 4.5
ORDER BY g.rating DESC;
```

```
name | rating
```

```
-----+-----
```

```
Connie Wiggins | 4.98
```

```
Tyler Perez | 4.93
```

```
Stephen Cox | 4.91
```

```
Michelle Martinez | 4.87
```

```
Jeffrey Martinez | 4.86
```

```
Sabrina Bryan | 4.78
```

```
Dr. Angela Skinner | 4.77
```

```
Jeffrey Spencer | 4.59
```

```
Mark Collins | 4.52
```

```
Katherine Jacobson | 4.52
```

(10 rows)

-- Problem C --

-- In order to get the address, I combined street, city, and state as one entity

```

SELECT u.user_id, u.email, (u.street, u.city, u.state) AS address
FROM zot_pets.user u
JOIN zot_pets.groomer g ON u.user_id = g.user_id
JOIN zot_pets.pet_owner po ON u.user_id = po.user_id
WHERE u.email LIKE '%@example.com';

```

user_id	email	address
26	ycarter@example.com	("96307 Stacy Plaza Apt. 273", "Port Barbara", OR)
29	shelbyhardy@example.com	("9152 Moore Crest", "Lake Joshuabury", TX)
56	tammy60@example.com	("594 Vargas Fall Apt. 393", "East Bradleyside", NM)
90	wardkatie@example.com	("3737 Lara Courts Suite 318", "Montgomeryfurt", CT)
93	phillipsfaith@example.com	("3825 Ellis Estate Apt. 839", "Jerryville", CO)
104	bmorrison@example.com	("993 Reynolds Loaf", "Kelleyfurt", ME)
111	andrew06@example.com	("3362 Matthew Meadow", "East Jacqueline", IN)
112	kentdarren@example.com	("0216 Hall Loop Suite 944", "Josephberg", AS)
124	hernandezjennifer@example.com	("50709 Kelly Forge", "Port Carolyn", TX)
133	carsonbenjamin@example.com	("092 Lance Tunnel Apt. 858", "Linside", NH)
135	wreyes@example.com	("3277 Tara Stream Apt. 597", "Martinezton", PW)

(11 rows)

-- Problem D --

-- I separated the date and time from the timestamp in order to get the individual values

```

SELECT a.appointment_id, a.appointment_datetime::date AS date,
a.appointment_datetime::time AS time, s.service_type
FROM zot_pets.appointment a, zot_pets.appointment_service aps,
zot_pets.service s

```

```

WHERE a.appointment_id = aps.appointment_id
AND aps.service_id = s.service_id
AND aps.service_groomer_id = s.groomer_id
AND a.pet_id = 5

```

```

ORDER BY a.appointment_datetime ASC;

```

appointment_id	date	time	service_type
94	2024-09-13	17:29:57	Haircut
94	2024-09-13	17:29:57	Nail Trim
179	2025-08-03	12:20:04	Nail Trim

179		2025-08-03		12:20:04		Haircut
179		2025-08-03		12:20:04		Haircut

(5 rows)

-- Problem E --

-- I used GROUP BY to get the number of baths, haircuts, and nail trims separately

```
SELECT service_type, COUNT(*) AS total_times_service_performed
FROM zot_pets.service
WHERE groomer_id = 11
GROUP BY service_type
ORDER BY service_type;
```

service_type	total_times_service_performed
Bath	2
Haircut	1
Nail Trim	2

(3 rows)

-- Problem F --

-- I used the JOIN statements to get from user to pet_owner to pet to access pet information

-- I used HAVING COUNT(DISTINCT) to count the number of unique species

```
SELECT u.name, u.email
FROM zot_pets.user u
JOIN zot_pets.pet_owner po ON u.user_id = po.user_id
JOIN zot_pets.pet p ON po.user_id = p.owner_id
GROUP BY u.user_id, u.name, u.email
HAVING COUNT(DISTINCT p.species) >= 3;
```

name	email
Candice Gonzales	annahorn@example.com
Heidi Ryan	annemoore@example.org
Matthew Chambers	elizabeth81@example.net
Morgan Ramos	griffithglenda@example.org
Michael Lopez	john43@example.net
Brenda Good	john70@example.net
John Baker	karen21@example.net
Jeffrey Ross	lindahernandez@example.org
Steven Ford	mike66@example.net
Darren Boone	scottmichael@example.org
Tammy Parker	tmoore@example.net

(11 rows)

-- Problem G --

-- I used the BOOL_OR() function to make sure baths and haircuts are included but not nail trims

-- I used GROUP BY groomer id to make sure the services provided by each groomer are together in the output

```
SELECT g.user_id, u.email
```

```

FROM zot_pets.groomer g, zot_pets.user u, zot_pets.service s,
zot_pets.appointment_service aps
WHERE g.user_id = u.user_id
      AND g.user_id = s.groomer_id
      AND s.groomer_id = aps.service_groomer_id
      AND s.service_id = aps.service_id
GROUP BY g.user_id, u.email
HAVING BOOL_OR(s.service_type = 'Bath')
      AND BOOL_OR(s.service_type = 'Haircut')
      AND NOT BOOL_OR(s.service_type = 'Nail Trim')
ORDER BY g.user_id ASC;
  user_id |          email
-----+-----
      68 | torressusan@example.org
      89 | bknight@example.net
     109 | john70@example.net
     134 | callahannatalie@example.org
(4 rows)

```

-- Problem H --

-- I made sure to filter out NULL values and empty photo_urls so that they do not count as part of the count

-- I used LIMIT to return only the pets with most photos

```

SELECT pet_id AS "PetID", name AS "Name",
array_length(string_to_array(photo_urls, ','), 1) AS num_photos
FROM zot_pets.pet
WHERE photo_urls IS NOT NULL
      AND photo_urls != ''
ORDER BY num_photos DESC
LIMIT 10;

```

PetID	Name	num_photos
1	Erin	3
1	Catherine	3
1	Jason	3
1	Shawn	3
1	Cheryl	3
1	Patricia	3
1	Amber	3
1	Gregory	3
1	Lori	3
1	Jason	3

(10 rows)

-- Problem I --

-- This part calculates the annual product spending per customer from purchases

-- I used EXTRACT(YEAR FROM) to find the year from the purchase date

```

WITH product_spending AS (
  SELECT EXTRACT(YEAR FROM p.purchase_date) AS year, p.pet_owner_id

```



```

AS user_id, SUM(pd.price) AS total_product_spending
  FROM zot_pets.purchase p, zot_pets.product pd
  WHERE p.product_id = pd.product_id
  GROUP BY year, p.pet_owner_id
),
-- This part calculates the annual service spending per customer from
appointments
-- I used EXTRACT(YEAR FROM) to find the year from the appointment
timestamp
appointment_spending AS (
  SELECT EXTRACT(YEAR FROM a.appointment_datetime) AS year,
a.pet_owner_id, SUM(s.price) AS total_service_spending
  FROM zot_pets.appointment a, zot_pets.appointment_service appts,
zot_pets.service s
  WHERE a.appointment_id = appts.appointment_id
  AND appts.service_id = s.service_id
  AND appts.service_groomer_id = s.groomer_id
  GROUP BY year, a.pet_owner_id
),
-- This part combines product and service spending
-- I used UNION ALL to get all the spending records and then group
them together
-- I used MAX and SUM to combine the product and service spending for
each customer
combined_prod_serve_spend AS (
  SELECT
    user_id AS pet_owner_id, year,
      MAX(total_service_spending) AS total_service_spending,
      MAX(total_product_spending) AS total_product_spending,
      MAX(total_service_spending) + MAX(total_product_spending) AS
total_spending
  FROM (
    -- Service spending records
    SELECT pet_owner_id AS user_id, year, 0 AS
total_product_spending, total_service_spending
    FROM appointment_spending
    UNION ALL
    -- Product spending records
    SELECT user_id, year, total_product_spending, 0 AS
total_service_spending
    FROM product_spending
  )
  GROUP BY user_id, year
),
-- This part calculates the previous year's spending for comparison
-- I used self-joins on the combined table to find spending from the
previous year
-- I used COALESCE to handle cases where no previous year data exists
combined_with_previous AS (
  SELECT

```

```

        current_year.pet_owner_id,
        current_year.year,
            current_year.total_service_spending,
        current_year.total_product_spending,
        current_year.total_spending,
        COALESCE(previous_year.total_spending, 0) AS
previous_year_spending
    FROM combined_prod_serve_spend current_year
    LEFT JOIN combined_prod_serve_spend previous_year
        ON current_year.pet_owner_id = previous_year.pet_owner_id
        AND current_year.year = previous_year.year + 1
),
-- This part ranks customers by total spending within each year
-- I used ROW_NUMBER() to assign rank 1 to the highest spender each
year
customer_rankings AS (
    SELECT
        spending.year,
        customer.user_id,
        customer.name,
        customer.email,
        spending.total_product_spending,
        spending.total_service_spending,
        spending.total_spending,
        spending.previous_year_spending,
        ROW_NUMBER() OVER (PARTITION BY spending.year ORDER BY
spending.total_spending DESC) AS ranking
    FROM combined_with_previous spending, zot_pets.user customer
    WHERE spending.pet_owner_id = customer.user_id
)
-- This part shows the final result (finding the top customer where
rank = 1 for each year)
SELECT
    year,
    user_id,
    name,
    email,
        total_service_spending,
    total_product_spending,
    total_spending,
    previous_year_spending
FROM customer_rankings
WHERE ranking = 1
ORDER BY year;
    year | user_id |      name      |          email          |
total_service_spending | total_product_spending | total_spending |
previous_year_spending
-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+

```

2023	127	Joseph Li	gcardenas@example.org
546.57	56.73	603.30	
0			
2024	8	William Flores	alicia18@example.com
1121.60	190.67	1312.27	
75.85			
2025	134	Mark Collins	callahannatalie@example.org
1498.62	0	1498.62	
319.07			

(3 rows)

```
-- Problem J --
-- I created the view to calculate lifetime value
CREATE VIEW PetOwnerLTV AS
SELECT user_id, SUM(spending) AS calculated_ltv
FROM (
    -- This part calculates the service spending, which is the sum of
    all service prices from appointments
    SELECT a.pet_owner_id AS user_id, s.price AS spending
    FROM zot_pets.appointment a, zot_pets.appointment_service aps,
    zot_pets.service s
    WHERE a.appointment_id = aps.appointment_id
    AND aps.service_groomer_id = s.groomer_id
    AND aps.service_id = s.service_id
    UNION ALL
    -- This part calculates the product spending, which is the sum of
    all product prices from purchases
    SELECT p.pet_owner_id AS user_id, pr.price AS spending
    FROM zot_pets.purchase p, zot_pets.product pr
    WHERE p.product_id = pr.product_id
)
GROUP BY user_id;
CREATE VIEW
    -- Table alteration DDL:
    -- This part adds the new column
ALTER TABLE zot_pets.pet_owner
ADD COLUMN lifetime_value NUMERIC(10, 2) NOT NULL DEFAULT 0.00;
ALTER TABLE

    -- Table update query:
    -- This part updates the new column with values from the view
    -- I used COALESCE to handle the cases where pet owners have no
    spending history
    -- and set those cases to 0.00 to satisfy the NOT NULL constraint
UPDATE zot_pets.pet_owner po
SET lifetime_value = COALESCE(
    (
        SELECT calculated_ltv
        FROM PetOwnerLTV ltv
        WHERE ltv.user_id = po.user_id
```

```

    ),
    0.00
);
UPDATE 143

```

-- Change verification query:

-- This part checks whether the lifetime_value column correctly stores
 PetOwnerLTV view calculations
 -- I used WHERE conditions to connect pet_owner, user, and PetOwnerLTV
 view

-- This orders by the highest LTV to make sure that the top spenders
 are correctly materialized

```

SELECT po.user_id, u.name, po.lifetime_value AS materialized_ltv,
       ltv.calculated_ltv AS view_ltv
FROM zot_pets.pet_owner po, zot_pets.user u, PetOwnerLTV ltv
WHERE po.user_id = u.user_id
      AND po.user_id = ltv.user_id
ORDER BY po.lifetime_value DESC
LIMIT 10;

```

user_id	name	materialized_ltv	view_ltv
100	Steven Ford	1997.32	1997.32
134	Mark Collins	1841.75	1841.75
127	Joseph Li	1837.60	1837.60
40	Nicole Dean	1820.15	1820.15
139	James Black	1805.25	1805.25
28	Morgan Ramos	1700.62	1700.62
34	Tammy Parker	1681.73	1681.73
109	Brenda Good	1639.20	1639.20
150	Candice Gonzales	1571.36	1571.36
8	William Flores	1509.28	1509.28

(10 rows)