```
1  //Example of No-argument Constructor
2
3  /*
4  A constructor in Java is a special method that is used to initialize
5  objects. The constructor is called when an object of a class is created.
6  It can be used to set initial values for object attributes.
7  At the time of calling the constructor, memory for the object is allocated
8  in the memory. Every time an object is created using the new() keyword,
9  at least one constructor is called. It calls a default constructor if
10 there is no constructor of any type available in the class. In such case,
11 Java compiler provides a default constructor by default.
12  */
13
14 /*
15 There are few rules defined for the constructor:
16    Constructor name must be the same as its class name,
17    A Constructor must have no explicit return type, not void even,
18    A Java constructor cannot be abstract, static, final, and synchronized.
19  */
20
21 /*
22 We can use access modifiers while declaring a constructor. It controls
23 the object creation. In other words, we can have private, protected,
24 public or default constructor in Java.
25  */
26
27 /*
28 Java allows two types of constructors namely:
29    No argument Constructors
30    Parameterized Constructors
31  */
32
33 /*
34 Following is the syntax of a no argument constructor:
35 class ClassName
36 {
37   accessModifier ClassName()
38    {
39    }
40 }
41  */
42
43 class Test
44 {
```

```
45      int num;
46
47      Test() //No-argument Constructor
48      {
49          num=8;
50      }
51      void disp()
52      {
53          System.out.println(num);
54      }
55  }
56
57  public class Main {
58      public static void main(String[] args) {
59
60          //Calling no-argument constructor Test() by object creation
61          Test obj=new Test();
62
63          /*
64          if we split the statement written on line 61, as:
65          Test obj;
66          obj=new Test();
67          line 66 will invoke default or no-argument constructor
68           */
69
70          obj.disp();
71      }
72  }
```