JSX

JSX (JavaScript XML) is a syntax extension for JavaScript used with React. It allows writing HTML-like code inside JavaScript. JSX makes it easier to write UI elements. Example: const element = Hello, World!; ReactDOM.render(element, document.getElementById('root'));

Babel

Babel is a JavaScript compiler that converts modern ES6+ code and JSX into plain JavaScript compatible with older browsers. For example, JSX is converted into React.createElement calls.

ES6 vs CommonJS (CJS)

ES6 uses `import` and `export`, while CommonJS uses `require` and `module.exports`. Example ES6: export const add = (a,b) => a+b; import { add } from './math.js'; Example CJS: module.exports.add = (a,b) => a+b; const { add } = require('./math.js');

Custom Styling

React allows inline styling, CSS modules, and styled-components. Example Inline Styling: function App() { const style = { color: 'blue', fontSize: '20px' }; return Styled Text; }

Date and Time Creation

In JavaScript: const now = new Date(); console.log(now.toString()); console.log(now.toLocaleDateString()); console.log(now.toLocaleTimeString());

Different Import/Export Methods

1. Named Export: export const val = 10; import { val } from './file'; 2. Default Export: export default function(){}; import myFunc from './file'; 3. Import all: import * as utils from './file';

React DevTools

React Developer Tools is a browser extension that lets you inspect React components, props, and state. It shows the component tree and helps debug applications.

Declarative vs Imperative

Declarative: Focuses on 'what' should happen. React is declarative. Imperative: Focuses on 'how' things happen step by step. Example Declarative: const items = [1,2,3]; return {items.map(i => {i})}; Example Imperative: const list = document.createElement('ul'); items.forEach(i => { const li = document.createElement('li'); li.textContent=i; list.appendChild(li); });

Array and Object Destructuring

Array Destructuring: const [a,b] = [1,2]; Object Destructuring: const {name, age} = {name:'John', age:25};

Event and Conditional Rendering

Events: alert('Clicked!')}>Click Conditional Rendering: {isLoggedIn ? Welcome : Please Login}

Spread Operator

Spread is used to expand arrays or objects. Example: const arr = [1,2,3]; const newArr = [...arr, 4,5]; const obj = {a:1, b:2}; const newObj = {...obj, c:3};

Component Tree

A component tree is a hierarchy that shows how React components are structured and related. It starts from the root App component and expands into child components.

react props practice :: https://github.com/vivekanand04/react_props_practice

map,filter, reduce: https://github.com/vivekanand04/javacript_es6_map_filter_reduc
js arrow function:: https://github.com/vivekanand04/javascript_ES6_arrow_functions
react form : https://github.com/vivekanand04/react_f
changing complex:https://github.com/vivekanand04/changing_comple