vivek choursiya

202501080104

INPUT:

```
import numpy as np

start = int(input("Enter start: "))
stop = int(input("Enter stop: "))
step = int(input("Enter step: "))

a = np.arange(start, stop, step)

print(a)
```

OUTPUT:

```
Edit Shell Debug Options Window Help
Python 3.14.3 (tags/v3.14.3:323c59a, Feb  3 20
26, 16:04:56) [MSC v.1944 64 bit (AMD64)] on w
in32
Enter "help" below or click "Help" above for m
ore information.

==================== RESTART: C:/Users/mk/Docum
ents/eds,py.py ====================
Enter start: 3
Enter stop: 10
Enter step: 2
[3 5 7 9]
```

INPUT:

```python
import numpy as np

def array_operations(A, B):

    A = np.array(A)
    B = np.array(B)

    # Arithmetic Operations
    sum_result = A + B
    diff_result = A - B
    prod_result = A * B

    # Statistical Operations
    mean_A = np.mean(A)
    median_A = np.median(A)
    std_dev_A = np.std(A)

    # Bitwise Operations
    and_result = A & B
    or_result = A | B
    xor_result = A ^ B

    # Print results
```


```python
    # Print results
```


```python
    print("Sum:", sum_result)
    print("Difference:", diff_result)
    print("Product:", prod_result)
    print("Mean of A:", mean_A)
    print("Median of A:", median_A)
    print("Standard Deviation of A:", std_dev_A)
    print("Bitwise AND:", and_result)
    print("Bitwise OR:", or_result)
    print("Bitwise XOR:", xor_result)


# Example input
A = [1, 2, 3]
B = [4, 5, 6]

array_operations(A, B)
```

OUTPUT:

```
== RESTART: C:/Users/mk/Documents/eds,py.py ==
Sum: [5 7 9]
Difference: [-3 -3 -3]
Product: [ 4 10 18]
Mean of A: 2.0
Median of A: 2.0
Standard Deviation of A: 0.816496580927726
Bitwise AND: [0 0 2]
Bitwise OR: [5 7 7]
Bitwise XOR: [5 7 5]
```

INPUT:

```
import numpy as np


inputlist = list(map(int, input().split(" ")))


original_array = np.array(inputlist)

# Create a view
view_array = original_array.view()

# Create a copy
copy_array = original_array.copy()

# Modify the view
view_array[0] = 99
print("Original array after modifying view:", original_array)
print("View array:", view_array)

# Modify the copy
copy_array[1] = 88
print("Original array after modifying copy:", original_array)
print("Copy array:", copy_array)
```

OUTPUT:

```
e  Edit  Shell  Debug  Options  Window  Help
Python 3.14.3 (tags/v3.14.3:323c59a, Feb  3 2026, 16:04:56) [
MSC v.1944 64 bit (AMD64)] on win32
Enter "help" below or click "Help" above for more information
.
>
==================== RESTART: C:/Users/mk/Documents/eds,py.py
====================
1 2 3 4
Original array after modifying view: [99  2  3  4]
View array: [99  2  3  4]
Original array after modifying copy: [99  2  3  4]
Copy array: [ 1 88  3  4]
>
```

INPUT:

```python
import numpy as np

# Input array from the user
array1 = np.array(list(map(int, input().split())))

# Searching
search_value = int(input("Value to search: "))
count_value = int(input("Value to count: "))
broadcast_value = int(input("Value to add: "))

# Find indices where value matches in array1
a = np.where(array1 == search_value)[0]
print(a)

# Count occurrences in array1
b = np.count_nonzero(array1 == count_value)
print(b)

# Broadcasting addition
c = array1 + broadcast_value
print(c)

# Sort the array
d = np.sort(array1)
print(d)
```

OUTPUT:

```
e  Edit  Shell  Debug  Options  Window  Help
   Python 3.14.3 (tags/v3.14.3:323c59a, Feb  3 2026, 16:04:56) [
   MSC v.1944 64 bit (AMD64)] on win32
   Enter "help" below or click "Help" above for more information
   .
>>
   ==================== RESTART: C:/Users/mk/Documents/eds,py.py
   ====================
   1 2 3 2 4 2
.. 2
.. 2
.. 5
   Value to search: Value to count: Value to add: [1 3 5]
   3
   [6 7 8 7 9 7]
   [1 2 2 2 3 4]
>>
```