```python
data = {}
print("Empty dictionary:", data)
#Ask how many items to add
n = int(input("How many items do you want to add? "))
# Add key-value pairs
for i in range(n):
    key = input("Enter key: ")
    value = input("Enter value: ")
    data[key] = value
    print("Dictionary after adding items:", data)
# Update a key's value
update_key = input("Enter key to update: ")
if update_key in data:
    new_value = input("Enter new value: ")
    data[update_key] = new_value
    print("Value updated")
else:
    print("Key not found")
# Retrieve value using key (normal method)
search_key = input("Enter key to retrieve value: ")
if search_key in data:
    print("Value:", data[search_key])
else:
    print("Key not found")
#Retrieve value using get() I
get_key = input("Enter key to retrieve using get(): ")
value = data.get(get_key)
if value is not None:
    print("Value:", value)
else:
    print("Key not found")
#Delete a key-value pair
```

```
#Delete a key-value pair
delete_key = input("Enter key to delete: ")
if delete_key in data:
    del data[delete_key]
    print("Deleted")
else:
    print("Key not found")
#Display updated dictionary print("Updated dictionary:", data)
```

```
Python 3.11.2 (tags/v3.11.2:878ead1, Feb  7 2023, 16:38:35) [MSC v.1934 64 bit (
AMD64)] on win32
Type "help", "copyright", "credits" or "license()" for more information.

= RESTART: C:/Users/Dell/AppData/Local/Programs/Python/Python311/dictionary.py =
Empty dictionary: {}
How many items do you want to add? 4
Enter key: y
Enter value: 8
Dictionary after adding items: {'y': '8'}
Enter key: j
Enter value: h
Dictionary after adding items: {'y': '8', 'j': 'h'}
Enter key:
```