

Optimisation via Adiabatic Quantum Computing

Vivek Katal

22/01/2020

Introduction

Main Research Question

- What instances characteristics of optimisation problems make them predisposed to being solved on a Quantum Computer?

Background

Quantum Bits (Qubits)

- In normal computation, bits have a *state* which is either 0 or 1. Similarly in qubits, states are either $|0\rangle$ or $|1\rangle$. In Linear Algebra we may represent the states as follows:

Quantum Bits (Qubits)

- In normal computation, bits have a *state* which is either 0 or 1. Similarly in qubits, states are either $|0\rangle$ or $|1\rangle$. In Linear Algebra we may represent the states as follows:

-

$$|0\rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix} \quad \text{and} \quad |1\rangle = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

Quantum Bits (Qubits)

- In normal computation, bits have a *state* which is either 0 or 1. Similarly in qubits, states are either $|0\rangle$ or $|1\rangle$. In Linear Algebra we may represent the states as follows:

-

$$|0\rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix} \quad \text{and} \quad |1\rangle = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- A single qubit may be represented by as follows:

Quantum Bits (Qubits)

- In normal computation, bits have a *state* which is either 0 or 1. Similarly in qubits, states are either $|0\rangle$ or $|1\rangle$. In Linear Algebra we may represent the states as follows:

-

$$|0\rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix} \quad \text{and} \quad |1\rangle = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- A single qubit may be represented by as follows:

-

$$|\psi\rangle = \alpha |0\rangle + \beta |1\rangle \quad \text{where } \alpha, \beta \in \mathbb{C}$$

Quantum Bits (Qubits)

- In normal computation, bits have a *state* which is either 0 or 1. Similarly in qubits, states are either $|0\rangle$ or $|1\rangle$. In Linear Algebra we may represent the states as follows:

-

$$|0\rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix} \quad \text{and} \quad |1\rangle = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- A single qubit may be represented by as follows:

-

$$|\psi\rangle = \alpha |0\rangle + \beta |1\rangle \quad \text{where } \alpha, \beta \in \mathbb{C}$$

- Also, $|\alpha|^2$ and $|\beta|^2$ correspond to the probability associated with measuring either $|0\rangle$ or $|1\rangle$,

Quantum Bits (Qubits)

- The state

$$|+\rangle = \frac{1}{\sqrt{2}} |0\rangle + \frac{1}{\sqrt{2}} |1\rangle$$

Quantum Bits (Qubits)

- The state

$$|+\rangle = \frac{1}{\sqrt{2}} |0\rangle + \frac{1}{\sqrt{2}} |1\rangle$$

- This state corresponds to a 50% chance of being in $|0\rangle$ or $|1\rangle$ as $\alpha^2 = \beta^2 = 0.5$

Extending to More Qubits

- Classically for **2-bit** system we have 4 possible bits 00, 01, 10 and 11.

Extending to More Qubits

- Classically for **2-bit** system we have 4 possible bits 00, 01, 10 and 11.
- In quantum computing these can be specified as the following: $|00\rangle$, $|01\rangle$, $|10\rangle$, $|11\rangle$. Using Linear Algebra the state can be represented by a vector of length $2^2 = 4$. For example:

Extending to More Qubits

- Classically for **2-bit** system we have 4 possible bits 00, 01, 10 and 11.
- In quantum computing these can be specified as the following: $|00\rangle$, $|01\rangle$, $|10\rangle$, $|11\rangle$. Using Linear Algebra the state can be represented by a vector of length $2^2 = 4$. For example:

- $$|00\rangle = \begin{pmatrix} 1 \\ 0 \\ 0 \\ 0 \end{pmatrix} \quad \text{also,} \quad \sum_{x \in \{0,1\}^2} |\alpha_x|^2 = 1$$

Extending to More Qubits

- Classically for **2-bit** system we have 4 possible bits 00, 01, 10 and 11.
- In quantum computing these can be specified as the following: $|00\rangle$, $|01\rangle$, $|10\rangle$, $|11\rangle$. Using Linear Algebra the state can be represented by a vector of length $2^2 = 4$. For example:

- $$|00\rangle = \begin{pmatrix} 1 \\ 0 \\ 0 \\ 0 \end{pmatrix} \quad \text{also, } \sum_{x \in \{0,1\}^2} |\alpha_x|^2 = 1$$

- The state $|\psi\rangle = \frac{1}{2} |00\rangle + \frac{1}{2} |01\rangle + \frac{1}{2} |10\rangle + \frac{1}{2} |11\rangle$ corresponds to an equal likelihood of being any of the basis states.

Extending to More Qubits

- Classically for **2-bit** system we have 4 possible bits 00, 01, 10 and 11.
- In quantum computing these can be specified as the following: $|00\rangle$, $|01\rangle$, $|10\rangle$, $|11\rangle$. Using Linear Algebra the state can be represented by a vector of length $2^2 = 4$. For example:

- $$|00\rangle = \begin{pmatrix} 1 \\ 0 \\ 0 \\ 0 \end{pmatrix} \quad \text{also,} \quad \sum_{x \in \{0,1\}^2} |\alpha_x|^2 = 1$$

- The state $|\psi\rangle = \frac{1}{2} |00\rangle + \frac{1}{2} |01\rangle + \frac{1}{2} |10\rangle + \frac{1}{2} |11\rangle$ corresponds to an equal likelihood of being any of the basis states.
- To extend this framework to n qubits, we must represent that state by a 2^n vector. A shorthand notation has been developed where $|0\rangle^{\otimes 2}$ corresponds to the state $|00\rangle$

Adiabatic Quantum Computing (AQC)

- Adiabatic Quantum Computation is a computational model which relies on the *adiabatic theorem* of quantum mechanics to compute calculations.

Adiabatic Quantum Computing (AQC)

- Adiabatic Quantum Computation is a computational model which relies on the *adiabatic theorem* of quantum mechanics to compute calculations.
- The famous *Schrödinger Equation* is well-known to describe the time evolution of a quantum state:

Adiabatic Quantum Computing (AQC)

- Adiabatic Quantum Computation is a computational model which relies on the *adiabatic theorem* of quantum mechanics to compute calculations.
- The famous *Schrödinger Equation* is well-known to describe the time evolution of a quantum state:

- $$i\hbar \frac{d}{dt} |\psi(t)\rangle = H(t) |\psi(t)\rangle$$

Adiabatic Quantum Computing (AQC)

- Adiabatic Quantum Computation is a computational model which relies on the *adiabatic theorem* of quantum mechanics to compute calculations.
- The famous *Schrödinger Equation* is well-known to describe the time evolution of a quantum state:

- $$i\hbar \frac{d}{dt} |\psi(t)\rangle = H(t) |\psi(t)\rangle$$

- $|\psi(t)\rangle$ is our state vector, $H(t)$ is the time dependent Hamiltonian. A Hamiltonian of an n -qubit system $H(t)$ is given by $2^n \times 2^n$ matrix.


Adiabatic Quantum Computing (AQC)

- An adiabatic computation can be expressed by specifying two Hamiltonians, denoted by H_B and H_P where H_B is our *initial* Hamiltonian and H_P is the *final* or *problem* Hamiltonian.

Adiabatic Quantum Computing (AQC)

- An adiabatic computation can be expressed by specifying two Hamiltonians, denoted by H_B and H_P where H_B is our *initial* Hamiltonian and H_P is the *final* or *problem* Hamiltonian.

-



Adiabatic Quantum Computing (AQC)

- An adiabatic computation can be expressed by specifying two Hamiltonians, denoted by H_B and H_P where H_B is our *initial* Hamiltonian and H_P is the *final* or *problem* Hamiltonian.

-

$$\begin{array}{ccc} H_B & \xrightarrow{\hspace{2cm}} & H_P \\ |\psi_B\rangle & \text{transform } H(t) & |\psi_P\rangle \\ \text{known state} & & \text{unknown} \end{array}$$

- Loosely speaking, the adiabatic theorem tells us that if we vary from H_B to H_P *slowly enough* the system will remain in its ground state. This fact is a direct result of the Adiabatic Theorem.

Adiabatic Quantum Computing (AQC)

- To conduct the computation we evolve $|\psi(t)\rangle$ till time $t = T$ such that $|\psi(t = T)\rangle$ encodes the answer. The computation is done using a Hamiltonian which linearly interpolates between H_B and H_P . Specifically as below:

Adiabatic Quantum Computing (AQC)

- To conduct the computation we evolve $|\psi(t)\rangle$ till time $t = T$ such that $|\psi(t = T)\rangle$ encodes the answer. The computation is done using a Hamiltonian which linearly interpolates between H_B and H_P . Specifically as below:

-

$$H(t) = \left(1 - \frac{t}{T}\right) H_B + \frac{t}{T} H_P$$

Adiabatic Quantum Computing (AQC)

- To conduct the computation we evolve $|\psi(t)\rangle$ till time $t = T$ such that $|\psi(t = T)\rangle$ encodes the answer. The computation is done using a Hamiltonian which linearly interpolates between H_B and H_P . Specifically as below:

-

$$H(t) = \left(1 - \frac{t}{T}\right) H_B + \frac{t}{T} H_P$$

- How fast?

Adiabatic Quantum Computing (AQC)

- To conduct the computation we evolve $|\psi(t)\rangle$ till time $t = T$ such that $|\psi(t = T)\rangle$ encodes the answer. The computation is done using a Hamiltonian which linearly interpolates between H_B and H_P . Specifically as below:

-

$$H(t) = \left(1 - \frac{t}{T}\right) H_B + \frac{t}{T} H_P$$

- How fast?

-

$$T = \frac{1}{\min_t g(t)^2}$$

Adiabatic Quantum Computing (AQC)

- To conduct the computation we evolve $|\psi(t)\rangle$ till time $t = T$ such that $|\psi(t = T)\rangle$ encodes the answer. The computation is done using a Hamiltonian which linearly interpolates between H_B and H_P . Specifically as below:

-

$$H(t) = \left(1 - \frac{t}{T}\right) H_B + \frac{t}{T} H_P$$

- How fast?

-

$$T = \frac{1}{\min_t g(t)^2}$$

- Where $g(t)$ is the difference between the first two smallest eigenvalues of $H(t)$

3SAT (Exact Cover)

- The satisfiability problem, abbreviated SAT, is a classic example of an NP-complete problem [1]

3SAT (Exact Cover)

- The satisfiability problem, abbreviated SAT, is a classic example of an NP-complete problem [1]
- The basic SAT formulation can be described as follows: Given a boolean formula (AND \wedge , OR \vee , NOT \neg) over n variables (z_1, z_2, \dots, z_n) . Can one set z_i 's in a manner such that the Boolean formula is true?

3SAT (Exact Cover)

- The satisfiability problem, abbreviated SAT, is a classic example of an NP-complete problem [1]
- The basic SAT formulation can be described as follows: Given a boolean formula (AND \wedge , OR \vee , NOT \neg) over n variables (z_1, z_2, \dots, z_n) . Can one set z_i 's in a manner such that the Boolean formula is true?
- A clause is an expression which the variables must satisfy. For example $z_1 \wedge z_2 \implies z_1 = z_2 = 1$

3SAT (Exact Cover Example)

- Consider a 3-bit number with two clauses:

3SAT (Exact Cover Example)

- Consider a 3-bit number with two clauses:
 - $z_1 + z_2 = 1$

3SAT (Exact Cover Example)

- Consider a 3-bit number with two clauses:
 - $z_1 + z_2 = 1$
 - $z_1 + z_3 = 1$

3SAT (Exact Cover Example)

- Consider a 3-bit number with two clauses:
 - $z_1 + z_2 = 1$
 - $z_1 + z_3 = 1$
- Here we have 8 possible assignments, namely $\{000, 001, 010, 011, 100, 101, 110, 111\}$

3SAT (Exact Cover Example)

- Consider a 3-bit number with two clauses:
 - $z_1 + z_2 = 1$
 - $z_1 + z_3 = 1$
- Here we have 8 possible assignments, namely $\{000, 001, 010, 011, 100, 101, 110, 111\}$
- However, our **satisfying assignments** are $z_1 = 1, z_2 = 0, z_3 = 0$ or $z_1 = 0, z_2 = 1, z_3 = 1$

3SAT (Exact Cover Example)

- Consider a 3-bit number with two clauses:
 - $z_1 + z_2 = 1$
 - $z_1 + z_3 = 1$
- Here we have 8 possible assignments, namely $\{000, 001, 010, 011, 100, 101, 110, 111\}$
- However, our **satisfying assignments** are $z_1 = 1, z_2 = 0, z_3 = 0$ or $z_1 = 0, z_2 = 1, z_3 = 1$
- The 3-SAT problem in particular is a problem where each clause is comprised of 3 literals.

Mapping 3SAT to AQC

- How do we construct H_B and H_P so that we can solve our optimisation problem?

Mapping 3SAT to AQC (H_B)

- We initialise our system in a state that is easy to prepare:

Mapping 3SAT to AQC (H_B)

- We initialise our system in a state that is easy to prepare:



$$|\psi\rangle = |z_1\rangle |z_2\rangle \dots |z_n\rangle$$

Mapping 3SAT to AQC (H_B)

- We initialise our system in a state that is easy to prepare:

-

$$|\psi\rangle = |z_1\rangle |z_2\rangle \dots |z_n\rangle$$

- We couple a magnetic field in the x -direction to each qubit. Resulting in the following ground state for H_B :

Mapping 3SAT to AQC (H_B)

- We initialise our system in a state that is easy to prepare:

-

$$|\psi\rangle = |z_1\rangle |z_2\rangle \dots |z_n\rangle$$

- We couple a magnetic field in the x -direction to each qubit. Resulting in the following ground state for H_B :

-

$$|\psi_g(T=0)\rangle = \frac{1}{2^{n/2}} \sum_{i=1}^n |z_1\rangle |z_2\rangle \dots |z_n\rangle$$

Mapping 3SAT to AQC (H_B)

- We initialise our system in a state that is easy to prepare:

-

$$|\psi\rangle = |z_1\rangle |z_2\rangle \dots |z_n\rangle$$

- We couple a magnetic field in the x -direction to each qubit. Resulting in the following ground state for H_B :

-

$$|\psi_g(T=0)\rangle = \frac{1}{2^{n/2}} \sum_{i=1}^n |z_1\rangle |z_2\rangle \dots |z_n\rangle$$

- This ground state corresponds to a uniform superposition across all possible qubit assignments.

Mapping 3SAT to AQC (H_B)

- Mathematically speaking, if we wish to apply an x rotation on the 1st qubit. We define the following Hamiltonian:

Mapping 3SAT to AQC (H_B)

- Mathematically speaking, if we wish to apply an x rotation on the 1st qubit. We define the following Hamiltonian:

-

$$H_B^1 = \sigma_1^X = X^{(1)} \otimes I^{(2)} \otimes I^{(3)} \dots \otimes I^{(n)}, \quad X = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}, \quad I = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

Mapping 3SAT to AQC (H_B)

- Mathematically speaking, if we wish to apply an x rotation on the 1st qubit. We define the following Hamiltonian:

-

$$H_B^1 = \sigma_1^X = X^{(1)} \otimes I^{(2)} \otimes I^{(3)} \dots \otimes I^{(n)}, \quad X = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}, \quad I = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

- This Hamiltonian is of dimensions $2^n \times 2^n$

Mapping 3SAT to AQC (H_B)

- Mathematically speaking, if we wish to apply an x rotation on the 1st qubit. We define the following Hamiltonian:

-

$$H_B^1 = \sigma_1^X = X^{(1)} \otimes I^{(2)} \otimes I^{(3)} \dots \otimes I^{(n)}, \quad X = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}, \quad I = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

- This Hamiltonian is of dimensions $2^n \times 2^n$
- Thus, our initial Hamiltonian is given by:

Mapping 3SAT to AQC (H_B)

- Mathematically speaking, if we wish to apply an x rotation on the 1st qubit. We define the following Hamiltonian:

-

$$H_B^1 = \sigma_1^X = X^{(1)} \otimes I^{(2)} \otimes I^{(3)} \dots \otimes I^{(n)}, \quad X = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}, \quad I = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

- This Hamiltonian is of dimensions $2^n \times 2^n$
- Thus, our initial Hamiltonian is given by:
-

$$H_B = \sum_{i=1}^n H_B^i, \quad H_B^i = \frac{1}{2} (1 - \sigma_i^X), \quad \text{where } \dim(H_B) = 2^n \times 2^n$$

Mapping 3SAT to AQC (H_B)

- Mathematically speaking, if we wish to apply an x rotation on the 1st qubit. We define the following Hamiltonian:

-

$$H_B^1 = \sigma_1^X = X^{(1)} \otimes I^{(2)} \otimes I^{(3)} \dots \otimes I^{(n)}, \quad X = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}, \quad I = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

- This Hamiltonian is of dimensions $2^n \times 2^n$
- Thus, our initial Hamiltonian is given by:
-

$$H_B = \sum_{i=1}^n H_B^i, \quad H_B^i = \frac{1}{2} (1 - \sigma_i^X), \quad \text{where } \dim(H_B) = 2^n \times 2^n$$

- Note:* We have applied a normalisation here.

Mapping 3SAT to AQC (H_P)

- Recall, H_P must be constructed such that it encodes the solution. Thus we prepare a Hamiltonian, whose lowest energy state corresponds to a state vector containing our solution.

Mapping 3SAT to AQC (H_P)

- Recall, H_P must be constructed such that it encodes the solution. Thus we prepare a Hamiltonian, whose lowest energy state corresponds to a state vector containing our solution.
- Let's suppose we have a clause C which involves the three bits i_C , j_C and k_C , and we define the following energy function:

Mapping 3SAT to AQC (H_P)

- Recall, H_P must be constructed such that it encodes the solution. Thus we prepare a Hamiltonian, whose lowest energy state corresponds to a state vector containing our solution.
- Let's suppose we have a clause C which involves the three bits i_C , j_C and k_C , and we define the following energy function:

-

$$h_C(z_{i_C}, z_{j_C}, z_{k_C}) = \begin{cases} 0 & \text{if } i_C, j_C, k_C \text{ satisfy } C \\ 1 & \text{if not satisfied} \end{cases}$$

Mapping 3SAT to AQC (H_P)

- Recall, H_P must be constructed such that it encodes the solution. Thus we prepare a Hamiltonian, whose lowest energy state corresponds to a state vector containing our solution.
- Let's suppose we have a clause C which involves the three bits i_C , j_C and k_C , and we define the following energy function:

-

$$h_C(z_{i_C}, z_{j_C}, z_{k_C}) = \begin{cases} 0 & \text{if } i_C, j_C, k_C \text{ satisfy } C \\ 1 & \text{if not satisfied} \end{cases}$$

- Now we let,

Mapping 3SAT to AQC (H_P)

- Recall, H_P must be constructed such that it encodes the solution. Thus we prepare a Hamiltonian, whose lowest energy state corresponds to a state vector containing our solution.
- Let's suppose we have a clause C which involves the three bits i_C , j_C and k_C , and we define the following energy function:

$$h_C(z_{i_C}, z_{j_C}, z_{k_C}) = \begin{cases} 0 & \text{if } i_C, j_C, k_C \text{ satisfy } C \\ 1 & \text{if not satisfied} \end{cases}$$

- Now we let,

$$H_P^C |z_1\rangle \dots |z_n\rangle = h_C(z_{i_C}, z_{j_C}, z_{k_C}) |z_1\rangle \dots |z_n\rangle$$

Mapping 3SAT to AQC (H_P)

- Finally we express our problem Hamiltonian as follows:

Mapping 3SAT to AQC (H_P)

- Finally we express our problem Hamiltonian as follows:

-

$$H_P = \sum_C H_P^C$$

Mapping 3SAT to AQC (H_P)

- Finally we express our problem Hamiltonian as follows:

-

$$H_P = \sum_C H_P^C$$

- We then evolve our system with the following interpolation:

Mapping 3SAT to AQC (H_P)

- Finally we express our problem Hamiltonian as follows:

-

$$H_P = \sum_C H_P^C$$

- We then evolve our system with the following interpolation:

-

$$H(t) = \left(1 - \frac{t}{T}\right) H_B + \frac{t}{T} H_P$$

Mapping 3SAT to AQC (H_P)

- Finally we express our problem Hamiltonian as follows:

-

$$H_P = \sum_C H_P^C$$

- We then evolve our system with the following interpolation:

-

$$H(t) = \left(1 - \frac{t}{T}\right) H_B + \frac{t}{T} H_P$$

- Finally, complete measurement

Proposed Research

- Depending on different structures of instances, classical algorithms may perform differently to Quantum ones.

Proposed Research

- Depending on different structures of instances, classical algorithms may perform differently to Quantum ones.
- We are looking to investigate which types of instances are more pre-disposed to being solved on Quantum Computers:

Proposed Research

- Depending on different structures of instances, classical algorithms may perform differently to Quantum ones.
- We are looking to investigate which types of instances are more pre-disposed to being solved on Quantum Computers:
- To do this we will simulate AQC and measure the “quantum-ness” of each instance:

Proposed Research

- Depending on different structures of instances, classical algorithms may perform differently to Quantum ones.
- We are looking to investigate which types of instances are more pre-disposed to being solved on Quantum Computers:
- To do this we will simulate AQC and measure the “quantum-ness” of each instance:
 1. Minimum Energy Gap g_{\min}

Proposed Research

- Depending on different structures of instances, classical algorithms may perform differently to Quantum ones.
- We are looking to investigate which types of instances are more pre-disposed to being solved on Quantum Computers:
- To do this we will simulate AQC and measure the “quantum-ness” of each instance:
 1. Minimum Energy Gap g_{\min}
 2. Maximum Entropy of Entanglement

Proposed Research

- This will involve large amounts of generating experimental data

Proposed Research

- This will involve large amounts of generating experimental data
- To survey the instances we will deploy the instance space analysis methodology

Proposed Research

- This will involve large amounts of generating experimental data
- To survey the instances we will deploy the instance space analysis methodology
- Ultimately, we can build a prediction model which maps instance features of different 3SAT instances to their inherent “Quantumness”

Proposed Research

- Given that we have access to IBM's Quantum Computer, we may also apply a discretized version of AQC and produce results from a *real quantum computer*

Proposed Research

- Given that we have access to IBM's Quantum Computer, we may also apply a discretized version of AQC and produce results from a *real quantum computer*
- This methodology can then be further extended to other optimisation problems such as Quadratic Unconstrained Binary Optimisation (QUBO)

Proposed Research

- Given that we have access to IBM's Quantum Computer, we may also apply a discretized version of AQC and produce results from a *real quantum computer*
- This methodology can then be further extended to other optimisation problems such as Quadratic Unconstrained Binary Optimisation (QUBO)
- More ideas likely to come. . .

Current Progress

1. Learning Quantum Mechanics and Quantum Computing

Current Progress

1. Learning Quantum Mechanics and Quantum Computing
2. Conducting literature review on current advances in Adiabatic Quantum Computing.

Current Progress

1. Learning Quantum Mechanics and Quantum Computing
2. Conducting literature review on current advances in Adiabatic Quantum Computing.
3. Developed working environment, set up GitHub, scripts, organizational tools enabling an efficient working environment.

Current Progress

4. Developed an architecture to run reproducible experiments at scale

Current Progress

4. Developed an architecture to run reproducible experiments at scale
5. Provisioned all infrastructure required for above on Melbourne Research Cloud and SPARTAN

Current Progress

4. Developed an architecture to run reproducible experiments at scale
5. Provisioned all infrastructure required for above on Melbourne Research Cloud and SPARTAN
6. Developed a working implementation of Adiabatic Quantum Computing on different instances of 3SAT.

Next Steps (till Confirmation)

1. Complete Literature Review of current advances in AQC.

Next Steps (till Confirmation)

1. Complete Literature Review of current advances in AQC.
2. Implement scripts to generate **hard** instances of 3SAT with respect to *instance characteristics*.

Next Steps (till Confirmation)

1. Complete Literature Review of current advances in AQC.
2. Implement scripts to generate **hard** instances of 3SAT with respect to *instance characteristics*.
3. Apply Instance Space Methodology from MATILDA to find decision boundaries for *Entanglement Entropy* and *Minimum Energy Gap*

Next Steps (till Confirmation)

4. Extend implementation to work on QAOA and VQE (discretized version of AQC)

Next Steps (till Confirmation)

4. Extend implementation to work on QAOA and VQE (discretized version of AQC)
5. Learn C++ effectively, this will be required when implementing larger simulations.

Next Steps (till Confirmation)

4. Extend implementation to work on QAOA and VQE (discretized version of AQC)
5. Learn C++ effectively, this will be required when implementing larger simulations.
6. Apply Tensor Network methodology on current simulations

Next Steps (till Confirmation)

4. Extend implementation to work on QAOA and VQE (discretized version of AQC)
5. Learn C++ effectively, this will be required when implementing larger simulations.
6. Apply Tensor Network methodology on current simulations
7. Further advance knowledge of Quantum Physics (possibly through taking a course in Quantum Computing)

Next Steps (till Confirmation)

4. Extend implementation to work on QAOA and VQE (discretized version of AQC)
5. Learn C++ effectively, this will be required when implementing larger simulations.
6. Apply Tensor Network methodology on current simulations
7. Further advance knowledge of Quantum Physics (possibly through taking a course in Quantum Computing)
8. Extend research to look at other optimisation problems

About Me

- Vivek Katial (vkatial@student.unimelb.edu.au)
 - PhD Candidate (Optimisation on Quantum Computers)
- Check out the slides at
<https://tinyurl.com/vkatial-preconfirmation>

References

References

1. Cook SA (1971) The complexity of theorem-proving procedures, In, *Proceedings of the third annual acm symposium on theory of computing*, ACM, 151–158.