

- **Get-RegistryKey:** Retrieves value names and value data for a specified registry key or optionally, a specific value.

Eg: Get-RegistryKey -Key

'HKLM:\SOFTWARE\Microsoft\Windows\CurrentVersion\Uninstall\{1AD147D0-BE0E-3D6C-AC11-64F6DC4163F1}'

Get-RegistryKey -Key 'HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\iexplore.exe'

- **Set-IniValue:** Opens an INI file and sets the value of the specified section and key.

Eg: Set-IniValue -FilePath "\$env:ProgramFilesX86\IBM\Notes\notes.ini" -Section 'Notes' -Key 'KeyFileName' -Value 'MyFile.ID'

- **Show-InstallationProgress:** Displays a progress dialog in a separate thread with an updateable custom message.

Eg: Show-InstallationProgress

Show-InstallationProgress -StatusMessage 'Installation in Progress...'

Registry keys: To create, delete, modify registry entries in Windows you'll use the Registry Editor

In order to perform some operations in the registries like creating, modifying and deleting you can use different commands for each of the following:

Create New Key:

New-Item -Path "HKLM:\Software\MyCompany" -Type Directory -ErrorAction SilentlyContinue.

Delete a key:

Remove-Item -Path "HKLM:\Software\MyCompany" -Recurse -Force -ErrorAction SilentlyContinue

Set a Registry Value:

Set-ItemProperty -Path "HKLM:\Software\MyCompany\MyKey" -Name "MyValue" -Value "MyData"

Stop a Service:

Stop-Service -Name "YourServiceName"

Start with Dependencies:

Start-ServiceAndDependencies -Name "YourServiceName"

Stop with Dependencies:

Stop-ADTServiceAndDependencies -Name "YourServiceName"

To force stop any service:

Stop-Service -Name "YourServiceName" -Force

Syntax for Start-ServiceAndDependencies:

Start-ServiceAndDependencies [-Name]<String> [[-ComputerName]<String>] [-SkipServiceExistsTest] [-SkipDependentServices][[-PendingStatusWait] <Timespan>] [-PassThru][[-ContinueOnError]<Boolean>][<CommonParameters>]

When deploying the application through PSADT you need to structure your toolkit file in a specific order.

The steps are as follows:

Proper Structure of files where Files contain the installed files and supportFiles are for additional files for your deployment

1. Deployapplication.exe is going to run .ps1 file eg: googlechrome.msi
2. Check .ps1 and edit the steps before actual installation starts
3. Deploy-Application.ps1 is where you spend most of your time
4. In this file you will find variables declared.
5. You can fill out this variable declared section by entering the installed package details.
6. Scrolling down you will see pre-installation comment. Below that comment you need to enter some commands for any installation of the msi package

After downloading chrome

1. Go to deploy-Application.ps1 and fill out the variables.
2. Go to installation section below the 'Perform installation' comment we write the following command:
Execute-MSI -Action 'Install' -Path 'googlechromestandaloneenterprise64.msi'
3. For uninstallation below it comments:
Remove-MSIApplications -Name "Google Chrome"

Testing

1. You can check the installing and uninstalling commands using the PSEXec

2. To start PSEXec you can use the following command:
PsExec.exe -s cmd.exe
3. For installation: .\Deploy-Application.exe Install
4. For uninstallation: .\Deploy-Application.exe Uninstall

Uploading it to Intune:

1. Wrap Deploy-Application.exe with Win32 content prep tool
2. Install command: Deploy-Application.exe Install
3. Uninstall command: Deploy-Application.exe Uninstall

To check the product code of the MSI File Go to:

HKLM\Software\Microsoft\Windows\CurrentVersion\Uninstall