

In PSAppDeployToolit, Execute-MSI is a function used for installing, uninstalling, patching, repairing, or performing active setup on MSI and MSP files, or using MSI product codes.

In the PowerShell App Deployment Toolkit (PSAppDeployToolkit), the main commands for installation and uninstallation are Execute-MSI and Uninstall-ADTApplication respectively.

- **Execute-MSI:** Used to run MSI installers
Eg: Execute-MSI -Action Install -Path "C:\path\to\your.msi" -DeployMode Silent
- **Uninstall-ADTApplication:** It handles uninstalling applications.
Eg: Execute-MSI -Action Uninstall -Path "{GUID of the product}"

For, Installation: /i

Uninstallation: /x

Silent install: /qn

Prevent System restart: /norestart

Verbose logging: /L*v

For installation you can use the following command:

```
Execute-MSI -Action 'Install' -Path 'Adobe_FlashPlayer_11.2.202.233_x64_EN.msi'
```

-Action Install tells it you want to install.

-Path is where your MSI file is.

For Uninstallation you can use the following command:

```
Execute-MSI -Action Uninstall -Path "C:\path\to\app.msi"
```

Optional Features

- **Use Product Code:** Instead of MSI path, you can use the app's product code to uninstall it.
- **Logging:** Add -LogName to control where the log file goes.
- **Skip Checks:** If you do not want to check if the app is already installed, use -SkipMSIAAlreadyInstalledCheck.
- **Error Handling:** If you want the script to keep going even if an error happens, add -ContinueOnError.

Some more commands are as follows:

1. Execute-MSI
2. Execute-Process
3. Execute-MSP
4. Install-MSUpdates
5. Copy-File
6. Set-ActiveSetup

1.Execute-MSI:

Command: Execute-MSI -Action 'Install' -Path 'Adobe_FlashPlayer_11.2.202.233_x64_EN.msi'

2. Execute-Process

Command: Execute-Process -Path 'uninstall_flash_player_64bit.exe' -Parameters '/uninstall' -
WindowStyle 'Hidden'

3. Execute-MSP:

Command: Execute-MSP -Path 'Adobe_Reader_11.0.3_EN.msp'

4. Install-MSUpdates:

Command: Install-MSUpdates -Directory "\$dirFiles\MSUpdates"

5. Copy-File:

Command: Copy-File -Path "\$dirSupportFiles\MyApp.in" -Destination "\$envWinDir\MyApp.ini"

6. Set-ActiveSetup

Command: Set-ActiveSetup -StubExePath 'C:\Users\Public\Company\ProgramUserConfig.vbs' -
Arguments '/Silent' -Description 'Program User Config' -Key 'ProgramUserConfig' -Locale 'en'