

Lead → Launch — Setup Guide

Find local-business clients, audit their websites, rank them, generate a site-builder prompt, and draft outreach — in one dashboard.

5 phases: Scrape Google Maps → Audit (Claude) → Rank (Claude) → Build site prompt (Claude) → Outreach (Claude, Hinglish/English + day-3 follow-up).

How it works — the dashboard runs on Claude Code

The dashboard is the UI. The thinking for Phases 2–5 (audit, ranking, website prompt, outreach) runs on Claude Code on your own machine, under your Claude subscription — no API key. When you click a button, the app calls your local `claude` and shows the result.

- Phase 1 (Scrape) — pulls leads from Apify (or the built-in demo data). Does not need Claude Code.
- Phases 2–5 (Audit → Rank → Build → Outreach) — require Claude Code installed and logged in. This is where the real analysis, ranking, website prompt, and outreach copy are generated.

A top-right badge shows "Claude Code connected" (green) or "not found" (red). If it's not found, Phases 2–5 show an "Install Claude Code" panel instead of running.

Same pipeline also runs as a pure chat skill in `.claude/skills/` — open the folder in Claude Code and say "run /lead-to-launch". No browser needed.

1. What you need

Requirement	Needed for	Cost
Node.js 18+	Running the dashboard	Free — nodejs.org (download LTS)
Claude Code (installed + logged in)	Phases 2–5 (audit, rank, build, outreach)	Your Claude subscription — claude.com/claude-code
Apify API token	Live Google Maps scraping (Phase 1) — optional	Free tier — \$5 monthly credit ≈ 500+ leads

Just exploring? Phase 1 works out of the box on a demo dataset (12 dentists in Bandra) with no keys. To actually run the AI phases, you need Claude Code installed and signed in (run `claude` once in a terminal and log in).

2. Install & run

Mac:

- Unzip the folder anywhere (e.g. Desktop).
- Double-click `Launch.command`.
- If macOS blocks it: right-click → Open → Open (one-time).
- Browser opens at `http://localhost:3000` automatically.

Windows:

- Unzip the folder.

- Double-click `Launch.bat` .
- Open `http://localhost:3000` in your browser.

Manual (any OS):

```
cd app
npm install
npm run dev
# open http://localhost:3000
```

First run installs dependencies (1–2 min). To stop: press `Ctrl + C` in the terminal window, or close it.

3. Turn on Claude Code (required for Phases 2–5)

The audit, ranking, website prompt, and outreach are generated by Claude Code running locally under your subscription — no API key.

- Install Claude Code: claude.com/claude-code.
- Open a terminal, run `claude` once, and sign in with your Claude account.
- Start (or restart) the dashboard. The top-right badge should read "Claude Code connected" (green).

If the badge says "not found", Phases 2–5 will show an "Install Claude Code" panel. Phase 1 (scraping) still works without it.

Each AI phase takes ~20–60 seconds (real inference on your machine) and shows a "Claude is working" state while it runs. That's normal.

4. Optional: live Google Maps scraping (Apify)

Without this, Phase 1 uses the built-in demo dataset. To scrape real businesses:

```
cd app
cp .env.local.example .env.local
```

(Windows: copy `.env.local.example` , rename the copy to `.env.local` .)

- Sign up free at apify.com (no card needed).
- Settings → API & Integrations → API tokens → copy your token (`apify_api_...`).
- Paste into `app/.env.local` :

```
APIFY_TOKEN=apify_api_xxxxxxxxxxxx
```

- Leave `APIFY_ACTOR` as is (Google Maps Scraper — no install needed). Restart the server.

Free tier = \$5/month credit ≈ 500–700 leads. A 12–25 lead run costs a few cents.

5. Using the tool

- Phase 1 — Scrape: enter niche ("Salon"), city ("Andheri, Mumbai"), count (12–25). Hit scrape. (Apify or demo data — no Claude needed.)

- Phase 2 — Audit: select leads → "Run audit with Claude". Claude analyzes each business's gaps, biggest opportunity, and estimated lost /month (~30–60s).
- Phase 3 — Rank: "Rank prospects with Claude" — scores each lead 0-100 with a one-line reason. Pick your best prospect.
- Phase 4 — Build: pick a platform → "Generate with Claude" → get a full builder prompt + pitch points. Copy into Lovable / Bolt / Claude Code, get a demo site, deploy free (Vercel/Netlify), copy the link.
- Phase 5 — Outreach: pick channel + Hinglish/English → "Draft with Claude" → a first message + day-3 follow-up. Before sending, replace:
 - `[your-demo-link]` → your deployed demo URL
 - `[Your Name]` → your name

6. Bonus — Claude Code skill

If you use Claude Code, the same pipeline works as a chat skill — no dashboard needed:

```
.claude/skills/lead-to-launch/SKILL.md
```

Open this folder in Claude Code and say "run /lead-to-launch" or just "scrape salons in Indiranagar". Connect the Apify MCP for live scraping inside chat.

First launch: what's normal

- After `npm run dev`, wait for the line `✓ Ready` before opening the browser.
- The first page load compiles the map/chart libraries once — it can take 10–30 seconds (the tab will spin, then the dashboard appears). This is normal; every load after is instant.
- If you opened the browser too early and got "localhost refused to connect", just refresh the tab (`Cmd/Ctrl + Shift + R`) once `✓ Ready` shows. `Launch.command` waits for the server automatically, so use it to avoid this.

Troubleshooting

Problem	Fix
<code>node: command not found</code>	Install Node.js from nodejs.org, restart terminal
Badge says "Claude Code not found" / Phases 2–5 won't run	Install Claude Code (claude.com/claude-code), run <code>claude</code> once in a terminal and sign in, then click Retry
A Claude phase errors with "usage credits" or "log in"	Run <code>claude</code> in a terminal to confirm you're signed in and your plan is active, then retry
Claude phase is slow (20–60s)	Normal — it's running real inference locally. The "Claude is working" state shows while it runs
Browser says "localhost refused to connect"	Server wasn't ready yet — wait for <code>✓ Ready</code> , then refresh. Or open <code>http://127.0.0.1:3000</code>

Problem	Fix
Server starts but every page hangs forever	You have a stray <code>package.json</code> / <code>package-lock.json</code> / <code>node_modules</code> in your home folder (<code>~/</code>). Next then tries to scan your whole home dir. Move them aside: <code>mv ~/package.json ~/package.json.bak</code> (same for <code>package-lock.json</code> and <code>node_modules</code>)
<code>npm run dev</code> hangs with no output at all	The project folder path contains a space and Turbopack stalls. Move the folder to a space-free path (e.g. <code>~/lead-to-launch</code>), or run <code>npm run dev:webpack</code>
Port 3000 busy	Another copy is already running — try <code>http://localhost:3000</code> first. Else <code>PORT=3001 npm run dev</code> (Mac) / <code>set PORT=3001 && npm run dev</code> (Windows)
Mac blocks Launch.command	Right-click → Open → Open. Or run <code>chmod +x Launch.command</code> in Terminal
Scrape returns demo data with token set	Key must be in <code>app/.env.local</code> (not the example file); restart server
Apify error / empty results	Check token, check credit balance at console.apify.com