

Question - 1
Project Estimates

SCORE: 50 points

Binary Search

Easy

Data Structures

Algorithms

Arrays

Problem Solving

Theme: Finance

A number of bids are being taken for a project. Determine the number of distinct pairs of project costs where their absolute difference is some target value. Two pairs are distinct if they differ in at least one value.

Example $n = 3$ $projectCosts = [1, 3, 5]$ $target = 2$

There are 2 pairs $[1, 3]$, $[3, 5]$ that have the target difference $target = 2$, therefore a value of 2 is returned.

Function Description

Complete the function *countPairs* in the editor below.

countPairs has the following parameter(s):

int projectCosts[n]: array of integers

int target: the target difference

Returns

int: the number of distinct pairs in *projectCosts* with an absolute difference of *target*

Constraints

- $5 \leq n \leq 10^5$
- $0 < projectCosts[i] \leq 2 \times 10^9$
- Each $projectCosts[i]$ is distinct, i.e. unique within *projectCosts*
- $1 \leq target \leq 10^9$

▼ Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n , the size of the array *projectCosts*.

The next n lines each contain an element $projectCosts[i]$ where $0 \leq i < n$.

The next line contains the integer *target*, the target difference.

▼ Sample Case 0**Sample Input 0**

STDIN	Function
-----	-----
5	→ projectCosts[] size n = 5
1	→ projectCosts = [1, 5, 3, 4, 2]
5	
3	
4	

```
2
2      →   target = 2
```

Sample Output 0

```
3
```

Explanation 0

Count the number of pairs in *projectCosts* whose difference is *target* = 2. The following three pairs meet the criterion: (1, 3), (5, 3), and (4, 2).

▼ Sample Case 1

Sample Input 1

```
STDIN      Function
-----
10          →   projectCosts[] size n = 10
363374326  →   projectCosts = [363374326, 364147530, 61825163, 107306571, 128124602, 139946991, 428047635,
491595254, 879792181, 106926279]
364147530
61825163
107306571
128124602
139946991
428047635
491595254
879792181
106926279
1          →   target = 1
```

Sample Output 1

```
0
```

Explanation 1

Count the number of pairs in *projectCosts* whose difference is *target* = 1. Because no such pair of integers exists, return 0.

▼ Sample Case 2

Sample Input 2

```
STDIN      Function
-----
6          →   projectCosts[] size n = 6
2          →   projectCosts = [2, 4, 6, 8, 10, 12]
4
6
8
10
12
2          →   target = 2
```

Sample Output 2

```
5
```

Explanation 2

Count the number of pairs in *projectCosts* whose difference is *target* = 2. The following five pairs meet the criterion: (2, 4), (4, 6), (6, 8), (8, 10), and (10, 12).

Question - 2
Merge 2 Arrays

SCORE: 50 points

- Easy
- Data Structures
- Algorithms
- Arrays
- Problem Solving
- Interviewer Guidelines

Given two sorted arrays, merge them to form a single, sorted array with all items in non-decreasing order.

Example

$a = [1, 2, 3]$

$b = [2, 5, 5]$

Merge the arrays to create array c as follows:

```
a[0] < b[0] → c = [a[0]] = [1]
a[1] = b[0] → c = [a[0], b[0]] = [1, 2]
a[1] < b[1] → c = [a[0], b[0], a[1]] = [1, 2, 2]
a[2] < b[1] → c = [a[0], b[0], a[1], a[2]] = [1, 2, 2, 3]
No more elements in a → c = [a[0], b[0], a[1], a[2], b[1], b[2]] = [1, 2, 2, 3, 5, 5]
```

Elements were alternately taken from the arrays in the order given, maintaining precedence.

Function Description

Complete the function `mergeArrays` in the editor below.

`mergeArrays` has the following parameter(s):

- `int a[n]`: a sorted array of integers
- `int b[n]`: a sorted array of integers

Returns

`int[n]`: an array of all the elements from both input arrays in non-decreasing order

Constraints

- $1 < n < 5 \times 10^5$
- $0 \leq a[i], b[i] \leq 10^9$, where $0 \leq i < n$

▼ Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n , the size of the array a .
The next n lines each contain an element $a[i]$ where $0 \leq i < n$.
The next line contains an integer n , the size of the array b .
The next n lines each contain an element $b[i]$ where $0 \leq i < n$.

▼ Sample Case 0

Sample Input 0

STDIN	Function
-----	-----
4	→ a[] size n = 4
1	→ a = [1, 5, 7, 7]
1	
5	
7	
7	
4	→ b[] size n = 4
0	→ b = [0, 1, 2, 3]

1
2
3

Sample Output 0

0
1
1
2
3
5
7
7

Explanation

The *mergedArray* function returns the following merged, non-decreasing array: [0, 1, 1, 2, 3, 5, 7, 7]

▼ Sample Case 1

Sample Input 1

STDIN		Function
-----		-----
5	→	a[] size n = 5
2	→	a = [2, 4, 5, 9, 9]
4		
5		
9		
9		
5	→	b[] size n = 5
0	→	b = [0, 1, 2, 3, 4]
1		
2		
3		
4		

Sample Output 1

0
1
2
2
3
4
4
5
9
9

Explanation

The *mergedArray* function returns the following merged, non-decreasing array: [0, 1, 2, 2, 3, 4, 4, 5, 9, 9]

Question - 3
River Records

SCORE: 50 points

Algorithms Arrays Problem Solving Easy

Given an array of integers, without reordering, determine the maximum difference between any element and any prior smaller element. If there is never a lower prior element, return -1.

Example

`arr = [5, 3, 6, 7, 4]`

- There are no earlier elements than `arr[0]`.
- There is no earlier reading with a value lower than `arr[1]`.
- There are two lower earlier readings with a value lower than `arr[2] = 6`:
- `arr[2] - arr[1] = 6 - 3 = 3`
 - `arr[2] - arr[0] = 6 - 5 = 1`
- There are three lower earlier readings with a lower value than `arr[3] = 7`:
- `arr[3] - arr[2] = 7 - 6 = 1`
 - `arr[3] - arr[1] = 7 - 3 = 4`
 - `arr[3] - arr[0] = 7 - 5 = 2`
- There is one lower earlier reading with a lower value than `arr[4] = 4`:
- `arr[4] - arr[1] = 4 - 3 = 1`

The maximum trailing record is `arr[3] - arr[1] = 4`.

Example

`arr = [4, 3, 2, 1]`

No item in `arr` has a lower earlier reading, therefore return -1

Function Description

Complete the function `maximumTrailing` in the editor below.

`maximumTrailing` has the following parameter(s):

`int arr[n]`: an array of integers

Returns:

`int`: the maximum trailing difference, or -1 if no element in `arr` has a lower earlier value

Constraints

- $1 \leq n \leq 2 \times 10^5$
- $-10^6 \leq arr[i] \leq 10^6$ and $0 \leq i < n$

▼ Input Format For Custom Testing

Input from stdin will be processed as follows and passed to the function:

The first line contains a single integer, *n*, the number of elements in the array *arr*.
Each of the *n* subsequent lines contains a single integer, each an element *arr[i]* where $0 \leq i < n$.

▼ Sample Case 0

Sample Input 0

STDIN		Function
-----		-----
7	→	arr[] size n = 7
2	→	arr = [2, 3, 10, 2, 4, 8, 1]
3		
10		
2		
4		
8		
1		

Sample Output

8

Explanation

Differences are calculated as:

- $3 - [2] = [1]$
- $10 - [3, 2] = [7, 8]$
- $4 - [2, 3, 2] = [2, 1, 2]$
- $8 - [4, 2, 3, 2] = [4, 6, 5, 6]$

The maximum trailing difference is $10 - 2 = 8$.

▼ Sample Case 1

Sample Input 1

STDIN	Function
-----	-----
6	→ arr[] size n = 6
7	→ arr = [7, 9, 5, 6, 3, 2]
9	
5	
6	
3	
2	

Sample Output

2

Explanation

Differences are calculated as:

- $9 - [7] = 2$
- $6 - [5] = 1$

The maximum trailing difference is 2.

Question - 4

Triangle Or Not?


SCORE: 50 points

- Loops
- Easy
- Arrays
- Problem Solving

Given 3 lines, find out if they can form a [non-degenerate triangle](#). If the 3 lines are placed with tips joined such that they form a triangle with non-zero angles at each vertex, then a non-degenerate triangle is formed.

Example

Lines with lengths $[3, 4, 5]$ make a non-degenerate triangle (left), lines with lengths $[2, 3, 5]$ make a degenerate triangle (right), and lines with lengths $[1, 1, 5]$ cannot form a triangle.



Function Description

Complete the function *triangleOrNot* in the editor below.

triangleOrNot has the following parameter(s):

- int a[n]*: an array where each index *i* describes the length of side *a* for triangle *i*
- int b[n]*: an array representing lengths of sides *b[i]*
- int c[n]*: an array representing lengths of sides *c[i]*

Returns:

String arr[n]: an array where the value at each index *i* is 'Yes' if *a[i]*, *b[i]*, and *c[i]* can form a non-degenerate triangle, otherwise, the value is 'No'

Constraints

- $1 \leq n \leq 10^5$
- $1 \leq a[i], b[i], c[i] \leq 10^3$, where $0 \leq i < n$

▼ Input Format For Custom Testing

Locked stub code reads input from stdin and passes it to the function.

The first line contains an integer, *n*, denoting the number of elements in *a[]*.
Each of the next *n* lines contains an integer *a[i]*.
The next line contains an integer, *n*, denoting the number of elements in *b[]*.
Each of the next *n* lines contains an integer *b[i]*.
The next line contains an integer, *n*, denoting the number of elements in *c[]*.
Each of the next *n* lines contains an integer *c[i]*.

▼ Sample Case 0

Sample Input

STDIN	Function
-----	-----
3	→ a[] size n = 3
7	→ a = [7, 10, 7]
10	
7	
3	→ b[] size n = 3
2	→ b = [2, 3, 4]
3	
4	
3	→ c[] size n = 3
2	→ c = [2, 7, 4]
7	
4	

Sample Output

No
No
Yes

Explanation

Check the following $n = 3$ possible triangles using the values given by $a = [7, 10, 7]$, $b = [2, 3, 4]$, and $c = [2, 7, 4]$:

- 0. $a[0] = 7$, $b[0] = 2$, and $c[0] = 2$ do not form a valid, non-degenerate triangle, so store 'No' in index 0 of the return array.
- 1. $a[1] = 10$, $b[1] = 3$, and $c[1] = 7$ do not form a valid, non-degenerate triangle, so store 'No' in index 1 of the return array.
- 2. $a[2] = 7$, $b[2] = 4$, and $c[2] = 4$ do form a valid, non-degenerate triangle, so store 'Yes' in index 2 of the return array.

Then return the array ['No', 'No', 'Yes'] as the answer.

Question - 5
Cutting Metal Surplus

SCORE: 75 points

Data Structures

Medium

Algorithms

Arrays

Problem Solving

The owner of a construction company has a surplus of rods of arbitrary lengths. A local contractor offers to buy any of the surplus, as long as all the rods have the same exact integer length, referred to as *saleLength*. The number of sellable rods can be increased by cutting each rod zero or more times, but each cut has a cost denoted by *costPerCut*. After all cuts have been made, any leftover rods having a length other than *saleLength* must be discarded for no profit. The owner's total profit for the sale is calculated as:

$$totalProfit = totalUniformRods \times saleLength \times salePrice - totalCuts \times costPerCut$$

where *totalUniformRods* is the number of sellable rods, *salePrice* is the per unit length price that the contractor agrees to pay, and *totalCuts* is the total number of times the rods needed to be cut.

Example

lengths = [30, 59, 110]

costPerCut = 1

salePrice = 10 per unit length

The following are tests based on lengths that are factors of 30, the length of the shortest bar. Factors of other lengths might also be tested, but this demonstrates the methodology.

Length	Rod	Cuts			Pieces
		Extra	Regular	Total	
30	30	0	0	0	1
	59	1	0	1	1
	110	1	2	3	3
	Revenue = (10*5*30) - (4*1) = 1496				
15	30	0	1	1	2
	59	1	2	3	3
	110	1	6	7	7
	Revenue = (10*12*15) - (11*1) = 1789				
10	30	0	2	2	3
	59	1	4	5	5
	110	0	10	10	11
	Revenue = (10*19*10) - (17*1) = 1883				
6	30	0	4	4	5
	59	1	8	9	9
	110	1	17	18	18
	Revenue = (10*32*6) - (31*1) = 1889				
5	30	0	5	5	6
	59	1	10	11	11
	110	0	21	21	21
	Revenue = (10*39*5) - (37*1) = 1913				
3	30	0	9	9	10
	59	1	18	19	19
	110	1	35	36	36
	Revenue = (10*65*3) - (64*1) = 1886				

Working through the first stanza, $length = 30$, it is the same length as the first rod, so no cuts are required and there is 1 piece. For the second rod, cut and discard the excess 29 unit rod. No more cuts are necessary and another 1 piece is left to sell. Cut 20 units off the 110 unit rod to discard leaving 90 units, then make two more cuts to have 3 more pieces to sell. Finally sell 5 *totalUniformRods*, *saleLength* = 30 at *salePrice* = 10 per unit length for 1500. The cost to produce was $totalCuts = 4$ times $costPerCut = 1$ per cut, or 4. Total revenue = $1500 - 4 = 1496$. The maximum revenue among these tests is obtained at length 5 for 1913.

Function Description

Complete the function *maxProfit* in the editor below.

maxProfit has the following parameter(s):

- costPerCut*: cost to make a cut
- salePrice*: per unit length sales price
- lengths[n]*: integer rod lengths

Returns:

- int*: maximum possible profit

Constraints

- $1 \leq n \leq 50$
- $1 \leq lengths[i] \leq 10^4$
- $1 \leq salePrice, costPerCut \leq 1000$

▼ Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer, *costPerCut*.

The second line contains an integer, *salePrice*.

The next line contains an integer *n*, the size of the array *lengths*.

Each of the next *n* lines contains an integer *lengths[i]* where $0 \leq i < n$.

▼ Sample Case 0

Sample Input

STDIN	Function
-----	-----
1	→ costPerCut = 1
10	→ salePrice = 10
3	→ lengths[] size n = 3
26	→ lengths = [26, 103, 59]
103	
59	

Sample Output

1770

Explanation

Since $costPerCut = 1$ is very inexpensive, a large number of cuts can be made to reduce the number of wasted pieces. The optimal rod length for maximizing profit is 6, and the rods are cut as shown:

- $lengths[0] = 26$: Cut off a piece of length 2 and discard it, resulting in a rod of length 24. Then, cut this rod into 4 pieces of length 6.
- $lengths[1] = 103$: Cut off a piece of length 1 and discard it, resulting in a rod of length 102. Then, cut this rod into 17 pieces of length 6.
- $lengths[2] = 59$: Cut off a piece of length 5 and discard it, resulting in a rod of length 54. Then, cut this rod into 9 pieces of length 6.

After performing $totalCuts = (1 + 3) + (1 + 16) + (1 + 8) = 30$ cuts, there are $totalUniformRods = 4 + 17 + 9 = 30$ pieces of length $saleLength = 6$ that can be sold at $salePrice = 10$. This yields a total profit of $salePrice \times totalUniformRods \times saleLength - totalCuts \times costPerCut = 10 \times 30 \times 6 - 30 \times 1 = 1770$.

Sample Input

STDIN	Function
-----	-----
100	→ costPerCut = 100
10	→ salePrice = 10
3	→ lengths[] size n = 3
26	→ lengths = [26, 103, 59]
103	
59	

Sample Output

1230

Explanation

Since $costPerCut = 100$, cuts are expensive and must be minimal. The optimal rod length for maximizing profit is 51 , and the rods are cut as shown:

- `lengths[0] = 26`: Discard this rod entirely.
- `lengths[1] = 103`: Cut off a piece of length 1 and discard it, resulting in a rod of length 102 . Then, cut this rod into 2 pieces of length 51 .
- `lengths[2] = 59`: Cut off a piece of length 8 and discard it, resulting in a rod of length 51 .

After performing $totalCuts = (0) + (1 + 1) + (1) = 3$ cuts, there are $totalUniformRods = 0 + 2 + 1 = 3$ pieces of length $saleLength = 51$ that can be sold at $salePrice = 10$ each. This yields a total profit of $salePrice \times totalUniformRods \times saleLength - totalCuts \times costPerCut = 10 \times 3 \times 51 - 3 \times 100 = 1230$.