

Visualization of Quantum Algorithms: A Comparative Study of Visualization Styles for Different Algorithm Families

Research Project Report
Department of Quantum Computing
Visualization of Algorithms Project

March 22, 2026

Abstract

Quantum algorithm visualization is essential for understanding the behavior and properties of quantum computations. Different algorithm families exhibit distinct characteristics that may be more effectively visualized through specific visualization approaches. This research investigates the hypothesis that **certain visualization styles are optimal for specific quantum algorithm families**. We conducted empirical testing across four algorithm families: Oracle-based (Grover's Search, Deutsch-Jozsa), Transform-based (QFT, QPE), Variational (QAOA, VQE), and Simulation-based (Rabi Oscillation, Ising Model). Five visualization techniques were evaluated: Bloch Sphere, State City (density matrix), Circuit Diagrams, Cost Landscapes, and Dynamic Flow trajectories. Our findings confirm the hypothesis: Oracle-based algorithms are best visualized with Bloch Sphere + State City, Transform-based algorithms with State City, Variational algorithms with Circuit Diagrams + Cost Landscapes, and Simulation-based algorithms with Dynamic Flow + Bloch trajectories. This research provides guidelines for researchers and practitioners in selecting appropriate visualization techniques for different quantum algorithm analysis tasks.

Keywords: Quantum Computing, Algorithm Visualization, Bloch Sphere, Density Matrix, Quantum Circuit, Comparative Analysis

1 Introduction

Quantum computing represents a paradigm shift in computational methodology, leveraging quantum mechanical phenomena such as superposition, entanglement, and interference to solve problems that remain intractable for classical computers. As quantum hardware matures and quantum algorithms become increasingly sophisticated, the need for effective visualization techniques becomes paramount. Understanding the behavior, properties, and dynamics of quantum algorithms requires tools that can represent complex quantum states and operations in intuitive and interpretable formats.

The field of quantum algorithm visualization has seen various approaches, ranging from geometric representations like the Bloch sphere to algebraic representations like density matrices and circuit diagrams. However, the question of which visualization technique is most appropriate for which type of quantum algorithm remains largely unexplored. This research addresses this fundamental question by empirically testing the hypothesis that **certain visualization styles are optimal for specific quantum algorithm families**.

1.1 Research Objectives

The primary objectives of this research are:

1. To test the hypothesis that algorithm-specific visualization techniques provide superior insight compared to generic approaches
2. To identify which visualization techniques reveal unique properties of different algorithm families
3. To evaluate the scalability of various visualization techniques with increasing qubit counts
4. To provide practical guidelines for researchers selecting visualization approaches for quantum algorithm analysis

1.2 Research Hypothesis

Based on theoretical analysis of quantum algorithm properties and visualization capabilities, we hypothesize:

- **Oracle-based algorithms** benefit from geometric (Bloch sphere) and algebraic (amplitude bars) visualizations because they exhibit rotational dynamics toward target states
- **Transform-based algorithms** are best visualized algebraically because phase periodicity in frequency domains is their key feature
- **Variational algorithms** require graph-based (circuit diagrams) and geometric (cost landscapes) representations due to parameter optimization landscapes
- **Simulation-based algorithms** need dynamic flow and trajectory visualizations because they evolve over time under Hamiltonian dynamics

2 Background and Related Work

2.1 Quantum State Representations

Quantum states in an n -qubit system exist in a 2^n -dimensional Hilbert space. A pure state $|\psi\rangle$ can be represented as:

$$|\psi\rangle = \sum_{i=0}^{2^n-1} \alpha_i |i\rangle, \quad \sum_{i=0}^{2^n-1} |\alpha_i|^2 = 1 \quad (1)$$

where α_i are complex amplitudes and $|i\rangle$ are basis states. This representation can be visualized through multiple techniques, each emphasizing different aspects of the quantum state.

2.2 Visualization Techniques

2.2.1 Bloch Sphere

The Bloch sphere represents a single qubit state as a point on the unit sphere in $\mathbb{R}^3$:

$$|\psi\rangle = \cos \frac{\theta}{2} |0\rangle + e^{i\phi} \sin \frac{\theta}{2} |1\rangle \quad (2)$$

The Bloch vector $\vec{r} = (x, y, z)$ is computed from the density matrix $\rho = |\psi\rangle\langle\psi|$:

$$x = \text{Tr}(\rho \sigma_x), \quad y = \text{Tr}(\rho \sigma_y), \quad z = \text{Tr}(\rho \sigma_z) \quad (3)$$

2.2.2 Density Matrix (State City)

The density matrix representation $\rho = |\psi\rangle\langle\psi|$ provides a complete description of quantum states. For an n -qubit system, this is a $2^n \times 2^n$ matrix where:

- Diagonal elements $|\alpha_i|^2$ represent probabilities
- Off-diagonal elements $\alpha_i \alpha_j^*$ represent coherences between basis states

2.2.3 Quantum Circuit Diagrams

Circuit diagrams represent quantum operations as a sequence of gates applied to qubits, showing the structural and computational flow of quantum algorithms.

2.2.4 Cost and Energy Landscapes

For variational algorithms, cost/energy landscapes visualize the objective function as a function of parameters, revealing optimization trajectories and local/global minima.

2.3 Algorithm Families

Quantum algorithms can be categorized into families based on their underlying structure and purpose:

- **Oracle-based:** Amplitude amplification through interference (Grover's, Deutsch-Jozsa)

- **Transform-based:** Signal processing in quantum Fourier domains (QFT, QPE)
- **Variational:** Hybrid quantum-classical optimization (QAOA, VQE)
- **Simulation-based:** Hamiltonian dynamics emulation (Rabi oscillation, Ising model)

3 Methodology

3.1 Experimental Design

Our methodology involved systematic testing of visualization techniques across multiple algorithms within each family. For each algorithm, we applied all relevant visualization techniques and evaluated their effectiveness in revealing key algorithm properties.

3.2 Visualization Tools Implemented

Five visualization tools were implemented in Python using NumPy and Matplotlib:

1. **Bloch Sphere Visualizer:** Renders single-qubit states on a 3D unit sphere
2. **State City Visualizer:** Displays density matrix elements as 3D bar charts
3. **Circuit Diagram Generator:** Produces quantum circuit schematics
4. **Cost Landscape Visualizer:** Plots parameter optimization surfaces
5. **Dynamic Flow Visualizer:** Shows state evolution trajectories over time

3.3 Algorithms Tested

Table 1 summarizes the algorithms tested across different families.

Table 1: Quantum Algorithms Tested in This Study

Family	Algorithm	Qubits	Purpose
Oracle-based	Grover's Search	2, 3, 4	Database search
Oracle-based	Deutsch-Jozsa	2	Function balancing
Transform-based	QFT	2, 3, 4	Fourier transformation
Transform-based	QPE	2	Phase estimation
Variational	QAOA	2, 3	Combinatorial optimization
Variational	VQE	2, 3	Ground state energy
Simulation-based	Rabi Oscillation	1	Time evolution
Simulation-based	Ising Model	2	Many-body physics

3.4 Evaluation Criteria

Each visualization was evaluated on:

- **Clarity:** How easily interpretable is the visualization?
- **Insight Level:** Does it reveal key algorithm properties?
- **Scalability:** How does it perform with increasing qubit counts?
- **Unique Value:** Does it provide information unavailable elsewhere?

4 Results

4.1 Oracle-Based Algorithms

Oracle-based algorithms use quantum oracles to mark solution states and employ amplitude amplification to increase their probabilities.


4.1.1 Grover's Search Algorithm

Grover's search demonstrates quadratic speedup for unstructured database search. The algorithm consists of:

1. Initialize qubits to $|0\rangle^{\otimes n}$
2. Apply Hadamard gates for uniform superposition
3. Repeat $O(\sqrt{N})$ times:
 - Oracle: Phase flip on target state
 - Diffusion: Amplitude amplification
4. Measure to obtain solution

Figure 1 shows the visualization comparison for Grover's algorithm.

Figure 1: Grover's Search: Comparison of Visualization Techniques



Key Findings:

- **Bloch Sphere** reveals the geometric rotation: the state vector rotates from the equator toward the target state $|11\rangle$

- **State City** quantifies probability: success probability increases from 0.25 to 1.0 across iterations
- **Circuit Diagram** shows structural elements: Oracle and Diffusion operators are clearly visible

Table 2: Visualization Effectiveness for Grover’s Search

Visualization	Insight Level	Unique Value
Bloch Sphere	High	Geometric rotation mechanism
State City	Medium	Probability quantification
Circuit Diagram	High	Structural understanding

4.1.2 Deutsch-Jozsa Algorithm

The Deutsch-Jozsa algorithm determines whether a function is constant or balanced with a single query.

Key Findings:

- **Bloch Sphere**: Final state returns to $|0\rangle$ for constant oracle
- **State City**: Shows deterministic collapse to $|00\rangle$
- Both visualizations effectively demonstrate the algorithm’s quantum advantage

4.2 Transform-Based Algorithms

Transform-based algorithms operate by transforming quantum states into different bases, particularly the Fourier basis.

4.2.1 Quantum Fourier Transform (QFT)

The QFT transforms basis states according to:

$$|j\rangle \rightarrow \frac{1}{\sqrt{N}} \sum_{k=0}^{N-1} e^{2\pi i jk/N} |k\rangle \quad (4)$$

Figure 2 shows the visualization comparison.

Key Findings:

- **Bloch Sphere** fails for multi-qubit phase relationships (only shows single-qubit phase)
- **State City** reveals periodic phase patterns in the imaginary part
- State City is **essential** for understanding QFT behavior

Figure 2: QFT: Visualization Comparison




Table 3: Visualization Effectiveness for QFT

Visualization	Insight Level	Unique Value
Bloch Sphere	Low	Cannot show multi-qubit phases
State City	High	Phase periodicity visible
Circuit Diagram	High	Butterfly pattern visible

4.3 Variational Algorithms

Variational algorithms combine quantum circuits with classical optimization to solve optimization problems.

4.3.1 QAOA (Quantum Approximate Optimization Algorithm)

QAOA solves combinatorial optimization problems by varying parameters γ and β :


$$|\psi(\gamma, \beta)\rangle = U(\beta)U(\gamma)|+\rangle^{\otimes n} \quad (5)$$

Figure 3 shows the visualization comparison.

Key Findings:

- **Bloch Sphere** provides limited value (doesn't show optimization)
- **State City** shows solution probability improvement

Figure 3: QAOA: Visualization Comparison



- **Cost Landscape** reveals the optimization surface with minima
- **Circuit Diagram** shows ansatz structure (problem + mixer layers)

Table 4: Visualization Effectiveness for QAOA

Visualization	Insight Level	Unique Value
Bloch Sphere	Low	No parameter optimization shown
State City	Medium	Solution quality visible
Cost Landscape	High	Optimization surface visible
Circuit Diagram	High	Ansatz structure visible

4.3.2 VQE (Variational Quantum Eigensolver)

VQE finds ground state energies by minimizing the expectation value $E(\theta) = \langle \psi(\theta) | H | \psi(\theta) \rangle$.

Key Findings:

- **Energy Landscape** shows minimization trajectory toward ground state
- State City demonstrates amplitude shift toward ground state basis states
- Circuit Diagram reveals hardware-efficient ansatz structure

4.4 Simulation-Based Algorithms

Simulation-based algorithms emulate quantum system dynamics under Hamiltonians.


4.4.1 Rabi Oscillation

Rabi oscillation demonstrates coherent population transfer between quantum states under resonant driving:

$$|\psi(t)\rangle = \cos(\Omega t)|0\rangle - i \sin(\Omega t)|1\rangle \quad (6)$$

Figure 4 shows the visualization comparison.

Figure 4: Rabi Oscillation: Trajectory Visualization



Key Findings:

- **Bloch Sphere Trajectory** shows the state vector rotating on the sphere surface
- **Dynamic Flow** reveals time evolution through multiple time points
- **Z vs Time** plot quantifies the oscillation period

Table 5: Visualization Effectiveness for Rabi Oscillation

Visualization	Insight Level	Unique Value
Bloch Sphere	High	Single-qubit trajectory
State City	Medium	Density matrix evolution
Dynamic Flow	High	Time evolution steps

4.5 Scalability Analysis

Scalability is critical for practical visualization. Table 6 summarizes how each visualization technique scales with qubit count.

Key Observation: State City (density matrix) scales poorly due to exponential growth ($2^n \times 2^n$ matrix), limiting practical use to approximately 4 qubits.

Table 6: Scalability of Visualization Techniques

Visualization	2 qubits	3 qubits	4 qubits	5+ qubits
Bloch Sphere	Excellent	Excellent	Excellent	Excellent
State City	Excellent	Good	Challenging	Impractical
Cost Landscape	Excellent	Excellent	Excellent	Excellent
Circuit Diagram	Excellent	Excellent	Good	Good
Dynamic Flow	Excellent	Excellent	Excellent	Excellent

5 Discussion

5.1 Hypothesis Validation

Our results strongly support the hypothesis that certain visualization styles are optimal for specific algorithm families.

1. **Oracle-based algorithms:** Confirmed. Bloch Sphere reveals the geometric rotation mechanism, while State City quantifies probability amplification. Circuit diagrams provide structural context.
2. **Transform-based algorithms:** Confirmed. State City is essential because it reveals phase periodicity in the density matrix imaginary part—information that Bloch Sphere cannot capture for multi-qubit systems.
3. **Variational algorithms:** Confirmed. Circuit diagrams show ansatz structure and parameter placement, while Cost Landscapes reveal the optimization landscape. Bloch Sphere provides minimal insight.
4. **Simulation-based algorithms:** Confirmed. Dynamic Flow and trajectory visualizations are essential for understanding Hamiltonian time evolution.

5.2 Visualization Selection Guidelines

Based on our findings, we provide the following guidelines:

Table 7: Recommended Visualizations by Algorithm Family

Algorithm Family	Recommended Visualizations
Oracle-based	Bloch Sphere + State City + Circuit
Transform-based	State City + Circuit
Variational	Circuit + Cost Landscape
Simulation-based	Dynamic Flow + Bloch Trajectory

5.3 Trade-offs and Limitations

- **Bloch Sphere:** Limited to single-qubit states; cannot represent entanglement
- **State City:** Excellent insight but impractical for 5+ qubits

- **Cost Landscape:** Requires parameter sweep computation
- **Dynamic Flow:** Static images; animation would improve understanding

6 Conclusions

This research empirically validated the hypothesis that certain visualization styles are optimal for specific quantum algorithm families. Our key findings are:

1. **Oracle-based algorithms** benefit from the combination of Bloch Sphere (geometric rotation) and State City (probability quantification), with Circuit diagrams providing structural context.
2. **Transform-based algorithms** require State City visualization to reveal phase periodicity that cannot be captured by Bloch Sphere for multi-qubit systems.
3. **Variational algorithms** need Circuit diagrams (for ansatz structure) and Cost Landscapes (for optimization understanding), as Bloch Sphere provides minimal insight.
4. **Simulation-based algorithms** are best understood through Dynamic Flow and trajectory visualizations showing time evolution.
5. **Scalability analysis** reveals that State City (density matrix) is practical only for up to 4 qubits, while Bloch Sphere, Circuit diagrams, and Dynamic Flow scale well.

These findings provide practical guidance for researchers and practitioners in selecting appropriate visualization techniques for quantum algorithm analysis.

6.1 Future Work

- Develop hybrid visualizations combining multiple techniques
- Implement interactive/animated visualizations
- Extend testing to 10+ qubit systems with alternative density matrix representations
- Apply these guidelines to real quantum hardware output visualization

Acknowledgments

This research was conducted as part of the Visualization of Algorithms project, exploring the intersection of quantum computing and visual analytics.

References

References

- [1] Quantum Algorithm Zoo. <https://quantumalgorithmzoo.org/>
- [2] Nielsen, M. A., & Chuang, I. L. (2010). *Quantum Computation and Quantum Information: 10th Anniversary Edition*. Cambridge University Press.
- [3] Preskill, J. (2018). Quantum Computing in the NISQ era and beyond. *Quantum*, 2, 79.
- [4] Farhi, E., Goldstone, J., & Gutmann, S. (2014). A Quantum Approximate Optimization Algorithm. *arXiv:1411.4028*.
- [5] Peruzzo, A., McClean, J., Shadbolt, P., et al. (2014). A variational eigenvalue solver on a photonic quantum processor. *Nature Communications*, 5, 4213.
- [6] Grover, L. K. (1996). A fast quantum mechanical algorithm for database search. *Proceedings of the 28th ACM STOC*, 212-219.
- [7] Deutsch, D., & Jozsa, R. (1992). Rapid solution of problems by quantum computation. *Proceedings of the Royal Society of London A*, 439, 553-558.