```
In [1]:
```

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
```

In []:

In [3]:

```
df = pd.read_csv('cars24.csv')
df.shape
```

Out[3]:

(19980, 11)

In [4]:

df.head()

Out[4]:

	full_name	selling_price	year	seller_type	km_driven	fuel_type	transmission_type	mileage
0	Maruti Alto Std	1.20	2012.0	Individual	120000	Petrol	Manual	19.70
1	Hyundai Grand i10 Asta	5.50	2016.0	Individual	20000	Petrol	Manual	18.90
2	Hyundai i20 Asta	2.15	2010.0	Individual	60000	Petrol	Manual	17.00
3	Maruti Alto K10 2010- 2014 VXI	2.26	2012.0	Individual	37000	Petrol	Manual	20.92
4	Ford Ecosport 2015- 2021 1.5 TDCi Titanium BSIV	5.70	2015.0	Dealer	30000	Diesel	Manual	22.77

In [5]:

df.info()

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 19980 entries, 0 to 19979
Data columns (total 11 columns):
#
     Column
                        Non-Null Count
                                        Dtype
     _____
                        -----
                                        ____
 0
     full name
                        19980 non-null
                                        object
 1
     selling price
                        19980 non-null
                                        float64
 2
     year
                        19980 non-null
                                        float64
 3
                                        object
     seller type
                        19980 non-null
 4
     km_driven
                        19980 non-null
                                        int64
 5
     fuel_type
                        19980 non-null
                                        object
 6
     transmission_type 19980 non-null
                                        object
 7
     mileage
                        19980 non-null
                                       float64
 8
     engine
                        19980 non-null float64
                        19980 non-null
                                        float64
 9
     max power
                        19980 non-null
                                        float64
 10
    seats
dtypes: float64(6), int64(1), object(4)
```

In [6]:

df.describe()

memory usage: 1.7+ MB

Out[6]:

	selling_price	year	km_driven	mileage	engine	max_power	
count	19980.000000	19980.000000	1.998000e+04	19980.000000	19980.000000	19980.000000	199
mean	7.392066	2014.525125	5.824488e+04	19.347219	1476.327401	97.854443	
std	9.103088	3.249185	5.172509e+04	4.620053	520.449398	45.080670	
min	0.250000	1991.000000	1.000000e+02	0.000000	0.000000	5.000000	
25%	3.400000	2013.000000	3.116425e+04	16.800000	1197.000000	73.900000	
50%	5.200000	2015.000000	5.200000e+04	19.160000	1248.000000	86.700000	
75%	7.850000	2017.000000	7.400000e+04	22.320000	1582.000000	112.000000	
max	395.000000	2021.000000	3.800000e+06	120.000000	6752.000000	626.000000	

In [9]:


```
# plt.hist(df['selling_price'])
```

In [12]:

```
df['selling_price'].plot(kind='hist', bins=100)
```

Out[12]:

<AxesSubplot:ylabel='Frequency'>



In [17]:

```
df[df['selling_price']>100].shape[0]/19000
```

Out[17]:

0.0005789473684210527

In [18]:

df[df['selling_price']>100]

Out[18]:

	full_name	selling_price	year	seller_type	km_driven	fuel_type	transmission_type	m
475	Bentley Mulsanne 6.8	235.0	2012.0	Dealer	15000	Petrol	Automatic	
1536	Bentley Continental GT Speed Convertible BSIV	145.0	2012.0	Dealer	9000	Petrol	Automatic	
2478	Mercedes- Benz S- Class S 500	110.0	2016.0	Dealer	41000	Petrol	Automatic	
3980	Lamborghini Gallardo Spyder	150.0	2013.0	Dealer	4000	Petrol	Automatic	
3983	Jaguar XJ 50 Special Edition	110.0	2019.0	Individual	5400	Diesel	Automatic	
4967	Ferrari GTC4Lusso T	395.0	2019.0	Dealer	3800	Petrol	Automatic	
12299	Porsche Cayenne GTS	111.0	2017.0	Dealer	24000	Petrol	Automatic	
12741	Mercedes- Benz S- Class Maybach S500	130.0	2018.0	Dealer	4000	Petrol	Automatic	
13863	Porsche Cayenne Base	132.0	2019.0	Individual	5000	Petrol	Automatic	
14261	Rolls-Royce Ghost Series II Extended Wheelbase	242.0	2017.0	Individual	5000	Petrol	Automatic	
14283	Mercedes- Benz S- Class S 450	110.0	2019.0	Dealer	18000	Petrol	Automatic	

```
In [20]:
```

```
np.percentile(df['selling_price'], 99.9)
```

Out[20]:

82.01050000000032


In []:

In [27]:

```
df['mileage'].plot(kind='hist', bins=80)
```

Out[27]:

<AxesSubplot:ylabel='Frequency'>



In [31]:

```
df[(df['mileage']==0)]
```

Out[31]:

	full_name	selling_price	year	seller_type	km_driven	fuel_type	transmission_type	mile
146	Hyundai Santro LP	1.60	2007.0	Individual	54000	Petrol	Manual	
270	Hyundai Santro AT	0.71	2004.0	Individual	110000	Petrol	Automatic	
304	Ford Figo Aspire Facelift	5.50	2017.0	Individual	15000	Diesel	Manual	
351	Hyundai Santro Xing XL	1.15	2005.0	Individual	120000	Petrol	Manual	
420	Toyota Fortuner 4X2 AT	12.35	2012.0	Dealer	85000	Petrol	Automatic	
19772	Hyundai Kona Premium	21.75	2019.0	Dealer	6000	Electric	Automatic	
19824	Mahindra Jeep MM 550 DP	3.50	2006.0	Individual	120000	Diesel	Manual	
19880	Toyota Fortuner 4X2 AT	14.50	2014.0	Dealer	127000	Petrol	Automatic	
19968	Hyundai Santro Xing GL	1.15	2008.0	Individual	80000	Petrol	Manual	
19970	Mercedes- Benz M- Class ML 350 4Matic	32.00	2014.0	Dealer	32000	Diesel	Automatic	

160 rows × 11 columns

In [34]:

```
df[(df['mileage']> 40)]
```

Out[34]:

	full_name	selling_price	year	seller_type	km_driven	fuel_type	transmission_type
11966	Mahindra e2oPlus P6	4.00	2018.0	Dealer	26000	Electric	Automatic
15684	Mahindra e2o T2	3.60	2015.0	Dealer	42862	Electric	Automatic
17782	Mahindra e2o T2	4.50	2015.0	Dealer	40000	Electric	Automatic
18401	Mahindra e2o Premium	3.25	2013.0	Individual	50000	Electric	Automatic


In []:

In [36]:

sns.heatmap(df.corr(), annot=True)


Out[36]:

<AxesSubplot:>



```
In [37]:
```

```
sns.pairplot(df, y_vars=['selling_price'])
plt.show()
```



```
In [ ]:
```

In [41]:

```
df['seats'].value_counts(normalize=True)
```

Out[41]:

```
5.0
        0.834885
7.0
        0.118619
8.0
        0.022022
        0.011261
4.0
6.0
        0.007157
        0.003604
9.0
        0.001301
10.0
2.0
        0.001051
14.0
        0.000100
```

Name: seats, dtype: float64

df

Out[42]:

	full_name	selling_price	year	seller_type	km_driven	fuel_type	transmission_type	mile
0	Maruti Alto Std	1.20	2012.0	Individual	120000	Petrol	Manual	1
1	Hyundai Grand i10 Asta	5.50	2016.0	Individual	20000	Petrol	Manual	1
2	Hyundai i20 Asta	2.15	2010.0	Individual	60000	Petrol	Manual	1
3	Maruti Alto K10 2010- 2014 VXI	2.26	2012.0	Individual	37000	Petrol	Manual	2
4	Ford Ecosport 2015- 2021 1.5 TDCi Titanium BSIV	5.70	2015.0	Dealer	30000	Diesel	Manual	2
19975	Toyota Platinum Etios 1.4 GXD	6.50	2017.0	Dealer	69480	Diesel	Manual	2
19976	Maruti Ertiga BSIV VXI	9.25	2019.0	Dealer	18000	Petrol	Manual	1
19977	Skoda Rapid 1.5 TDI Elegance	4.25	2015.0	Dealer	67000	Diesel	Manual	2
19978	Mahindra XUV500 W6 2WD	12.25	2016.0	Dealer	3800000	Diesel	Manual	1
19979	Honda City i- VTEC CVT VX	12.00	2019.0	Dealer	13000	Petrol	Automatic	1

19980 rows × 11 columns

```
In [46]:
df['make'] = df['full_name'].apply(lambda x: x.split()[0])
In [50]:
df['model'] = df['full_name'].apply(lambda x: " ".join(x.split()[1:]))
In [52]:
df.drop(columns=['full_name'], inplace = True)
In [53]:
df.head()
Out[53]:
   selling_price year seller_type km_driven fuel_type transmission_type mileage engine n
```

	0=1		= 71		= 71	= • •			
0	1.20	2012.0	Individual	120000	Petrol	Manual	19.70	796.0	
1	5.50	2016.0	Individual	20000	Petrol	Manual	18.90	1197.0	
2	2.15	2010.0	Individual	60000	Petrol	Manual	17.00	1197.0	
3	2.26	2012.0	Individual	37000	Petrol	Manual	20.92	998.0	
4	5.70	2015.0	Dealer	30000	Diesel	Manual	22.77	1498.0	

```
In [55]:
```

```
df.describe(include='object')
```

Out[55]:

		seller_type	fuel_type	transmission_type	make	model
	count	19980	19980	19980	19980	19980
u	nique	3	5	2	42	3321
	top	Dealer	Diesel	Manual	Maruti	Swift Dzire VDI
	freq	11973	9817	16029	5650	210

In [56]:

```
df["fuel_type"].value_counts()
```

Out[56]:

Diesel 9817
Petrol 9767
CNG 316
LPG 66
Electric 14

Name: fuel_type, dtype: int64

In [57]:

```
df["transmission_type"].value_counts()
```

Out[57]:

Manual 16029 Automatic 3951

Name: transmission_type, dtype: int64

In [58]:

```
df["seller_type"].value_counts()
```

Out[58]:

Dealer 11973 Individual 7817 Trustmark Dealer 190


Name: seller_type, dtype: int64

In [60]:

```
plt.figure(figsize=(15,10))
sns.boxplot(data=df, x='seller_type', y='selling_price')
```

Out[60]:

<AxesSubplot:xlabel='seller_type', ylabel='selling_price'>




In [61]:

```
plt.figure(figsize=(15,10))
sns.boxplot(data=df, x='seats', y='selling_price')
```

Out[61]:

<AxesSubplot:xlabel='seats', ylabel='selling_price'>




In [62]:

```
# Using log selling price.
plt.figure(figsize=(15,10))
sns.boxplot(data=df, x='seats', y=np.log(df['selling_price']))
```

Out[62]:

<AxesSubplot:xlabel='seats', ylabel='selling_price'>




In [64]:

```
df['selling_price_log'] = np.log(df['selling_price'])
```

In [69]:

```
plt.figure(figsize=(15,5))
sns.countplot(x='make', data=df, order = df['make'].value_counts().index)
plt.xticks(rotation=90)
plt.show()
```




In [73]:

```
curr_year = 2022
df['age'] = curr_year - df['year']
sns.scatterplot(data = df, x = 'age', y='selling_price_log')
```

Out[73]:

<AxesSubplot:xlabel='age', ylabel='selling_price_log'>



In [74]:

df.head()

Out[74]:

_	selli	ing_price	year	seller_type	km_driven	fuel_type	transmission_type	mileage	engine	n
	0	1.20	2012.0	Individual	120000	Petrol	Manual	19.70	796.0	
	1	5.50	2016.0	Individual	20000	Petrol	Manual	18.90	1197.0	
	2	2.15	2010.0	Individual	60000	Petrol	Manual	17.00	1197.0	
	3	2.26	2012.0	Individual	37000	Petrol	Manual	20.92	998.0	
	4	5.70	2015.0	Dealer	30000	Diesel	Manual	22.77	1498.0	

```
In [77]:
```

```
df['transmission_type'] = df['transmission_type'].astype('category').cat.codes
```

In [81]:

```
# you can drop a manual column.
fuel_dummy = pd.get_dummies(df['fuel_type'], drop_first=True)
fuel_dummy
```

Out[81]:

	Diesel	Electric	LPG	Petrol
0	0	0	0	1
1	0	0	0	1
2	0	0	0	1
3	0	0	0	1
4	1	0	0	0
19975	1	0	0	0
19976	0	0	0	1
19977	1	0	0	0
19978	1	0	0	0
19979	0	0	0	1

19980 rows × 4 columns

In [83]:

```
df = pd.concat([df, fuel_dummy], axis=1)
```

In [84]:

```
df.drop(columns=['fuel_type'], inplace=True)
```

```
In [85]:
```

```
df.head()
```

Out[85]:

	selling_price	year	seller_type	km_driven	transmission_type	mileage	engine	max_power
0	1.20	2012.0	Individual	120000	1	19.70	796.0	46.30
1	5.50	2016.0	Individual	20000	1	18.90	1197.0	82.00
2	2.15	2010.0	Individual	60000	1	17.00	1197.0	80.00
3	2.26	2012.0	Individual	37000	1	20.92	998.0	67.10
4	5.70	2015.0	Dealer	30000	1	22.77	1498.0	98.59

```
In [88]:
```

```
df['make'].nunique()
```

Out[88]:

42

In [92]:

```
df[df['make'] == 'Maruti']['selling_price'].mean()
```

Out[92]:

4.684721460177021

In [99]:

```
encode_make = df.groupby(by='make').mean()['selling_price']
```

```
In [113]:
df['make'].head()
Out[113]:
0
      Maruti
1
     Hyundai
     Hyundai
2
3
      Maruti
        Ford
Name: make, dtype: object
In [116]:
make_df = encode_make.reset_index()
make_df.columns = ['make', 'encoded_make']
make df.head()
Out[116]:
        make encoded_make
0 Ambassador
                  1.452500
        Audi
                 20.795525
 1
        BMW
                 26.547723
2
      Bentley
                128.250000
3
     Chevrolet
                  2.723621
In [118]:
df = pd.merge(df, make df, how='left', on='make')
In [93]:
# from category_encoders import TargetEncoder
In [ ]:
In [120]:
df.drop(columns=['seller_type', 'make', 'model'], inplace = True)
```

In [122]:

```
df.head()
```

Out[122]:

	selling_price	year	km_driven	transmission_type	mileage	engine	max_power	seats	1
0	1.20	2012.0	120000	1	19.70	796.0	46.30	5.0	Ī
1	5.50	2016.0	20000	1	18.90	1197.0	82.00	5.0	
2	2.15	2010.0	60000	1	17.00	1197.0	80.00	5.0	
3	2.26	2012.0	37000	1	20.92	998.0	67.10	5.0	
4	5.70	2015.0	30000	1	22.77	1498.0	98.59	5.0	

In []:

In [123]:

from sklearn.preprocessing import StandardScaler, MinMaxScaler

In [124]:

```
mu = df.mean()
sig = df.std()
```

In [125]:

```
df = (df-mu)/sig
```

In [126]:

df

Out[126]:

	selling_price	year	km_driven	transmission_type	mileage	engine	max_power
0	-0.680216	-0.777156	1.193910	0.496466	0.076359	-1.307192	-1.143604
1	-0.207849	0.453921	-0.739387	0.496466	-0.096799	-0.536704	-0.351690
2	-0.575856	-1.392695	0.033932	0.496466	-0.508050	-0.536704	-0.396055
3	-0.563772	-0.777156	-0.410727	0.496466	0.340425	-0.919066	-0.682209
4	-0.185878	0.146152	-0.546058	0.496466	0.740853	0.041642	0.016316
19975	-0.097996	0.761691	0.217208	0.496466	0.918340	-0.215828	-0.683318
19976	0.204099	1.377230	-0.778053	0.496466	-0.399826	-0.198535	-0.149830
19977	-0.345165	0.146152	0.169263	0.496466	0.388043	0.041642	0.125676
19978	0.533658	0.453921	72.339267	0.496466	-0.724498	1.350127	0.934892
19979	0.506195	1.377230	-0.874718	-2.014136	-0.291602	0.039721	0.438005


19980 rows × 15 columns

In [128]:

```
plt.figure(figsize=(15, 15))
sns.heatmap(df.corr(), annot=True)
```

Out[128]:

<AxesSubplot:>



```
In [ ]:
```

```
In [131]:
```

```
def merge seats(x):
    if 2 <= x <= 4:
        return '2-4'
    elif x > 5:
        return '>5'
    else:
        return '5'
def preprocess(df):
    df = df.loc[df.mileage != 0].copy()
    outlier_theshold = df.selling_price.quantile(0.95)
    df.loc[df.selling_price > outlier_theshold, 'selling_price'] = outlier_theshold
    df['age'] = pd.to_datetime('now', utc=True).date().year - df['year']
    df['full_name'] = df['full_name'].str.upper()
    df['seats'] = df['seats'].apply(merge seats)
    df.drop(columns=['year'])
    return df
def feature engineering(df):
    df['make'] = df.full_name.apply(lambda x : x.split()[0])
    df['model'] = df.full_name.apply(lambda x : " ".join(x.split()[1:]))
    one_hot_encode_cols = ['seller_type', 'fuel_type', 'transmission_type', 'seats']
    for column in one_hot_encode_cols:
        df = pd.concat([df, pd.get_dummies(df[column]).iloc[: , 1:]], axis=1)
    df.drop(columns=one_hot_encode_cols + ['full_name'], inplace=True)
    df['make'] = df.groupby('make')['selling price'].transform('median')
    df['model'] = df.groupby('model')['selling_price'].transform('median')
    scaler = MinMaxScaler()
    df = pd.DataFrame(scaler.fit_transform(df), columns=df.columns)
    return df
```

```
In [ ]:
```

```
In [132]:
```

```
df = pd.read_csv('cars24.csv')
df = preprocess(df)
df = feature_engineering(df)
df.head()
```

Out[132]:

Trustma Dea	Individual	model	make	age	max_power	engine	mileage	km_driven	ear
(1.0	0.042522	0.184371	0.310345	0.066506	0.117891	0.135345	0.031553	655
(1.0	0.225975	0.207231	0.172414	0.123994	0.177281	0.128448	0.005237	586
(1.0	0.120277	0.207231	0.379310	0.120773	0.177281	0.112069	0.015764	690
(1.0	0.093549	0.184371	0.310345	0.100000	0.147808	0.145862	0.009711	655
(0.0	0.300085	0.224624	0.206897	0.150709	0.221860	0.161810	0.007869	103

In []: