



PTT PHENOL COMPANY
LIMITED

PROCESS SPECIFICATION

COMBINED FEED SURGE DRUM (D-2201)

Docu. No. : 14780-8120-PS-D2201
Project No. : 120117
Rev. No. : Z1
Date : MAY 10, 2016
Page : 1 / 4

TITLE :

COMBINED FEED SURGE DRUM

(D-2201)

DISCIPLINE : PROCESS
DOCUMENT NO. : 14780-8120-PS-D2201
PROJECT NAME : PTT Phenol Train II Project
PROJECT NO. : 120117
OWNER : PTT Phenol Company Limited (PPCL)

Z1	MAY 10, 2016	AS BUILT	S.W.Park	J.S.Chung	-	S.W.Lee
F1	MAY 22, 2014	FINAL ISSUE	S.W.Park	J.S.Chung	-	S.W.Lee
A2	DEC 11, 2013	APPROVED FOR DESIGN	S.W.Park	J.S.Chung	-	S.W.Lee
A1	OCT 2, 2013	APPROVED FOR DESIGN	S.W.Park	J.S.Chung	-	S.W.Lee
O1	JUN 27, 2013	COMMENT ISSUE	S.W.Park	J.S.Chung	-	S.W.Lee
REV. NO.	DATE	DESCRIPTION	PREP'N	REVIEW	QA REVIEW	APPROVAL
REV. NO.	PREPARATION DEPT.	PREPARATION	REVIEW	QA REVIEW	APPROVAL	
Z1	PROCESS	S.W.Park	J.S.Chung	-	S.W.Lee	
		MAY 10, 2016	MAY 10, 2016	-	MAY 10, 2016	

This Document is the property of POSCO Engineering Co., Ltd. Therefore, it shall not be released to Any third party without permission of an authorized personnel of the POSCO Engineering Co., Ltd.

[illegible]



Note: The information in this document is confidential and the property of UOP LLC and must not be disclosed to others or reproduced in any manner or used for any purpose whatsoever without its written permission.



VESSELS

PROJECT SPECIFICATION

963765 — 301

SHEET 3 / 4

REV	DATE	BY	APVD	REV	DATE	BY	APVD
0	27APR12	TS	HDT				

General Notes

- A. Vessels shall be constructed in accordance with the following unless otherwise specified on the individual vessel specification sheet.

Standards:

UOP Standard Specification 3-11

- B. Although the resulting inside diameter may be slightly different than specified, vessels without trays or packing, may be fabricated from pipe.
- C. The dimensioned location of some of the vessel level nozzles may be noted as min (minimum) or max (maximum). It is the responsibility of the contractor to adjust these dimensions to suit the specific level requirements specified on the UOP Piping and Instrument Diagram(s) and on UOP Standard Drawing 8-121. When additional nozzles are required for level instrumentation, the contractor shall specify them consistent with the size, class and facing requirements specified in the UOP Project Specification 301-Vessels and on the UOP Piping and Instrument Diagram(s).
- D. When system of measurement is metric, all dimensions are in millimeters unless noted otherwise.
- E. Contractor shall not locate TI thermowells in a downcomer. Contractor shall also ensure that TI thermowells are located to avoid interference with downcomers, weirs, distributors, collectors, baffles, chimneys, traps and all other vessel internals.
- F. Suppliers (or equal):

Spray Nozzle:

BETE Fog Nozzle Inc.
www.bete.com

Profile Wire Screens:

Johnson Screens
www.johnsonscreens.com

Nagaoka International Corporation
www.nagaokajapan.co.jp

Other specifications
referenced in this
specification:

UOP Standard Specification: 3-11, 3-15, 3-35, 9-11

UOP Standard Drawing: 3-115, 3-116, 3-122, 3-123, 3-144, 3-183, 3-190, 3-264, 3-266, 3-313, 3-322, 8-121

UOP Project Specification: 963765-106, 963765-307



PROJECT SPECIFICATION

963765 - 301

SHEET 4 / 4

REV	DATE	BY	APP'D	REV	DATE	BY	APP'D
0	27MAR12	TS	HDT				

VESSELS

REV

SERVICE COMBINED FEED SURGE DRUM

ITEM NO D-2201

Design	INT	3.5 kg/cm2(g)	@	120° C
Conditions	EXT	FULL VACUUM	@	250° C
at Top	Metal Temperature(Min)			15° C
Operating	VESSEL	0.7 kg/cm2(g)	@	39° C
Conditions			@	

Radiograph	MR
Postweld Heat Treat	MR

	Material	Corrosion Allowance
VESSEL	SA 240 TYPE 304L	1.5
DROP LEG	SA 240 TYPE 304L	1.5

This Vessel is in the Following Service(s):

Hydrogen	NO
Hydrofluoric (HF) Acid	NO
Hydrofluoric (HF) Acid (with Resid. Elem. Control)	NO
Wet Hydrogen Sulfide (H2S)	NO
Cyclic	NO
Caustic	YES
Carbonate	NO
Amine	NO

Vessel Heads

Vessel	2:1 ELLIPTICAL
Drop Leg	2:1 ELLIPTICAL

Accessories Applied by Fabricator

Ladders & Platform Clips	AS REQUIRED
Insulation Clips and Rings	NO
Vessel Support	YES

Nozzles and Manways


Mark	No	Size inches	Service
I01	1	8	INLET
M01	1	24 ID	MANWAY
S01	1	3	STEAMOUT (2)
B02	1	24 ID	MANWAY
G02	1	3	VENT/N2
K02	2	2	LG (2)
L02	2	2	LG (2)
N02	1	12	OUTLET
R02	2	2	PRESSURE (2)
V02	1	3	VENT
U01	1	10	RELIEF
W02	1	3	OUTLET
X02	2	2	LT (2)
Y02	2	2	LT (2)

Class - ASME CL150

(2) ASME CL300

Facing - RAISED FACE

Normal Liquid Level	=	307 mm ABOVE
	=	VESSEL CENTERLINE
Specific Gravity	=	0.847



NOTES

- VESSEL SHALL BE CONSTRUCTED IN ACCORDANCE WITH UOP STANDARD SPECIFICATION 3-15.

Drawings Referred to in this Specification

3-122	3-123	3-266	3-183			
-------	-------	-------	-------	--	--	--