



```
In [29]: 1 # NetworkX Tutorial  
2
```

```
In [30]: 1 import networkx as nx  
2 import numpy as np  
3 import matplotlib.pyplot as plt  
4 from collections import Counter
```


```
In [31]: 1 # Social networks  
2 karate = nx.karate_club_graph()  
3 nx.draw_networkx(karate)
```



```
In [32]: 1 c10 = nx.complete_graph(10)
          2 nx.draw_networkx(c10)
```




```
In [33]: 1 lattice5 = nx.grid_2d_graph(5,5)
          2 nx.draw_networkx(lattice5)
```




```

In [34]: 1 # Erdos Renyi (Random) Graphs:  $G(n, p)$ 
          2 #  $n$  nodes and there is an edge with probability  $p$ 
          3 # The Erdős-Rényi model is interesting because of the
          4 # structural properties of the graphs it generates.
          5 # For example, these graphs undergo a phase transition
          6 # as  $p$  changes. When  $p$  is below a certain threshold,
          7 # the graph will almost surely be composed of many small
          8 # components. When  $p$  is above this threshold, the graph
          9 # will almost surely contain a single giant component
         10 # that includes a large fraction of the nodes, with the
         11 # rest of the nodes forming smaller components. The study
         12 # of these phase transitions and their implications in
         13 # network theory has been a significant focus in the
         14 # field of complex networks.
         15
         16 er = nx.erdos_renyi_graph(500, .05)
         17 nx.draw_networkx(er)

```




```
In [35]: 1 n = 500
2 P = np.linspace(0, .1, 500)
3 cc = []
4 for p in P:
5     G = nx.erdos_renyi_graph(n,p)
6     cc.append(nx.number_connected_components(G))
7
8 plt.xscale('log')
9 plt.scatter(P, cc, marker='.')
10 plt.title("Phase Transition in Connected Components")
11 plt.xlabel("Pr(Edge)")
12 plt.ylabel("# Connected Components")
13 plt.grid()
```




In [36]:

```
1 # \The Barabási–Albert (BA) model is a model of network growth w
2 # which is often used to generate random scale-free networks. Sca
3 # property that the node degrees follow a power law distribution.
4 # by incrementally adding nodes to the network and preferring to
5 # nodes with higher degree.
6 # Applications:
7 # - Internet infrastrucur
8 # - Social networks
9 # - Biological networks
10 #
11 #  $G(n, m)$ :  $n$  = number of nodes,  $m$  = number of edges to attach fro
12 # A. L. Barabási and R. Albert "Emergence of scaling in random ne
13
14 ba = nx.barabasi_albert_graph(500, 1)
15 nx.draw_networkx(ba, with_labels=False, node_size = 50)
16
17
```






In [66]:

```
1 # Watts-Strogatz "Small World" Graphs
2 # Short average path lengths
3 # High clustering
4
5 # Social Networks: In social networks, the small-world phenomenon
6 # "six degrees of separation," the idea being that any two people
7 # connected through a surprisingly small number of mutual acquaintances.
8
9 # Neural Networks: The connections between neurons in the brain also
10 # small-world properties. There is a high level of local clustering
11 # but neurons can also reach other neurons that are far away via
12 # small number of steps.
13
14 # Collaboration Networks: In networks of scientific collaboration
15 # (where nodes are scientists and edges represent collaboration on a
16 # paper), it has been found that most pairs of scientists are connected
17 # through a short path of collaborations, reflecting the small-world
18
19 # Power Grids: The western United States power grid, which was studied
20 # in the original Watts-Strogatz paper, is another example of a small-world
21 # network, where power stations are interconnected in a way that allows
22 # power to be transmitted efficiently across long distances.
23
24 # Not Scale-Free!
25
26
27
28 # Parameters for Watts-Strogatz Graph
29 n = 50 # Number of nodes
30 k = 3 # Each node is connected to k nearest neighbors
31 p = 0.3 # The probability of rewiring each edge
32
33 # Create a Watts-Strogatz graph
34 ws = nx.watts_strogatz_graph(n, k, p)
35
36 # Draw the graph
37 #plt.figure(figsize=(10,10))
38 nx.draw_networkx(ws, with_labels=False, node_size=50)
39 plt.show()
40
41
42
43
```




```
In [38]: 1 def degree_distribution(G):
2         degrees = [deg for node, deg in G.degree()]
3         dd = Counter(degrees)
4         xs = [t[0] for t in dd.items()]
5         ys = [t[1] for t in dd.items()]
6         return xs, ys
7
8 def plot_dd(G, log_scale=True):
9     xs, ys = degree_distribution(G)
10    plt.xlabel('degree')
11    plt.ylabel('frequency')
12    if log_scale:
13        plt.xscale('log')
14        plt.yscale('log')
15    plt.scatter(xs, ys)
16    plt.grid()
17    plt.show()
18
19 plot_dd(ba)
20 plot_dd(er, log_scale=False)
21 plot_dd(ws, log_scale=False)
```





```
In [39]: 1 # Power Law distributions
2 # Frequency = C x Degree ^ (-gamma)
3
4 gamma = -2
5 xs = np.linspace(1, 200, 500)
6 ys = 500 * xs ** gamma
7 plt.scatter(xs, ys)
8 plt.xscale('log')
9 plt.yscale('log')
10 plt.grid()
11 plt.show()
```



Label Propagation is a simple yet efficient method for community detection in graphs. The main idea behind this algorithm is to propagate labels (representing community IDs) throughout the network and form communities based on the process of label propagation.

Here is a basic outline of how the label propagation algorithm works:

1. **Initialization:** Each node is initialized with a unique label (i.e., each node is considered its own community at the beginning).
2. **Propagation Step:** Nodes are visited in a random order. During each visit, the node updates its label to the label that the majority of its neighbors currently have. Ties are broken uniformly and randomly.
3. **Termination:** The algorithm terminates when each node has a label that the maximum number of their neighbors also have. At the end of the propagation step, nodes with the same label are considered to be in the same community.


The Label Propagation algorithm has the advantage of not requiring prior knowledge of the number or sizes of the communities, and it tends to be fast because it only needs to inspect local information and make decisions based on that. However, it can sometimes lead to less

In [146]:


```

1 import networkx as nx
2 import matplotlib.pyplot as plt
3 from networkx.algorithms.community import label_propagation_comm
4
5 def visualize_communities(G, node_size=50, with_labels=False):
6
7     # Detect communities
8     communities = label_propagation_communities(G)
9
10
11     # Map node to a color based on the community it belongs to
12     color_map = {}
13     for idx, com in enumerate(communities):
14         for node in com:
15             color_map[node] = idx
16
17     # Create a list of colors for all nodes in the graph
18     colors = [color_map[node] for node in G.nodes]
19
20     # Draw the graph
21     nx.draw_networkx(G, node_color=colors, with_labels=with_labels)
22     plt.show()
23
24 visualize_communities(karate)
25


```




```
In [147]: 1 visualize_communities(ws)
```



```
In [148]: 1 visualize_communities(er)
```



```
In [149]: 1 visualize_communities(ba)
```



```
In [150]: 1 # Are there "components" or communities" hidden in the protein-pi
          2 # If so, how many?
          3 import pandas as pd
          4 import sqlite3
          5
          6 con = sqlite3.connect('ppi.db')
          7 ppi = pd.read_sql_query("SELECT * FROM ppi", con)
          8 ppi
```

Out[150]:

	a	b
0	ENSG00000000005	ENSG000000061656
1	ENSG00000000005	ENSG000000099968
2	ENSG00000000005	ENSG000000104765
3	ENSG00000000005	ENSG000000105383
4	ENSG00000000005	ENSG000000114455
...
52543	ENSG000000273899	ENSG000000273899
52544	ENSG000000275302	ENSG000000278619
52545	ENSG000000275774	ENSG000000275774
52546	ENSG000000276070	ENSG000000278619
52547	ENSG000000276076	ENSG000000276076

52548 rows × 2 columns

```
In [117]: 1 # Convert to a graph
          2 G_ppi = nx.from_pandas_edgelist(ppi, 'a', 'b', create_using=nx.G
          3 cc_ppi = list(nx.connected_components(G_ppi))
          4 len(list(cc_ppi))
          5 # There are 72 connected components in the PPI data!
```

Out[117]: 72

```
In [151]: 1 # Not so interesting - one big hairball and lots of spurious friends  
2  
3 for i, cc in enumerate(cc_ppi):  
4     print(i, len(cc))
```

```
0 8149
1 3
2 3
3 2
4 2
5 2
6 2
7 1
8 2
9 2
10 2
11 2
12 3
13 2
14 2
15 2
16 2
17 1
18 2
19 2
20 1
21 1
22 2
23 1
24 2
25 3
26 1
27 1
28 2
29 3
30 1
31 2
32 1
33 1
34 1
35 2
36 2
37 2
38 2
39 2
40 1
41 1
42 1
43 1
44 2
45 1
46 1
47 1
48 2
49 1
50 2
51 1
52 1
53 2
54 1
55 2
56 2
```



```

57 1
58 2
59 2
60 2
61 3
62 2
63 1
64 2
65 1
66 3
67 2
68 3
69 2
70 1
71 1

```

```

In [152]: 1 hairball = cc_ppi[0]
          2 G_hairball = G_ppi.subgraph(hairball)
          3 communities = label_propagation_communities(G_hairball)
          4 # communities

```

```

In [153]: 1
          2 for i, community in enumerate(communities):
          3     # print(i, len(community))
          4     if 9 < len(community) < 100:
          5         plt.figure(figsize=(5,5), dpi=100)
          6         print(i, len(community))
          7         subG = G_ppi.subgraph(community)
          8         nx.draw_networkx(subG)
          9         plt.show()


```



18 29



```
In [154]: 1 G68 = G_ppi.subgraph(list(communities)[68])
2 plt.figure(figsize=(15,15), dpi=200)
3 nx.draw_networkx(G68)
```



```
In [145]: 1 G68.nodes()
2 # ENSG00000206172 = HBA2
3 # ENSG00000206172 = HBA1
4 # ENSG00000086506 = HBQ1
5 # ENSG00000244734 = HBB
```

```
Out[145]: NodeView(('ENSG00000206177', 'ENSG00000213931', 'ENSG00000164944',
'ENSG00000223609', 'ENSG00000206172', 'ENSG00000175449', 'ENSG00000086506',
'ENSG00000188536', 'ENSG00000244734', 'ENSG00000196565'))
```

From ChatGPT:

The HBA1, HBA2, and HBQ1 genes all code for components of hemoglobin, the protein molecule in red blood cells that carries oxygen from the lungs to the body's tissues and returns carbon dioxide from the tissues to the lungs.

Here is some specific information about each gene:

HBA1: This gene provides instructions for making a protein called alpha-globin, which is a component (subunit) of hemoglobin. More specifically, it helps produce a form of hemoglobin known as hemoglobin A, which is the most common form of this protein in mature red blood cells.

HBA2: This gene also provides instructions for making alpha-globin. Both HBA1 and HBA2 are located very close to each other on chromosome 16 and together are known as the "alpha-globin locus". Mutations in either or both of these genes can lead to alpha-thalassemia, a blood disorder that reduces the production of hemoglobin.

HBQ1: This gene provides instructions for making a protein called hemoglobin subunit theta 1. This protein is a component of a form of hemoglobin known as hemoglobin A2, which is a minor form of hemoglobin present in small amounts in mature red blood cells. Although the exact function of hemoglobin subunit theta 1 is unclear, it is thought to be involved in the formation of hemoglobin during the development of red blood cells.

So, in summary, all three genes are involved in the production of hemoglobin, but they contribute to different components (subunits) of the protein. Mutations in these genes can lead to conditions such as thalassemia, which affect the body's ability to produce functioning hemoglobin.


Hemoglobin is a protein found in red blood cells that carries oxygen from the lungs to all parts of the body. It is composed of four protein subunits: two alpha globin chains and two beta globin chains in the most common form of hemoglobin in adults, called hemoglobin A (HbA).

There are several genes that contribute to the production of different subunits of hemoglobin:

1. **HBA1 and HBA2:** These genes encode the alpha globin subunits. Both genes are located on chromosome 16.
2. **HBB:** This gene encodes the beta globin subunit, the other component of HbA. HBB is located on chromosome 11.
3. **HBD:** This gene encodes the delta globin subunit. Hemoglobin A2 (HbA2) is a minor form of hemoglobin found in adults that consists of two alpha chains and two delta chains. HBD is located on chromosome 11, close to HBB.
4. **HBG1 and HBG2:** These genes encode the gamma globin subunits. Hemoglobin F (HbF) is the main type of hemoglobin present during fetal development, and it consists of two alpha chains and two gamma chains. After birth, the production of gamma chains decreases and beta chain synthesis increases, leading to the replacement of HbF with HbA in the blood. HBG1 and HBG2 are also located on chromosome 11.
5. **HBE1:** This gene encodes the epsilon globin subunit. Hemoglobin E is a part of embryonic hemoglobin which is expressed in the early stages of embryonic development and then its expression decreases.
6. **HBZ:** This gene encodes the zeta globin subunit. Zeta globin combines with epsilon globin to form hemoglobin Gower-1 ($\zeta\epsilon 2$), and with gamma globin to form hemoglobin Portland-1 ($\zeta\gamma 2$), both of which are embryonic hemoglobins.

7. **HBQ1:** As mentioned before, this gene encodes the theta globin subunit, and its exact function is not very clear.

Each of these genes can undergo mutations that could affect the production and function of hemoglobin, leading to various types of hemoglobinopathies, including different forms of



What is thalassemia?


Thalassemia is a blood disorder passed down through families (inherited) in which the body makes an abnormal form or inadequate amount of hemoglobin, the protein in red blood cells that carries oxygen. The disorder results in excessive destruction of red blood cells, which leads to anemia.

Thalassemia is caused by mutations in the DNA of cells that make hemoglobin — the substance in your red blood cells that carries oxygen throughout your body. The mutations associated with thalassemia are passed from parents to children.


Thalassemias are classified according to which part of the hemoglobin molecule is affected. In alpha thalassemia, production of the alpha globin chain is affected, while in beta thalassemia, production of the beta globin chain is affected.

Thalassemia

Normal



Thalassemia



In []:

1