

.1bn

// Baptiste COMBEAU
// Maël LEMAIRE
// Vivien SINGIER

```
koz fibo.lbn finkoz
```

```
zafer fibo(n)
```

```
ouver
```

```
    kan n piti 2 ouver ran n fèrm
```

```
    ran fibo(n mwin 1) èk fibo(n mwin 2)
```

```
fèrm
```

```
afise(fibo(24))
```

```
koz cordes.lbn finkoz
```

```
zafer batis(n, s)
```

```
ouver
```

```
    kan n piti 1 ouver ran s fèrm
```

```
    ran batis(n mwin 1, s èk "ab")
```

```
fèrm
```

```
zafer repete(k)
```

```
ouver
```

```
    kan k piti 1 ouver ran 0 fèrm
```

```
    batis(60, "")
```

```
    ran repete(k mwin 1)
```

```
fèrm
```

```
afise(batis(5, ">"))
```

```
afise(repete(800))
```

lexer → parser → analyse sémantique → Tree Walking
→ Vm à registres
→ Compilation JIT

Méthode	fibonacci.fibn		cordes.cbn	
	médiane (ms)	gain	médiane (ms)	gain
Tree Walking	71.664	×1	31.502	×1
VM à registre	4.327	×16.6	5.818	×5.4
Compilation JIT	1.465	×48.9 ×3.0 vs VM	4.622	×6.8 ×1.3 vs VM
Gain par rapport au Tree Walking · médiane sur 100 exécutions				