

**Q1.** Given an array of integers `nums` and an integer `target`, return indices of the two numbers such that they add up to `target`.

You may assume that each input would have exactly one solution, and you may not use the same element twice.

You can return the answer in any order.

**Example:** Input: `nums = [2,7,11,15]`, `target = 9` Output: `[0,1]`

**Explanation:** Because `nums[0] + nums[1] == 9`, we return `[0, 1]`

**Ans.** <https://github.com/vivu96/PPT-Assignment/blob/6dd4f3b9f5a6dba7d71c8e21a020541c8c1b963d/OneDArray/src/Question1.java> .

**Q2.** Given an integer array `nums` and an integer `val`, remove all occurrences of `val` in `nums` in-place. The order of the elements may be changed. Then return the number of elements in `nums` which are not equal to `val`. Consider the number of elements in `nums` which are not equal to `val` be `k`, to get accepted, you need to do the following things:

- Change the array `nums` such that the first `k` elements of `nums` contain the elements which are not equal to `val`. The remaining elements of `nums` are not important as well as the size of `nums`.
- Return `k`.

**Example :** Input: `nums = [3,2,2,3]`, `val = 3` Output: `2`, `nums = [2,2,*,*]`

**Explanation:** Your function should return `k = 2`, with the first two elements of `nums` being `2`. It does not matter what you leave beyond the returned `k` (hence they are underscores)

**Ans.** <https://github.com/vivu96/PPT-Assignment/blob/6dd4f3b9f5a6dba7d71c8e21a020541c8c1b963d/OneDArray/src/Question2.java> .

**Q3.** Given a sorted array of distinct integers and a target value, return the index if the target is found. If not, return the index where it would be if it were inserted in order.

**Ans.** <https://github.com/vivu96/PPT-Assignment/blob/6dd4f3b9f5a6dba7d71c8e21a020541c8c1b963d/OneDArray/src/Question4.java> .

**Q4.** You are given a large integer represented as an integer array `digits`, where each `digits[i]` is the *i*th digit of the integer. The digits are ordered from most significant to least significant in left-to-right order. The large integer does not contain any leading 0's.

**Ans.** <https://github.com/vivu96/PPT-Assignment/blob/6dd4f3b9f5a6dba7d71c8e21a020541c8c1b963d/OneDArray/src/Question3.java> .

**Q5.** You are given two integer arrays `nums1` and `nums2`, sorted in non-decreasing order, and two integers `m` and `n`, representing the number of elements in `nums1` and `nums2` respectively.

**Ans.** <https://github.com/vivu96/PPT-Assignment/blob/6dd4f3b9f5a6dba7d71c8e21a020541c8c1b963d/OneDArray/src/Question5.java> .

**Q6.** Given an integer array nums, return true if any value appears at least twice in the array, and return false if every element is distinct.

**Ans.** <https://github.com/vivu96/PPT-Assignment/blob/6dd4f3b9f5a6dba7d71c8e21a020541c8c1b963d/OneDArray/src/Question6.java> .

**Q7.** Given an integer array nums, move all 0's to the end of it while maintaining the relative order of the nonzero elements.

**Ans.** <https://github.com/vivu96/PPT-Assignment/blob/6dd4f3b9f5a6dba7d71c8e21a020541c8c1b963d/OneDArray/src/Question7.java> .

**Q8.** You have a set of integers s, which originally contains all the numbers from 1 to n. Unfortunately, due to some error, one of the numbers in s got duplicated to another number in the set, which results in repetition of one number and loss of another number.

You are given an integer array nums representing the data status of this set after the error.

Find the number that occurs twice and the number that is missing and return them in the form of an array.

**Ans.** <https://github.com/vivu96/PPT-Assignment/blob/6dd4f3b9f5a6dba7d71c8e21a020541c8c1b963d/OneDArray/src/Question8.java> .