

Bulk delete / Clear all + Vehicles as a full record — request, ship, verify

Scope: Admin panel (shipped) and MG-GO rider app (coded, no Play build). Written so each step can be marked pass/fail and handed to a developer without a meeting.

0. Builds and access

Thing	Value
Admin production	https://dpdadmin-prod.vercel.app
Admin commit	cd8ec3b (branch vk-dev) — this is the deployment that owns the production alias
Rider app repo	MG-GO, branch vk-dev, commit 4323af9
Supabase	eoksxkdssptgyqyywdju (production)
Migrations applied	20261030900000 (vehicle RPC), 20261031000000 (bulk-delete gate + purge-all), 20261031100000 (FK guards)
Play build	Not published. The rider-app section can only be verified from a locally built vk-dev build against production.

Accounts needed: (1) super admin, (2) a Manager, (3) a User with *none* of the bulk-delete ticks, (4) a User you can grant exactly one tick to, (5) two riders — one with a vehicle assigned and history, one with no vehicle.

1. What the client requested

- 1. Empty a whole module in one operation instead of ticking rows, **gated by its own permission** — never implied by Edit or Delete.
- 2. **No silent grant:** shipping must not hand the capability to anyone who already exists.
- 3. A **count before the act**, and a typed confirmation — never a single click.
- 4. Cover the modules: drivers, deliveries, requests, visits, earnings, attendance, vehicles, assets, fuel, zones, partners, companies, rules, notifications, e-signature, wrong actions, reconciliation, verifications, payroll.
- 5. Clean the **files** too, not just the rows.
- 6. Vehicles: one identity (plate, not a second "bike ID"), counts on the list, a real detail page, assign a rider from the fleet side, see and assign the rider's assets.
- 7. Riders should see their own vehicle's handover / accident / document / service / asset history in the app, read-only, without exposing paperwork.

2. What we shipped (mapped to the request)

#	Request	Implementation
1	Own permission	New verb <code>bulk_delete</code> added to the staff matrix → <code>{module}.bulk_delete</code> . 22 slugs seeded in <code>admin_permissions</code> ; 24 clearable entities map onto them because rules and payouts borrow <code>earnings.bulk_delete</code> .
2	No silent grant	Role junction and user ticks left empty by the migration. Verified on production: 22 catalogue rows, 0 role grants, 0 user ticks .
3	Never implied by manage / delete	<code>permissionGrantedByTicks</code> returns false for <code>bulk_delete</code> however the ticks are spelled; <code>roleSlugsForSave</code> does not synthesise the slug from CRUD verbs. Pinned by <code>staff-access.test.ts</code> .
4	Count + typed confirm	<code>admin_purge_preview_all(entity)</code> returns the row count and blocker codes; <code>ConfirmDeleteDialog</code> requires the phrase <code>CLEAR {count} {NOUN}</code> .
5	Module coverage	24 entities, go-live order 1→6 (deliveries → reference data). Rules and payouts borrow <code>earnings.bulk_delete</code> .
6	Files cleaned	<code>admin_purge_run_all</code> returns <code>storage_keys</code> + <code>manifest</code> and the server action sweeps storage <i>after</i> the rows are gone.
7	Vehicle identity	Plate (<code>reg_number</code>) is the unique Vehicle ID; <code>bike_id</code> is a slug alias only.
8	Counts on the list	KPI strip: Total, Unassigned, Bike, Car, Active, Replacement; tiles and dropdowns filter the same list.
9	Real detail page	Drivers-style identity header + 6-column field grid; Edit + Assign driver.

#	Request	Implementation
10	Assign rider from fleet	<code>assignVehicleDriver(vehicleId, driverId null)</code> — clears the vehicle from any other rider, writes <code>drivers.vehicle_id + matching driver_intakes.vehicle_id</code> .
11	Rider assets	Vehicle Assets tab lists the rider's assigned assets with Assign (catalogue search + qty, same stock gate) and Add asset; Assets → Assignments gained its own Add.
12	Rider app ledgers	<code>driver_get_assigned_vehicle</code> extended additively : 6 identity fields + 5 arrays, entries <code>{ at, notes, kind, has_file }</code> with no storage key and no signed URL .

3. Permission model — the exact gate

- **Matrix wording:** View data · Add data · Edit data · Delete individual records · **Bulk delete / Clear all data**.
- **Who may clear:** super admin; a Manager (`access_kind = 'manager'` , full catalogue); a User holding that module's individual tick; or a non-custom role that carries the slug. Enforced in the database by `_admin_purge_require(slug)` via `_admin_purge_slug_for_entity(entity)` .
- **Page access:** the route requires `data.cleanup` . That slug is granted automatically to anyone holding a bulk-delete tick, so a User lands on Clear all rather than on a tab whose every request would be refused. The row-by-row candidate tabs and their storage sweeps remain super admin.
- **Not aliased:** holding `{module}.manage` , `.create` , `.edit` or `.delete` clears nothing.

3.1 Read-only SQL proof (safe to run on production)

```
select (select count(*) from admin_permissions
       where slug like '%.bulk_delete')          as catalog_rows,  -- expect 22
(select count(*) from admin_role_permissions
       where permission_slug like '%.bulk_delete') as role_grants,  -- expect 0
(select count(*) from admin_user_permissions
       where permission_slug like '%.bulk_delete') as user_ticks,  -- expect 0
(select count(*) from admin_permissions
       where slug = 'data.cleanup')              as data_cleanup;  -- expect 1
```

3.2 Gate refuses a non-staff session (already proven, re-run if you like)

```
set local role authenticated;          -- simulate a rider session
select admin_purge_preview_all('zones');
-- expected: ERROR P0001: not_authorized
--          CONTEXT: _admin_purge_require(text) line 4 at RAISE
```

Run both statements in one transaction so the role change rolls back with it.

4. Go-live order and blockers

Step	Modules (entity keys)	Slug checked
1	deliveries · attendance · earnings · payouts	deliveries/attendance/earnings <code>.bulk_delete</code>
2	requests · visits · notifications · esign	requests/notifications <code>.bulk_delete</code> , visits/esign category slugs
3	drivers · driver_groups	drivers/driver_groups <code>.bulk_delete</code>
4	vehicles · assets · fuel	vehicles/assets/fuel <code>.bulk_delete</code>
5	restaurants · zones · partners · companies · delivery_rules · incentive_rules	own slugs; the two rule entities borrow <code>earnings.bulk_delete</code>
6	wrong_actions · documents · order_recon · verifications · payroll	own slugs

Blocker codes the preview can return, and their client copy: `blocked_by_deliveries` → “Deliveries still point at these rows.” · `blocked_by_restaurants` → “Restaurants still point at these rows.” · `blocked_by_fuel` → “Fuel log rows still point at these vehicles.”

`admin_purge_run_all(entity, limit)` clamps the batch to 500 rows; the server action loops batches inside a time budget and reports how many are left if it stops early.

QA data-destruction rules. Never run Clear all on production Drivers or Deliveries during testing — that removes real riders and real orders. Use `driver_groups` or `order_recon` for a genuine run, and use the preview-only path (count + blockers) for the rest. A clear is permanent.

5. Verify — Admin

A. Staff Access matrix

- ☐ Super admin → `/en/settings/staff-access`. The module matrix has a fifth column **Bulk delete / Clear all data**.
- ☐ Every existing user shows that column **unticked** (0 grants at ship).
- ☐ Tick *Bulk delete* for one module on the test User and save. Re-open: the tick persisted; no other module's tick changed.
- ☐ On the same user, tick *Delete individual records* only. The bulk-delete column must stay unticked — Delete must not carry it.
- ☐ Untick the bulk-delete tick again and confirm the User loses the Clear all surface (section E).

B. Where the control appears

- ☐ Sidebar → *Settings* → *Data cleanup* is visible to super admin and to a bulk-delete holder, and hidden from a User with none.
- ☐ The page opens on the **Clear all data** tab for a bulk-delete-only User (no row-by-row tabs drawn).
- ☐ As super admin, the row-by-row candidate tabs are still present and still work.
- ☐ List-page **Clear all** buttons exist (destructive + trash icon, visually distinct from Add) on the 14 list pages that have one: drivers, deliveries, requests, visits, zones, partners, assets, fuel, notifications, document expiry, delivery rules, incentive rules, wrong actions, order reconciliation — and are absent when the tick is missing.

C. Preview — count and blockers

- ☐ Open Clear all on **Driver groups**: the button shows a live row count ("N rows"); the dialog title reads "Clear driver groups".
- ☐ Open Clear all on **Zones** while drivers still reference zones: the primary button is disabled and the reason names deliveries/restaurants/fuel as applicable.
- ☐ Repeat after clearing drivers (step D): the block lifts.
- ☐ Confirm the count is the whole module, not selected rows — the banner says so.

D. The run itself

- ☐ Trigger Clear all on **Driver groups**. The typed phrase is required (for example `CLEAR 3 DRIVER GROUPS`); any other text leaves the confirm disabled.
- ☐ Confirm → success toast names the module and the number cleared; the list is empty afterwards.
- ☐ Run it a second time → it finds nothing left (idempotent, no error).
- ☐ If you stop it early (a large module), the toast reports rows cleared *and* rows remaining, and running again continues.
- ☐ Buttons are disabled while the run is in flight (no double submit).

E. Access refusal, both layers

- ☐ As the User with *no* bulk-delete tick: the Clear all control is not drawn anywhere.
- ☐ Call it directly (devtools → invoke the server action or POST the RPC): it is refused, not silently ignored.
- ☐ As a rider session (`set local role authenticated`): `not_authorized`, as in §3.2.
- ☐ As a User holding only `{module}.bulk_delete` for one module: clearing a *different* module is refused.

F. Storage and linked logins

- ☐ Clear a module that had attachments (safe candidate: a driver group is not enough — use order reconciliation or a small request set you created for QA).
- ☐ The storage objects for those rows are gone afterwards, not orphaned.
- ☐ Clearing **Drivers** (only with approval) removes the linked rider app logins, and those riders can no longer sign in with their old passcode.

G. Preserved data

- ☐ After every test run above: `app_settings`, roles, locales, menu layouts and staff profiles are untouched.
- ☐ The two system companies (MG / Unassigned) survive a Companies clear.
- ☐ Audit log (`/en/settings/logs`) has one entry per clear, with the entity and count.

H. Vehicles — list

- ☐ `/en/vehicles` shows the KPI strip: Total, Unassigned, Bike, Car, Active, Replacement.
- ☐ Each tile equals the row count of the list after clicking it; **Unassigned** shows only vehicles with no rider; **Bike/Car** match the kind dropdown.
- ☐ Clicking **Total** clears the KPI-driven filters.

- ❑ No vehicle can be identified by a “bike ID” anywhere a plate should appear.

I. Vehicles — detail and assignment

- ❑ Open a vehicle: plate is the ID badge, with Kind / Condition / Status / On Duty badges beside it.
- ❑ The field grid is six across on a laptop and carries Chassis, Model, Year, Kind, Car type, Type of use, Fuel, Chip, Limit, Location, Owner, Replacement, Driver, MG ID, Phone, Project.
- ❑ **Assign driver** searches by name, MG ID or driver code (recents appear first, the trigger never shows a raw UUID). Saving shows “Driver assignment saved” and the Driver / MG ID / Phone rows update.
- ❑ Assign rider B to a vehicle that already had rider A: A is unassigned (their `vehicle_id` is cleared), and the vehicle shows B.
- ❑ Unassign: the vehicle becomes Unassigned on the list and the KPI count moves.
- ❑ Edit form also offers the driver picker and saves without touching the assignment unexpectedly.

J. Vehicles — assets, and the Assets module

- ❑ Vehicle → **Assets** tab lists the assigned rider’s assets (empty state when none, with the prompt to assign a driver first).
- ❑ **Assign** opens a catalogue search, requires a quantity, respects the stock gate, and the row appears after saving.
- ❑ **Add asset** opens the asset sheet (needs `assets.create`).
- ❑ `/en/assets` → **Assignments** tab now has its own Add (previously only the catalogue tab had one).
- ❑ Assets actions are refused for a user without `assets.manage` / `assets.create`.

K. Companies popup

- ❑ `/en/settings/source-companies` → Edit: wide dialog (~96vw, ~95dvh on a laptop), two columns — fields left, live preview right.
- ❑ Actions sit in the footer (left title/subtitle, right Cancel + primary); the Close X is outside the frame top-right.
- ❑ No inner scrollbar at 1366×768.

6. Verify — Rider app (MG-GO)

Play build is not published. Production Play still shows the old Vehicle tab. Build from branch `vk-dev` (commit `4323af9`) against production Supabase and install on a test phone. Do not file “missing in app” bugs against the Play build for this section.

- ❑ Rider with a vehicle assigned → **Vehicle**: six extra rows appear (Chassis, Year, Condition, Car type, Type of use, Status) when the data exists; missing fields simply do not render.
- ❑ Five sections render below: **Handover, Accident, Documents, Service, Assets**.
- ❑ A section with no history shows its empty line (“No handover records yet.” etc.), not a blank card.
- ❑ Entries show date · kind · notes, newest first, capped at 20.
- ❑ Where a file exists the row shows **File** only — the app never receives, displays or can open a storage path or signed URL (inspect the RPC response and confirm keys are absent).
- ❑ Rider with **no** vehicle assigned: none of another rider’s vehicle data appears.
- ❑ An older payload (simulate by removing the new keys) must not break the screen — the arrays are optional.
- ❑ Arabic: RTL direction correct, no overflow or clipped rows.

7. Automated coverage and commands

```
cd dpdadmin
npm run test:permissions # 30 pass - staff-access + purge entity map
npm run test:vehicles     # 60 pass - KPI filters, list utils, import
npm run test:drivers      # 177 pass
npx tsc --noEmit          # 0 errors
npm run build             # production build, exit 0
```

```
cd MG-GO
flutter test test/assigned_vehicle_test.dart test/fleet_vehicle_ui_test.dart # 9 pass
```

8. Known issues — do not file these as new bugs

Item	State	Evidence
<code>arabic_overflow_test.dart</code> → <i>request detail in Arabic</i> golden	Pre-existing	0.47% (1769px) diff. Reproduced at the commit <i>before</i> this change (<code>6e7b0ab</code>) with identical numbers, so it is not caused by the vehicle work.
<code>arabic_overflow_test.dart</code> → <i>visit ticket in Arabic</i> golden	Pre-existing	5.05% (19027px) diff, identical at <code>6e7b0ab</code> . Environment-dependent golden.

Item	State	Evidence
Rider app Vehicle ledgers on the Play build	Expected	Needs a Play release; see §6.
Two Arabic goldens refresh	Deferred on purpose	Client decision: leave the goldens as they are rather than re-baseline.

9. Engineering appendix

Key files (Admin).

- src/features/settings/purge-entities.ts — the 24 entity → {module}.bulk_delete map, go-live order, permission filter.
- src/features/settings/data-cleanup-actions.ts — preview / run / storage sweep server actions, batch loop and budget.
- src/features/settings/clear-all-module-button.tsx, data-cleanup-clear-all-panel.tsx, data-cleanup-panel.tsx, purge-blockers.ts — UI and blocker copy.
- src/lib/auth/staff-access.ts — bulk_delete never aliased; grantDataCleanupIfBulkDelete.
- src/features/vehicles/* — KPI filters, identity header, assignVehicleDriver, assets tab.
- scripts/release-pdf.mjs — renders this pack and the client note to PDF (the two files beside the HTML).

Key files (MG-GO). lib/features/vehicle/assigned_vehicle.dart, lib/features/vehicle/vehicle_screen.dart, lib/110n/app_{en,ar}.arb, test/assigned_vehicle_test.dart, test/fleet_vehicle_ui_test.dart.

Migrations (already applied to eoksxkdssptgyqyywdju).

- 20261030900000_driver_vehicle_record.sql — additive driver_get_assigned_vehicle.
- 20261031000000_bulk_delete_purge_all.sql — 24 permission rows, _admin_purge_require, _admin_purge_slug_for_entity, admin_purge_preview_all, admin_purge_run_all.
- 20261031100000_bulk_delete_purge_fk_guards.sql — FK-guard nullifications and junction cleanup.

API contract for the rider app: docs/DRIVER_APP_HANDOFF.md → driver_get_assigned_vehicle return shape, including the ledger keys and the explicit statement that no storage key or signed URL is returned.

10. Sign-off

#	Test group	Owner	Pass / Fail	Notes
A	Staff Access matrix			
B	Control visibility			
C	Preview count + blockers			
D	Clear-all run + idempotence			
E	Refusals (UI, action, role, per-module)			
F	Storage + linked logins			
G	Preserved data + audit			
H-J	Vehicles list / detail / assets			
K	Companies popup			
6	Rider app vehicle tab			needs vk-dev build