











Event Handling

Goal of the Class

- Refresh memory of event handling in d3
- The special case of interacting with line type graphs
- Custom events using `d3.dispatch()`







Native event handling: `selection.on()`

```
selection.on(eventType, listener);
```

eventType: a DOM event such as “mouseenter”, “mouseleave”, “click” etc.

listener: a function; anytime the event is fired, this function is invoked with current datum *d* and index *i*

this: the DOM element that emitted the event

Special consideration 1: mouseenter vs. mouseover

<http://bl.ocks.org/mbostock/5247027>

Special consideration 2: multiple listeners

```
selection1.on('click', function(d,i){  
    console.log('First function');  
});  
selection1.on('click', function(d,i){  
    console.log('Second function');  
});
```


Special consideration 2: multiple listeners

```
selection1.on('click.first', function(d,i){  
    console.log('First function');  
});  
selection1.on('click.second', function(d,i){  
    console.log('Second function');  
});
```

`d3.mouse()` **and** `d3.event`

`d3.event` provides specific information about each event within its listener

`d3.mouse(node)` returns the [x, y] coordinate of the mouse within mouse events, relative the DOM node.

The special case of interacting with line type graphs

```
svg.append('path')  
  .datum(array)  
  .on('mousemove',function(d){  
    ...  
  });
```

The special case of interacting with line type graphs

```
svg.append('path')  
  .datum(array)  
  .on('mousemove',function(d){
```

1. using d3.mouse(), discover current mouse position
2. use mouse position to find the nearest point in the array
3. visualize tooltip using the nearest point

```
});
```

d3.bisector()


Returns a **bisect** function









Assuming array is **sorted**, the bisect function returns an insertion point index.

d3.bisector()

```
var bisect = d3.bisector(function(d){return  
d.x}).left;
```

```
var index = bisect(timeSeries, new  
Date(2012,2,3));
```





Advanced events: `d3.dispatch()`

- Allows us to design custom events
- Emitter / subscriber model

Basic usage of d3.dispatch()

1. Create an event dispatcher, and register some custom events

```
var dispatcher1 = d3.dispatch('customEvent1',  
    'customEvent2');
```

2. This dispatcher allows us to emit custom events with any arbitrary arguments

```
dispatcher1.customEvent1(arg1, arg2, arg3...);
```

3. Subscribe to custom events

```
dispatcher1.on('customEvent1', function(arg1,  
    arg2, arg3){  
    ...  
});
```

Basic usage of d3.dispatch()

1. Create an event dispatcher, and register some custom events

```
var dispatcher1 = d3.dispatch('customEvent1',  
    'customEvent2');
```

2. This dispatcher allows us to emit custom events with any arbitrary arguments

```
dispatcher1.customEvent1(arg1, arg2, arg3...);
```

3. Subscribe to custom events

```
dispatcher1.on('customEvent1', function(arg1,  
    arg2, arg3){  
    ...  
});
```

