## *Modifying Route Scripts*

To change or stop/start comm servers:

(1) Open the Citrix Receiver
(2) Open the appbar for the corresponding domain

- Use OpenView to browse the com servers, browse the routing scripts, or configure the comm servers.
- In Controller, you can browse the com servers and find their PIDs.
- In the OUTBOUND_ROUTE routing script, the PIDs are referenced in order to route messages depending on the message type.
- If you need to remove a com server, edit the script to remove the route to its PID.

*Example of removing a route:*

(1) Remove the SET OENROUTE -> ROUTE_LIST [ 2 ]-> R_PID = 1119 line to prevent routing messages to the Hub.
(2) Change the number of entries in the route list from 2 to 1.

*Old Code:*

```
CASE ( MSG_TYPE )
 OF "ADT":
   SET STAT = ALTERLIST ( OENROUTE -> ROUTE_LIST, 2 )
   SET OENROUTE -> ROUTE_LIST [ 1 ]-> R_PID = 1114    /* CorePoint_ADT_OUT */
   SET OENROUTE -> ROUTE_LIST [ 2 ]-> R_PID = 1119    /* RT_CERNERHUB_MULTI_OUT */
   SET OENSTATUS -> STATUS = 1
```

*New Code:*

```
CASE ( MSG_TYPE )
 OF "ADT":
   SET STAT = ALTERLIST ( OENROUTE -> ROUTE_LIST, 1 )
   SET OENROUTE -> ROUTE_LIST [ 1 ]-> R_PID = 1114    /* CorePoint_ADT_OUT */
   SET OENSTATUS -> STATUS = 1
```