

CHAPTER - 9

ARRAYS, STRINGS AND POINTERS

CHAPTER 9

ARRAYS, STRINGS, AND POINTERS

POINTERS TO ARRAYS

POINTERS AND ARRAYS

CHARACTER STRING WITH POINTERS

ARRAYS, STRINGS AND POINTERS

POINTER TO ARRAYS

```
/* A program to display the contents of array using pointer*/
void main()
{
    int a[100];
    int i, j = 0, n;
    printf ("\nEnter the elements of the array\n");
    scanf ("%d", &n);
    printf ("Enter the array elements");
    for (i = 0; i < n; i++)
        scanf ("%d", &a[i]);
    printf ("Array element are");
    for (ptr = a; ptr < (a + n); ptr++)
        printf ("Value of a[%d] = %d stored at address %u",
                j ++, *ptr, ptr);
}
```

ARRAYS, STRINGS AND POINTERS

POINTERS AND ARRAYS


- Pointers and arrays are very closely linked in C.
- Array elements arranged in consecutive memory locations.

```
int a[10], x;
```

```
int *pa;
```

```
pa = &a[0]; /* pa pointer to address of a[0] */
```


```
x = *pa; /* x = contents of pa (a[0] in this case) */
```



ARRAYS, STRINGS AND POINTERS

ARRAYS OF POINTERS

- **Arrays of Pointers are a data representation that will cope efficiently and conveniently with variable length text lines**



ARRAYS, STRINGS AND POINTERS

CHARACTER STRINGS WITH POINTERS

- The *suit* [4] declaration indicates an array of 4 elements. The char * portion of the declaration indicates that each element of array *suit* is of type “*pointer to char*.”
- The suits could have been placed into a double array in which each row would represent one suit, and each column would represent one of the letters of a suit name.

		ace	deuce	three	four	five	six	seven	eight	nine	ten	jack	queen	king
		0	1	2	3	4	5	6	7	8	9	10	11	12
Hearts	0													
Diamonds	1													
Clubs	2													
Spades	3													

suit[2][10] is a Jack of Clubs.

ARRAYS, STRINGS AND POINTERS

EXAMPLES OF POINTER AND STRINGS

```
int strlen (char *s)
{
    int x = 0;
    while (*s != '\0')
    {
        x++;
        s++;
    }
    return(x);
}

int strlen (char *s)
{
    int x = 0;
    while (*s++)
        x++;
    return (x);
}
```

```
strcpy (char *s1, char *s2)
{
    while (*s2 != '\0')
    {
        *s1 = *s2;
        s1++;
        s2++;
    }
}

strcpy (char *s1, char *s2)
{
    while (*s2)
        *s1++ = *s2++;
}
```

ARRAYS, STRINGS AND POINTERS

EXAMPLE USING POINTER

```
#include <stdio.h>

void main ()
{ static char *days[] = {"Sunday", "Monday", "Tuesday",
                          "Wednesday", "Thursday", "Friday", "Saturday"};
  int i;
  for( i = 0; i < 6; ++i )
    printf ( "%s\n", days[i]);
  return;
}
```