

🌐 WEB SERVICE

# Prep-Place

Node

Free

[Upgrade your instance →](#)

Connect ▾

Manual Deploy

Service ID: `srv-d9jm581l565s739p2nvg` 📄

👤 vjjaat63 / Prep-Place 🔑 main

<https://prep-place.onrender.com> 📄

✖ Failed

🔄 37a20f7

32.7s

## Settings

### General

#### Name

A unique name for your Web Service.

Prep-Place

[✎](#) Edit

#### Region

Your services in the same [region](#) can communicate over a [private network](#).

Oregon (US West)

#### Instance Type

**Free**

0.1 CPU 512 MB

Update

❗ Please [enter your payment information](#) to select an instance type with higher limits.

❗ See [remaining free usage](#), or learn about [free service limits](#).

### Build

## Source

The build source for your Web Service

 vjjaat63 / Prep-Place

 Edit

## Branch

The Git branch to build and deploy.

 main

 Edit

## Root Directory Optional

If set, Render runs commands from this directory instead of the repository root. Additionally, code changes outside of this directory do not trigger an auto-deploy. Most commonly used with a [monorepo](#).

backend

 Edit

## Build Command

Render runs this command to build your app before each deploy.

backend/ \$ yarn install

 Edit

## Git Credentials

User providing the credentials to pull the repository.

vjjhahjria63@gmail.com (you)

Use My Credentials

## Build Filters

Include or ignore specific paths in your repo when determining whether to trigger an auto-deploy. Paths are relative to your repo's root directory. [Learn more](#).

 Edit

### Included Paths

Changes that match these paths will trigger a new build.

+ Add Included Path

### Ignored Paths

Changes that match these paths will not trigger a new build.

+ Add Ignored Path

## Deploy

### Pre-Deploy Command Optional

Render runs this command before the start command. Useful for database migrations and static asset uploads.

backend/ \$



Edit

### Start Command

Render runs this command to start your app with each deploy.

backend/ \$ node server.js

Edit

### Auto-Deploy

By default, Render automatically deploys your service whenever you update its code or configuration. Disable to handle deploys manually. [Learn more.](#)

On Commit



Edit

### Deploy Hook

Your private URL to trigger a deploy for this server. Remember to keep this a secret.

.....



Regenerate hook

## Custom Domains

You can point [custom domains](#) you own to this service.

+ Add Custom Domain

### Render Subdomain

If enabled, your service remains reachable at its `onrender.com` subdomain in addition to all custom domains. Disable to serve exclusively from custom domains.

☒ Enabled

Your service is reachable at <https://prep-place.onrender.com>.

## PR Previews

### Pull Request Previews

Spin up temporary instances to test pull requests opened against the main branch of `vjjaat63/Prep-Place`. Choose **Automatic** to preview all PRs, or **Manual** for only PRs with `[render preview]` in their title. [Pull Request Previews](#) create a new instance for just this service. Use [Preview Environments](#) to clone a group of services for every PR.

Off



[Edit](#)

## Networking

## Edge Caching

Serve static content at the edge to improve performance and reduce service load.

[Learn more.](#)

### Cacheable File Types

Specify which file types Render is allowed to cache for your service. You can fine-tune this behavior with `Cache-Control` headers.

None



[Edit](#)

 PAID

Edge Caching is only available for paid instances.

[Upgrade](#)

## Notifications

### Service Notifications

Set notifications to receive for your service. This setting will override your workspace's default settings.

Use workspace default (Only failure notifications)



 Edit

### Preview Environment Notifications

Configure notifications for [preview environments](#) and [service previews](#).

Use account default (Disabled)



 Edit

## Health Checks

### Health Check Path

Provide an HTTP endpoint path that Render messages periodically to monitor your service. [Learn More](#).

 Edit

## Maintenance Mode

### Maintenance Mode

Temporarily disable public access to your service. While enabled, Render serves a static maintenance page for all incoming requests. [Learn more](#).



Maintenance Mode Disabled

### Custom Maintenance Page Optional

If provided, Render uses the specified URL for your maintenance page instead of serving the [default page](#).

 PAID

Maintenance mode is only available for paid instances.

[Upgrade](#)

[Delete Web Service](#)

 [Suspend Web Service](#)

