

SIMATIC S7-1200, Analog input, SM 1231, 4 AI, +/-10 V, +/-5 V, +/-2.5 V, or 0-20 mA/4-20 mA, 12 bit+sign (13 bit ADC)



| General information | |
|--|---|
| Product type designation | SM 1231, AI 4x13 bit |
| Supply voltage | |
| Rated value (DC) <ul style="list-style-type: none">• 24 V DC | Yes |
| Input current | |
| Current consumption, typ. | 45 mA |
| from backplane bus 5 V DC, typ. | 80 mA |
| Power loss | |
| Power loss, typ. | 1.5 W |
| Analog inputs | |
| Number of analog inputs | 4; Current or voltage differential inputs |
| permissible input voltage for current input (destruction limit), max. | ± 35 V |
| permissible input voltage for voltage input (destruction limit), max. | 35 V |
| permissible input current for voltage input (destruction limit), max. | 40 mA |

| | |
|---|--|
| permissible input current for current input (destruction limit), max. | 40 mA |
| Cycle time (all channels) max. | 625 μ s |
| Input ranges | |
| • Voltage | Yes; ± 10 V, ± 5 V, ± 2.5 V |
| • Current | Yes; 4 to 20 mA, 0 to 20 mA |
| • Thermocouple | No |
| • Resistance thermometer | No |
| • Resistance | No |
| Input ranges (rated values), voltages | |
| • -10 V to +10 V | Yes |
| • Input resistance (-10 V to +10 V) | ≥ 9 MOhm |
| • -2.5 V to +2.5 V | Yes |
| • Input resistance (-2.5 V to +2.5 V) | ≥ 9 MOhm |
| • -5 V to +5 V | Yes |
| • Input resistance (-5 V to +5 V) | ≥ 9 MOhm |
| Input ranges (rated values), currents | |
| • 0 to 20 mA | Yes |
| • Input resistance (0 to 20 mA) | 280 Ω |
| • 4 mA to 20 mA | Yes |
| • Input resistance (4 mA to 20 mA) | 280 Ω |
| Analog value generation for the inputs | |
| Integration and conversion time/resolution per channel | |
| • Resolution with overrange (bit including sign), max. | 12 bit; + sign |
| • Integration time, parameterizable | Yes |
| • Interference voltage suppression for interference frequency f1 in Hz | 40 dB, DC to 60 V for interference frequency 50 / 60 Hz |
| Smoothing of measured values | |
| • parameterizable | Yes |
| • Step: None | Yes |
| • Step: low | Yes |
| • Step: Medium | Yes |
| • Step: High | Yes |
| Errors/accuracies | |
| Temperature error (relative to input range), (+/-) | 25 °C $\pm 0.1\%$, to 55 °C $\pm 0.2\%$ total measurement range |
| Basic error limit (operational limit at 25 °C) | |
| • Voltage, relative to input range, (+/-) | 0.1 % |
| • Current, relative to input range, (+/-) | 0.1 % |
| Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency | |
| • Common mode voltage, max. | 12 V |

| | |
|---|---------------------------------------|
| Interrupts/diagnostics/status information | |
| Alarms | Yes |
| Diagnostic functions | Yes |
| Alarms | |
| • Diagnostic alarm | Yes |
| Diagnostic messages | |
| • Monitoring the supply voltage | Yes |
| • Wire-break | Yes |
| Diagnostics indication LED | |
| • for status of the inputs | Yes |
| • for maintenance | Yes |
| Degree and class of protection | |
| Degree of protection acc. to EN 60529 | |
| • IP20 | Yes |
| Standards, approvals, certificates | |
| CE mark | Yes |
| CSA approval | Yes |
| FM approval | Yes |
| RCM (formerly C-TICK) | Yes |
| Marine approval | Yes |
| Ambient conditions | |
| Free fall | |
| • Fall height, max. | 0.3 m; five times, in product package |
| Ambient temperature during operation | |
| • min. | -20 °C |
| • max. | 60 °C |
| • horizontal installation, min. | -20 °C |
| • horizontal installation, max. | 60 °C |
| • vertical installation, min. | -20 °C |
| • vertical installation, max. | 50 °C |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 70 °C |
| Air pressure acc. to IEC 60068-2-13 | |
| • Operation, min. | 795 hPa |
| • Operation, max. | 1 080 hPa |
| • Storage/transport, min. | 660 hPa |
| • Storage/transport, max. | 1 080 hPa |
| Relative humidity | |
| • Operation at 25 °C without condensation, max. | 95 % |
| Pollutant concentrations | |

- SO2 at RH < 60% without condensation

S02: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free

Connection method

required front connector

Yes

Mechanics/material

Enclosure material (front)

- Plastic

Yes

Dimensions

Width

45 mm

Height

100 mm

Depth

75 mm

Weights

Weight, approx.

180 g

last modified:

04/02/2018