Package 'substackR'

June 17, 2025

Title Access Substack Data via API	
Version 0.1.15	
Description An interface to access data from Substack publications via API. Users can fetch the latest, top, search for specific posts, or retrieve a single post by its slug. This functionality is useful for developers and researchers looking to analyze Substack conter integrate it into their applications. For more information, visit the API documentation at https://substackapi.dev/introduction .	
License MIT + file LICENSE	
<pre>URL https://github.com/posocap/substackR</pre>	
BugReports https://github.com/posocap/substackR/issues	
Encoding UTF-8	
RoxygenNote 7.3.2	
Suggests knitr, rmarkdown, testthat (>= 3.0.0)	
Config/testthat/edition 3	
VignetteBuilder knitr	
Imports cli, httr2, rlang	
Depends R (>= 4.1.0)	
NeedsCompilation no	
Author Jason Rand [aut, cre]	
Maintainer Jason Rand <info@posocap.com></info@posocap.com>	
Repository CRAN	
Date/Publication 2025-06-17 06:50:02 UTC	
Contents	
get_substack_latest	

2 get_substack_post

Index 5

Description

Fetch the latest posts from a Substack publication.

Usage

```
get_substack_latest(publication_url, limit = 10L, offset = 0L)
```

Arguments

```
publication_url
```

Character, e.g. "example.substack.com".

limit Integer [1-50], default 10.
offset Integer >= 0, default 0.

Value

A data. frame (possibly zero-row) of post records.

Description

Fetch a single post by its slug. Returns a one-row data. frame, or zero-row if not found.

Usage

```
get_substack_post(publication_url, slug)
```

Arguments

```
publication_url
```

Character.

slug Character. Post slug.

Value

A data. frame with one row (or zero rows if missing).

get_substack_search 3

Description

Search posts in a Substack publication. If zero results, returns an empty data.frame.

Usage

```
get_substack_search(publication_url, query, limit = 10L, offset = 0L)
```

Arguments

publication_url

Character, e.g. "example.substack.com".

query Character. Search term.

limit Integer [1-50], default 10.

offset Integer >= 0, default 0.

Value

A data.frame (possibly zero-row).

get_substack_top Top Posts

Description

Fetch the most popular posts from a Substack publication.

Usage

```
get_substack_top(publication_url, limit = 10L, offset = 0L)
```

Arguments

publication_url

Character, e.g. "example.substack.com".

limit Integer [1-50], default 10. offset Integer >= 0, default 0.

Value

A data. frame (possibly zero-row) of post records.

4 set_substack_key

set_substack_key

Set your Substack API Key

Description

Store your key once per session. Subsequent calls to other functions will use this key automatically.

Usage

```
set_substack_key(key)
```

Arguments

key

A single string: your Substack API key.

Value

Invisibly TRUE if successful.

Index

```
get_substack_latest, 2
get_substack_post, 2
get_substack_search, 3
get_substack_top, 3
set_substack_key, 4
```