

# Package ‘ggsced’

January 21, 2026

**Type** Package

**Title** Utilities and Helpers for Single Case Experimental Design (SCED)  
using 'ggplot2'

**Version** 0.1.6

**Description** Provides specialized visualization tools for Single-Case Experimental Design (SCED) research using 'ggplot2'. SCED studies are a crucial methodology in behavioral and educational research where individual participants serve as their own controls through carefully designed experimental phases. This package extends 'ggplot2' to create publication-ready graphics with professional phase change lines, support for multiple baseline designs, and styling functions that follow SCED visualization conventions. Key functions include adding phase change demarcation lines to existing plots and formatting axes with broken axis appearance commonly used in single-case research.

**License** GPL (>= 2)

**Encoding** UTF-8

**LazyData** true

**Depends** ggplot2, ggh4x, R (>= 3.5.0)

**Imports** grid, gtable, assert

**Suggests** knitr, rmarkdown, testthat (>= 3.0.0), usethis, tidyverse

**RoxygenNote** 7.2.3

**Config/testthat/edition** 3

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Shawn Gilroy [aut, cre, cph] (ORCID:  
<<https://orcid.org/0000-0002-1097-8366>>)

**Maintainer** Shawn Gilroy <[sgilroy1@lsu.edu](mailto:sgilroy1@lsu.edu)>

**Repository** CRAN

**Date/Publication** 2026-01-21 20:10:14 UTC

Contents

ggsced . . . . .	2
ggsced_condition_labels . . . . .	3
ggsced_extract_domain . . . . .	3
ggsced_facet_labels . . . . .	4
ggsced_get_panels . . . . .	4
ggsced_internal_x_axis . . . . .	5
ggsced_internal_y_axis . . . . .	5
ggsced_name_dogleg . . . . .	6
ggsced_name_dogleg_lateral . . . . .	6
ggsced_output_console . . . . .	7
ggsced_scale_units . . . . .	7
ggsced_style_x . . . . .	8
ggsced_style_y . . . . .	8
Gilroyetal2015 . . . . .	9
Gilroyetal2021 . . . . .	9
sced_phase_change_complex_lateral_grob . . . . .	10
sced_phase_change_complex_lateral_post_grob . . . . .	11
sced_phase_change_complex_lateral_pre_grob . . . . .	11
sced_phase_change_main_panel_grob . . . . .	12
sced_phase_change_simple_lateral_grob . . . . .	12
<b>Index</b>	<b>13</b>

---

ggsced	<i>ggsced</i>
--------	---------------

---

Description

Core exported function to facilitate the drawing of phase change lines atop a ggplot object. Primarily designed to be used *after* the plot is finalized, with the lines being the last element drawn at the highest z index (i.e., atop all elements).

Usage

```
ggsced(plt, legs, offs = NULL, print = TRUE, verbose = FALSE)
```

Arguments

plt	ggplot object as typically designed/printed in userspace
legs	list of 'legs' to be drawn
offs	mapping of lines that require minor offset
print	output result directly to graphical device (default = TRUE)
verbose	Optional ability to view process output (debugging primarily)

**Value**

Finalized figure with respective phase change lines embedded.

---

ggsced\_condition\_labels  
*generate\_condition\_labels*

---

**Description**

Optional helper class to prepare condition labels (e.g., Baseline, Intervention) based on the grouping of an existing ggplot object

**Usage**

```
ggsced_condition_labels(plt, y = NULL)
```

**Arguments**

plt	ggplot object
y	ordinate of respective label (Default = last tick from plot object)

**Value**

a data frame that can be used with a geom\_text layer

---

ggsced\_extract\_domain *ggsced\_extract\_domain*

---

**Description**

Internal helper to pull respective panel parameters and assert validity.

**Usage**

```
ggsced_extract_domain(panel_params)
```

**Arguments**

panel_params	respective parameters of panel grob
--------------	-------------------------------------

**Value**

numeric vector specifying size in min-max units

---

<code>ggsced_facet_labels</code>	<i><code>ggsced_facet_labels</code></i>
----------------------------------	---

---

### Description

Optional helper class to prepare facet labels (e.g., Participant names) based on the faceting of an existing ggplot object

### Usage

```
ggsced_facet_labels(plt, y = 0, x = NULL)
```

### Arguments

<code>plt</code>	ggplot object
<code>y</code>	ordinate of respective label (typically very low or very high)
<code>x</code>	position on the x-axis (Default = last tick from plot object)

### Value

a data frame that can be used with a `geom_text` layer

---

<code>ggsced_get_panels</code>	<i><code>ggsced_get_panels</code></i>
--------------------------------	---------------------------------------

---

### Description

Honestly, a bit of a 'hackish' solution to extract grobs that are associated with data to be drawn. Probably fragile and specific to modern gg implementations, but probably the close we'll get. Subject to change.

### Usage

```
ggsced_get_panels(ggplot_grobs)
```

### Arguments

<code>ggplot_grobs</code>	list of grobs prepared by <code>ggplotGrob</code>
---------------------------	---

### Value

filtered list of grobs restricted to faceted levels

---

```
ggsced_internal_x_axis  
  ggsced_internal_x_axis
```

---

**Description**

Internal helper class to draw a conventional x-axis per SCED publication suggestions.

**Usage**

```
ggsced_internal_x_axis(expansion = 0, lwd = 2, col = "black")
```

**Arguments**

expansion	Percentage of axis to pad (left/right) to break axis (Note: normalized parent units)
lwd	Width of axis line
col	Color of axis drawn (default = 'black')

**Value**

Rendering of customized x axis across facets

---

```
ggsced_internal_y_axis  
  ggsced_internal_y_axis
```

---

**Description**

Internal helper class to draw a conventional y-axis per SCED publication suggestions.

**Usage**

```
ggsced_internal_y_axis(expansion = 0, lwd = 2, col = "black")
```

**Arguments**

expansion	Percentage of axis to pad (top/bottom) to break axis (Note: normalized parent units)
lwd	Width of axis line
col	Color of axis drawn (default = 'black')

**Value**

Rendering of customized y axis across facets

---

<code>ggscd_name_dogleg</code>	<i><code>ggscd_name_dogleg</code></i>
--------------------------------	---------------------------------------

---

**Description**

Grobs need to have unique names lest they get accidentally overwritten. This is a convenience naming function for the 'main' phase break within a facet level.

**Usage**

```
ggscd_name_dogleg(panel, index, n_leg)
```

**Arguments**

<code>panel</code>	name of the parent grob
<code>index</code>	index of the phase change in sequence
<code>n_leg</code>	leg in the phase change

**Value**

a name corresponding with unique phase-change grob element

---

<code>ggscd_name_dogleg_lateral</code>	<i><code>ggscd_name_dogleg_lateral</code></i>
--	---

---

**Description**

Grobs need to have unique names lest they get accidentally overwritten. This is a convenience naming function for the 'lateral' part of a phase break within a facet level.

**Usage**

```
ggscd_name_dogleg_lateral(panel, index, n_leg)
```

**Arguments**

<code>panel</code>	name of the parent grob
<code>index</code>	index of the phase change in sequence
<code>n_leg</code>	leg in the phase change

**Value**

a name corresponding with unique phase-change grob element

---

ggsced_output_console	<i>ggsced_output_console</i>
-----------------------	------------------------------

---

**Description**

Optional output function to support debugging (mainly for testing)

**Usage**

ggsced\_output\_console(msg, output)

**Arguments**

- |        |   |
|--------|---|
| msg    | Message to be output to console                     |
| output | Boolean to discern whether or not to output message |

---

ggsced_scale_units	<i>ggsced_scale_units</i>
--------------------	---------------------------

---

**Description**

Internal helper to discern exactly where a vertical would need to be placed within a specific grob (i.e., panel grob). Uses the domain and phase change location as a reference to convert to npc units for gtable and grid.

**Usage**

ggsced\_scale\_units(session\_value, domain\_size)

**Arguments**

- |               |  |
|---------------|--|
| session_value | Session associated with phase-change line    |
| domain_size   | Total size of domain per panel specification |

**Value**

A proportional value given value in a panel domain

---

ggsced_style_x	ggsced_style_x
----------------	----------------

---

**Description**

This is a convenience element designed to support a more complete interpretation of SCED-specific style conventions through ggplot. Specifically, an axis is drawn with a specific manner of expansion to support the broken axis (i.e., non-connected x/y) expected of SCED-specific publication guidelines.

**Usage**

```
ggsced_style_x(expansion = 0, lwd = 2, col = "black")
```

**Arguments**

expansion	Percentage of axis to pad (left/right) to break axis (Note: normalized parent units)
lwd	Width of axis line
col	Color of axis drawn (default = 'black')

**Value**

Annotation to simulate a disconnected y-axis via expansion

---

ggsced_style_y	ggsced_style_y
----------------	----------------

---

**Description**

This is a convenience element designed to support a more complete interpretation of SCED-specific style conventions through ggplot. Specifically, an axis is drawn with a specific manner of expansion to support the broken axis (i.e., non-connected x/y) expected of SCED-specific publication guidelines.

**Usage**

```
ggsced_style_y(expansion = 0, lwd = 2, col = "black")
```

**Arguments**

expansion	Percentage of axis to pad (top/bottom) to break axis (Note: normalized parent units)
lwd	Width of axis line
col	Color of axis drawn (default = 'black')



**Value**

Annotation to simulate a disconnected y-axis via expansion

---

Gilroyetal2015	<i>Plotting data from Gilroy et al. (2015)</i>
----------------	--

---

**Description**

This is data either extracted or included (with permission) to assist with illustrating and replicating the functionality of the package. Specifically, this data is used to illustrate conventions regarding a multiple probe design and how that may be constructed in this package.

**Usage**

Gilroyetal2015

**Format**

A data frame with 40 rows and 6 variables:

**Participant** Participant name

**Session** Session number

**Condition** Condition name

**Responding** Responding rates

**PhaseNum** Phase number

**LineOff** Offset for phase line

**Source**

<doi:https://doi.org/10.1016/j.rasd.2015.04.004>

---

Gilroyetal2021	<i>Plotting data from Gilroy et al. (2021)</i>
----------------	--

---

**Description**

Treatment data from Gilroy et al. (2021)

**Usage**

Gilroyetal2021

**Format**

A data frame with 69 rows and 7 variables:

- Participant** Participant name
- Session** Session number
- Condition** Functional analysis condition
- Responding** Rates of responding
- Reinforcers** Reinforcer deliveries
- PhaseNum** Sequenced phase number
- LineOff** Offset of phase line

**Source**

<doi:https://doi.org/10.1002/jaba.826>

---

sced_phase_change_complex_lateral_grob
<i>sced_phase_change_complex_lateral_grob</i>

---

**Description**

This is a helper class to standardize drawing grobs

**Usage**

sced\_phase\_change\_complex\_lateral\_grob(x0, x1, segment\_name)

**Arguments**

- |              |   |
|--------------|---|
| x0           | value corresponding to respective domain in npc units |
| x1           | value corresponding to respective domain in npc units |
| segment_name | name associated with object                           |

**Value**

graphical object

---

<i>sced_phase_change_complex_lateral_post_grob</i>
<i>sced_phase_change_complex_lateral_post_grob</i>

---

**Description**

This is a helper class to standardize drawing grobs

**Usage**

`sced_phase_change_complex_lateral_post_grob(x, segment_name)`

**Arguments**

- `x` value corresponding to respective domain in npc units
- `segment_name` name associated with object

**Value**

graphical object

---

<i>sced_phase_change_complex_lateral_pre_grob</i>
<i>sced_phase_change_complex_lateral_pre_grob</i>

---

**Description**

This is a helper class to standardize drawing grobs

**Usage**

`sced_phase_change_complex_lateral_pre_grob(x, segment_name)`

**Arguments**

- `x` value corresponding to respective domain in npc units
- `segment_name` name associated with object

**Value**

graphical object

---

<i>sced_phase_change_main_panel_grob</i>
<i>sced_phase_change_main_panel_grob</i>

---

**Description**

This is a helper class to standardize drawing grobs

**Usage**

`sced_phase_change_main_panel_grob(x, segment_name)`

**Arguments**

- `x` value corresponding to respective domain in npc units
- `segment_name` name associated with object

**Value**

graphical object

---

<i>sced_phase_change_simple_lateral_grob</i>
<i>sced_phase_change_simple_lateral_grob</i>

---

**Description**

This is a helper class to standardize drawing grobs

**Usage**

`sced_phase_change_simple_lateral_grob(x0, x1, segment_name)`

**Arguments**

- `x0` value corresponding to respective domain in npc units
- `x1` value corresponding to respective domain in npc units
- `segment_name` name associated with object

**Value**

graphical object

# Index

## \* datasets

Gilroyetal2015, [9](#)

Gilroyetal2021, [9](#)

ggsced, [2](#)

ggsced\_condition\_labels, [3](#)

ggsced\_extract\_domain, [3](#)

ggsced\_facet\_labels, [4](#)

ggsced\_get\_panels, [4](#)

ggsced\_internal\_x\_axis, [5](#)

ggsced\_internal\_y\_axis, [5](#)

ggsced\_name\_dogleg, [6](#)

ggsced\_name\_dogleg\_lateral, [6](#)

ggsced\_output\_console, [7](#)

ggsced\_scale\_units, [7](#)

ggsced\_style\_x, [8](#)

ggsced\_style\_y, [8](#)

Gilroyetal2015, [9](#)

Gilroyetal2021, [9](#)

sced\_phase\_change\_complex\_lateral\_grob,

[10](#)

sced\_phase\_change\_complex\_lateral\_post\_grob,

[11](#)

sced\_phase\_change\_complex\_lateral\_pre\_grob,

[11](#)

sced\_phase\_change\_main\_panel\_grob, [12](#)

sced\_phase\_change\_simple\_lateral\_grob,

[12](#)