Package 'AeroSampleR'

January 5, 2023

variatif 5, 2025
Type Package
Title Estimate Aerosol Particle Collection Through Sample Lines
Version 0.2.0
Author Mark Hogue
Maintainer Mark Hogue <mark.hogue.chp@gmail.com></mark.hogue.chp@gmail.com>
Description Estimate ideal efficiencies of aerosol sampling through sample lines. Functions were developed consistent with the approach described in Hogue, Mark; Thompson, Martha; Farfan, Eduardo; Hadlock, Dennis, (2014), "Hand Calculations for Transport of Radioactive Aerosols through Sampling Systems" Health Phys 106, 5, S78-S87, <doi:10.1097 hp.000000000000000000000000000000000000<="" td=""></doi:10.1097>
License GPL-3
Encoding UTF-8
LazyData true
Imports dplyr, purrr, tidyr, ggplot2, ggthemes, stringr, tidyselect, flextable
RoxygenNote 7.2.1
Depends R (>= 3.4)
Suggests knitr, rmarkdown
VignetteBuilder knitr
NeedsCompilation no
Repository CRAN
Date/Publication 2023-01-05 21:30:18 UTC
R topics documented:
AeroSampleR

2 bend_eff

Index																				12
	tube_eff		 •			 				 •	•	•				•	•	•	•	10
	set_params_2 .					 														9
	set_params_1 .					 														9
	report_plots					 														8
	report_log_mass					 														7
	report_cum_plots	s .				 														7
	report_basic																			

AeroSampleR

Estimate Aerosol Particle Collection Through Sample Lines

Description

This package provides a method to estimate sampling efficiency of sampling systems drawing aerosol particles through tubing.

Details

Functions were developed consistent with the approach described in Hogue, Mark; Thompson, Martha; Farfan, Eduardo; Hadlock, Dennis, (2014), "Hand Calculations for Transport of Radioactive Aerosols through Sampling Systems" Health Phys 106, 5, S78-S87, <doi:10.1097/HP.0000000000000092>.

To learn how to use AeroSampleR, start with the vignette: 'browseVignettes(package = "AeroSampleR")'

bend_eff

bend efficiency

Description

In order to run this function, first produce a particle distribution with the 'particle_dist' function, then produce a parameter set with the 'set_params' function. Both of these results must be stored as per examples described in the help set with each.

Usage

```
bend_eff(df, params, method, bend_angle, bend_radius, elnum)
```

Arguments

df is the particle data set (data frame) established with the 'particle_dist' function params is the parameter data set for parameters that are not particle size-dependent

method choice of models: Pui, McFarland, or Zhang

bend_angle bend angle in degrees bend_radius bend radius in m

elnum element number to provide unique column names

dat_for_plots 3

Value

data frame containing original particle distribution with added data for this element

References

A. R. McFarland, H. Gong, A. Muyshondt, W. B. Wente, and N. K. Anand Environmental Science & Technology 1997 31 (12), 3371-3377 <doi:10.1021/es960975c>

Pusheng Zhang, Randy M. Roberts, André Bénard, Computational guidelines and an empirical model for particle deposition in curved pipes using an Eulerian-Lagrangian approach, Journal of Aerosol Science, Volume 53, 2012, Pages 1-20,ISSN 0021-8502, <doi:10.1016/j.jaerosci.2012.05.007>

David Y. H. Pui, Francisco Romay-Novas & Benjamin Y. H. Liu (1987) Experimental Study of Particle Deposition in Bends of Circular Cross Section, Aerosol Science and Technology, 7:3, 301-315, <doi:10.1080/02786828708959166>

Examples

```
df <- particle_dist() # set up particle distribution
params <- set_params_1("D_tube" = 2.54, "Q_lpm" = 100,
"T_C" = 25, "P_kPa" = 101.325) #example system parameters
df <- set_params_2(df, params) #particle size-dependent parameters
df <- probe_eff(df, params, orient = 'h') #probe orientation - horizontal
df <- bend_eff(df, params, method='Zhang', bend_angle=90,
bend_radius=0.1, elnum=3)
head(df)</pre>
```

dat_for_plots

Data from readme file for use in plot examples

Description

This data was created by running the readme script. It is needed for simple plot examples.

Usage

```
dat_for_plots
```

Format

A data.frame

D_p particle diameter in micrometers

dens probability density

dist either log_norm or discrete

C_c Cunningham slip correction factor

v_ts particle terminal velocity

Re_p Reynold's number for particle

4 particle_dist

```
Stk Stokes' number for particle
eff_probe aspiration efficiency for probe
eff_bend_2 transport efficiency for the second component, a bend
eff_tube_3 transport efficiency for the third component, a straight tube
```

particle_dist

Create a particle distribution

Description

Needed as a first step in estimating system efficiency. Make the data frame that will be used to estimate efficiency of variously sized aerosol particles' transport through the sampling system. To create your data, save this data to the global environment as shown in the examples.

Usage

```
particle_dist(
   AMAD = 5,
   log_norm_sd = 2.5,
   log_norm_min = 5e-04,
   log_norm_max = 100,
   discrete_vals = c(1, 5, 10)
)
```

Arguments

```
AMAD default is 5 based on ICRP 66
log_norm_sd default is 2.5 based on ICRP 66
log_norm_min default is 0.0005 based on ICRP 66
log_norm_max default is 100 based on ICRP 66
discrete_vals default is c(1, 5, 10)
```

Details

All inputs are in micron AMAD, meaning: the aerodynamic diameter of a particle is the diameter of a standard density (1000 kg/m3) sphere that has the same gravitational settling velocity as the particle in question.

Value

a data frame containing a lognormally distributed set of particles and discrete particle sizes

probe_eff 5

Examples

probe_eff

Probe efficiency

Description

In order to run this function, first produce a particle distribution with the 'particle_dist' function, then produce a parameter set with the 'set_params' function. Both of these results must be stored as per examples described in the help set with each.

Usage

```
probe_eff(df, params, orient = "u", method = "blunt pipe")
```

Arguments

df	is the particle data set (data frame) established with the 'particle_dist' function
params	is the parameter data set for parameters that are not particle size-dependent
orient	orientation of the probe. Options are 'u' for up, 'd' for down, and 'h' for horizontal $% \left(1\right) =\left(1\right) \left(1\right) \left$
method	is the model for the probe efficiency. Default is 'blunt pipe', based on Su WC and Vincent JH, Towards a general semi-empirical model for the aspiration efficiencies of aerosol samplers in perfectly calm air, Aerosol Science 35 (2004) 1119-1134

Value

data frame containing original particle distribution with added data for this element

```
df <- particle_dist() # set up particle distribution
params <- set_params_1("D_tube" = 2.54, "Q_lpm" = 100,
"T_C" = 25, "P_kPa" = 101.325) #example system parameters
df <- set_params_2(df, params) #particle size-dependent parameters
df <- probe_eff(df, params, orient = 'u') #probe orientation - draws upward
head(df)</pre>
```

report_basic

re	nor	t r	asi	\mathcal{C}

report on transport efficiency

Description

In order to run a report, first produce a model of each individual element. Start with producing a particle distribution with the 'particle_dist' function, then produce a parameter set with the 'set_params' function. Both of these results must be stored as per examples described in the help set with each. Next, add elements in the sample system until all are complete.

Usage

```
report_basic(df, params, dist)
```

Arguments

df	is the particle data set (data frame) established with the 'particle_dist' function
params	is the parameter data set for parameters that are not particle size-dependent
dist	selects the distribution for the report. Options are 'discrete' for discrete particle sizes or 'log' for the log-normal distribution of particles that were started with the 'particle_dist' function.

Value

report of system efficiency

```
df <- particle_dist() # set up particle distribution
params <- set_params_1("D_tube" = 2.54, "Q_lpm" = 100,
"T_C" = 25, "P_kPa" = 101.325) #example system parameters
df <- set_params_2(df, params) #particle size-dependent parameters
df <- probe_eff(df, params, orient = 'h') #probe orientation - horizontal
df <- bend_eff(df, params, method='Zhang', bend_angle=90,
bend_radius=0.1, elnum=3)
df <- tube_eff(df, params, L = 100,
angle_to_horiz = 90, elnum = 3)
report_basic(df, params, dist = 'discrete')</pre>
```

report_cum_plots 7

report_cum_plots	report on cumulative transport system efficiency (discrete particle sizes only)

Description

In order to run a report, first produce a model of each individual element. Start with producing a particle distribution with the 'particle_dist' function, then produce a parameter set with the 'set_params' function. Both of these results must be stored as per examples described in the help set with each. Next, add elements in the sample system until all are complete.

Usage

```
report_cum_plots(df, micron)
```

Arguments

df is the particle data set - after transport analysis by element

micron selects the particle size (aerodynamic mass activity diameter in micrometers).

This must be selected from the original distribution of particles that were started

with the 'particle_dist' function.

Value

A plot of cumulative transport efficiencies is generated in a plot window

Examples

```
report_cum_plots(dat_for_plots, micron = 10)
```

report_log_mass

report relative masses by particle of a log-normal distribution

Description

This function shows the entire table of results by particle diameter.

Usage

```
report_log_mass(df)
```

Arguments

df

is the particle data set - after transport analysis by element

8 report_plots

Value

data frame containing mass-based particle fractions in ambient location and in distribution delivered through the system.

Examples

```
df <- particle_dist() # set up particle distribution
params <- set_params_1("D_tube" = 2.54, "Q_lpm" = 100,
"T_C" = 25, "P_kPa" = 101.325) #example system parameters
df <- set_params_2(df, params) #particle size-dependent parameters
df <- probe_eff(df, params, orient = 'h') #probe orientation - horizontal
df <- bend_eff(df, params, method='Zhang', bend_angle=90,
bend_radius=0.1, elnum=3)
df <- tube_eff(df, params, L = 100,
angle_to_horiz = 90, elnum = 3)
report_log_mass(df)</pre>
```

report_plots

plots of individual on transport system elements

Description

In order to run a report, first produce a model of each individual element. Start with producing a particle distribution with the 'particle_dist' function, then produce a parameter set with the 'set_params' function. Both of these results must be stored as per examples described in the help set with each. Next, add elements in the sample system until all are complete.

Usage

```
report_plots(df, dist)
```

Arguments

df is the particle data set - after transport analysis by element

dist selects the distribution for the report. Options are 'discrete' for discrete particle

sizes or 'log' for the log-normal distribution of particles that were started with

the 'particle_dist' function.

Value

A plot of transport efficiencies is generated in a plot window

```
report_plots(dat_for_plots, dist = 'discrete')
```

set_params_1

set_params_1	Set parameters (not particle size specific)	
--------------	---	--

Description

Make a set of parameters that will be used throughout this package. 'set_params_1' sets all single parameters. 'set_params_2' adds particle-size-dependent parameters to the particle distribution

Usage

```
set_params_1(D_tube_cm, Q_lpm, T_C = 20, P_kPa = 101.325)
```

Arguments

D_tube_cm Inside diameter of tubing in cm, no default

Q_lpm System flow in lpm, no default T_C System temperature in Celsius

P_kPa System pressure in kPa (Pa is the MKS unit)

Details

All parameters are to be in MKS units, except as noted.

Value

```
a data frame with singular parameters examples params <- set_params_1("D_tube" = 2.54, "Q_lpm" = 100, "T_C" = 25, "P_kPa" = 101.325) t(params)
```

set_params_2

Make a set of particle-size-dependent parameters

Description

This set of parameters will be used for evaluation of transport efficiency for particle-size-dependent parameters.

Usage

```
set_params_2(df, params)
```

Arguments

df is the particle data set (data frame) established with the 'particle_dist' function params is the parameter data set for parameters that are not particle size-dependent

10 tube_eff

Details

No user-selected arguments are needed. Parameters are used in efficiency functions. For each particle diameter, an entry is made in the data frame for the Cunningham slip correction factor, the particle terminal velocity, the particle Reynold's number, and the Stokes factor.

'set_params_1' sets all single parameters. 'set_params_2' adds particle size-dependent parameters to the particle distribution

Value

a data frame starting with the submitted particle distribution with additional columns for particle-size-dependent parameters

Examples

```
df <- particle_dist()
params <- set_params_1("D_tube" = 2.54, "Q_lpm" = 100,
"T_C" = 25, "P_kPa" = 101.325)
df <- set_params_2(df, params)
head(df)</pre>
```

tube_eff

Tube efficiency

Description

Computation is consistent with the approach described in Hogue, Mark; Thompson, Martha; Farfan, Eduardo; Hadlock, Dennis, (2014), "Hand Calculations for Transport of Radioactive Aerosols through Sampling Systems" Health Phys 106, 5, S78-S87, <doi:10.1097/HP.00000000000000092>, with the exception that the diffusion deposition mechanism is included.

Usage

```
tube_eff(df, params, L_cm, angle_to_horiz, elnum)
```

Arguments

df is the particle data set (data frame) established with the 'particle_dist' function params is the parameter data set for parameters that are not particle size-dependent

L_cm tube length, cm

angle_to_horiz angle to horizontal in degrees

elnum element number to provide unique column names

Details

In order to run this function, first produce a particle distribution with the 'particle_dist' function, then produce a parameter set with the 'set_params' function. Both of these results must be stored as per examples described in the help set with each.

tube_eff 11

Value

data frame containing original particle distribution with added data for this element

```
# Example output is a sample of the full particle data set.
# laminar flow (Reynolds number < 2100)</pre>
df <- particle_dist() # distribution</pre>
params <- set_params_1("D_tube" = 2.54, "Q_lpm" = 20,</pre>
"T_C" = 25, "P_kPa" = 101.325) #example system parameters
df <- set_params_2(df, params) #particle size-dependent parameters</pre>
df <- probe_eff(df, params, orient = 'h') #probe orientation - horizontal</pre>
df <- tube_eff(df, params, L_cm = 100,</pre>
angle_to_horiz = 90, elnum = 2)
(df[sort(sample(1:1000, 10)), ])
# turbulent flow (Reynolds number > 4000)
df <- particle_dist() # distribution</pre>
params <- set_params_1("D_tube" = 2.54, "Q_lpm" = 100,</pre>
"T_C" = 25, "P_kPa" = 101.325) #example system parameters
df <- set_params_2(df, params) #particle size-dependent parameters</pre>
df <- probe_eff(df, params, orient = 'h') #probe orientation - horizontal</pre>
df <- tube_eff(df, params, L_cm = 100,</pre>
angle_to_horiz = 90, elnum = 2)
(df[sort(sample(1:1000, 10)), ])
# midrange flow (Reynolds number > 2100 and < 4000)</pre>
df <- particle_dist() # distribution</pre>
params <- set_params_1("D_tube" = 2.54, "Q_lpm" = 60,
"T_C" = 25, "P_kPa" = 101.325) #example system parameters
df <- set_params_2(df, params) #particle size-dependent parameters</pre>
df <- probe_eff(df, params, orient = 'h') #probe orientation - horizontal
df <- tube_eff(df, params, L_cm = 100,</pre>
angle_to_horiz = 90, elnum = 2)
(df[sort(sample(1:1000, 10)), ])
```

Index

```
* datasets
dat_for_plots, 3

AeroSampleR, 2

bend_eff, 2

dat_for_plots, 3

particle_dist, 4
probe_eff, 5

report_basic, 6
report_cum_plots, 7
report_log_mass, 7
report_plots, 8

set_params_1, 9
set_params_2, 9

tube_eff, 10
```