Package 'SFDesign'

May 8, 2025

Type Package

Title Space-Filling Designs			
Version 0.1.0			
Date 2025-04-25			
Maintainer Shangkun Wang <shangkunwang01@gmail.com></shangkunwang01@gmail.com>			
Description Construct various types of space-filling designs, including Latin hypercube designs, clustering-based designs, maximin designs, maximum projection designs, and uniform designs (Joseph 2016 <doi:10.1080 08982112.2015.1100447="">). It also offers the option to optimize designs based on user-defined criteria.</doi:10.1080>			
Depends Rcpp (>= 1.0.8)			
Imports GenSA, nloptr, primes, proxy, spacefillr			
LinkingTo Rcpp, RcppArmadillo			
License GPL (>= 2)			
Encoding UTF-8			
Repository CRAN			
NeedsCompilation yes			
RoxygenNote 7.3.2			
Author Shangkun Wang [aut, cre], Roshan Joseph [aut]			
Date/Publication 2025-05-08 09:20:02 UTC			
Contents			
SFDesign-package			
cluster.error			
clustering.design			
continuous.optim			
customLHD			
maximin.augment			
maximin crit			

2 SFDesign-package

	maximin.optim	13
	maximin.remove	14
	maximinLHD	15
	maxpro.crit	16
	maxpro.optim	17
	maxpro.remove	18
	maxproLHD	19
	randomLHD	21
	uniform.crit	21
	uniform.discrete	22
	uniform.optim	24
	uniformLHD	
Index		27
SFDes	gn-package Space-Filling designs.	

Description

This pacakge offers a comprehensive suite of functions to construct various types of space-filling designs, including Latin hypercube designs, clustering-based designs, maximin designs, maximum projection designs, and uniform designs (Joseph 2016). It also offers the option to optimize designs based on user-defined criteria.

Author(s)

Shangkun Wang, V. Roshan Joseph

Maintainer: Shangkun Wang <shangkunwang01@gmail.com>

References

Wang, Shangkun, Xie, Weijun and V. Roshan Joseph. SFDesign: An R package for Space-Filling Designs.

Joseph, V. R. (2016). Space-filling designs for computer experiments: A review. Quality Engineering, 28(1), 28-35.

cluster.error 3

cluster.error

Clustering error

Description

This function computes the clustering error.

Usage

```
cluster.error(design, X = NULL, alpha = 1)
```

Arguments

design a design matrix. $\hbox{$\mathsf{X}$} \qquad \text{candidate points in } [0,1]^p. \ \text{If X is not provided, Sobol points are generated as candidate points.}$ alpha $\hbox{$\mathsf{power of the Euclidean distance.} }$

Details

cluster error computes the clustering error. The clustering error for a design $D = [\boldsymbol{x}_1, \dots, \boldsymbol{x}_n]^T$ is defined as $\frac{1}{N} \sum_{i=1}^n \sum_{\boldsymbol{x} \in V_i} \|\boldsymbol{x} - \boldsymbol{x}_i\|^{\alpha}$, where V_i is the Voronoi cell of each design point \boldsymbol{x}_i for $i = 1, \dots, n$, N is the size of X. When $\alpha = 2$, we obtain K-means and when $\alpha = 1$, we obtain K-medians.

Value

clustering error of the design.

```
n = 20
p = 3
D = randomLHD(n, p)
cluster.error(D)
```

4 clustering.design

clustering.design

Designs generated by clustering algorithms

Description

This function is for producing designs by minimizing the clustering error.

Usage

```
clustering.design(
  p,
 X = NULL
 D.ini = NULL,
 multi.start = 1,
  alpha = 1,
 Lloyd.iter.max = 100,
  cen.iter.max = 10,
 Lloyd.tol = 1e-04,
  cen.tol = 1e-04
)
```

Arguments

n	design size.
р	design dimension.
X	candidate points in $[0,1]^p$. If X is not provided, Sobol points is generated as cluster points.
D.ini	initial design points. If D.ini is not provided, Sobol points are generated as initial design.
multi.start	number of starting designs (cluster centers).
alpha	power of the Euclidean distance.
${\tt Lloyd.iter.max}$	maximum number of iterations for the Lloyd algorithm.
cen.iter.max	maximum number of iterations for the center calculation for each cluster.
Lloyd.tol	minimum relative change for the Lloyd algorithm to continue.
cen.tol	minimum relative change for the center calculation algorithm to continue.

Details

clustering design produces a design by clustering algorithms. It minimize the clustering error (see cluster.error) by Lloyd's algorithm. When $\alpha > 2$, accelerated gradient descent is used to find the center for each cluster (Mak, S. and Joseph, V. R. 2018). When $\alpha \leq 2$: Weizfeld algorithm is used to find the center for each cluster. Let $x_i^{(0)} = x_i$ denote the initial position of the *i*th center and and let S_i represent the points within its Voronoi cell. The center is then updated as:

$$\mathbf{x}_{i}^{(k+1)} = \left(\sum_{s \in S_{i}} \frac{s}{\|s - \mathbf{x}_{i}^{(k)}\|_{2}^{2-\alpha}}\right) / \left(\sum_{s \in S_{i}} \frac{1}{\|s - \mathbf{x}_{i}^{(k)}\|_{2}^{2-\alpha}}\right) \quad \text{for } k = 0, 1, \dots$$

continuous.optim 5

Value

design final design points.

cluster cluster assignment for each cluster points.

cluster.error final cluster error.

References

Mak, S. and Joseph, V. R. (2018), "Minimax and minimax projection designs using clustering," Journal of Computational and Graphical Statistics, 27, 166–178.

Examples

```
n = 20
p = 3
X = spacefillr::generate_sobol_set(1e5*p, p)
D = clustering.design(n, p, X)
```

continuous.optim

Continuous optimization of a design

Description

This function does continuous optimization of an existing design based on a specified criterion. It has an option to run simulated annealing after the continuous optimization.

Usage

```
continuous.optim(
  D.ini,
  objective,
  gradient = NULL,
  iteration = 10,
  sa = FALSE,
  sa.objective = NULL
)
```

Arguments

D. ini initial design matrix.

objective the criterion to minimize for the design. It can also return gradient information

at the same time in a list with elements "objective" and "gradient".

gradient the gradient of the objective with respect to the design.

iteration number iterations for LBFGS.

sa whether to use simulated annealing. If the final criterion is different from the

objective function specified above, simulated annealing can be useful. Use this

option only when the design size and dimension are not large.

sa. objective the criterion to minimize for the simulated annealing.

6 continuous.optim

Details

continuous.optim optimizes an existing design based on a specified criterion. It is a wrapper for the L-BFGS-B function from the nloptr packakge (Johnson 2008) and/or GenSA function in GenSA package (Xiang, Gubian, Suomela and Hoeng 2013).

Value

the optimized design.

References

Johnson, S. G. (2008), The NLopt nonlinear-optimization package, available at https://github.com/stevengj/nlopt. Xiang Y, Gubian S, Suomela B, Hoeng (2013). "Generalized Simulated Annealing for Efficient Global Optimization: the GenSA Package for R". The R Journal Volume 5/1, June 2013.

```
# Below is an example showing how to create functions needed to generate MaxPro design manually by
# continuous.optim without using the maxpro.optim function in the package.
compute.distance.matrix <- function(A){</pre>
   log_prod_metric = function(x, y) 2 * sum(log(abs(x-y)))
   return (c(proxy::dist(A, log_prod_metric)))
optim.obj = function(x){
  D = matrix(x, nrow=n, ncol=p)
  d = exp(compute.distance.matrix(D))
  d_matrix = matrix(0, n, n)
  d_matrix[lower.tri(d_matrix)] = d
  d_matrix = d_matrix + t(d_matrix)
  fn = sum(1/d)
  lfn = log(fn)
  I = diag(n)
  diag(d_matrix) = rep(1,n)
  A = B = D
  for(j in 1:p)
  {
   A = t(outer(D[,j], D[,j], "-"))
   diag(A) = rep(1, n)
   B[, j] = diag((1/A - I) %*% (1/d_matrix - I))
  grad = 2 * B / fn
  return(list("objective"=lfn, "gradient"=grad))
}
n = 20
p = 3
D.ini = maxproLHD(n, p)$design
D = continuous.optim(D.ini, optim.obj)
```

customLHD 7

customLHD	Generate a Latin-hypercube design (LHD) based on a custom crite-
	rion.

Description

This function generates a LHD by minimizing a user-specified design criterion.

Usage

```
customLHD(
  compute.distance.matrix,
  compute.criterion,
  update.distance.matrix,
  n,
  p,
  design = NULL,
  max.sa.iter = 1e+06,
  temp = 0,
  decay = 0.95,
  no.update.iter.max = 400,
  num.passes = 10,
 max.det.iter = 1e+06,
 method = "full",
  scaled = TRUE
)
```

Arguments

```
compute.distance.matrix
                  a function to calculate pairwise distance
compute.criterion
                  a function to calculate the criterion based on the pairwise distance
update.distance.matrix
                  a function to update the distance matrix after swapping one column of two de-
                  sign points
                  design size.
n
                  design dimension.
                  an initial LHD. If design=NULL, a random LHD is generated.
design
max.sa.iter
                  maximum number of swapping involved in the simulated annealing (SA) algo-
                  rithm.
                  initial temperature of the simulated annealing algorithm. If temp=0, it will be
temp
                  automatically determined.
                  the temperature decay rate of simulated annealing.
decay
```

8 customLHD

no.update.iter.max

the maximum number of iterations where there is no update to the global opti-

mum before SA stops.

num.passes the maximum number of passes of the whole design matrix if deterministic

swapping is used.

max.det.iter maximum number of swapping involved in the deterministic swapping algo-

rithm.

method choice of "deterministic", "sa", or "full". See details for the description of each

choice.

scaled whether the design is scaled to unit hypercube. If scaled=FALSE, the design is

represented by integer numbers from 1 to design size. Leave it as TRUE when

no initial design is provided.

Details

customLHD generates a LHD by minimizing a user-specified design criterion.

- If method='sa', then a simulated annealing algorithm is used to optimize the LHD. To custom the optimization process, you can change the default values for max.sa.iter, temp, decay, no.update.iter.max. In this optimization step, two design points are randomly chosen and their coordinate along one dimension are swaped. If the new design improves the criterion, then it is accepted; otherwise, it is accepted with some probability.
- If method='deterministic', then a deterministic swap algorithm is used to optimize the LHD. To custom the optimization process, you can change the default values for num.passes, max.det.iter. In this optimization step, we swap the coordinates of all pairs of design points (start with design point 1 with design point 2, then 1 with 3, ... 1 with n, then 2 with 3 until n-1 with n). Only accept the change if the swap leads to an improvement.
- If method='full', then optimization goes through the above two stages.

Value

design optimized LHD.

total.iter total number of swaps in the optimization.

criterion optimized criterion.

crit.hist criterion history during the optimization process.

```
# Below is an example showing how to create functions needed to generate
# MaxPro LHD manually by customLHD without using the maxproLHD function in
# the package.
compute.distance.matrix <- function(A){
    s = 2
    log_prod_metric = function(x, y) s * sum(log(abs(x-y)))
    return (c(proxy::dist(A, log_prod_metric)))
}
compute.criterion <- function(n, p, d) {
    s = 2</pre>
```

customLHD 9

```
dim \leftarrow as.integer(n * (n - 1) / 2)
  # Find the minimum distance
  Dmin <- min(d)</pre>
  # Compute the exponential summation
  avgdist <- sum(exp(Dmin - d))</pre>
  # Apply the logarithmic transformation and scaling
  avgdist <- log(avgdist) - Dmin</pre>
  avgdist \leftarrow exp((avgdist - log(dim)) * (p * s) ^ (-1))
  return(avgdist)
}
update.distance.matrix <- function(A, col, selrow1, selrow2, d) {</pre>
  s = 2
  n = nrow(A)
  # transform from c++ idx to r idx
  selrow1 = selrow1 + 1
  selrow2 = selrow2 + 1
  col = col + 1
  # A is the updated matrix
  row1 <- min(selrow1, selrow2)</pre>
  row2 <- max(selrow1, selrow2)</pre>
  compute_position <- function(row, h, n) {</pre>
    n * (h-1) - h*(h-1)/2 + row-h
  # Update for rows less than row1
  if (row1 > 1) {
    for (h in 1:(row1-1)) {
      position1 <- compute_position(row1, h, n)</pre>
      position2 <- compute_position(row2, h, n)</pre>
      for (c in col){
        d[position1] <- d[position1] + s * log(abs(A[row1, c] - A[h, c])) -</pre>
          s * log(abs(A[row2, c] - A[h, c]))
        d[position2] \leftarrow d[position2] + s * log(abs(A[row2, c] - A[h, c])) -
          s * log(abs(A[row1, c] - A[h, c]))
    }
  }
  # Update for rows between row1 and row2
  if ((row2-row1) > 1){
    for (h in (row1+1):(row2-1)) {
      position1 <- compute_position(h, row1, n)</pre>
      position2 <- compute_position(row2, h, n)</pre>
      for (c in col){
        d[position1] \leftarrow d[position1] + s * log(abs(A[row1, c] - A[h, c])) -
          s * log(abs(A[row2, c] - A[h, c]))
        d[position2] \leftarrow d[position2] + s * log(abs(A[row2, c] - A[h, c])) -
          s * log(abs(A[row1, c] - A[h, c]))
      }
    }
  }
```

10 full.factorial

```
# Update for rows greater than row2
  if (row2 < n) {
    for (h in (row2+1):n) {
      position1 <- compute_position(h, row1, n)</pre>
      position2 <- compute_position(h, row2, n)</pre>
      for (c in col){
        d[position1] \leftarrow d[position1] + s * log(abs(A[row1, c] - A[h, c])) -
          s * log(abs(A[row2, c] - A[h, c]))
        d[position2] \leftarrow d[position2] + s * log(abs(A[row2, c] - A[h, c])) -
          s * log(abs(A[row1, c] - A[h, c]))
    }
  }
  return (d)
n = 10
p = 2
# Find an appropriate initial temperature
crit1 = 1 / (n-1)
crit2 = (1 / ((n-1)^{(p-1)} * (n-2))) ^ (1/p)
delta = crit2 - crit1
temp = - delta / log(0.99)
result_custom = customLHD(compute.distance.matrix,
function(d) compute.criterion(n, p, d),
update.distance.matrix, n, p, temp = temp)
```

full.factorial

Full factorial design.

Description

This function generates a full factorial design.

Usage

```
full.factorial(p, level)
```

Arguments

p design dimension.

level an integer specifying the number of levels.

Details

full. factorial generates a p dimensional full factorial design.

maximin.augment 11

Value

```
a full factorial design matrix (scaled to [0, 1])
```

Examples

```
p = 3
level = 3
D = full.factorial(p, level)
```

maximin.augment

Augment a design by adding new design points that minimize the reciprocal distance criterion greedily

Description

This function augments a design by adding new design points one-at-a-time that minimize the reciprocal distance criterion.

Usage

```
maximin.augment(n, p, D.ini, candidate = NULL, r = 2 * p)
```

Arguments

n the size of the final design.

p design dimension.

D. ini initial design.

candidate candidate points to choose from. The default candidates are Sobol points of size

100n.

r the power parameter in the maximin.crit. By default it is set as 2p.

Details

maximin.augment augments a design by adding new design points that minimize the reciprocal distance criterion (see maximin.crit) greedily. In each iteration, the new design points is selected as the one from the candidate points that has the smallest sum of reciprocal distance to the existing design, that is, $\boldsymbol{x}_{k+1} = \arg\min_{\boldsymbol{x}} \sum_{i=1}^k \frac{1}{\|\boldsymbol{x} - \boldsymbol{x}_i\|^r}.$

Value

the augmented design.

12 maximin.crit

Examples

```
n.ini = 10
n = 20
p = 3
D.ini = maximinLHD(n.ini, p)$design
D = maximin.augment(n, p, D.ini)
```

maximin.crit

Maximin criterion

Description

This function calculates the maximin distance or the average reciprocal distance of a design.

Usage

```
maximin.crit(design, r = 2 * ncol(design), surrogate = FALSE)
```

Arguments

design the design matrix.

r the power used in the reciprocal distance objective function. The default value

is set as twice the dimension of the design.

surrogate whether to return the surrogate average reciprocal distance objective function or

the maximin distance. If setting surrogate=TRUE, then the average reciprocal

distance is returned.

Details

maximin.crit calculates the maximin distance or the average reciprocal distance of a design. The maximin distance for a design $D = [\mathbf{x}_1, \dots, \mathbf{x}_n]^T$ is defined as $\phi_{Mm} = \min_{i \neq j} \|\mathbf{x}_i - \mathbf{x}_j\|_2$. In optimization, the average reciprocal distance is usually used (Morris and Mitchell, 1995):

$$\phi_{\text{rec}} = \left(\frac{2}{n(n-1)} \sum_{i \neq j} \frac{1}{\|\boldsymbol{x}_i - \boldsymbol{x}_j\|_2^r}\right)^{1/r}.$$

The r is a power parameter and when it is large enough, the reciprocal distance is similar to the exact maximin distance.

Value

the maximin distance or reciprocal distance of the design.

References

Morris, M. D. and Mitchell, T. J. (1995), "Exploratory designs for computational experiments," Journal of statistical planning and inference, 43, 381–402.

maximin.optim 13

Examples

```
n = 20
p = 3
D = randomLHD(n, p)
maximin.crit(D)
```

maximin.optim

Optimize a design based on maximin or reciprocal distance criterion.

Description

This function optimizes a design by continuous optimization based on reciprocal distance criterion. A simulated annealing step can be enabled in the end to directly optimize the maximin distance criterion.

Usage

```
maximin.optim(D.ini, iteration = 10, sa = FALSE, find.best.ini = FALSE)
```

Arguments

D. ini the initial design.

iteration number iterations for L-BFGS-B algorithm.

sa whether to use simulated annealing in the end. If sa=TRUE, continuous opti-

mization is first used to optimize the reciprocal distance criterion and then SA

is performed to optimize the maximin criterion.

find.best.ini whether to generate other initial designs. If find.best.ini=TRUE, it will first find

the closest full factorial design in terms of size to D.ini. If the size of the full factorial design is larger than D.ini, design points will be removed by the maximin.remove function. If the the size of the full factorial design is smaller than D.ini, then we will augment the design by maximin.augment. In this case, we have two different candidate set to choose from: one is a full factorial design with level+1 and another is Sobol points. All initial designs are optimized and

the best is returned.

Details

maximin.optim optimizes a design by L-BFGS-B algorithm (Liu and Nocedal 1989) based on the reciprocal distance criterion. A simulated annealing step can be enabled in the end to directly optimize the maximin distance criterion. Optimization detail can be found in continuous.optim. We also provide the option to try other initial designs generated internally besides the D.ini provided by the user (see argument find.best.ini).

14 maximin.remove

Value

design the optimized design.

D. ini initial designs. If find.best.ini=TRUE, a list will be returned containing all the

initial designs considered.

References

Liu, D. C., & Nocedal, J. (1989). On the limited memory BFGS method for large scale optimization. Mathematical programming, 45(1), 503-528.

Examples

```
n = 20p = 3
```

b - 2

D = maximinLHD(n, p)\$design

D = maximin.optim(D, sa=FALSE)\$design

D = maximin.optim(D, sa=TRUE)\$design # Let sa=TRUE only when the n and p is not large.

maximin.remove

Sequentially remove design points from a design while maintaining low reciprocal distance criterion as possible

Description

This function sequentially removes design points one-at-a-time from a design while maintaining low reciprocal distance criterion as possible.

Usage

```
maximin.remove(D, n.remove, r = 2 * p)
```

Arguments

D the design matrix.

n.remove number of design points to remove.

r the power parameter in the maximin.crit. By default it is set as 2p.

Details

maximin.remove sequentially removes design points from a design in a greedy way while maintaining low reciprocal distance criterion (see maximin.crit) as possible. In each iteration, the design point with the largest sum of reciprocal distances with the other design points is removed, that is, $k^* = \arg\max_k \sum_{i \neq k} \frac{1}{\|x_k - x_i\|^r}$.

Value

the updated design.

maximinLHD 15

Examples

```
n = 20
p = 3
n.remove = 5
D = maximinLHD(n, p)$design
D = maximin.remove(D, n.remove)
```

maximinLHD

Generate a maximin Latin-hypercube design (LHD)

Description

This function generates a LHD with large maximin distance.

Usage

```
maximinLHD(
    n,
    p,
    design = NULL,
    power = 2 * p,
    max.sa.iter = 1e+06,
    temp = 0,
    decay = 0.95,
    no.update.iter.max = 100,
    num.passes = 10,
    max.det.iter = 1e+06,
    method = "full",
    scaled = TRUE
)
```

Arguments

n design size.

p design dimension.

design an initial LHD. If design=NULL, a random LHD is generated.

power the power used in the maximin objective function.

max.sa.iter maximum number of swapping involved in the simulated annealing (SA) algo-

rithm.

temp initial temperature of the simulated annealing algorithm. If temp=0, it will be

automatically determined.

decay the temperature decay rate of simulated annealing.

no.update.iter.max

the maximum number of iterations where there is no update to the global opti-

mum before SA stops.

16 maxpro.crit

num.passes the maximum number of passes of the whole design matrix if deterministic

swapping is used.

max.det.iter maximum number of swapping involved in the deterministic swapping algo-

rithm.

method choice of "deterministic", "sa", or "full". If the method="full", the design is first

optimized by SA and then deterministic swapping.

scaled whether the design is scaled to unit hypercube. If scaled=FALSE, the design is

represented by integer numbers from 1 to design size. Leave it as TRUE when

no initial design is provided.

Details

maximinLHD generates a LHD or optimize an existing LHD to achieve large maximin distance by optimizing the reciprocal distance (see maximin.crit). The optimization details can be found in customLHD.

Value

design final design points.

total.iter total number of swaps in the optimization.

criterion final optimized criterion.

crit.hist criterion history during the optimization process.

Examples

```
# We show three different ways to use this function.
n = 20
p = 3
D.random = randomLHD(n, p)
# optimize over a random LHD by SA
D = maximinLHD(n, p, D.random, method='sa')
# optimize over a random LHD by deterministic swapping
D = maximinLHD(n, p, D.random, method='deterministic')
# Directly generate an optimized LHD for maximin criterion which goes
# through the above two optimization stages.
D = maximinLHD(n, p)
```

maxpro.crit

Maximum projection (MaxPro) criterion

Description

This function calculates the MaxPro criterion of a design.

Usage

```
maxpro.crit(design, delta = 0)
```

maxpro.optim 17

Arguments

design the design matrix.

delta a small value added to the denominator of the maximum projection criterion. By

default it is set as zero.

Details

maxpro.crit calculates the MaxPro criterion of a design. The MaxPro criterion for a design $D = [x_1, \dots, x_n]^T$ is defined as

$$\left\{ \frac{1}{\binom{n}{2}} \sum_{i=1}^{n-1} \sum_{j=i+1}^{n} \frac{1}{\prod_{l=1}^{p} (x_{il} - x_{jl})^2 + \delta} \right\}^{1/p},$$

where p is the dimension of the design (Joseph, V. R., Gul, E., & Ba, S. 2015).

Value

the MaxPro criterion of the design.

References

Joseph, V. R., Gul, E., & Ba, S. (2015). Maximum projection designs for computer experiments. Biometrika, 102(2), 371-380.

Examples

```
n = 20
p = 3
D = randomLHD(n, p)
maxpro.crit(D)
```

maxpro.optim

Optimize a design based on the maximum projection criterion

Description

This function optimizes a design by continuous optimization based on maximum projection criterion (Joseph, V. R., Gul, E., & Ba, S. 2015).

Usage

```
maxpro.optim(D.ini, iteration = 10)
```

Arguments

D. ini the initial design.

iteration number iterations for L-BFGS-B.

18 maxpro.remove

Details

maxpro.optim optimizes a design by L-BFGS-B algorithm (Liu and Nocedal 1989) based on the maximum projection criterion maxpro.crit.

Value

```
design optimized design.

D. ini initial design.
```

References

Liu, D. C., & Nocedal, J. (1989). On the limited memory BFGS method for large scale optimization. Mathematical programming, 45(1), 503-528.

Joseph, V. R., Gul, E., & Ba, S. (2015). Maximum projection designs for computer experiments. Biometrika, 102(2), 371-380.

Examples

```
n = 20
p = 3
D = maxproLHD(n, p)$design
D = maxpro.optim(D)$design
```

maxpro.remove

Sequentially remove design points from a design while maintaining low maximum projection criterion as possible

Description

This function sequentially removes design points one-at-a-time from a design while maintaining low maximum projection criterion as possible.

Usage

```
maxpro.remove(D, n.remove, delta = 0)
```

Arguments

D design

n. remove number of design points to remove

delta a small value added to the denominator of the maximum projection criterion. By

default it is set as zero.

maxproLHD 19

Details

maxpro.remove sequentially removes design points from a design while maintaining low maximum projection criterion (see maxpro.crit) as possible. The maximum projection criterion is modified to include a small delta term:

$$\phi_{\text{maxpro}}(\boldsymbol{D}_n) = \left\{ \frac{1}{\binom{n}{2}} \sum_{i=1}^{n-1} \sum_{j=i+1}^{n} \frac{1}{\prod_{l=1}^{p} (x_{il} - x_{jl})^2 + \delta} \right\}^{1/p}.$$

The index of the point to remove is $k^* = \arg\min_k \sum_{i \neq k} \frac{1}{\prod_{l=1}^p (x_{il} - x_{kl})^2 + \delta}$.

Value

the updated design.

Examples

```
n = 20
p = 3
n.remove = 5
D = maxproLHD(n, p)$design
D = maxpro.remove(D, n.remove)
```

maxproLHD

Generate a MaxPro Latin-hypercube design

Description

This function generates a MaxPro Latin-hypercube design.

Usage

```
maxproLHD(
   n,
   p,
   design = NULL,
   max.sa.iter = 1e+06,
   temp = 0,
   decay = 0.95,
   no.update.iter.max = 400,
   num.passes = 10,
   max.det.iter = 1e+06,
   method = "full",
   scaled = TRUE
)
```

20 maxproLHD

Arguments

n design size.

p design dimension.

design an initial LHD. If design=NULL, a random LHD is generated.

max.sa.iter maximum number of swapping involved in the simulated annealing (SA) algo-

rithm.

temp initial temperature of the simulated annealing algorithm. If temp=0, it will be

automatically determined.

decay the temperature decay rate of simulated annealing.

no.update.iter.max

the maximum number of iterations where there is no update to the global opti-

mum before SA stops.

num.passes the maximum number of passes of the whole design matrix if deterministic

swapping is used.

max.det.iter maximum number of swapping involved in the deterministic swapping algo-

rithm.

method choice of "deterministic", "sa", or "full". If the method="full", the design is first

optimized by SA and then deterministic swapping.

scaled whether the design is scaled to unit hypercube. If scaled=FALSE, the design is

represented by integer numbers from 1 to design size. Leave it as TRUE when

no initial design is provided.

Details

maxproLHD generates a MaxPro Latin-hypercube design (Joseph, V. R., Gul, E., & Ba, S. 2015). The major difference with the MaxPro packages is that we have a deterministic swap algorithm, which can be enabled by setting method="deterministic" or method="full". For optimization details, see the detail section in customLHD.

Value

design final design points.

total.iter total number of swaps in the optimization.

criterion final optimized criterion.

crit.hist criterion history during the optimization process.

References

Joseph, V. R., Gul, E., & Ba, S. (2015). Maximum projection designs for computer experiments. Biometrika, 102(2), 371-380.

Examples

```
n = 20
p = 3
```

D = maxproLHD(n, p)

randomLHD 21

 ${\sf randomLHD}$

Random Latin hypercube design

Description

This function generates a random Latin hypercube design.

Usage

```
randomLHD(n, p)
```

Arguments

n design size.

p design dimension.

Details

randomLHD generates a random Latin hypercube design.

Value

a random Latin hypercube design.

Examples

```
n = 20

p = 3

D = randomLHD(n, p)
```

uniform.crit

Uniform criterion

Description

This function calculates the wrap-around discrepancy of a design.

Usage

```
uniform.crit(design)
```

Arguments

design

a design matrix.

22 uniform.discrete

Details

uniform.crit calculates the wrap-around discrepancy of a design. The wrap-around discrepancy for a design $D = [x_1, \dots, x_n]^T$ is defined as (Hickernell, 1998):

$$\phi_{wa} = -\left(\frac{4}{3}\right)^p + \frac{1}{n^2} \sum_{i,j=1}^n \prod_{k=1}^p \left[\frac{3}{2} - |x_{ik} - x_{jk}|(1 - |x_{ik} - x_{jk}|)\right].$$

Value

wrap-around discrepancy of the design

References

Hickernell, F. (1998), "A generalized discrepancy and quadrature error bound," Mathematics of computation, 67, 299–322.

Examples

```
n = 20
p = 3
D = randomLHD(n, p)
uniform.crit(D)
```

uniform.discrete

Generate a uniform design for discrete factors with different number of levels

Description

This function generates a uniform design for discrete factors with different number of levels.

Usage

```
uniform.discrete(
   t,
   p,
   levels,
   design = NULL,
   max.sa.iter = 1e+06,
   temp = 0,
   decay = 0.95,
   no.update.iter.max = 400,
   num.passes = 10,
   max.det.iter = 1e+06,
   method = "full",
   scaled = TRUE
)
```

uniform.discrete 23

multiple of the least common multiple of the levels.

Arguments t

	C	multiple of the least common multiple of the levels.
	p	design dimension.
	levels	a vector of the number of levels for each dimension.
	design	an initial design. If design=NULL, a random design is generated.
	max.sa.iter	maximum number of swapping involved in the simulated annealing (SA) algorithm.
	temp	initial temperature of the simulated annealing algorithm. If temp=0, it will be automatically determined.
	decay	the temperature decay rate of simulated annealing.
no.update.iter.max		
		the maximum number of iterations where there is no update to the global optimum before SA stops.
	num.passes	the maximum number of passes of the whole design matrix if deterministic swapping is used.
	max.det.iter	maximum number of swapping involved in the deterministic swapping algorithm.
		1. 1. 1. C. 1. 1. C. 1. C.

method choice of "deterministic", "sa", or "full". If the method="full", the design is first

optimized by SA and then deterministic swapping.

scaled whether the design is scaled to unit hypercube. If scaled=FALSE, the design is

represented by integer numbers from 1 to design size. Leave it as TRUE when

no initial design is provided.

Details

uniform.discrete generates a uniform design of discrete factors with different number of levels by minimizing the wrap-around discrepancy criterion (see uniform.crit).

Value

design	final design points.
design.int	design transformed to integer numbers for each dimenion
total.iter	total number of swaps in the optimization.
criterion	final optimized criterion.
crit.hist	criterion history during the optimization process.

```
p = 5
levels = c(3, 4, 6, 2, 3)
t = 1
D = uniform.discrete(t, p, levels)
```

24 uniform.optim

uniform.optim

Optimize a design based on the wrap-around discrepancy

Description

This function optimizes a design through continuous optimization of the wrap-around discrepancy.

Usage

```
uniform.optim(D.ini, iteration = 10)
```

Arguments

D. ini the initial design.

iteration number iterations for LBFGS.

Details

uniform.optim optimizes a design through continuous optimization of the wrap-around discrepancy (see uniform.crit) by L-BFGS-B algorithm (Liu and Nocedal 1989).

Value

design optimized design.

D.ini initial design.

References

Liu, D. C., & Nocedal, J. (1989). On the limited memory BFGS method for large scale optimization. Mathematical programming, 45(1), 503-528.

```
n = 20
p = 3
D = uniformLHD(n, p)$design
D = uniform.optim(D)$design
```

uniformLHD 25

uniformLHD

Generate a uniform Latin-hypercube design (LHD)

Description

This function generates a uniform LHD by minimizing the wrap-around discrepancy.

Usage

```
uniformLHD(
   n,
   p,
   design = NULL,
   max.sa.iter = 1e+06,
   temp = 0,
   decay = 0.95,
   no.update.iter.max = 400,
   num.passes = 10,
   max.det.iter = 1e+06,
   method = "full",
   scaled = TRUE
)
```

Arguments

n	design size.
р	design dimension.
design	an initial LHD. If design=NULL, a random LHD is generated.
max.sa.iter	maximum number of swapping involved in the simulated annealing (SA) algorithm.
temp	initial temperature of the simulated annealing algorithm. If temp=0, it will be automatically determined.
decay	the temperature decay rate of simulated annealing.
no.update.iter	r.max
	the maximum number of iterations where there is no update to the global optimum before SA stops.
num.passes	the maximum number of passes of the whole design matrix if deterministic swapping is used.
max.det.iter	maximum number of swapping involved in the deterministic swapping algorithm.
method	choice of "deterministic", "sa", or "full". If the method="full", the design is first optimized by SA and then deterministic swapping.
scaled	whether the design is scaled to unit hypercube. If scaled=FALSE, the design is represented by integer numbers from 1 to design size. Leave it as TRUE when no initial design is provided.

26 uniformLHD

Details

uniformLHD generates a uniform LHD minimizing wrap-around discrepancy (see uniform.crit). The optimization details can be found in customLHD.

Value

design final design points.

total.iter total number of swaps in the optimization.

criterion final optimized criterion.

crit.hist criterion history during the optimization process.

```
n = 20
p = 3
D = uniformLHD(n, p)
```

Index

```
cluster.error, 3, 4
clustering.design, 4
continuous.optim, 5, 13
customLHD, 7, 16, 20, 26
full.factorial, 10
maximin.augment, 11
maximin.crit, 11, 12, 14, 16
{\tt maximin.optim}, {\tt 13}
maximin.remove, 14
maximinLHD, 15
maxpro.crit, 16, 18, 19
maxpro.optim, 17
maxpro.remove, 18
maxproLHD, 19
randomLHD, 21
SFDesign-package, 2
uniform.crit, 21, 23, 24, 26
uniform.discrete, 22
uniform.optim, 24
\verb"uniformLHD", 25"
```