Package 'viafr'

August 28, 2024

Title Interface to the 'VIAF' ('Virtual International Authority File')

Version 0.3.1
Maintainer Stefanie Schneider < stefanie.schneider@itg.uni-muenchen.de>
Description Provides direct access to linked names for the same entity across the world's major name authority files, including national and regional variations in language, character set, and spelling. For more information go to https://viaf.org/ .
License GPL-3
Encoding UTF-8
LazyData true
RoxygenNote 7.3.2
URL https://github.com/stefanieschneider/viafr
BugReports https://github.com/stefanieschneider/viafr/issues
Suggests testthat (>= 2.1.0), roxygen2
Imports utf8, crul, jsonlite, assertthat, magrittr, stringr, tibble, tidyr, purrr, dplyr, rlang
Depends R (>= 2.10)
NeedsCompilation no
Author Stefanie Schneider [cre, aut] (https://orcid.org/0000-0003-4915-6949)
Repository CRAN
Date/Publication 2024-08-28 17:30:02 UTC
Contents
authorities 2 name_types 2 viaf_get 2 viaf_search 3 viaf_suggest 4
Index 5

2 viaf_get

authorities

VIAF Authorities

Description

A dataset containing the names and schemes of 55 organizations and libraries that participate in the VIAF.

Usage

```
data(authorities)
```

Format

A tibble with 55 rows and 2 variables.

 $name_types$

VIAF Name Types

Description

A dataset containing the 5 possible name types in the VIAF.

Usage

```
data(name_types)
```

Format

A tibble with 5 rows and 2 variables.

viaf_get

Get Data for VIAF Identifier(s)

Description

Get authority cluster data based on supplied VIAF identifier(s).

Usage

```
viaf_get(query = NULL, ...)
```

viaf_search 3

Arguments

query The VIAF identifier(s) to get data for.
... Optional VIAF API query parameters.

Value

A tibble with data items.

Note

An internet connection is required. The MARC 21 field definitions are used. This function does not currently work due to changes to the VIAF.

Examples

```
## Not run: viaf_get(c("64013650", "102333412"))
```

viaf_search

Search VIAF records

Description

Search VIAF records where the authority includes the given terms.

Usage

```
viaf_search(query = NULL, ...)
```

Arguments

query The search query (or queries) to get data for.
... Optional VIAF API query parameters.

Value

A named list of tibbles with data items.

Note

An internet connection is required. The MARC 21 field definitions are used.

Examples

```
viaf_search(c("Rembrandt", "Jane Austen"))
```

viaf_suggest

viaf_suggest

Suggest VIAF records

Description

Suggest VIAF records based on given terms passed in a query.

Usage

```
viaf_suggest(query = NULL, ...)
```

Arguments

query The search query (or queries) to get data for.
... Optional VIAF API query parameters.

Value

A named list of tibbles with data items.

Note

An internet connection is required.

Examples

```
viaf_suggest(c("rembrandt", "austen"))
```

Index

```
* datasets
    authorities, 2
    name_types, 2

authorities, 2

name_types, 2

viaf_get, 2
viaf_search, 3
viaf_suggest, 4
```