Package 'GWASExactHW'

March 12, 2024

Type Package
Title Exact Hardy-Weinburg Testing for Genome Wide Association Studies
Version 1.2
Date 2024-03-11
Author Ian Painter, University of Washington
Maintainer Stephanie Gogarten <sdmorris@uw.edu></sdmorris@uw.edu>
Description Exact Hardy-Weinburg testing (using Fisher's test) for SNP genotypes as typically obtained in a Genome Wide Association Study (GWAS).
License GPL-3
LazyLoad yes
Repository CRAN
NeedsCompilation yes
Date/Publication 2024-03-12 07:00:02 UTC
R topics documented:
GWASExactHW-package
Index
GWASExactHW-package Exact Hardy-Weinburg testing for Genome Wide Association Studies
Description
This package contains a function to do exact Hardy-Weinburg testing (using Fisher's test) over all o a selection of SNP genotypes as typically obtained in a Genome Wide Association Study (GWAS)

Details

2 HWExact

Package: GWASExactHW

Type: Package Version: 1.01 Date: 2013-01-04

License: GNU LazyLoad: yes

The function HWExact runs fast Hardy-Weinburg testing for a set of bi-alleleic genotypes.

Author(s)

Ian Painter, University of Washington

Maintainer: Ian Painter <ipainter@u.washington.edu>

References

Wigginton, JE, Cutler, DJ, and Abecasis, GR (2005) A Note on Exact Tests of Hardy-Weinberg Equilibrium. American Journal of Human Genetics. 76

HWExact

Function to calculate Hardy-Weinburg exact p-values

Description

This function calculates Hardy-Weinburg (Fisher's) exact p-values for GWAS SNP data.

Usage

HWExact(GenotypeCounts)

Arguments

GenotypeCounts A dataframe of genotype counts, with columns called nAA, nAa and naa, one row for each SNP.

Value

A vector of exact p-values.

Note

This function uses a C function SNPHWE.c written by Jan Wigginton as described in the above reference.

Author(s)

Ian Painter

HWExact 3

References

Wigginton, JE, Cutler, DJ, and Abecasis, GR (2005) A Note on Exact Tests of Hardy-Weinberg Equilibrium. American Journal of Human Genetics. 76

Examples

```
pA<- runif(1)
pAA<- pA^2
pAa<- 2*pA*(1-pA)
paa<- (1-pA)^2

counts<- rmultinom(1000, 3000, c(pAA, pAa, paa) )
genotypes<- data.frame(nAA = counts[1,], nAa = counts[2,], naa = counts[3,])
hwPvalues<- HWExact(genotypes)</pre>
```

Index

```
* htest
     HWExact, 2
* package
     GWASExactHW-package, 1

GWASExactHW (GWASExactHW-package), 1
GWASExactHW-package, 1

HWExact, 2
```