

Package ‘fmi’

November 17, 2025

Title Hierarchical Permutation Tests for Functional Measurement Invariance

Description Provides a suite of functions to test for Functional Measurement Invariance (FMI) between two groups. Implements hierarchical permutation tests for configural, metric, and scalar invariance, adapting concepts from Multi-Group Confirmatory Factor Analysis (MGCFA) to functional data. Methods are based on concepts from:
Meredith, W. (1993) <[doi:10.1007/BF02294825](https://doi.org/10.1007/BF02294825)>,5
Yao, F., Müller, H. G., & Wang, J. L. (2005) <[doi:10.1198/016214504000001745](https://doi.org/10.1198/016214504000001745)>,
and Lee, K. Y., & Li, L. (2022) <[doi:10.1111/rssb.12471](https://doi.org/10.1111/rssb.12471)>.

Version 0.1.7

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

Imports dplyr, ggplot2, knitr, magrittr, methods, purrr, refund, stats, tibble, tidyr, utils

Suggests fda, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Hyeri Kim [aut, cre]

Maintainer Hyeri Kim <gpfl3616@naver.com>

Depends R (>= 4.1.0)

Repository CRAN

Date/Publication 2025-11-17 21:20:07 UTC

Contents

build_scee_plot	2
compare_latent_means	3
determine_npc	3

run_dti_example	4
run_fmi	5
run_growth_example	6
simulate_fmi_data	7
test_configural	8
test_metric	8
test_scalar	9
test_strict	10
Index	11

build_scee_plot	<i>Build Scree Plot for Configural Invariance</i>
-----------------	---

Description

Creates a ggplot2 scree plot comparing the PVE by FPCs for two groups.

Usage

```
build_scee_plot(fpca_A, fpca_B, groups)
```

Arguments

fpca_A	An fpca.sc object for Group A.
fpca_B	An fpca.sc object for Group B.
groups	A character vector of the two group names.

Value

A ggplot object.

Examples

```
sim <- simulate_fmi_data(N_A = 20, N_B = 20, T_points = 30)
g_fac <- factor(sim$group_vec)
idx_A <- which(g_fac == levels(g_fac)[1])
# --- FIX: Added Y= and argvals= ---
fpca_A <- refund::fpca.sc(Y = sim$Y_mat[idx_A, ], argvals = sim$argvals, npc = 3)
fpca_B <- refund::fpca.sc(Y = sim$Y_mat[-idx_A, ], argvals = sim$argvals, npc = 3)
build_scee_plot(fpca_A, fpca_B, levels(g_fac))
```

compare_latent_means	<i>Compare Latent Means</i>
----------------------	-----------------------------

Description

Performs Welch's t-tests on FPC scores between groups. This function should only be run after scalar invariance is established.

Usage

```
compare_latent_means(fmi_results, group_vec)
```

Arguments

fmi_results	The list object returned by run_fmi().
group_vec	The original group vector used in run_fmi().

Value

A tibble summarizing the t-test results for each FPC.

Examples

```
sim <- simulate_fmi_data(N_A = 20, N_B = 20, T_points = 30)
fmi_results <- run_fmi(
  Y_mat = sim$Y_mat,
  group_vec = sim$group_vec,
  argvals = sim$argvals,
  n_perms = 9,
  progress = FALSE
)
# This will run only if scalar invariance passed
if (!is.null(fmi_results$scalar) && fmi_results$scalar$passed) {
  mean_results <- compare_latent_means(fmi_results, sim$group_vec)
  print(mean_results)
}
```

determine_npc	<i>Determine Number of FPCs Automatically</i>
---------------	---

Description

Determines the number of functional principal components (FPCs) required to meet a target Proportion of Variance Explained (PVE).

Usage

```
determine_npc(Y_mat, argvals, target_pve = 0.95, max_npc = 6L)
```

Arguments

<code>Y_mat</code>	A numeric matrix (N x M) where N is subjects, M is time points.
<code>argvals</code>	A numeric vector of length M listing the observation points.
<code>target_pve</code>	The target cumulative PVE to reach (default: 0.95).
<code>max_npc</code>	The maximum number of components to retain (default: 6L).

Value

A list containing:

<code>npc</code>	The selected number of components.
<code>pooled_fpca</code>	The fpca.sc object from the refund package.
<code>scree</code>	A tibble with PVE and cumulative PVE for each component.

Examples

```
sim <- simulate_fmi_data(N_A = 20, N_B = 20, T_points = 30)
npc_info <- determine_npc(sim$Y_mat, sim$argvals)
print(npc_info$npc)
```

run_dti_example

DTI Example Data Wrapper

Description

A helper function to load and pre-process the DTI dataset from the 'refund' package for use in examples.

Usage

```
run_dti_example(n_perms = 499L)
```

Arguments

<code>n_perms</code>	The number of permutations (default: 499L). Passed to run_fmi.
----------------------	--

Value

Invisibly returns the FMI results list.

Examples

```
# n_perms=9 is for a quick check. Use 499+ for real analysis.
if (requireNamespace("refund", quietly = TRUE)) {
  dti_results <- run_dti_example(n_perms = 9)
}
```

run_fmi

Run Hierarchical Functional Measurement Invariance (FMI) Tests

Description

A wrapper function that performs a sequence of permutation tests for configural, metric, scalar, and (optionally) strict invariance.

Usage

```
run_fmi(
  Y_mat,
  group_vec,
  argvals,
  alpha = 0.05,
  npc = NULL,
  target_pve = 0.95,
  max_npc = 6L,
  n_perms = 499L,
  strict_test = FALSE,
  progress = interactive()
)
```

Arguments

<code>Y_mat</code>	A numeric matrix (N x M) where N is subjects, M is time points.
<code>group_vec</code>	A vector of length N specifying group membership (2 groups).
<code>argvals</code>	A numeric vector of length M listing the observation points.
<code>alpha</code>	Significance level (default: 0.05).
<code>npc</code>	Optional. The number of FPCs. If NULL (default), it is determined automatically by <code>determine_npc</code> .
<code>target_pve</code>	The target PVE if npc is NULL (default: 0.95).
<code>max_npc</code>	The max FPCs if npc is NULL (default: 6L).
<code>n_perms</code>	The number of permutations (default: 499L).
<code>strict_test</code>	Boolean. Whether to perform the strict invariance test (default: FALSE).
<code>progress</code>	Boolean. Show progress bars? (default: <code>interactive()</code>).

Value

A list containing test results for each invariance level, settings, and the pooled FPCA object.

Examples

```
# Use small N and n_perms for a quick example
sim <- simulate_fmi_data(N_A = 20, N_B = 20, T_points = 30)
fmi_results <- run_fmi(
  Y_mat = sim$Y_mat,
  group_vec = sim$group_vec,
  argvals = sim$argvals,
  n_perms = 9, # Use 499+ for actual research
  progress = FALSE
)
print(fmi_results)
```

run_growth_example	<i>Berkeley Growth Example Data Wrapper</i>
--------------------	---

Description

A helper function to load and pre-process the Growth dataset from the 'fda' package for use in examples.

Usage

```
run_growth_example(n_perms = 499L)
```

Arguments

n_perms The number of permutations (default: 499L). Passed to run_fmi.

Value

Invisibly returns the FMI results list.

Examples

```
# n_perms=9 is for a quick check. Use 499+ for real analysis.
if (requireNamespace("fda", quietly = TRUE)) {
  growth_results <- run_growth_example(n_perms = 9)
}
```

simulate_fmi_data	<i>Simulate FMI Data</i>
-------------------	--------------------------

Description

Generates functional data for two groups with optional differences in latent means or scalar intercepts.

Usage

```
simulate_fmi_data(  
  N_A = 50,  
  N_B = 50,  
  T_points = 51,  
  mean_shift = 0,  
  scalar_shift = 0,  
  eigenvalues = c(4, 1, 0.5, 0.1),  
  noise_sd = 0.5,  
  seed = NULL  
)
```

Arguments

N_A	Sample size for Group A (default: 50).
N_B	Sample size for Group B (default: 50).
T_points	Number of time points (default: 51).
mean_shift	A shift added to FPC 1 scores for Group B (default: 0).
scalar_shift	A shift added to the mean function for Group B (default: 0).
eigenvalues	A vector of eigenvalues for FPCs (default: c(4, 1, 0.5, 0.1)).
noise_sd	Standard deviation of measurement error (default: 0.5).
seed	Optional. A random seed for reproducibility.

Value

A list with Y_mat, group_vec, and argvals.

Examples

```
sim_data <- simulate_fmi_data(N_A = 10, N_B = 10, T_points = 20, seed = 123)  
str(sim_data)
```

test_configural	<i>Test for Configural Invariance</i>
-----------------	---------------------------------------

Description

Permutation test to check if the cumulative PVE is equivalent across groups.

Usage

```
test_configural(Y_mat, group_vec, argvals, npc, n_perms, alpha, progress)
```

Arguments

Y_mat	A numeric matrix (N x M) where N is subjects, M is time points.
group_vec	A vector of length N specifying group membership (2 groups).
argvals	A numeric vector of length M listing the observation points.
npc	Optional. The number of FPCs. If NULL (default), it is determined automatically by determine_npc.
n_perms	The number of permutations (default: 499L).
alpha	Significance level (default: 0.05).
progress	Boolean. Show progress bars? (default: interactive()).

Value

A list with passed (boolean), p_value, statistic, and plot.

Examples

```
sim <- simulate_fmi_data(N_A = 20, N_B = 20, T_points = 30)
res <- test_configural(sim$Y_mat, sim$group_vec, sim$argvals,
                      npc = 3, n_perms = 9, alpha = 0.05, progress = FALSE)
print(res$p_value)
```

test_metric	<i>Test for Metric Invariance</i>
-------------	-----------------------------------

Description

Permutation test to check if the eigenfunctions are equivalent across groups.

Usage

```
test_metric(Y_mat, group_vec, argvals, npc, n_perms, alpha, progress)
```


Arguments

Y_mat	A numeric matrix (N x M) where N is subjects, M is time points.
group_vec	A vector of length N specifying group membership (2 groups).
argvals	A numeric vector of length M listing the observation points.
npc	Optional. The number of FPCs. If NULL (default), it is determined automatically by determine_npc.
n_perms	The number of permutations (default: 499L).
alpha	Significance level (default: 0.05).
progress	Boolean. Show progress bars? (default: interactive()).

Value

A list with passed (boolean), p_value, and statistic.

Examples

```
sim <- simulate_fmi_data(N_A = 20, N_B = 20, T_points = 30)
res <- test_metric(sim$Y_mat, sim$group_vec, sim$argvals,
                  npc = 3, n_perms = 9, alpha = 0.05, progress = FALSE)
print(res$p_value)
```

test_scalar	<i>Test for Scalar Invariance</i>
-------------	-----------------------------------

Description

Permutation test to check if the mean functions (intercepts) are equivalent across groups, after accounting for latent factors.

Usage

```
test_scalar(Y_mat, group_vec, argvals, pooled_fpca, n_perms, alpha, progress)
```

Arguments

Y_mat	Numeric matrix (N x M).
group_vec	A vector of length N specifying group membership.
argvals	Numeric vector of length M.
pooled_fpca	The fpca.sc object from the determine_npc function.
n_perms	Integer, number of permutations.
alpha	Significance level (default: 0.05).
progress	Boolean, show progress bar? (default: interactive()).

Value

A list with passed (boolean), p_value, and statistic.

Examples

```
sim <- simulate_fmi_data(N_A = 20, N_B = 20, T_points = 30)
npc_info <- determine_npc(sim$Y_mat, sim$argvals, max_npc = 3)
res <- test_scalar(sim$Y_mat, sim$group_vec, sim$argvals,
                  pooled_fpca = npc_info$pooled_fpca,
                  n_perms = 9, alpha = 0.05, progress = FALSE)
print(res$p_value)
```

test_strict	<i>Test for Strict Invariance</i>
-------------	-----------------------------------

Description

Permutation test to check if the residual error variances are equivalent across groups.

Usage

```
test_strict(Y_mat, group_vec, argvals, npc, n_perms, alpha, progress)
```

Arguments

Y_mat	A numeric matrix (N x M) where N is subjects, M is time points.
group_vec	A vector of length N specifying group membership (2 groups).
argvals	A numeric vector of length M listing the observation points.
npc	Optional. The number of FPCs. If NULL (default), it is determined automatically by determine_npc.
n_perms	The number of permutations (default: 499L).
alpha	Significance level (default: 0.05).
progress	Boolean. Show progress bars? (default: interactive()).

Value

A list with passed (boolean), p_value, and statistic.

Examples

```
sim <- simulate_fmi_data(N_A = 20, N_B = 20, T_points = 30)
res <- test_strict(sim$Y_mat, sim$group_vec, sim$argvals,
                  npc = 3, n_perms = 9, alpha = 0.05, progress = FALSE)
print(res$p_value)
```

Index

`build_scree_plot`, [2](#)
`compare_latent_means`, [3](#)
`determine_npc`, [3](#)
`run_dti_example`, [4](#)
`run_fmi`, [5](#)
`run_growth_example`, [6](#)
`simulate_fmi_data`, [7](#)
`test_configural`, [8](#)
`test_metric`, [8](#)
`test_scalar`, [9](#)
`test_strict`, [10](#)