

# Package ‘blockr.dock’

December 11, 2025

**Title** A Docking Layout Manager for 'blockr'

**Version** 0.1.0

**Description** Building on the docking layout manager provided by 'dockViewR', this provides a flexible front-end to 'blockr.core'. It provides an extension mechanism which allows for providing means to manipulate a board object via panel-based user interface components.

**URL** <https://bristolmyerssquibb.github.io/blockr.dock/>

**BugReports** <https://github.com/BristolMyersSquibb/blockr.dock/issues>

**License** GPL (>= 3)

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**Imports** blockr.core (>= 0.1.1), bsicons, shiny, shinyjs, bslib, glue, dockViewR (>= 0.2.1), htmltools, cli, shinyWidgets, jsonlite

**Suggests** testthat (>= 3.0.0), DT, colorspace, methods, withr, shinytest2

**Config/testthat/edition** 3

**Collate** 'action-class.R' 'action-block.R' 'action-link.R'  
'action-modal.R' 'action-stack.R' 'action-ui.R'  
'action-utils.R' 'block-meta.R' 'block-ui.R' 'board-plugins.R'  
'board-server.R' 'board-ui.R' 'dock-board.R' 'dock-stack.R'  
'ext-class.R' 'ext-edit.R' 'ext-ui.R' 'layout-class.R'  
'plugin-block.R' 'plugin-serdes.R' 'utils-dock.R' 'utils-id.R'  
'utils-misc.R' 'utils-pkg.R' 'utils-serdes.R' 'utils-serve.R'  
'utils-ui.R'

**NeedsCompilation** no

**Author** Nicolas Bennett [aut, cre],  
David Granjon [aut]

**Maintainer** Nicolas Bennett <nicolas@cynkra.com>

**Repository** CRAN

**Date/Publication** 2025-12-11 13:30:14 UTC

Contents

blks_metadata . . . . .	2
dock_id . . . . .	3
new_action . . . . .	4
new_dock_board . . . . .	7
new_dock_extension . . . . .	8
new_dock_layout . . . . .	10
new_dock_stack . . . . .	11
new_edit_board_extension . . . . .	12
show_panel . . . . .	13
<b>Index</b>	<b>14</b>

---

blks_metadata	<i>Get block metadata</i>
---------------	---------------------------

---

Description

Returns various metadata for blocks or block categories, as well as styling for block icons.

Usage

```
blks_metadata(blocks)

blk_color(category)

blk_icon_data_uri(icon_svg, color, size = 48, mode = c("uri", "inline"))
```

Arguments

blocks	Blocks passed as blocks or block object
category	Block category
icon_svg	Character string containing the SVG icon markup
color	Hex color code for the background
size	Numeric size in pixels (default: 48)
mode	Switch between URI and inline HTML mode

Details

- `blks_metadata()`: Retrieves metadata given a block or blocks object from the block registry. Can also handle blocks which are not registered and provides default values in that case.
- `blk_color()`: Produces colors using the Okabe-Ito colorblind-friendly palette for a character vector of block categories.
- `blk_icon_data_uri()`: Processes block icons to add color and turn them into square-shaped icons.

**Value**

Metadata is returned from `blks_metadata()` as a `data.frame` with each row corresponding to a block. Both `blk_color()` and `blk_icon_data_uri()` return character vectors.

**Examples**

```
blk <- blockr.core::new_dataset_block()
meta <- blks_metadata(blk)

col <- blk_color(meta$category)
blk_icon_data_uri(meta$icon, col)
```

---

dock_id	<i>ID utilities</i>
---------	---------------------

---

**Description**

Objects, such as blocks and dock extensions carry their own IDs. These can be converted into other ID types, such as panel IDs or "handle" IDs. Panel IDs are used to refer to dock panels, while handle IDs provide "handles" for DOM manipulations. All such IDs inherit from `dock_id` and panel IDs additionally inherit from `dock_panel_id`, while handle IDs inherit from `dock_handle_id`. For panel IDs, depending on whether the panel is showing a block or an extension, the inheritance structure additionally contains `block_panel_id` or `ext_panel_id`, respectively. Similarly, for handle IDs, we have `block_handle_id` and `ext_handle_id`. All `dock_id` objects can be converted back to native IDs, by calling `as_obj_id()`. The utility function `dock_id()` returns a (possibly namespaced) ID of the dock instance that is used to manage all visible panels.

**Usage**

```
dock_id(ns = NULL)

as_dock_panel_id(x)

as_obj_id(x)

as_block_panel_id(x)

as_ext_panel_id(x)

as_dock_handle_id(x)

as_block_handle_id(x)

as_ext_handle_id(x)
```

**Arguments**

ns	Namespace prefix
x	Object

**Value**

Coercion functions `as_block_panel_id()`, `as_ext_panel_id()`, `as_block_handle_id()` and `as_ext_handle_id()` return objects that inherit from `block_panel_id`, `ext_panel_id`, `block_handle_id` and `ext_handle_id` as classed character vectors. The less specific coercion functions `as_dock_panel_id()` and `as_dock_handle_id()` return objects that inherit from `dock_panel_id` and `dock_handle_id`, in addition to a sub-class such as `block_panel_id` or `ext_panel_id` (in the case of `as_dock_panel_id()`). If a mix of sub-classes is returned, this will be represented by a list of classed character vectors. Finally, `as_obj_id()` returns a character vector, as does `dock_id()`.

**Examples**

```
blks <- c(
  a = blockr.core::new_dataset_block(),
  b = blockr.core::new_head_block()
)

ext <- new_edit_board_extension()

as_dock_panel_id(blks)
as_dock_panel_id(ext)

identical(names(blks), as_obj_id(as_block_panel_id(blks)))

as_dock_handle_id(blks)
as_dock_handle_id(ext)

identical(names(blks), as_obj_id(as_block_handle_id(blks)))
```

---

new\_action

*Board actions*


---

**Description**

Logic including a modal-based UI for board actions such as "append block" or "edit stack" can be specified using action objects, which essentially are classed functions that can either be called to return a shiny module `as_module = TRUE` or a function `as_module = FALSE` which injects code (passed as `expr`) into a shiny server context.

**Usage**

```

new_action(func)

is_action(x)

is_action_module(x)

is_action_function(x)

add_block_action(trigger, as_module = TRUE)

append_block_action(trigger, as_module = TRUE)

remove_block_action(trigger, as_module = TRUE)

add_link_action(trigger, as_module = TRUE)

remove_link_action(trigger, as_module = TRUE)

add_stack_action(trigger, as_module = TRUE)

edit_stack_action(trigger, as_module = TRUE)

remove_stack_action(trigger, as_module = TRUE)

block_input_select(
  block = NULL,
  block_id = NULL,
  links = NULL,
  mode = c("create", "update", "inputs"),
  ...
)

block_registry_selectize(id, blocks = list_blocks())

board_select(id, blocks, selected = NULL, ...)

```

**Arguments**

func	A function which will be evaluated (with modified formals) in a shiny server context
x	Object
trigger	A string, function or <a href="#">shiny::reactive()</a>
as_module	Logical flag controlling the return type
block	Block object
block_id	Block ID
links	Links object

mode	Switch for determining the return object
...	Forwarded to other methods
id	Input ID
blocks	Character vector of block registry IDs
selected	Character vector of pre-selected block (registry) IDs

## Details

An action is a function that can be called with arguments `trigger` and `as_module` to return another function. The action `trigger` may either be a string (referring to an input), a function (that will be called with a single argument `input`) or a `shiny::reactive()` object. The flag `as_module` controls the behavior of the returned function: if `TRUE`, it is a function (inheriting from `action_module`) with arguments `board`, `update`, ... and `domain`, which, when called, again returns a function with arguments `input`, `output` and `session`, suitable as argument to `shiny::moduleServer()`. If `FALSE` is passed instead, a function (inheriting from `action_function`) with arguments `board`, `update`, ... and `domain` is returned.

The expression `expr`, passed when instantiating an action object will be evaluated in a context, where the following bindings exist: `board`, `update`, `domain`, `input`, `output` and `session`. In the case of `as_module = FALSE`, `domain` is an alias for `session`.

## Value

The constructor `new_action` returns a classed function that inherits from `action`. Inheritance can be checked with functions `is_action()`, `is_action_module()` and `is_action_function()`, which all return scalar logicals.

For utilities `block_input_select()`, `block_registry_selectize()` and `board_select`, see the respective sections.

### block\_input\_select()

Determine input options for a block by removing inputs that are already used and also takes into account some edge-cases, such as variadic blocks. If `mode` is set as "inputs", this will return a character vector, for "create", the return value of a `shiny::selectizeInput()` call and for "update", the return value of a `shiny::updateSelectizeInput()` call.

### block\_registry\_selectize()

This creates UI for a block registry selector via `shiny::selectizeInput()` and returns an object that inherits from `shiny.tag`.

### board\_select()

Block selection UI, enumerating all blocks in a board is available as `board_select()`. An object that inherits from `shiny.tag` is returned, which contains the result from a `shiny::selectizeInput()` call.

---

new_dock_board	<i>Dock board</i>
----------------	-------------------

---

## Description

Using the docking layout manager provided by dockViewR, a dock\_board extends `blockr.core::new_board()`. In addition to the attributes contained in a core board, this also includes dock extensions (as `extensions`) and the panel arrangement (as `layout`).

## Usage

```
new_dock_board(
  blocks = list(),
  links = list(),
  stacks = list(),
  ...,
  extensions = new_dock_extensions(),
  layout = default_grid(blocks, extensions),
  options = dock_board_options(),
  ctor = NULL,
  pkg = NULL,
  class = character()
)

is_dock_board(x)

as_dock_board(x, ...)

dock_layout(x)

dock_layout(x) <- value

dock_extensions(x)

dock_extensions(x) <- value

dock_ext_ids(x)

dock_board_options()
```

## Arguments

<code>blocks</code>	Set of blocks
<code>links</code>	Set of links
<code>stacks</code>	Set of stacks
<code>...</code>	Further (metadata) attributes

extensions	Dock extensions
layout	Dock layout
options	Board-level user settings
ctor, pkg	Constructor information (used for serialization)
class	Board sub-class
x	Board object
value	Replacement value

### Value

The constructor `new_dock_board()` returns a board object, as does the coercion function `as_dock_board()`. Inheritance can be checked using `is_dock_board()`, which returns a boolean. Getters `dock_layout()` and `dock_extensions()` return `dock_layout` and `dock_extension` objects while setters `dock_layout<-(())` and `dock_extensions<-(())` return the updated board object (invisibly). A character vector of IDs is returned by `dock_ext_ids()` and `dock_board_options()` returns a `board_options` object.

### Examples

```
brd <- new_dock_board(c(a = blockr.core::new_dataset_block()))
str(dock_layout(brd), max.level = 2)
```

---

new_dock_extension	<i>Dock extensions</i>
--------------------	------------------------

---

### Description

Functionality of a `dock_board` can be extended by supplying one or more `dock_extension` objects, which essentially provide UI shown in a dock panel that allows for manipulating the board state. A set of dock extensions can be combined into a `dock_extensions` object.

### Usage

```
new_dock_extension(
  server,
  ui,
  name,
  class,
  ctor = sys.parent(),
  pkg = NULL,
  options = new_board_options(),
  ...
)

is_dock_extension(x)
```



```

validate_extension(x, ...)

extension_ui(x, id, ...)

extension_server(x, ...)

extension_id(x)

extension_name(x)

extension_ctor(x)

new_dock_extensions(x = list())

is_dock_extensions(x)

validate_extensions(x)

as_dock_extensions(x, ...)

## S3 method for class 'dock_extensions'
as_dock_extensions(x, ...)

## S3 method for class 'dock_extension'
as_dock_extensions(x, ...)

## S3 method for class 'list'
as_dock_extensions(x, ...)

extension_block_callback(x, ...)

```

## Arguments

server	A function returning <code>shiny::moduleServer()</code>
ui	A function with a single argument (ns) returning a <code>shiny.tag</code>
name	Name for extension
class	Extension subclass
ctor	Constructor function name
pkg	Package to look up ctor
options	Board options supplied by an extension
...	Further attributes
x	Extension object
id	Namespace ID

**Value**

The constructors `new_dock_extension()` and `new_dock_extensions()`, as do the coercion functions `as_dock_extension()` and `as_dock_extensions()`, return objects that inherit from `dock_extension` and `dock_extensions` respectively. This inheritance structure can be checked using `is_dock_extension()` and `is_dock_extensions()`, which both return a boolean. A `dock_extension` can be validated using `validate_extension()` and a `dock_extensions` object using `validate_extensions()`, which return the input object invisibly and throw errors as side-effects. Several getter functions return extension attributes, including `extension_ui()` (a function), `extension_server()` (a function), `extension_id()` (a string), `extension_name()` (a string) and `extension_ctor()` (an object that inherits from `blockr_ctor`).

**Examples**

```
ext <- new_edit_board_extension()
is_dock_extension(ext)
```

---

<code>new_dock_layout</code>	<i>Dock layout</i>
------------------------------	--------------------

---

**Description**

The arrangement of panels in a dock can be specified using a `dock_layout` object. A default layout is available via `default_grid()` which results in two panel groups, the one on the left containing all extension panels and the one on the right all block panels. Complementing the low-level constructor `new_dock_layout()`, a high-level entry point `create_dock_layout()` will create panels for extensions and blocks, which can then be arranged via a nested list of character vectors passed as `grid` argument.

**Usage**

```
new_dock_layout(grid = NULL, panels = NULL, active_group = NULL)

default_grid(blocks, extensions)

create_dock_layout(
  blocks = list(),
  extensions = list(),
  grid = default_grid(blocks, extensions)
)

is_dock_layout(x)

validate_dock_layout(x, blocks = character())

as_dock_layout(x, ...)
```

**Arguments**

grid, panels, active_group	Layout components
blocks, extensions	Dock board components
x	Object
...	Generic consistency

**Value**

The constructor `new_dock_layout()`, as does the high-level utility `create_dock_layout()`, as well as the coercion function `as_dock_layout()`, all return a `dock_layout` object. A helper function for specifying a default grid is available as `default_grid()`, which returns a list of character vectors. The validator `validate_dock_layout()` returns its input and throws errors as side-effect and inheritance can be checked using `is_dock_layout` which returns a boolean.

**Examples**

```
blks <- c(
  a = blockr.core::new_dataset_block(),
  b = blockr.core::new_head_block()
)

exts <- list(
  edit = new_edit_board_extension()
)

grid <- list("edit", list("a", "b"))

layout <- create_dock_layout(blks, exts, grid)
is_dock_layout(layout)
```

---

new\_dock\_stack

*Colored stacks*


---

**Description**

While stacks created via `blockr.core::new_stack()` do not keep track of a color attribute, a `dock_stack` object does. Such objects can be created via `new_dock_stack()`. The color attribute can be extracted using `stack_color()` and set with `stack_color<-()`. A new color suggestion, based on existing colors, is available through `suggest_new_colors()`.

**Usage**

```

new_dock_stack(..., color = suggest_new_colors())

is_dock_stack(x)

stack_color(x)

suggest_new_colors(colors = character(), n = 1)

stack_color(x) <- value

as_dock_stack(x, ...)

```

**Arguments**

...	Passed to <code>blockr.core::new_stack()</code>
color	String-valued color value (using hex encoding)
x	object
colors	Currently used color values
n	Number of new colors to generate
value	Replacement value

**Value**

The constructor `new_dock_stack()` returns a "dock\_stack" object, which is a stack object as returned by `blockr.core::new_stack()`, with an additional color attribute. Inheritance can be checked using `is_dock_stack()`, which returns a scalar logical and the color attribute can be set and retrieved using `stack_color<-(x, value)` (returns the modified stack object invisibly) and `stack_color(x)` (returns a string), respectively. Stack objects may be coerced to "dock\_stack" using `as_dock_stack(x)` and finally, a utility function `suggest_new_colors()` which returns a character vector of new colors, based on an existing palette.

---

```
new_edit_board_extension
```

*Edit board extension*

---

**Description**

A simplistic example of an extension which can be used for manipulating the board via a table-based UI. Mainly relevant for testing purposes.

**Usage**

```
new_edit_board_extension(...)
```

**Arguments**

... Forwarded to new\_dock\_extension()

**Value**

A board extension object that additionally inherits from edit\_board\_extension.

**Examples**

```
ext <- new_edit_board_extension()
is_dock_extension(ext)
```

---

show\_panel

*UI utilities*

---

**Description**

Exported utilities for manipulating dock panels (i.e. displaying panels).

**Usage**

```
show_panel(id, board, dock, type = c("block", "extension"))
```

**Arguments**

id	Object ID
board	Board object
dock	Object available as dock in extensions
type	Either "block" or "extensions", depending on what kind of panel should be shown

**Value**

NULL, invisibly

# Index

`add_block_action (new_action)`, 4  
`add_link_action (new_action)`, 4  
`add_stack_action (new_action)`, 4  
`append_block_action (new_action)`, 4  
`as_block_handle_id (dock_id)`, 3  
`as_block_panel_id (dock_id)`, 3  
`as_dock_board (new_dock_board)`, 7  
`as_dock_extensions`  
    (`new_dock_extension`), 8  
`as_dock_handle_id (dock_id)`, 3  
`as_dock_layout (new_dock_layout)`, 10  
`as_dock_panel_id (dock_id)`, 3  
`as_dock_stack (new_dock_stack)`, 11  
`as_ext_handle_id (dock_id)`, 3  
`as_ext_panel_id (dock_id)`, 3  
`as_obj_id (dock_id)`, 3  
  
`blk_color (blks_metadata)`, 2  
`blk_icon_data_uri (blks_metadata)`, 2  
`blks_metadata`, 2  
`block_input_select (new_action)`, 4  
`block_registry_selectize (new_action)`, 4  
`blockr.core::new_board()`, 7  
`blockr.core::new_stack()`, 11, 12  
`board_select (new_action)`, 4  
  
`create_dock_layout (new_dock_layout)`, 10  
  
`default_grid (new_dock_layout)`, 10  
`dock_board_options (new_dock_board)`, 7  
`dock_ext_ids (new_dock_board)`, 7  
`dock_extensions (new_dock_board)`, 7  
`dock_extensions<- (new_dock_board)`, 7  
`dock_id`, 3  
`dock_layout (new_dock_board)`, 7  
`dock_layout<- (new_dock_board)`, 7  
  
`edit_stack_action (new_action)`, 4  
`extension_block_callback`  
    (`new_dock_extension`), 8  
  
`extension_ctor (new_dock_extension)`, 8  
`extension_id (new_dock_extension)`, 8  
`extension_name (new_dock_extension)`, 8  
`extension_server (new_dock_extension)`, 8  
`extension_ui (new_dock_extension)`, 8  
  
`is_action (new_action)`, 4  
`is_action_function (new_action)`, 4  
`is_action_module (new_action)`, 4  
`is_dock_board (new_dock_board)`, 7  
`is_dock_extension (new_dock_extension)`, 8  
`is_dock_extensions`  
    (`new_dock_extension`), 8  
`is_dock_layout (new_dock_layout)`, 10  
`is_dock_stack (new_dock_stack)`, 11  
  
`new_action`, 4  
`new_dock_board`, 7  
`new_dock_extension`, 8  
`new_dock_extensions`  
    (`new_dock_extension`), 8  
`new_dock_layout`, 10  
`new_dock_stack`, 11  
`new_edit_board_extension`, 12  
  
`remove_block_action (new_action)`, 4  
`remove_link_action (new_action)`, 4  
`remove_stack_action (new_action)`, 4  
  
`shiny::moduleServer()`, 6, 9  
`shiny::reactive()`, 5, 6  
`shiny::selectizeInput()`, 6  
`shiny::updateSelectizeInput()`, 6  
`show_panel`, 13  
`stack_color (new_dock_stack)`, 11  
`stack_color<- (new_dock_stack)`, 11  
`suggest_new_colors (new_dock_stack)`, 11  
  
`validate_dock_layout (new_dock_layout)`, 10

`validate_extension`  
    `(new_dock_extension)`, 8  
`validate_extensions`  
    `(new_dock_extension)`, 8