

# Package ‘quantbayes’

December 18, 2025

**Type** Package

**Title** Bayesian Quantification of Evidence Sufficiency

**Version** 0.1.0

**License** MIT + file LICENSE

**Language** en-GB

**Description** Implements the Quantification Evidence Standard algorithm for computing Bayesian evidence sufficiency from binary evidence matrices. It provides posterior estimates, credible intervals, percentiles, and optional visual summaries. The method is universal, reproducible, and independent of any specific clinical or rule based framework. For details see The Quantitative Omics Epidemiology Group et al. (2025) <[doi:10.64898/2025.12.02.25341503](https://doi.org/10.64898/2025.12.02.25341503)>.

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Depends** R (>= 4.1)

**Imports** ggplot2, tibble, dplyr, tidyr, purrr, stats, grDevices

**Suggests** knitr, rmarkdown, tidyverse

**LazyData** true

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Dylan Lawless [aut, cre, cph] (ORCID:  
<<https://orcid.org/0000-0001-8496-3725>>)

**Maintainer** Dylan Lawless <[admin@switzerlandomics.ch](mailto:admin@switzerlandomics.ch)>

**Repository** CRAN

**Date/Publication** 2025-12-18 14:00:02 UTC

## Contents

core_test_data . . . . .	2
quant_es_core . . . . .	2
quant_es_from_binary_table . . . . .	3
quant_es_plots . . . . .	4

Index	5
-------	---

---

core_test_data	Example binary evidence dataset for Quant ES
----------------	--

---

**Description**

Demonstration dataset used in vignettes and examples.

**Usage**

```
data(core_test_data)
```

**Format**

A data frame with 50 variants and 12 binary evidence columns.

---

quant_es_core	QuantBayES Universal Bayesian Evidence Sufficiency Scoring
---------------	--

---

**Description**

Computes posterior theta, credible intervals and percentiles for each variant given a binary evidence matrix.

**Usage**

```
quant_es_core(x, a = 1, b = 1, ci_level = 0.95)
```

**Arguments**

- x matrix of 0 and 1, rows are variants and columns are evidence rules.
- a prior alpha parameter.
- b prior beta parameter.
- ci\_level credible interval width.

**Value**

A list with:

- variants** Data frame of per variant scores.
- global** Summary list of global posterior distribution.

---

`quant_es_from_binary_table`*Read a flat binary table and run quant\_es\_core*

---

## Description

Reads a TSV, CSV or other delimited file where:

- the first column is a variant identifier (unless removed)
- remaining columns contain binary 0, 1, or NA evidence indicators.

## Usage

```
quant_es_from_binary_table(  
  path,  
  sep = "\t",  
  header = TRUE,  
  variant_col = NULL  
)
```

## Arguments

<code>path</code>	Path to a text file.
<code>sep</code>	Field separator (default tab).
<code>header</code>	Whether the file has a header.
<code>variant_col</code>	Column name containing the variant IDs. If NULL and no such column exists, sequential IDs will be created.

## Value

A standard quantbayes result list.

## Examples

```
tmp <- tempfile(fileext = ".tsv")  
write.table(core_test_data, tmp, sep = "\t", quote = FALSE, row.names = FALSE)  
res <- quant_es_from_binary_table(tmp)  
res$global
```

---

quant_es_plots	<i>quantbayes plotting utilities</i>
----------------	--------------------------------------

---

## Description

Produces diagnostic plots: global density, overlay density, evidence matrix, p\_hat, and theta credible intervals.

## Usage

```
quant_es_plots(
  res,
  x_matrix,
  top_n = 20,
  top_overlay = 10,
  highlight_points = NULL,
  palette10 = (grDevices::colorRampPalette(c("#2f4356", "#656d87", "#f1e1d4", "#ffbf00",
    "#ee4035")))(10),
  palette20 = (grDevices::colorRampPalette(c("#656d87", "#2f4356")))(20)
)
```

## Arguments

res	Result from quant_es_core.
x_matrix	Evidence matrix used for the run.
top_n	Number of variants for matrix and summary plots.
top_overlay	Number of top variants used in overlay density.
highlight_points	Optional list of highlighted variants.
palette10	Colour palette for overlay density lines.
palette20	Colour palette for p_hat plot.

## Value

A list of ggplot objects.

# Index

## \* **datasets**

core\_test\_data, [2](#)

core\_test\_data, [2](#)

quant\_es\_core, [2](#)

quant\_es\_from\_binary\_table, [3](#)

quant\_es\_plots, [4](#)