# Package 'WaveletGBM'

April 7, 2023

Type Package
Title Wavelet Based Gradient Boosting Method
Version 0.1.0
Author Dr. Ranjit Kumar Paul [aut, cre], Dr. Md Yeasin [aut]
Maintainer Dr. Ranjit Kumar Paul <ranjitstat@gmail.com></ranjitstat@gmail.com>
<b>Description</b> Wavelet decomposition method is very useful for modelling noisy time series data. Wavelet decomposition using 'haar' algorithm has been implemented to developed hybrid Wavelet GBM (Gradient Boosting Method) model for time series forecasting using algorithm by Anjoy and Paul (2017) < DOI:10.1007/s00521-017-3289-9>.
License GPL-3
Encoding UTF-8
Imports caret, dplyr, caretForecast, Metrics, tseries, stats, wavelets, gbm
RoxygenNote 7.2.1
NeedsCompilation no
Repository CRAN
<b>Date/Publication</b> 2023-04-07 08:20:02 UTC
R topics documented:
WaveletGBM
Index 3

2 WaveletGBM

1	1.0014
Wavel	etGBM

Wavelet Based Gradient Boosting Method

#### Description

Wavelet Based Gradient Boosting Method

#### Usage

```
WaveletGBM(ts, MLag = 12, split_ratio = 0.8, wlevels = 3)
```

# **Arguments**

ts Time Series Data
MLag Maximum Lags

split\_ratio Training and Testing Split
wlevels Number of Wavelet Levels

## Value

• Lag: Lags used in model

• Parameters: Parameters of the model

• Train\_actual: Actual train series

• Test\_actual: Actual test series

• Train\_fitted: Fitted train series

• Test\_predicted: Predicted test series

• Accuracy: RMSE and MAPE of the model

#### References

- Aminghafari, M. and Poggi, J.M. 2012. Nonstationary time series forecasting using wavelets and kernel smoothing. Communications in Statistics-Theory and Methods, 41(3),485-499.
- Paul, R.K. A and Anjoy, P. 2018. Modeling fractionally integrated maximum temperature series in India in presence of structural break. Theory and Applied Climatology 134, 241–249.

## **Examples**

```
library("WaveletGBM")
data<- rnorm(100,100, 10)
WG<-WaveletGBM(ts=data)</pre>
```

# **Index**

WaveletGBM, 2