

Package ‘geonuts’

January 9, 2026

Type Package

Title Identification and Visualisation of European NUTS Regions from Geolocations

Version 1.0.0

Description Provides functions to identify European NUTS (Nomenclature of Territorial Units for Statistics) regions for geographic coordinates (latitude/longitude) using Eurostat geospatial boundaries. Includes map-based visualisation of the matched regions for validation and exploration. Designed for regional data analysis, reproducible workflows, and integration with common geospatial R packages.

License GPL (>= 3)

URL <https://github.com/aikatona/geonuts>

BugReports <https://github.com/aikatona/geonuts/issues>

Depends R (>= 4.1.0)

Imports eurostat, ggplot2, giscoR, units, grid, sf

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.2

VignetteBuilder knitr

NeedsCompilation no

Author Attila I. Katona [aut, cre],
Marcell T. Kurbucz [aut]

Maintainer Attila I. Katona <katona.attila@gtk.uni-pannon.hu>

Repository CRAN

Date/Publication 2026-01-09 15:10:13 UTC

Contents

get_nuts	2
map_nuts	3

get_nuts

*Identify NUTS Regions for Geolocations***Description**

Vectorised identification of NUTS regions for input coordinates using Eurostat geospatial layers. Supports a single level (0–3) or "all" to return all levels. Optional country pre-filter and "nearest" fallback make the function robust to points falling just outside polygon boundaries.

Usage

```
get_nuts(
  latitude,
  longitude,
  level = "all",
  year = 2021,
  resolution = 20,
  crs = 4326,
  country = NULL,
  match_strategy = c("within", "nearest"),
  nearest_max_km = Inf,
  verbose = TRUE
)
```

Arguments

latitude	(numeric, mandatory) Latitudes in decimal degrees (WGS84). Must be within $[-90, 90]$.
longitude	(numeric, mandatory) Longitudes in decimal degrees (WGS84). Must be within $[-180, 180]$. Length must match latitude.
level	(integer or character, optional) One of 0, 1, 2, 3, "all". Default: "all". When "all", the result includes nuts0..nuts3.
year	(integer, optional) NUTS reference year for the Eurostat layer. Default: 2021.
resolution	(integer, optional) Eurostat map resolution. Typical values: 1, 3, 10, 20, 60. Default: 20.
crs	(integer, optional) EPSG code of input coordinates. If not 4326, inputs are transformed to WGS84 (EPSG:4326). Default: 4326.
country	(character, optional) Two-letter CNTR_CODE to pre-filter polygons (e.g., "DE", "IT"). Reduces memory and speeds up queries.
match_strategy	(character, optional) Matching strategy: "within" (default) assigns a NUTS only when the point lies within a polygon; "nearest" uses the nearest NUTS polygon for unmatched points.
nearest_max_km	(numeric, optional) Maximum distance (km) for nearest fallback; use Inf to allow any distance. Default: Inf.
verbose	(logical, optional) Print informative messages. Default: TRUE.

Details

- Geometries are downloaded via `eurostat::get_eurostat_geospatial()` and cached per (level, year, resolution) to avoid repeated I/O.
- Polygons are pre-filtered using the points' bounding box to accelerate joins on continental layers (with safe fallback).
- Nearest distances are computed with units and converted to kilometers.

Value

If level is a single integer: a data.frame with columns lat, lon, nuts, cntr_code, match_status, match_dist_km, level, year, resolution. If level = "all": a data.frame with lat, lon, nuts0, nuts1, nuts2, nuts3, cntr_code, match_status, match_dist_km, year, resolution. Here match_status/match_dist_km are computed using level 3 (most granular).

See Also

[map_nuts](#)

Examples

```
res <- get_nuts(52.52, 13.405, level = 3, year = 2021, resolution = 20)
head(res)
```

map_nuts

Plot NUTS Matches on a Map

Description

Visualises the frequency of matched NUTS regions and (optionally) overlays the input points (matched vs. unmatched) for validation. Works with both single-level and multi-level (level = "all") outputs from [get_nuts](#).

Usage

```
map_nuts(
  nuts,
  map_level = 3,
  country = NULL,
  show_points = TRUE,
  border_col = "lightgrey",
  low_col = "lightgreen",
  high_col = "darkgreen",
  id_col = "black",
  uid_col = "red",
  verbose = TRUE
)
```

Arguments

nuts	(data.frame, mandatory) Output of get_nuts . Must include lat, lon, and either nuts (single-level) or any of nuts0..nuts3, plus year, resolution. If both single and multi-level columns exist, map_level selects which to display.
map_level	(integer, optional) NUTS level to display when multiple levels are present. One of 0, 1, 2, 3. Default: 3.
country	(character, optional) Two-letter CNTR_CODE to filter the map polygons (e.g., "DE", "FR"). If NULL, uses all available regions.
show_points	(logical, optional) Overlay input points. Default: TRUE.
border_col	(character, optional) Polygon border colour. Default: "lightgrey".
low_col	(character, optional) Fill colour for lower frequencies. Default: "lightgreen".
high_col	(character, optional) Fill colour for higher frequencies. Default: "darkgreen".
id_col	(character, optional) Point colour for matched/nearest inputs. Default: "black".
uid_col	(character, optional) Point colour for unmatched inputs. Default: "red".
verbose	(logical, optional) Print informative messages. Default: TRUE.

Value

A ggplot2 object showing a choropleth of NUTS frequencies with optional point overlays.

See Also

[get_nuts](#)

Examples

```
res <- get_nuts(52.52, 13.405, level = 3, year = 2021, resolution = 20)
p <- map_nuts(res, map_level = 3)
print(p)
```

Index

`get_nuts`, [2](#), [3](#), [4](#)

`map_nuts`, [3](#), [3](#)