# Package 'piiR'

April 10, 2025

Type P	ackage
Title P	redictive Information Index ('PII')
Version	0.2.0
Mainta	iner Kevin E. Wells <kevin.e.wells@usm.edu></kevin.e.wells@usm.edu>
m	<b>A</b> simple implementation of the Predictive Information Index ('PII') using mutual information and entropy from the 'infotheo' package.  or related methodology, see Wells (2025) <a href="https://github.com/TheotherDrWells/piiR">https://github.com/TheotherDrWells/piiR</a> >.
License	MIT + file LICENSE
Encodi	ng UTF-8
Import	s stats (>= 3.6.0), infotheo (>= 1.2.0), pROC (>= 1.18.0)
Vignett	eBuilder knitr
Suggest	s knitr, rmarkdown
Roxyge	nNote 7.3.2
NeedsC	compilation no
Author	Kevin E. Wells [aut, cre]
Reposit	ory CRAN
- Date/Pı	ublication 2025-04-10 14:30:08 UTC
Cont	ents
	compare_scores
	pii
	pii_batch
	pii_classification
	pii_compare
	pii_plot
Index	

2 pii

compare\_scores

Compare Multiple Scoring Methods

#### **Description**

Compare Multiple Scoring Methods

#### Usage

```
compare_scores(outcome, scores, bins = 10)
```

#### **Arguments**

outcome Vector of outcomes

scores Named list of score vectors

bins Number of bins

#### Value

Data frame with PII and RMSE

pii

Predictive Information Index (PII)

#### **Description**

Computes the Predictive Information Index using one of three methods: "r2" (R-squared ratio), "rm" (RMSE-based), or "v" (variance ratio).

#### Usage

```
pii(full_preds, score_preds, type = c("r2", "rm", "v"))
```

## **Arguments**

full\_preds Predicted values from the full (benchmark) model.
score\_preds Predicted values from the score-based model.
type Type of PII to compute: "r2", "rm", or "v".

#### Value

A numeric value between 0 and 1.

#### **Examples**

```
full <- rnorm(100)
score <- full + rnorm(100, sd = 0.5)
pii(full, score, type = "rm")</pre>
```

pii\_batch 3

#### **Description**

Evaluates PII and RMSE for multiple predictors

#### Usage

```
pii_batch(formula, data, bins = 10)
```

#### Arguments

formula A formula with multiple predictors (e.g., outcome  $\sim x1 + x2 + x3$ )

data A data.frame

bins Number of bins for discretization

#### Value

A data.frame of PII and RMSE for each predictor

#### Description

PII for Classification Outcomes with Metrics

## Usage

```
pii_classification(score, outcome, bins = 10)
```

#### Arguments

score Predicted numeric score outcome Binary factor outcome

bins Number of bins for discretization

#### Value

List with PII, AUC, accuracy, confusion matrix

pii\_plot

pii\_compare

Compare PII and RMSE Across Multiple Scores

### Description

Compare PII and RMSE Across Multiple Scores

#### Usage

```
pii_compare(outcome, scores, bins = 10)
```

#### Arguments

outcome A numeric outcome vector
scores A named list of score vectors
bins Number of bins for PII

#### Value

A data frame of comparison metrics

pii\_plot

Plot Score vs Outcome for Visual PII Insight

#### Description

Plot Score vs Outcome for Visual PII Insight

#### Usage

```
pii_plot(score, outcome, bins = 10)
```

#### **Arguments**

score Numeric score vector
outcome Numeric outcome vector

bins Number of bins for discretization

#### Value

A base R plot

pii\_test 5

pii_test	Permutation Test for PII	

## Description

Permutation Test for PII

#### Usage

```
pii_test(score, outcome, bins = 10, n_perm = 1000)
```

#### Arguments

score Numeric score vector outcome Outcome vector

bins Number of bins for discretization

n\_perm Number of permutations

#### Value

List with observed PII, p-value, and null distribution

## **Index**

```
compare_scores, 2
pii, 2
pii_batch, 3
pii_classification, 3
pii_compare, 4
pii_plot, 4
pii_test, 5
```