

Package ‘contextFind’

October 26, 2025

Title Find Code Snippets with Context and Click to Navigate Directly to Results

Version 1.0.1

Description

Search across R files with contextual results, highlights and clickable links. Includes an add-in for further workflow enhancement.

License CC0

Encoding UTF-8

RoxygenNote 7.3.2

Imports rstudioapi, cli, shiny, miniUI

Suggests testthat (>= 3.0.0), knitr, rmarkdown

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Steve Jackson [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-3337-7846>>)

Maintainer Steve Jackson <s87jackson@gmail.com>

Repository CRAN

Date/Publication 2025-10-26 20:30:08 UTC

Contents

contextFind	2
contextFind_addin	3
Index	4

`contextFind`*Search R and Rmd Files for Matching Text, Get Context and Links*

Description

Search R and Rmd Files for Matching Text, Get Context and Links

Usage

```
contextFind(  
  search_text,  
  path = ".",  
  recursive = TRUE,  
  contextLines = 2,  
  verbose = TRUE  
)
```

Arguments

<code>search_text</code>	Text to search for
<code>path</code>	Root directory to search
<code>recursive</code>	Whether to recurse into subfolders
<code>contextLines</code>	Number of context lines around match
<code>verbose</code>	If TRUE (the default), prints the results to the console

Value

A list of lists, one for each match, with objects: `file`, `match_line`, `mtime`, and `context`. `file` is the file path in which the match was found, `match_line` is the line number for this particular match, `mtime` is a POSIXct datetime value indicating when the file was last modified, and `context` contains the number of lines before and after the found match (set by the `contextLines` parameter).

Examples

```
# Find custom functions in your codebase  
contextFind("<- function")  
  
# Get more context  
contextFind("<- function", contextLines = 3)  
  
# Explicitly set the search directory  
contextFind("<- function", path = getwd())  
  
# Exclude subdirectories  
contextFind("<- function", recursive = FALSE)
```

contextFind_addin	<i>RStudio Add-in for contextFind</i>
-------------------	---------------------------------------

Description

Launches an interactive gadget for searching project files. The gadget allows the user to enter a search string, choose a directory, specify whether the search should be recursive, and how many lines of context to print. Results are displayed in the console with clickable links to matched lines.

Usage

```
contextFind_addin()
```

Value

Invisibly returns the search results as a list (see [contextFind\(\)](#)).

See Also

[contextFind\(\)](#)

Index

contextFind, [2](#)
contextFind(), [3](#)
contextFind_addin, [3](#)