# Package 'esback'

September 3, 2023

Type Package
Title Expected Shortfall Backtesting
Version 0.3.1
<b>Date</b> 2023-09-02
Description Implementations of the expected shortfall backtests of Bayer and Dimitriadis (2020) <doi:10.1093 jjfinec="" nbaa013=""> as well as other well known backtests from the literature. Can be used to assess the correctness of forecasts of the expected shortfall risk measure which is e.g. used in the banking and finance industry for quantifying the market risk of investments. A special feature of the backtests of Bayer and Dimitriadis (2020) <doi:10.1093 jjfinec="" nbaa013=""> is that they only require forecasts of the expected shortfall, which is in striking contrast to all other existing backtests, making them particularly attractive for practitioners.</doi:10.1093></doi:10.1093>
License GPL-3
Encoding UTF-8
LazyData true
<b>Depends</b> $R(>=2.10.0)$
Imports esreg
RoxygenNote 7.2.3
NeedsCompilation no
Author Sebastian Bayer [aut, cre], Timo Dimitriadis [aut]
Maintainer Sebastian Bayer < sebastian.bayer@uni-konstanz.de>
Repository CRAN
<b>Date/Publication</b> 2023-09-03 19:10:05 UTC
R topics documented:  cc_backtest

2 cc\_backtest

Inday	risk_forecasts		•	•	 	•	•	•	•	•		٠		•			•	•	•	 •	•	•		•	 •	5 7
	esr_backtest .																									
	er_backtest . esback																									

# Description

The simple and general conditional calibration backtests of Nolde & Ziegel (2007).

# Usage

```
cc_backtest(r, q, e, s = NULL, alpha, hommel = TRUE)
```

# Arguments

r	A vector of returns.
q	A vector of Value-at-Risk forecasts.
е	A vector of Expected Shortfall forecasts.
S	A vector of volatility forecasts.
alpha	Scalar probability level in $(0, 1)$ .
hommel	If TRUE, use Hommels correction, otherwise use the classical Bonferroni cor-
	rection.

#### Value

Returns a list with the following components:

- pvalue\_twosided\_simple
- pvalue\_onesided\_simple
- pvalue\_twosided\_general
- pvalue\_onesided\_general

#### References

Nolde & Ziegel (2007) doi:10.1214/17AOAS1041

# **Examples**

```
data(risk_forecasts)
r <- risk_forecasts$r
q <- risk_forecasts$q
e <- risk_forecasts$e
s <- risk_forecasts$s
cc_backtest(r = r, q = q, e = e, s = s, alpha = 0.025)</pre>
```

er\_backtest 3

er	backtest	
er	Dacktest	

Exceedance Residuals Backtest

#### **Description**

Tests whether the mean of the exceedance residuals, respectively the mean of the standardized exceedance residuals is zero.

#### Usage

```
er_backtest(r, q, e, s = NULL, B = 1000)
```

# Arguments

r	A vector of returns.
q	A vector of Value-at-Risk forecasts.
е	A vector of Expected Shortfall forecasts.
S	A vector of volatility forecasts.
В	Number of bootstrap iterations

#### Value

Returns a list with the following components:

- pvalue\_twosided\_simple
- pvalue\_onesided\_simple
- pvalue\_twosided\_standardized
- pvalue\_onesided\_standardized

#### References

McNeil & Frey (2000) doi:10.1016/S09275398(00)000128

#### **Examples**

```
data(risk_forecasts)
r <- risk_forecasts$r
q <- risk_forecasts$q
e <- risk_forecasts$e
s <- risk_forecasts$s
er_backtest(r = r, q = q, e = e, s = s)</pre>
```

4 esr\_backtest

esback

esback: A package for backtesting expected shortfall forecasts

#### **Description**

The esback package contains functions for backtesting expected shortfall forecasts.

#### Available backtest functions

- Exceedance Residuals Backtest (McNeil & Frey, 2000)
- Conditional Calibration Backtest (Nolde & Ziegel, 2017)
- Expeced Shortfall Regression Backtests (Bayer & Dimitriadis, 2018)

#### Author(s)

**Maintainer**: Sebastian Bayer <sebastian.bayer@uni-konstanz.de> Authors:

• Timo Dimitriadis <timo.dimitriadis@awi.uni-heidelberg.de>

esr\_backtest

Expected Shortfall Regression Backtest

#### **Description**

This function implements multiple expected shortfall regression (esreg) based backtests. Using the version argument, the following backtests are available:

- 1. ("Strict ESR") Regresses the returns on the expected shortfall forecasts and tests the ES coefficients for (0, 1).
- 2. ("Auxiliary ESR") Regresses the returns on the quantile and the expected shortfall forecasts and tests the ES coefficients for (0, 1).
- 3. ("Strict Intercept") Tests whether the expected shortfall of the forecast error r e is zero.

#### Usage

```
esr_backtest(
   r,
   q,
   e,
   alpha,
   version,
   B = 0,
   cov_config = list(sparsity = "nid", sigma_est = "scl_sp", misspec = TRUE)
)
```

risk\_forecasts 5

#### **Arguments**

r	A vector of returns.
q	A vector of Value-at-Risk forecasts.
е	A vector of Expected Shortfall forecasts.
alpha	Scalar probability level in (0, 1).
version	Version of the backtest to be used
В	Number of bootstrap samples. Set to 0 to disable bootstrapping.
cov_config	a list with three components: sparsity, sigma_est, and misspec, see vcovA

#### Value

Returns a list with the following components:

```
• pvalue_two_sided_asymptotic
```

- pvalue\_one\_sided\_asymptotic (for version 3)
- pvalue\_two\_sided\_bootstrap
- pvalue\_one\_sided\_bootstrap (for version 3)

#### References

Bayer & Dimitriadis (2020) doi:10.1093/jjfinec/nbaa013

#### **Examples**

```
data(risk_forecasts)
r <- risk_forecasts$r
q <- risk_forecasts$q
e <- risk_forecasts$e
esr_backtest(r = r, q = q, e = e, alpha = 0.025, version = 1)</pre>
```

risk\_forecasts

Returns and risk forecasts for the S&P 500 index

# Description

A dataset containing the daily log returns and risk forecasts for the S&P 500 index. The quantile and expected shortfall forecasts are for the probability level 2.5%.

#### Usage

```
data(risk_forecasts)
```

#### Format

A data.frame with 4396 rows and 4 variables

risk\_forecasts

# **Details**

Description of the variables:

r Daily log returns from January 3, 2000 to September 29, 2017 (4465 days)

- q Value-at-Risk forecasts of the Historical Simulation approach
- e Expected shortfall forecasts of the Historical Simulation approach
- $\boldsymbol{s}$  Volatility forecasts of the Historical Simulation approach

# **Index**