

Package ‘evidenceratio’

January 21, 2026

Type Package

Title Likelihood-Based Evidence Ratios for Classical Statistical Tests

Version 0.1.0

License MIT + file LICENSE

Language en-GB

Description Implements likelihood-based evidence ratios for unified reporting in classical statistical testing. The package reports effect estimates, uncertainty intervals, and likelihood ratios on the log 10 scale derived from a single statistical model. It applies to standard normal mean tests, contingency tables, and regression coefficients, and provides a direct evidential measure while retaining classical error guarantees. For the Evidence Ratio Reporting Standard see Lawless (2026) [<doi:10.5281/zenodo.18261076>](https://doi.org/10.5281/zenodo.18261076).

Encoding UTF-8

Depends R (>= 4.0)

Imports stats

Suggests testthat (>= 3.1.0), waldo (>= 0.5.0), knitr, rmarkdown, ggplot2

VignetteBuilder knitr

RoxygenNote 7.3.2

NeedsCompilation no

Author Dylan Lawless [aut, cre, cph] (ORCID: [<https://orcid.org/0000-0001-8496-3725>](https://orcid.org/0000-0001-8496-3725))

Maintainer Dylan Lawless <admin@switzerlandomics.ch>

Repository CRAN

Date/Publication 2026-01-21 20:00:08 UTC

Contents

evidence_test	2
Index	3

evidence_test	<i>Likelihood-based evidence ratio test</i>
---------------	---

Description

Computes an effect estimate, a Wald-style uncertainty interval, and a likelihood-based evidence ratio (log10 scale) from a single statistical model.

Usage

```
evidence_test(...)
```

Arguments

... Arguments defining the data and model.

Value

An object of class `evidence_result`.

Examples

```
x <- sleep$extra[sleep$group == 1]
evidence_test(x)

tbl <- matrix(c(30, 70, 20, 80), nrow = 2)
evidence_test(tbl)

evidence_test(mpg ~ wt, data = mtcars, coef = "wt")
```

Index

evidence_test, [2](#)