

Package ‘spatialAtomizeR’

December 10, 2025

Type Package

Title Spatial Analysis with Misaligned Data Using Atom-Based Regression Models

Version 0.2.3

Date 2025-11-28

Description Implements atom-based regression models (ABRM) for analyzing spatially misaligned data. Provides functions for simulating misaligned spatial data, preparing NIMBLE model inputs, running MCMC diagnostics, and comparing different spatial analysis methods including dasymetric mapping. All main functions return S3 objects with print(), summary(), and plot() methods for intuitive result exploration. Methods are described in Nethery et al. (2023) <doi:10.1101/2023.01.10.23284410>. Further methodological details and software implementation are described in Qian et al. (in review).

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 4.0.0)

Imports sp, sf, spdep, MASS, raster, dplyr, tidyr, ggplot2, reshape2, nimble, coda, BiasedUrn, stats, utils, grDevices, methods

Suggests testthat (>= 3.0.0), knitr, rmarkdown

VignetteBuilder knitr

URL <https://github.com/bellayqian/spatialAtomizeR>

BugReports <https://github.com/bellayqian/spatialAtomizeR/issues>

RoxygenNote 7.3.3

NeedsCompilation no

Author Yunzhe Qian [aut, cre],
Rachel Nethery [aut],
Nancy Krieger [ctb] (Contributed to the project conceptualization and manuscript),
Nykesha Johnson [ctb] (Contributed to the project conceptualization and manuscript)

Maintainer Yunzhe Qian <qyzanemos@gmail.com>

Repository CRAN

Date/Publication 2025-12-10 21:10:07 UTC

Contents

biasedUrn_rmfnc	3
check_mcmc_diagnostics	3
create_comparison_plots	4
create_diagnostic_plots	4
create_sensitivity_summary_plots	5
create_summary_statistics	5
dasymetric_mapping	6
fit_dasymetric_model	6
gen_correlated_spat	7
get_abrm_model	7
plot.abrm	8
plot.abrm_comparison	8
prepare_adjacency_matrices	9
prepare_nimble_inputs	9
prepare_spatial_bookkeeping	10
print.abrm	11
print.abrm_comparison	11
print.misaligned_data	12
print.sensitivity_analysis	12
print_convergence_summary	13
register_nimble_distributions	13
run_abrm	14
run_both_methods	15
run_nimble_model	16
run_sensitivity_analysis	17
simulate_misaligned_data	18
summary.abrm	20
summary.abrm_comparison	20
summary.misaligned_data	21
summary.sensitivity_analysis	21

Index

22

biasedUrn_rmfnc	<i>R Wrapper Function for BiasedUrn Sampling</i>
-----------------	--

Description

Wraps the BiasedUrn::rMFNCHypergeo function for use in NIMBLE models

Usage

```
biasedUrn_rmfnc(total, odds, ni)
```

Arguments

total	Integer, total number of items to sample
odds	Numeric vector of odds for each category
ni	Integer vector of population sizes

Value

Numeric vector of sampled counts

check_mcmc_diagnostics	<i>Check MCMC Diagnostics</i>
------------------------	-------------------------------

Description

Calculates convergence diagnostics including Gelman-Rubin statistics and effective sample sizes for MCMC output

Usage

```
check_mcmc_diagnostics(mcmc_output, sim_metadata = NULL)
```

Arguments

mcmc_output	Output from NIMBLE MCMC containing samples
sim_metadata	Optional list with simulation metadata

Value

List with diagnostic results including convergence statistics and plots

`create_comparison_plots`*Create Comparison Plots*

Description

Create Comparison Plots

Usage

```
create_comparison_plots(comparison_data, output_dir, true_params = NULL)
```

Arguments

<code>comparison_data</code>	Data frame with comparison results
<code>output_dir</code>	Output directory for plots
<code>true_params</code>	True parameter values (optional)

Value

No return value, called for side effects. Creates and displays/saves comparison plots of coefficient estimates, bias, and coverage rates across different methods. If `output_dir` is provided, plots are saved to a PDF file.

`create_diagnostic_plots`*Create Diagnostic Plots*

Description

Create Diagnostic Plots

Usage

```
create_diagnostic_plots(chains_list, sim_metadata)
```

Arguments

<code>chains_list</code>	List of MCMC chains
<code>sim_metadata</code>	Simulation metadata

Value

List with trace and density plots

create_sensitivity_summary_plots
Create Sensitivity Summary Plots

Description

Create Sensitivity Summary Plots

Usage

```
create_sensitivity_summary_plots(combined_results, output_dir)
```

Arguments

combined_results	Combined results data frame
output_dir	Output directory

Value

No return value, called for side effects. Creates and displays/saves summary plots for sensitivity analysis including correlation effects, bias patterns, and coverage rates. If output_dir is provided, plots are saved to a PDF file.

create_summary_statistics
Create Summary Statistics

Description

Create Summary Statistics

Usage

```
create_summary_statistics(all_results, output_dir)
```

Arguments

all_results	Combined results data frame
output_dir	Output directory

Value

A list with two components: method_summary (data frame containing overall summary statistics for each method, including mean bias, relative bias, and coverage rates) and param_summary (data frame containing parameter-specific comparisons across methods). The function also saves these summaries to CSV files in the output directory.

dasymetric_mapping	<i>Dasymetric Mapping</i>
--------------------	---------------------------

Description

Maps X-grid covariates to Y-grid using centroid-based spatial join

Usage

```
dasymetric_mapping(misaligned_data)
```

Arguments

misaligned_data	List with gridx and gridy from simulate_misaligned_data
-----------------	---

Value

sf object with Y grid containing mapped X covariates

fit_dasymetric_model	<i>Fit Dasymetric Model</i>
----------------------	-----------------------------

Description

Fits regression model to dasymetrically mapped data

Usage

```
fit_dasymetric_model(mapped_data, outcome_type)
```

Arguments

mapped_data	Output from dasymetric_mapping
outcome_type	Distribution type: 'normal', 'poisson', or 'binomial'

Value

Data frame with parameter estimates and confidence intervals

gen_correlated_spat	<i>Generate Correlated Spatial Effects</i>
---------------------	--

Description

Generate Correlated Spatial Effects

Usage

```
gen_correlated_spat(
  W,
  n_vars,
  rho = 0.6,
  var_spat = 1,
  correlation = 0.5,
  verify = FALSE
)
```

Arguments

W	Spatial adjacency matrix
n_vars	Number of variables
rho	Spatial correlation parameter (default = 0.6)
var_spat	Spatial variance (default = 1)
correlation	Correlation between variables (default = 0.5)
verify	Logical for verification (default = FALSE)

Value

Matrix of spatial effects

get_abrm_model	<i>Get ABRM Model Code for NIMBLE</i>
----------------	---------------------------------------

Description

Returns the NIMBLE code for the Atom-Based Regression Model with mixed-type variables. Automatically registers custom distributions if not already registered.

Usage

```
get_abrm_model()
```

Value

A nimbleCode object containing the model specification

plot.abrm	<i>Plot method for abrm objects</i>
-----------	-------------------------------------

Description

Plot method for abrm objects

Usage

```
## S3 method for class 'abrm'
plot(x, ...)
```

Arguments

x	An object of class "abrm"
...	Additional arguments (ignored)

Value

Invisibly returns the input object x. The function is called for its side effect of displaying MCMC diagnostic plots (trace plots and density plots) if they are available in the abrm object.

plot.abrm_comparison	<i>Plot method for abrm_comparison objects</i>
----------------------	--

Description

Plot method for abrm_comparison objects

Usage

```
## S3 method for class 'abrm_comparison'
plot(x, ...)
```

Arguments

x	An object of class "abrm_comparison"
...	Additional arguments (ignored)

Value

Invisibly returns the input object x. The function is called for its side effect of displaying comparison plots between methods if true parameters are available in the comparison object.

```
prepare_adjacency_matrices
```

Prepare Adjacency Matrices

Description

Prepare Adjacency Matrices

Usage

```
prepare_adjacency_matrices(gridy_yorder, gridx_xorder)
```

Arguments

gridy_yorder	Reordered Y grid
gridx_xorder	Reordered X grid

Value

List containing W_x and W_y adjacency matrices

```
prepare_nimble_inputs
```

Prepare NIMBLE Model Inputs

Description

Prepare NIMBLE Model Inputs

Usage

```
prepare_nimble_inputs(
  bookkeeping,
  adjacency,
  data,
  norm_idx_x = NULL,
  pois_idx_x = NULL,
  binom_idx_x = NULL,
  norm_idx_y = NULL,
  pois_idx_y = NULL,
  binom_idx_y = NULL,
  dist_y = 2
)
```

Arguments

bookkeeping	Output from prepare_spatial_bookkeeping
adjacency	Output from prepare_adjacency_matrices
data	Original simulated data
norm_idx_x	Indices of normal-distributed X covariates
pois_idx_x	Indices of Poisson-distributed X covariates
binom_idx_x	Indices of binomial-distributed X covariates
norm_idx_y	Indices of normal-distributed Y covariates
pois_idx_y	Indices of Poisson-distributed Y covariates
binom_idx_y	Indices of binomial-distributed Y covariates
dist_y	Distribution type for outcome (1=normal, 2=poisson, 3=binomial)

Value

List containing constants, data, and inits for NIMBLE

```
prepare_spatial_bookkeeping
```

Prepare Spatial Bookkeeping

Description

Prepare Spatial Bookkeeping

Usage

```
prepare_spatial_bookkeeping(data)
```

Arguments

data	List containing gridy, gridx, and atoms from simulate_misaligned_data
------	---

Value

List of bookkeeping objects for NIMBLE model

print.abrm	<i>Print method for abrm objects</i>
------------	--------------------------------------

Description

Print method for abrm objects

Usage

```
## S3 method for class 'abrm'
print(x, ...)
```

Arguments

x	An abrm object
...	Additional arguments (unused)

Value

Invisibly returns the input object x. The function is called for its side effect of printing a summary of the ABRM model results including convergence status, number of parameters estimated, and key fit statistics.

print.abrm_comparison	<i>Print method for abrm_comparison objects</i>
-----------------------	---

Description

Print method for abrm_comparison objects

Usage

```
## S3 method for class 'abrm_comparison'
print(x, ...)
```

Arguments

x	A abrm_comparison object
...	Additional arguments (unused)

Value

Invisibly returns the input object x. The function is called for its side effect of printing a summary of method comparison results including the number of simulations and methods compared.

`print.misaligned_data` *Print method for misaligned_data objects*

Description

Print method for misaligned_data objects

Usage

```
## S3 method for class 'misaligned_data'  
print(x, ...)
```

Arguments

<code>x</code>	A misaligned_data object
<code>...</code>	Additional arguments (unused)

Value

Invisibly returns the input object `x`. The function is called for its side effect of printing a summary of the simulated misaligned spatial data including grid dimensions and number of atoms.

`print.sensitivity_analysis`
Print method for sensitivity_analysis objects

Description

Print method for sensitivity_analysis objects

Usage

```
## S3 method for class 'sensitivity_analysis'  
print(x, ...)
```

Arguments

<code>x</code>	A sensitivity_analysis object
<code>...</code>	Additional arguments (unused)

Value

Invisibly returns the input object `x`. The function is called for its side effect of printing a summary of the sensitivity analysis results including the number of simulations and scenarios tested.

```
print_convergence_summary
```

Print Convergence Summary

Description

Print Convergence Summary

Usage

```
print_convergence_summary(convergence_results)
```

Arguments

```
convergence_results
```

Results from check_mcmc_diagnostics

Value

No return value, called for side effects. Prints convergence diagnostics including overall convergence status, minimum effective sample size, median ESS, maximum Rhat statistic, and identifies parameters with high relative variance.

```
register_nimble_distributions
```

Register Custom NIMBLE Distributions

Description

Registers the custom multivariate non-central hypergeometric distribution for use in NIMBLE models. This function is called automatically when needed.

Usage

```
register_nimble_distributions()
```

Value

Invisible TRUE if successful

Note

The «- operator is used intentionally to create package-level nimbleFunctions accessible across the package environment.

run_abrm

*Run ABRM Analysis***Description**

Runs the Atom-Based Regression Model on simulated data

Usage

```
run_abrm(
  gridx,
  gridy,
  atoms,
  model_code,
  true_params = NULL,
  norm_idx_x = NULL,
  pois_idx_x = NULL,
  binom_idx_x = NULL,
  norm_idx_y = NULL,
  pois_idx_y = NULL,
  binom_idx_y = NULL,
  dist_y = 2,
  niter = 50000,
  nburnin = 30000,
  nchains = 2,
  thin = 10,
  sim_metadata = NULL,
  save_plots = TRUE,
  output_dir = NULL
)
```

Arguments

gridx	The X-grid sf dataframe, containing a numeric area ID variable named 'ID' and covariates named 'covariate_x_1', 'covariate_x_2', ...
gridy	The Y-grid sf dataframe, containing a numeric area ID variable named 'ID', covariates named 'covariate_y_1', 'covariate_y_2', ..., and an outcome named 'y'.
atoms	The atom sf dataframe, which should contain numeric variables named 'ID_x' and 'ID_y' holding the X-grid and Y-grid cell IDs for each atom, as well as an atom-level population count named 'population'.
model_code	NIMBLE model code from get_abrm_model()
true_params	The true outcome model regression coefficient parameters, if known (e.g., from simulate_misaligned_data())
norm_idx_x	Vector of numeric indices of X-grid covariates (ordered as 'covariate_x_1', 'covariate_x_2', ...) that should be treated as normally-distributed

pois_idx_x	Vector of numeric indices of X-grid covariates (ordered as 'covariate_x_1','covariate_x_2',...) that should be treated as Poisson-distributed
binom_idx_x	Vector of numeric indices of X-grid covariates (ordered as 'covariate_x_1','covariate_x_2',...) that should be treated as binomial-distributed
norm_idx_y	Vector of numeric indices of Y-grid covariates (ordered as 'covariate_y_1','covariate_y_2',...) that should be treated as normally-distributed
pois_idx_y	Vector of numeric indices of Y-grid covariates (ordered as 'covariate_y_1','covariate_y_2',...) that should be treated as Poisson-distributed
binom_idx_y	Vector of numeric indices of Y-grid covariates (ordered as 'covariate_y_1','covariate_y_2',...) that should be treated as binomial-distributed
dist_y	Distribution type for outcome (1=normal, 2=poisson, 3=binomial)
niter	Number of MCMC iterations (default: 50000)
nburnin	Number of burn-in iterations (default: 30000)
nchains	Number of MCMC chains (default: 2)
thin	Thinning interval (default: 10)
sim_metadata	Optional simulation metadata list
save_plots	Logical, whether to save diagnostic plots (default: TRUE)
output_dir	Directory for saving outputs (default: NULL)

Value

List containing MCMC results and parameter estimates

run_both_methods	<i>Run Both Methods and Compare</i>
------------------	-------------------------------------

Description

Runs both ABRM and dasymetric mapping methods and compares results

Usage

```
run_both_methods(
  sim_data,
  sim_metadata,
  model_code,
  nimble_params,
  output_dir,
  norm_idx_x,
  pois_idx_x,
  binom_idx_x,
  norm_idx_y,
  pois_idx_y,
```

```

    binom_idx_y,
    dist_y,
    outcome_type
  )

```

Arguments

sim_data	List of data elements to be used in the ABRM, structured like the output from the <code>simulate_misaligned_data()</code> function. The first element of this list is the Y-grid sf dataframe (named 'gridy'), containing a numeric area ID variable named 'ID_y', covariates named 'covariate_y_1','covariate_y_2',..., and an outcome named 'y'. The second element of this list is the X-grid sf dataframe (named 'gridx'), containing a numeric area ID variable named 'ID_x' and covariates named 'covariate_x_1','covariate_x_2',... The third element of the list is the atom sf dataframe (named 'atoms'), which should contain variables named 'ID_x' and 'ID_y' holding the X-grid and Y-grid cell IDs for each atom, as well as an atom-level population count named 'population'.
sim_metadata	Simulation metadata
model_code	NIMBLE model code
nimble_params	List of NIMBLE parameters (niter, nburnin, thin, nchains)
output_dir	Output directory
norm_idx_x	Indices of normal X covariates
pois_idx_x	Indices of Poisson X covariates
binom_idx_x	Indices of binomial X covariates
norm_idx_y	Indices of normal Y covariates
pois_idx_y	Indices of Poisson Y covariates
binom_idx_y	Indices of binomial Y covariates
dist_y	Distribution type for outcome (1=normal, 2=poisson, 3=binomial)
outcome_type	Outcome distribution name

Value

List with combined comparison, ABRM results, and dasymetric results

run_nimble_model	<i>Run NIMBLE Model with Diagnostics</i>
------------------	--

Description

Run NIMBLE Model with Diagnostics

Usage

```
run_nimble_model(
  constants,
  data,
  inits,
  sim_metadata = NULL,
  model_code,
  niter = 50000,
  nburnin = 30000,
  nchains = 2,
  thin = 10,
  save_plots = TRUE,
  output_dir = NULL
)
```

Arguments

constants	List of model constants
data	List of data
inits	List of initial values
sim_metadata	List with simulation metadata (optional)
model_code	NIMBLE code object
niter	Number of MCMC iterations (default: 50000)
nburnin	Number of burn-in iterations (default: 30000)
nchains	Number of MCMC chains (default: 2)
thin	Thinning interval (default: 10)
save_plots	Logical, whether to save diagnostic plots (default: TRUE)
output_dir	Directory for saving plots (default: NULL)

Value

List containing MCMC samples, summary, and convergence diagnostics

```
run_sensitivity_analysis
```

Run Sensitivity Analysis

Description

Performs sensitivity analysis across different correlation structures

Usage

```
run_sensitivity_analysis(
  correlation_grid = c(0.2, 0.6),
  n_sims_per_setting = 3,
  base_params = list(dist_covariates_x = c("normal", "poisson", "binomial"),
    dist_covariates_y = c("normal", "poisson", "binomial"), dist_y = "poisson",
    x_intercepts = c(4, -1, -1), y_intercepts = c(4, -1, -1), beta0_y = -1, beta_x =
    c(-0.03, 0.1, -0.2), beta_y = c(0.03, -0.1, 0.2)),
  mcmc_params = list(niter = 50000, nburnin = 30000, thin = 10, nchains = 2),
  model_code,
  base_seed = 123,
  output_dir = NULL
)
```

Arguments

correlation_grid	Vector of correlation values to test
n_sims_per_setting	Number of simulations per correlation setting
base_params	List of base simulation parameters
mcmc_params	List of MCMC parameters
model_code	NIMBLE model code
base_seed	Base random seed
output_dir	Output directory for results (default: NULL, uses tempdir())

Value

List with combined results, summary statistics, and output directory

simulate_misaligned_data

Simulate Misaligned Spatial Data

Description

Simulate Misaligned Spatial Data

Usage

```
simulate_misaligned_data(
  seed = 2,
  dist_covariates_x = c("normal", "poisson", "binomial"),
  dist_covariates_y = c("normal", "poisson", "binomial"),
  dist_y = "poisson",
```

```

x_intercepts = rep(0, 3),
y_intercepts = rep(0, 3),
rho_x = 0.6,
rho_y = 0.6,
x_correlation = 0.5,
y_correlation = 0.5,
beta0_y = NULL,
beta_x = NULL,
beta_y = NULL,
diff_pops = TRUE,
xy_cov_cor = FALSE
)

```

Arguments

seed	Random seed (default = 2)
dist_covariates_x	Vector specifying distribution type for each synthetic X-grid covariate ('poisson', 'binomial', or 'normal')
dist_covariates_y	Vector specifying distribution type for each synthetic Y-grid covariate ('poisson', 'binomial', or 'normal')
dist_y	Distribution type for synthetic outcome variable (one of 'poisson', 'binomial', or 'normal')
x_intercepts	Intercepts for X covariates
y_intercepts	Intercepts for Y covariates
rho_x	Spatial correlation parameter for X-grid covariates (0 to 1 with higher values yielding more spatial correlation, default = 0.6)
rho_y	Spatial correlation parameter for Y-grid covariates and outcome (0 to 1 with higher values yielding more spatial correlation, default = 0.6)
x_correlation	Between-variable correlation for all pairs of X-grid covariates (default = 0.5)
y_correlation	Between-variable correlation for all pairs of Y-grid covariates (default = 0.5)
beta0_y	Intercept for outcome model
beta_x	Outcome model coefficients for X-grid covariates
beta_y	Outcome model coefficients for Y-grid covariates
diff_pops	Logical, indicating whether the atoms should be generated with different population sizes (diff_pops = TRUE) or a common population size (diff_pops = FALSE)
xy_cov_cor	Logical, indicating whether the atom-level spatial random effects for X-grid and Y-grid covariates should be correlated (xy_cov_cor = TRUE) or not. When set to TRUE, the x_correlation and rho_x parameters are used to generate all covariates (separate correlation parameters are not allowed for X-grid and Y-grid covariates).

Value

List containing gridy, gridx, atoms, and true_params

summary.abrm

Summary method for abrm objects

Description

Summary method for abrm objects

Usage

```
## S3 method for class 'abrm'
summary(object, ...)
```

Arguments

object	An abrm object
...	Additional arguments (unused)

Value

Invisibly returns the input object object. The function is called for its side effect of printing the ABRM model summary including detailed parameter estimates.

summary.abrm_comparison

Summary method for abrm_comparison objects

Description

Summary method for abrm_comparison objects

Usage

```
## S3 method for class 'abrm_comparison'
summary(object, ...)
```

Arguments

object	An object of class "abrm_comparison"
...	Additional arguments (ignored)

Value

Invisibly returns the input object object. The function is called for its side effect of printing the method comparison summary including combined comparison results across all simulations.

`summary.misaligned_data`*Summary method for misaligned_data objects*

Description

Summary method for misaligned_data objects

Usage

```
## S3 method for class 'misaligned_data'  
summary(object, ...)
```

Arguments

object	A misaligned_data object
...	Additional arguments (unused)

Value

Invisibly returns the input object object. The function is called for its side effect of printing the misaligned data summary including grid information and true parameter values (beta_x and beta_y).

`summary.sensitivity_analysis`*Summary method for sensitivity_analysis objects*

Description

Summary method for sensitivity_analysis objects

Usage

```
## S3 method for class 'sensitivity_analysis'  
summary(object, ...)
```

Arguments

object	A sensitivity_analysis object
...	Additional arguments (unused)

Value

Invisibly returns the input object object. The function is called for its side effect of printing the sensitivity analysis summary including comprehensive results across all simulation scenarios.

Index

biasedUrn_rmfnc, [3](#)

check_mcmc_diagnostics, [3](#)
create_comparison_plots, [4](#)
create_diagnostic_plots, [4](#)
create_sensitivity_summary_plots, [5](#)
create_summary_statistics, [5](#)

dasymetric_mapping, [6](#)

fit_dasymetric_model, [6](#)

gen_correlated_spat, [7](#)
get_abrm_model, [7](#)

plot.abrm, [8](#)
plot.abrm_comparison, [8](#)
prepare_adjacency_matrices, [9](#)
prepare_nimble_inputs, [9](#)
prepare_spatial_bookkeeping, [10](#)
print.abrm, [11](#)
print.abrm_comparison, [11](#)
print.misaligned_data, [12](#)
print.sensitivity_analysis, [12](#)
print_convergence_summary, [13](#)

register_nimble_distributions, [13](#)
run_abrm, [14](#)
run_both_methods, [15](#)
run_nimble_model, [16](#)
run_sensitivity_analysis, [17](#)

simulate_misaligned_data, [18](#)
summary.abrm, [20](#)
summary.abrm_comparison, [20](#)
summary.misaligned_data, [21](#)
summary.sensitivity_analysis, [21](#)