Package 'mospiR'

October 27, 2026

Type Package

Title Client for the 'MoSPI' Microdata Portal

Version 0.1.0

Description Download unit-level survey microdata from the Ministry of Statistics and Programme Implementation ('MoSPI', Government of India) Microdata Portal <https://microdata.gov.in>. Provides functions to list datasets, list files within a dataset, and download individual files or entire datasets through the portal's 'NADA' API.

License MIT + file LICENSE

Encoding UTF-8

Language en-US

Depends R (>= 4.1.0)

Imports httr2 (>= 1.0.0)

Suggests testthat (>= 3.0.0), knitr, rmarkdown

VignetteBuilder knitr

Config/testthat/edition 3

Config/Needs/website pkgdown

URL https://mospir.saketlab.org, https://github.com/saketkc/mospiR

BugReports https://github.com/saketkc/mospiR/issues

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author Saket Choudhary [aut, cre] (ORCID: <https://orcid.org/0000-0001-5202-7633>)

Maintainer Saket Choudhary <saketc@iitb.ac.in>

Repository CRAN

Date/Publication 2026-10-27 17:10:02 UTC

Contents

download_dataset 2
download_file 3
list_datasets 3
list_files 4

Index **5**

`download_dataset` *Download all files for a dataset*

Description

Download all files for a dataset

Usage

```
download_dataset(dataset_id, folder_path, api_key, overwrite = FALSE)
```

Arguments

`dataset_id`	Dataset ‘idno‘.
`folder_path`	Destination directory. The function makes the directory if it does not exist.
`api_key`	MoSPI API key.
`overwrite`	If ‘FALSE‘ (default), the function does not download the files that are already in ‘folder_path‘.

Value

A character vector of the paths of the saved files, as an invisible value.

Examples

```
# This dataset is approximately 270 MB.
paths <- download_dataset(
  "DDI-IND-NSO-ASI-2020-21", tempdir(), Sys.getenv("MOSPI_KEY")
)
```

download_file *Download a single file from a dataset*

Description

Download a single file from a dataset

Usage

```
download_file(dataset_id, file_name, folder_path, api_key, .files_cache = NULL)
```

Arguments

dataset_id	Dataset 'idno'.
file_name	File name from the 'name' column of [list_files()].
folder_path	Destination directory. The function makes the directory if it does not exist.
api_key	MoSPI API key.
.files_cache	A file list from [list_files()]. If 'NULL' (default), the function gets the file list from the portal. Use this argument when you download many files from one dataset. This prevents more API requests.

Value

The path of the saved file, as an invisible value. 'NULL' if the download is not successful.

Examples

```
path <- download_file(
  "DDI-IND-NSO-ASI-2020-21", "DDI-IND-NSO-ASI-2020-21.xml",
  tempdir(), Sys.getenv("MOSPI_KEY")
)
```

list_datasets *List datasets from the MoSPI Microdata Portal*

Description

List datasets from the MoSPI Microdata Portal

Usage

```
list_datasets(api_key, page = NULL, query = NULL)
```

Arguments

api_key	MoSPI API key.
page	Page number to get. If ‘NULL‘ (default), the function gets all the pages.
query	Text to find in the dataset titles. Upper case and lower case letters are equal. The comparison occurs on your computer.

Value

A data frame with the columns ‘id‘, ‘idno‘, ‘title‘, and other columns. ‘NULL‘ if the request is not successful.

Examples

```
page1 <- list_datasets(Sys.getenv("MOSPI_KEY"), page = 1)
head(page1[, c("idno", "title")])
```

---

list_files *List files available for a dataset*

Description

List files available for a dataset

Usage

```
list_files(dataset_id, api_key)
```

Arguments

dataset_id	Dataset ‘idno‘, for example ‘"DDI-IND-NSO-ASI-2020-21"‘.
api_key	MoSPI API key.

Value

A data frame with the columns ‘name‘, ‘base64‘, ‘size‘, and other columns. ‘NULL‘ if the request is not successful.

Examples

```
files <- list_files("DDI-IND-NSO-ASI-2020-21", Sys.getenv("MOSPI_KEY"))
```

Index

download_dataset, 2
download_file, 3

list_datasets, 3
list_files, 4