Package 'climabr'

October 20, 2026

Title Interface for Accessing Weather Data from Climatempo

Version 0.1.0

Description
Provides functions for downloading meteorological data from the CLIMATEMPO (<https://www.climatempo.com.br/>) web platform through web scraping, designed for ecological and environmental analyses.

License MIT + file LICENSE

Encoding UTF-8

URL https://github.com/jrz-s/climabr

BugReports https://github.com/jrz-s/climabr/issues

Depends R (>= 3.5)

Imports dplyr, stringr, stringi, purrr, rvest, magrittr, rlang

LazyData true

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Jhonatan Rafael Zárate-Salazar [aut, cre] (ORCID: <https://orcid.org/0000-0001-9251-5340>), Omar E. Benites-Alfaro [ctb] (ORCID: <https://orcid.org/0000-0002-6852-9598>), Eduardo V. da Silva Oliveira [ctb] (ORCID: <https://orcid.org/0000-0003-4858-3930>), Sidney F. Gouveia [ctb] (ORCID: <https://orcid.org/0000-0003-4941-7440>)

Maintainer Jhonatan Rafael Zárate-Salazar <rzaratesalazar@gmail.com>

Repository CRAN

Date/Publication 2026-10-20 17:40:02 UTC

Contents

climate_data 2
linksdataset 3
search_locations 3

Index **5**

`climate_data` *Retrieve climatological data*

Description

Retrieves monthly climatological data from Climatempo using flexible location inputs and automated web scraping.

Usage

```
climate_data(
  region = NULL,
  state = NULL,
  city = NULL,
  max_cities = 5,
  delay = 1,
  add_site = TRUE,
  add_avg = TRUE
)
```

Arguments

`region`	Character. Optional region name (e.g., "north", "northeast").
`state`	Character. State abbreviation or full name (e.g., "se", "sergipe").
`city`	Character. City name (partial or full; accent-insensitive).
`max_cities`	Numeric. Maximum number of locations allowed to prevent excessive requests. Default is 5.
`delay`	Numeric. Time delay in seconds between successive web requests. Default is 1.
`add_site`	Logical. If TRUE, adds a site identifier column to the output.
`add_avg`	Logical. If TRUE, computes monthly averages across locations (only when more than one location is selected).

Details

Main function to retrieve climate data

Value

A tibble containing monthly climatological variables, including minimum temperature (tmin), maximum temperature (tmax), and precipitation (precip).

Examples

```
climate_data(state = "se", city = "aracaju")
```

linksdataset *Climate links dataset*

Description

A dataset containing links and metadata for Brazilian municipalities

Usage

```
linksdataset
```

Format

A data frame with 5 variables:

id Location ID

region Region name

state State abbreviation

city_name City name

links Climatempo URL

search_locations *Search locations*

Description

Searches the internal location database using flexible matching for region, state, and city names.

Usage

```
search_locations(region = NULL, state = NULL, city = NULL)
```

Arguments

region	Character. Optional region name.
state	Character. State abbreviation or full name.
city	Character. City name (partial or full).

Details

Main function to retrieve search_locations

Value

A tibble containing matching locations and associated metadata, including region, state, city name, and data source links.

Examples

```
search_locations(state = "se", city = "arac")
```

Index

∗ **datasets**
    linksdataset, 3

climate_data, 2

linksdataset, 3

search_locations, 3