

Package ‘likingInitiative’

October 2, 2026

Title Access the Liking Rating Database

Version 0.2.2

Description Download and work with the Liking Rating Database, a curated collection of subjective liking ratings from published decision-making studies, described in Fernandez, Goyal and Krajbich (2026) [doi:10.5281/zenodo.22216442](https://doi.org/10.5281/zenodo.22216442). Data is read from versioned release files and cached for the session, so a pinned version returns the same rows regardless of when it is run. Provides access by dataset, by item across studies, or as the whole corpus, together with the metadata and citations needed to report it.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

Depends R (>= 4.1)

Imports cli, fs, httr2, jsonlite, readr, tibble, tools

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

URL <https://liking-rating-frontend.onrender.com>,
<https://github.com/liking-initiative/likingInitiative-r>

BugReports <https://github.com/liking-initiative/likingInitiative-r/issues>

NeedsCompilation no

Author Kianté Fernandez [aut, cre, cph]

Maintainer Kianté Fernandez <kiantefernan@gmail.com>

Repository CRAN

Date/Publication 2026-10-02 10:50:07 UTC

Contents

bibtex	2
cache_info	3
cite	3
clear_cache	4
get_dataset	4
get_item	5
list_datasets	6
list_items	6
list_studies	7
load_database	7
release_info	8
use_persistent_cache	8

Index	10
-------	----

bibtex	<i>BibTeX for a dataset's source publication</i>
--------	--

Description

BibTeX for a dataset's source publication

Usage

bibtex(x, ...)

Arguments

- x A dataset from `get_dataset()`.
- ... Unused.

Value

A character string holding a BibTeX entry.

Examples

bibtex(get_dataset("leeholyoak2021"))

cache_info	<i>Report on the local asset cache</i>
------------	--

Description

Shows where downloaded release files are kept, how much space they use, and which versions are present.

Usage

```
cache_info()
```

Value

A list, invisibly, with path, bytes and versions.

Examples

```
cache_info()
```

cite	<i>Citation text</i>
------	----------------------

Description

Please cite both the database and the study whose data you used.

Usage

```
cite(x, ...)
```

Arguments

x	A dataset or item from get_dataset() / get_item() . With no argument, returns the citation for the database itself.
...	Unused.

Value

A character string.

Examples

```
cite()
```

clear_cache	<i>Delete cached release files</i>
-------------	------------------------------------

Description

Delete cached release files

Usage

```
clear_cache(version = NULL)
```

Arguments

version	Version to remove. NULL (default) clears every version.
---------	---

Value

Invisibly, the number of bytes freed.

Examples

```
clear_cache()
```

get_dataset	<i>Download one or more datasets</i>
-------------	--------------------------------------

Description

Reads a dataset's ratings from the release, with the metadata needed to interpret them.

Usage

```
get_dataset(dataset, version = "latest", timepoint = NULL)
```

Arguments

dataset	A dataset code ("leeholyoak2021"), a unique prefix, a dataset id, or a character vector of them.
version	Release version, or "latest".
timepoint	Optional rating phase to keep.

Details

Two datasets repeat their rating phase – leeholyoak2021 (phases 1-3) and leehare2023exp2 (phases 1-2). For those, subject_id and item_id together are **not** unique; include timepoint, or pass the timepoint argument to take a single phase.

Value

An object of class `likingInitiative_dataset` with elements `data` (a tibble), `metadata`, `dataset_code` and `version`. For several datasets, a named list of them.

Examples

```
d <- get_dataset("leeholyoak2021")
head(d$data)
d$metadata$rating_scale_max
cite(d)
```

get_item

One stimulus across every study that used it

Description

The cross-study view. Because the underlying studies use different response scales, compare on `normalized_rating`, not `rating`.

Usage

```
get_item(item, version = "latest")
```

Arguments

<code>item</code>	An item name, e.g. "kitkat".
<code>version</code>	Release version, or "latest".

Details

Only the first rating phase of a repeated-phase dataset is included, so those studies do not carry extra weight in a cross-study comparison.

Value

An object of class `likingInitiative_item` with `data`, `datasets` and `version`.

Examples

```
k <- get_item("kitkat")
k$data
```

list_datasets	<i>List the datasets in the database</i>
---------------	--

Description

timepoints gives the rating phases a dataset holds. All but two datasets have a single phase; see [get_dataset\(\)](#).

Usage

```
list_datasets(version = "latest")
```

Arguments

version Release version, or "latest".

Value

A tibble with one row per dataset.

Examples

```
list_datasets()
```

list_items	<i>List the stimuli in the database</i>
------------	---

Description

List the stimuli in the database

Usage

```
list_items(version = "latest")
```

Arguments

version Release version, or "latest".

Value

A tibble with one row per item.

Examples

```
list_items()
```

list_studies	<i>List the publications in the database</i>
--------------	--

Description

List the publications in the database

Usage

```
list_studies(version = "latest")
```

Arguments

version Release version, or "latest".

Value

A tibble with one row per study.

Examples

```
list_studies()
```

load_database	<i>The whole corpus in one call</i>
---------------	-------------------------------------

Description

The whole corpus in one call

Usage

```
load_database(version = "latest")
```

Arguments

version Release version, or "latest".

Value

A list of tibbles: ratings, studies, datasets, items. Held in memory after the first call.

Examples

```
db <- load_database()
nrow(db$ratings)
```

release_info	<i>Version, date and headline counts for the release in use</i>
--------------	---

Description

Version, date and headline counts for the release in use

Usage

```
release_info(version = "latest")
```

Arguments

version	Release version, or "latest".
---------	-------------------------------

Value

A list describing the release.

Examples

```
release_info()
```

use_persistent_cache	<i>Keep downloaded files between sessions</i>
----------------------	---

Description

By default release files are cached inside the session's temporary directory, so nothing is written outside it and the cache goes away when R exits. Call this to cache in a directory that persists instead, so a later session reuses the files rather than downloading them again.

Usage

```
use_persistent_cache(dir = tools::R_user_dir("likingInitiative", "cache"))
```

Arguments

dir	Directory to cache in. Defaults to this package's per-user cache directory, as given by <code>tools::R_user_dir()</code> .
-----	--

Details

The choice lasts for the session. Put `likingInitiative::use_persistent_cache()` in your `.Rprofile` to make it the default for every session, and use `clear_cache()` to remove what it has stored.

use_persistent_cache

9

Value

The cache directory, invisibly.

Examples

```
# cache somewhere disposable for the rest of this session
use_persistent_cache(tempfile("likingInitiative-cache-"))
```

Index

bibtex, [2](#)

cache_info, [3](#)

cite, [3](#)

clear_cache, [4](#)

clear_cache(), [8](#)

get_dataset, [4](#)

get_dataset(), [2](#), [3](#), [6](#)

get_item, [5](#)

get_item(), [3](#)

list_datasets, [6](#)

list_items, [6](#)

list_studies, [7](#)

load_database, [7](#)

release_info, [8](#)

tools::R_user_dir(), [8](#)

use_persistent_cache, [8](#)