Name: Shubham Patgavkar

Div: C Batch: C3 Roll No: 233074 PRN No: 22320100

Practical No: 2

Title: Create a binary search tree (BST) of and perform following operations: i) Insert ii) Display inorder iii) Search a node iv) Find height of the tree v) level wise display iv) Delete v) Mirror

Code:

```
class Node {
    int data;
    Node left, right;
    Node(int data) {
        this.data = data;
        this.left = null;
        this.right = null;
public class binarysearchtreep {
    Node root;
    binarysearchtreep() {
        root = null;
    }
    public Node insert(int data, Node root) {
        if (root == null) {
            Node newNode = new Node(data);
            root = newNode;
            return root;
        } else if (root.data > data) {
            root.left = insert(data, root.left);
        } else {
            root.right = insert(data, root.right);
        return root;
```

```
public boolean search(int data, Node root) {
    if (root == null) {
        return false;
    if (root.data > data) {
        return search(data, root.left);
    } else if (root.data == data) {
        return true;
    } else {
        return search(data, root.right);
    }
}
public void inorder(Node root) {
    if (root == null)
        return;
    inorder(root.left);
    System.out.print(root.data + " ");
    inorder(root.right);
}
public Node inorderSuccessor(Node root) {
    while (root.left != null) {
        root = root.left;
    return root;
}
public Node delete(Node root, int data) {
    if (root == null) {
        return root;
    }
    if (root.data > data) {
        root.left = delete(root.left, data);
    } else if (root.data < data) {</pre>
        root.right = delete(root.right, data);
    } else {
        if (root.left == null) {
            return root.right;
        } else if (root.right == null) {
```

```
return root.left;
        }
        Node successor = inorderSuccessor(root.right);
        root.data = successor.data;
        root.right = delete(root.right, successor.data);
    return root;
}
public int height(Node root) {
    if (root == null) {
        return 0;
    int heightLeft = height(root.left);
    int heightRight = height(root.right);
    return Math.max(heightLeft, heightRight) + 1;
}
public void printLevelOrder(Node root) {
    int h = height(root);
    for (int i = 1; i <= h; i++)
        printCurrentLevel(root, i);
}
public void printCurrentLevel(Node root, int level) {
    if (root == null)
        return;
    if (level == 1)
        System.out.print(root.data + " ");
    else if (level > 1) {
        printCurrentLevel(root.left, level - 1);
        printCurrentLevel(root.right, level - 1);
    }
}
public void printMirror() {
    root = mirror(root);
}
public Node mirror(Node root) {
    if (root == null)
        return root;
```

```
Node left = mirror(root.left);
        Node right = mirror(root.right);
        root.left = right;
        root.right = left;
        return root;
    }
    public int getCol(int h) {
        if (h == 1)
            return 1;
        return getCol(h - 1) + getCol(h - 1) + 1;
    }
    public void printTree(int[][] M, Node root, int col, int row, int
height) {
        if (root == null)
            return;
        M[row][col] = root.data;
        printTree(M, root.left, col - (int) Math.pow(2, height - 2),
row + 1, height - 1);
        printTree(M, root.right, col + (int) Math.pow(2, height -
2), row + 1, height - 1);
    }
    public void treePrinter(binarysearchtreep tree) {
        int h = height(tree.root);
        int col = getCol(h);
        int[][] M = new int[h][col];
        printTree(M, tree.root, col / 2, 0, h);
        for (int i = 0; i < h; i++) {
            for (int j = 0; j < col; j++) {
                if (M[i][j] == 0)
                    System.out.print(" ");
                else
                    System.out.print(M[i][j] + " ");
            System.out.println();
        }
```

```
public static void main(String[] args) {
        int treedata[] = { 500, 300, 200, 400, 700, 600, 800 };
        binarysearchtreep tree = new binarysearchtreep();
        for (int i = 0; i < treedata.length; i++) {</pre>
            tree.root = tree.insert(treedata[i], tree.root);
        System.out.println("Printing tree:");
        tree.treePrinter(tree);
        System.out.println("\nInorder traversal:");
        tree.inorder(tree.root);
        if (tree.search(200, tree.root)) {
            System.out.println("\nFound");
        } else {
            System.out.println("\nNot found");
        tree.delete(tree.root, 200);
        System.out.println("\nInorder traversal after deletion:");
        tree.inorder(tree.root);
        System.out.println("\nHeight of tree: " +
tree.height(tree.root));
        System.out.println("Level order traversal:");
        tree.printLevelOrder(tree.root);
        tree.printMirror();
        System.out.println("\nMirror:");
        tree.inorder(tree.root);
        System.out.println("\nPrinting tree after mirror
operation:");
        tree.treePrinter(tree);
```

Output:

Printing tree: 500 300 700 200 400 600 800

Inorder traversal: 200 300 400 500 600 700 800 Found Inorder traversal after deletion: 300 400 500 600 700 800 Height of tree: 3 Level order traversal: 500 300 700 400 600 800 Mirror: 800 700 600 500 400 300 Printing tree after mirror operation: 500 700 300 800 600 400