
PYTHON STRING METHODS

1 Case Conversion Methods

 These methods are used to change the letter case of a string.

Method	Full sentence explanation
upper()	The upper() method converts all characters of the string into uppercase letters.
lower()	The lower() method converts all characters of the string into lowercase letters.
capitalize()	The capitalize() method converts only the first character of the string into uppercase and the remaining characters into lowercase.
title()	The title() method converts the first character of each word in the string into uppercase.
swapcase()	The swapcase() method changes uppercase letters to lowercase and lowercase letters to uppercase.

♦ 2 Searching and Counting Methods

👉 These methods are used to search text and count occurrences in a string.

Method	Full sentence explanation
find()	The find() method returns the index position of the first occurrence of a substring in the string, and returns -1 if the substring is not found.
rfind()	The rfind() method searches for a substring from the right side of the string and returns its position.
index()	The index() method returns the index position of a substring, but gives an error if the substring is not found.
count()	The count() method returns the number of times a substring appears in the string.

♦ 3 Checking / Validation Methods

👉 These methods are used to check the type of characters present in a string.

Method	Full sentence explanation
isalpha()	The isalpha() method returns True if the string contains only alphabetic characters.
isdigit()	The isdigit() method returns True if the string contains only digits.
isalnum()	The isalnum() method returns True if the string contains both letters and digits.
islower()	The islower() method returns True if all alphabetic characters in the string are lowercase.
isupper()	The isupper() method returns True if all alphabetic characters in the string are uppercase.
isspace()	The isspace() method returns True if the string contains only whitespace characters.
startswith()	The startswith() method checks whether the string starts with a specified substring.

endswith()	The endswith() method checks whether the string ends with a specified substring.
-------------------	--

◆ 4 Trimming / Whitespace Removal Methods

👉 These methods are used to remove unwanted spaces from a string.

Method	Full sentence explanation
strip()	The strip() method removes whitespace characters from both the beginning and the end of the string.
lstrip()	The lstrip() method removes whitespace characters only from the left side of the string.
rstrip()	The rstrip() method removes whitespace characters only from the right side of the string.

◆ 5 Splitting and Joining Methods

👉 These methods are used to break a string or combine multiple strings.

Method	Full sentence explanation
split()	The split() method breaks the string into a list of words based on a separator.
rsplit()	The rsplit() method splits the string from the right side.
splitlines()	The splitlines() method splits the string at line breaks and returns a list of lines.

join()	The join() method joins elements of a list into a single string using a specified separator.
---------------	--

◆ 6 Replace and Modify Methods

👉 These methods are used to change or format string content.

Method	Full sentence explanation
replace()	The replace() method replaces one substring with another substring in the string.
zfill()	The zfill() method adds leading zeros to a string until it reaches the specified length.
center()	The center() method aligns the string in the center by adding characters on both sides.
ljust()	The ljust() method left-aligns the string by adding characters on the right.
rjust()	The rjust() method right-aligns the string by adding characters on the left.

◆ 7 String Formatting Methods

👉 These methods are used to display values inside strings neatly.

Method	Full sentence explanation
f-string	The f-string method allows variables to be directly inserted inside a string in an easy and readable way.

format()	The format() method inserts values into placeholders inside the string.
% operator	The % operator is an old method used to format strings with values.

◆ 8 String Comparison Operators

👉 These operators are used to compare two strings.

Operator	Full sentence explanation
==	The == operator checks whether two strings are exactly the same.
!=	The != operator checks whether two strings are different.
<	The < operator compares strings based on alphabetical order.
>	The > operator compares strings based on alphabetical order.