## **CS 530 INTERNET WEB AND CLOUD SYSTEMS**

Name:Varsha Karinje PSU ID: 925923534

Set up Identity Provider	4
-	2
Running the code	4
Removing access	8
APIs #1 (Vision, Speech, Translate, Natural Language APIs)	g
IAM service account setup	9
Vision	10
Speech	11
Translate	12
Natural Language	13
Code	14
Test integration	15
APIs #2 (Video Intelligence API)	16
Video setup	16
Video Intelligence labeling script	17
Video Intelligence	18
APIs #3 (Web site integration)	20
IAM service account setup	21
Application	21
Code	23
Clean up	26
Project setup	26
Authentication setup	27
CLI setup	28


Bundling with Webpack	28
Configure Firebase within application	30
nitialize Firebase within application	31
Test application	32
Add authentication	32
Jpdate UI	33
Test application with authentication	34
Add text messaging	35
Test application with text messaging	36
Manual message insertion	37
Add image messaging	38
Test application with image messaging	38
Deploy application	40

### 08.1 OAuth2 Guestbook


# Set up Identity Provider




3



Running the code




 Take a screenshot of the Headers that includes the URL and the returned HTTP status code for each request for your lab notebook.



 Based on the description of the source code, what lines of code in our application are responsible for the second request?

#### Ans:


 Take a screenshot of the Headers that includes the entire Callback URL and its returned HTTP status code. What location is the User sent to as a result of this request?




The user is sent back to the location <a href="http://localhost:8000/sign">http://localhost:8000/sign</a>


The status code returned is 302 FOUND

Find the request within Developer Tools that fetches the embedded image and take a screenshot of its URL




 Take a screenshot showing multiple authenticated accounts have been able to sign the Guestbook.





## Removing access



08.2g: ML APIs

APIs #1 (Vision, Speech, Translate, Natural Language APIs)

```
Search for resources, docs, products, and more (/)

Q. Search

The Terminal (Abadic SEO Maniper-Maniper) X + ▼

Terminal (Abadic SEO Maniper-Maniper) X + ▼
```

# IAM service account setup

```
activators Enableticators (Childreticator, Fabblicators, Fabblicators, Pythodisticator, Pyt
```

## Vision

• Show the output for your lab notebook

Answer the following questions:

What is the name of the function?

The name of the function is detect\_labels\_uri

What type of Vision client is instantiated in it?

The type of Vision client that is instantiated in it is ImageAnnotatorClient

• What method is invoked in the Vision client to perform the detection?

The method that is invoked in the Vision client to perform the detection is label\_detection

• What is the name of the attribute in the response object that contains the results we seek?

The name of the attribute in the response object that contains the results we seek is label\_annotations

Take a screenshot of the output for the above commands

```
| Cor. mote and/o on extor mentages, closel: https://ciocut.google.com/spain/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-sup-learing/extord=cs-s
```

• What method is invoked in the Vision client to perform the detection?

detect\_logos

### Speech

```
| Collecting propie-closed-speech | Coll
```

• Show the output for your lab notebook

```
(env) vkarinje@cloudshell: "/python-docs-samples/vision/snippets/detect (cloud-cs-530-karinje-vkarinje) $ cd -/python-speech/samples/snippets

(env) vkarinje@cloudshell: "/python-speech/samples/snippets (cloud-cs-530-karinje-vkarinje) $ python transcribe.py resources/audio.raw

Transcript: how old is the Brooklyn Bridge

(env) vkarinje@cloudshell: "/python-speech/samples/snippets (cloud-cs-530-karinje-vkarinje) $ |
```

Answer the following questions:

• What is the name of the function?

transcribe\_file is the name of the function.

• What method is invoked in the Speech client to perform the detection?

recognize method is invoked in the Speech client to perform the detection

• What is the name of the attribute in the response object that contains the results we seek?

result.alternatives[0].transcript is the name of the attribute in the response object that contains the results we seek

### **Translate**

```
| Exercises been add as the Boostlay Enging opened/magning/supposts (Condence-330-Assert)ge-Assert)gelf pip install geople-cloud-translates | Collecting geople
```

• Show the output for your lab notebook

```
(env) vharinje@cloudshell:~/python-speech/samples/snippets (cloud-cs-530-karinje-vkarinje)$ cd ~/python-translate/samples/snippets (env) vharinje@cloudshell:~/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ python snippets.py translate-text en '你有沒有帶外套'
Text: 你有沒有帶外套
Translation: do you have a coat
Detected source language: sh-TN
(env) vharinje@cloudshell:~/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ |
```

Answer the following questions:

What is the name of the function?

The name of the function is translate\_text

• What method is invoked in the Translate client to perform the detection?

The method translate is invoked in the Translate client to perform the detection

• What is the name of the attribute in the response object that contains the results we seek?

```
input, translatedText, detectedSourceLanguage
```

```
print(u"Text: {}".format(result["input"]))
print(u"Translation: {}".format(result["translatedText"]))
print(u"Detected source language: {}".format(result["detectedSourceLanguage"]))
```

## Natural Language

```
Common Company (1987)

Description of the Common Company (1987)

Description of the Common Company (1987)

Description of the Common Co
```

Show the output for your lab notebook

```
print(f'name: (entity.name)')
(env) vharinje@cloudshell:-/python-tvanclate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ python language.py 'homework is awful!'
'homework is awful!' has sentiment—0.800000011920929

Entities are:
(name: homework
(nov) vharinje@cloudshell:-/python-tvanclate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ python language.py 'homework is ok'
'homework is ok' has sentiment—0.30000001192092896

Entities are:
(name: homework
(new) vharinje@cloudshell:-/python-tvanclate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ python language.py 'homework is awesome?'
'homework is awesome?' has sentiment—0.000000059604645

Entities are:
(name: homework
(new) vharinje@cloudshell:-/python-tvanclate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ python language.py 'homework is awesome!'
'homework is awesome!' has sentiment=0.8999999761581421

Entities are:
(name: homework
(new) vharinje@cloudshell:-/python-tvanclate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ python language.py 'The protestors in Oregon put on gas masks and wore yellow t-shirts'
'The protestors in Oregon put on gas masks and wore yellow t-shirts' has sentiment=0.6000000228418579

Entities are:
(name: protestors
(name: gas masks
(name: protestors
(name: gas masks
(name: protestors
(name: protestors)
```

### Code

Examine the code and answer the following questions:

• What is the name of the function that performs the transcription?

Ans: The name of the function that performs the transcription is transcribe\_gcs

• What is the name of the function that performs the translation?

Ans: The name of the function that performs the translation is translate\_text

• What is the name of the function that performs the entity analysis on the translation?

Ans: The name of the function that performs the entity analysis on the translation is entities\_text

• What is the name of the function that performs the entity analysis on the image?

Ans: label\_detection

### Test integration

```
(env) wharinje@cloudshell:-/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ python solution.py de-DE gs://ml-api-codelab/de-ball.wav gs://ml-api-codelab/football.jpg
Translation: do you want to play soccer with us
Entities: ('soccer')
Image labels: ('soccer')
Image labels: ('soccer')
The audio and image do not appear to be related.

(env) wharinje@cloudshell:-/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ |
```

• If the program deems them unrelated, then based on the results from the APIs, what must be changed in the program to address this?

Ans: The program is case sensitive while checking for entities and labels. The program must be made case insensitive to make sure that the comparison is matched.

```
(emv) wharinje@cloudshell:-/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ python solution.py tr-TR gs://ml-api-codelab/tr-bike.wav gs://ml-api-codelab/bicycle.jpg
Translation: leave my bike on the street
Entities: ['bike', 'street']
Image labels: ['Bicycle', 'Stocking', 'Footwear', 'Tixe', 'Wheel', 'Bicycles--Equipment and supplies', 'Land vehicle', 'Shoe', 'Bicycle frame', 'Bicycle wheel']
The audio and image do not appear to be related.

(env) wharinje@cloudshell:-/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ |
```

• If the program deems them unrelated, then based on the results from the APIs, what must be changed in the program to address this?

Ans: The program seems to be working fine. The translation returns bike and street. The labels contain words like bicycle and nothing relates to street. Hence, no tags match.

```
The sudio and image do not appear to be related.


(env) vkarinje@cloudshell:-/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ python solution.py tr-TR gs://ml-api-codelab/tr-ostrich.wav gs://ml-api-codelab/birds.jpg
Transcription: qob fasla deve kugu var
Translation: these are too many ostriches
Entities: ('vostriches')
Image labels: ('Bird', 'Batite', 'Cloud', 'Sky', 'Beak', 'Plant', 'Green', 'Neck', 'Ostrich', 'Casuariiformes')
The audio and image do not appear to be related.

(env) vkarinje@cloudshell:-/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$|
```

• If the program deems them unrelated, then based on the results from the APIs, what must be changed in the program to address this?

Ans: The program returns singular and plural words and not the exact matches. For entities Ostriches the label Ostrich is returned. A method that matches the comparisons entities and labels while comparing even if the entity is case-sensitive or singular/plural can be added.

## APIs #2 (Video Intelligence API)



## Video setup

```
[notice] I new resease of pip available. ... / 22.3.1
[notice] To update, run: pip install --upgrade pip
(env) vkarinje@cloudshell: "/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ gsutil mb gs://vkarinje-bucket
Creating gs://vkarinje-bucket/...
(env) vkarinje@cloudshell: "/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ | |
```

```
[notice] In update, run: pp install --pgrade pip (cloud-cs-530-karinje-vkarinje) gsutil mb gs://vkarinje-bucket

(cenv) vkarinje@cloudshell:-/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje) gsutil mb gs://vkarinje-bucket

Creating gs://vkarinje-bucket/...

(cenv) vkarinje@cloudshell:-/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje) gsutil acl set public-read gs://$(CLOUD_STORAGE_BUCKET)

Setting ACL on gs://vkarinje-bucket/...

(cenv) vkarinje@cloudshell:-/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje) gsutil acl set public-read gs://$(CLOUD_STORAGE_BUCKET)

Setting ACL on gs://vkarinje-bucket/...

(cenv) vkarinje@cloudshell:-/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje) gsutil defacl set public-read gs://$(CLOUD_STORAGE_BUCKET)

Setting default object ACL on gs://vkarinje-bucket/...

(cenv) vkarinje@cloudshell:-/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje) $ | |
```

```
(env) wharinje@cloudshell:-/python-translate/amples/anippets (cloud-ca-530-harinje-wharinje)$ curl https://thefengs.com/wuchang/courses/cs420/5poxtsBloopers2016.mp4 | gsstil "h "Content-Type:video/mp4" op - gs://$(CLOUD_STORME_BUCKET/SportsBloopers2016.mp4 | gsstil "h "Content-Type:video/mp4" op - gsstil "h "Content-Type
```

### Video Intelligence labeling script

```
(env) vkarinje@cloudshell:~/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ vi labels.py (env) vkarinje@cloudshell:~/python-translate/samples/snippets (cloud-cs-530-karinje-vkarinje)$ cat labels.py
from google.cloud import videointelligence
def analyse_labels(path):
""" Detects labels given a GCS path. """
     video_client = videointelligence.VideoIntelligenceServiceClient()
     features = [videointelligence.Feature.LABEL_DETECTION]
     operation = video_client.annotate_video(input_uri=path, features=features)
     print('\nProcessing video for label annotations:')
     result = operation.result(timeout=90)
print('\nFinished processing.')
      segment_labels = result.annotation_results[0].segment_label_annotations
     for i, segment_label in enumerate(segment_labels):
    print('Video label description: {}'.format(
                segment_label.entity.description))
           for category_entity in segment label.category_entities:
print('\tLabel category_description: {}'.format(
                       category_entity.description))
           for i, segment in enumerate(segment_label.segments):
                 start time = segment.segment.start time offset.seconds
end_time = segment.segment.end_time_offset.seconds
positions = '{}s to {}s'.format(start_time, end_time)
                 confidence = segment.confidence
                 print('\tSegment {}: {}'.format(i, positions))
print('\tConfidence: {}'.format(confidence))
           print('\n')
```

### Video Intelligence

Table description: stadium

Label category description: stadium

Label category description: location

Label category description: structure

Segment 0: 0s to 170s

Confidence: 0.1918-0518-058-08

Video label description: hashetball player

Label category description: person

Segment 0: 0s to 170s

Confidence: 0.1939-05000039918

Video label description: ice hockey

Label category description: hockey

Segment 0: 0s to 170s

Confidence: 0.1939-05000039918

Video label description: ice hockey

Label category description: hockey

Segment 0: 0s to 170s

Confidence: 0.1939-05000039918

Video label description: ball game

Label category description: hockey

Segment 0: 0s to 170s

Confidence: 0.1939-050000391185

Video label description: ball game

Label category description: portes

Confidence: 0.564892021850215

Video label description: ball game

Label category description: solution: sportes

Confidence: 0.564892021850215

Video label description: ball game

Label category description: sports

Segment 0: 0s to 178s

Confidence: 0.5648892521858215

Video label description: audience

Label category description: people

Segment 0: 0s to 178s

Confidence: 0.4254549741744995

Video label description: games

Segment 0: 0s to 178s Confidence: 0.7786175012588501

Video label description: team sport

Label category description: sports

Segment 0: 0s to 178s

Confidence: 0.688680112361908

Video label description: sport venue

Label category description: location Label category description: structure

Segment 0: 0s to 178s Confidence: 0.3432130515575409

Video label description: crowd

Label category description: people

Segment 0: 0s to 178s

Confidence: 0.3974151611328125

Video label description: basketball

Label category description: sports

Segment 0: 0s to 178s Confidence: 0.9137870669364929

```
Video label description: sport venue

Label category description: location
Label category description: structure
Segment 0: 0s to 178s
Confidence: 0.3432130515575409

Video label description: crowd
Label category description: people
Segment 0: 0s to 178s
Confidence: 0.3974151611328125

Video label description: basketball
Label category description: sports
Segment 0: 0s to 178s
Confidence: 0.9137870669364929

Video label description: sports
Segment 0: 0s to 178s
Confidence: 0.9218811392784119
```

Answer the following for your lab notebook.

 What are the top 3 labels that the Video Intelligence API associates with the video and what is its confidence in them?

Ans: The top 3 labels are player, basketball and sports. The confidence in them is 0.8, 0.91 and 0.92 respectively.

Finished processing.

Video label description: player

Segment 0: 0s to 178s

Confidence: 0.8446521162986755

Video label description: basketball
Label category description: sports
Segment 0: 0s to 178s
Confidence: 0.9137870669364929

Video label description: sports
Segment 0: 0s to 178s
Confidence: 0.9218811392784119

Answer the following questions:

• What is the name of the client class in the package that is used?

Ans: VideoIntelligenceServiceClient

What method is used in that class to perform the annotation?

Ans: annotate\_video

## APIs #3 (Web site integration)

```
(env) vkarinje@cloudshell:~/python-translate/samples/snippets {cloud-cs-530-karinje-vkarinje}$ cd ~/python-docs-samples/codelabs/flex_and_vision (env) vkarinje@cloudshell:~/python-docs-samples/codelabs/flex_and_vision (cloud-cs-530-karinje-vkarinje)$|
```


# IAM service account setup


```
cloud-cs-530-karinje-vkarinje) f geloud projects add-iam-policy-binding f(GOOGLE_CLOUD_PROJECT) --member serviceAccount:cs480flex@f(GOOGLE_CLOUD_PROJECT).ia
```

## **Application**

```
The contract of the contract o
```

Take a screenshot for your lab notebook that includes the URL.






### Code


Answer the following questions:

• What line of code creates the query for previous detections?



Line 39

• What line of code sends the query to Cloud Datastore?



#### Line 40

• Show the line that retrieves the name of the storage bucket to use.

```
25
26 CLOUD_STORAGE_BUCKET = os.environ.get("CLOUD_STORAGE_BUCKET")
27
28
```

```
💲 cloud-CS-530-karinje-vkarinje 🕶
```

```
View Go Run Terminal Help
              model_datastore.py
                                    main.py x
               python-docs-samples > codelabs > flex_and_vision > • main.py
                     def upload_photo():
                48
                         photo = request.files["file"]
             • 49
                         # Create a Cloud Storage client.
                         storage_client = storage.Client()
                51
                52
                53
                         # Get the bucket that the file will be uploaded to.
                       bucket = storage_client.get_bucket(CLOUD_STORAGE_BUCKET)
                55
                         # Create a new blob and upload the file's content.
                56
                         blob = bucket.blob(photo.filename)
                57
                         blob.upload_from_string(photo.read(), content_type=photo.content_type)
                58
                59
                         # Make the blob publicly viewable.
                60
                         blob.make_public()
                61
                62
                         # Create a Cloud Vision client.
                         vision_client = vision.ImageAnnotatorClient()
             A Problems @

  □ Output ×
```

Line 26, Line 54

What form field is used to specify the uploaded photo?

```
photo = request.files["file"]
```

The form field input of the type file specifies the uploaded photo.

• Show the line that copies the photo's contents to the storage bucket.

```
source_uri = "gs://{}/{}".format(CLOUD_STORAGE_BUCKET, blob.name)

# Create a new blob and upload the file's content.
blob = bucket.blob(photo.filename)
blob.upload_from_string(photo.read(), content_type=photo.content_type)
```

What method in Vision's annotation client is used to perform the analysis?

Ans: vision\_client.face\_detection(image=image)

• What fields are stored in Cloud Datastore for each image?

#### blob\_name, image\_public\_url, timestamp, joy

```
# construct the new entity using the key. Set dictionary val
# keys blob_name, storage_public_url, timestamp, and joy.
entity = datastore.Entity(key)
entity["blob_name"] = blob.name
entity["image_public_url"] = blob.public_url
entity["timestamp"] = current_datetime
entity["joy"] = face_joy
```


What happens at the end of the upload\_photo route?

It redirects to home page


### Clean up

08.3g: Firebase

### Project setup



# Authentication setup



Answer the following questions for your lab notebook

What other domains are given access to this Firebase project by default?

Ans: localhost, fir-vkarinje-f2548.firebaseapp.com, fir-vkarinje-f2548.web.app


### CLI setup


```
∠ Open Editor
★ ② □ : □ X
                                                           rsions may use Math.random() in certain circumstances, which is known to be problematic. See https://v8.dev/b
                    ase-whatinje)$ firebase login --mo-localhost
the CLI and Damlator Suite usage and error reporting information to help improve our products. Data is collected in accordance with Google's privacy policy (https:
y) and is not used to identify you.
 vkarinje@cloudshell:~/codelab-friendlychat-web/web-start (firebase-vkarinje)$ firebase use --add
  Which project do you want to add? firebase-wkari
  What alias do you want to use for this project? (e.g. staging) default
Created alias default for firebase-wkarinje.
Now using alias default (firebase-wkarinje)
vkarinje@cloudshell:~/codelab-friendlychat-web/web-start (firebase-vkarinje)$
```

## **Bundling with Webpack**


```
vkarinje@cloudshell:~/codelab-friendlychat-web/web-start (firebase-vkarinje)$ npm install
added 244 packages, and audited 245 packages in 15s
20 packages are looking for funding
 run 'npm fund' for details
found 0 vulnerabilities
vkarinje@cloudshell:~/codelab-friendlychat-web/web-start (firebase-vkarinje)$ npm run start
> friendlychat@1.0.0 start
> webpack --watch --progress
asset main.js 4.21 MiB [emitted] (name: main)
runtime modules 617 bytes 3 modules
modules by path ./node_modules/ 1.58 MiB
  modules by path ./node_modules/@firebase/ 1.56 MiB
    modules by path ./node_modules/@firebase/auth/dist/esm2017/*.js 378 KiB 2 modules
    + 10 modules
  modules by path ./node_modules/firebase/ 1.17 KiB
    ./node modules/firebase/app/dist/index.esm.js 827 bytes [built] [code generated]
    + 5 modules
  modules by path ./node_modules/idb/build/*.js 10.4 KiB
    ./node modules/idb/build/index.js 3.09 KiB [built] [code generated]
    ./node_modules/idb/build/wrap-idb-value.js 7.32 KiB [built] [code generated]
  ./node_modules/tslib/tslib.es6.js 12 KiB [built] [code generated]
modules by path ./src/*.js 11.1 KiB
 ./src/index.js 10.4 KiB [built] [code generated]
./src/firebase-config.js 719 bytes [built] [code generated]
webpack 5.75.0 compiled successfully in 1751 ms
asset firebase-messaging-sw.js 1.74 KiB [emitted] (name: main)
./src/firebase-messaging-sw.js 55 bytes [built] [code generated]
webpack 5.75.0 compiled successfully in 180 ms
```

• Take a screenshot of the first 10 lines of the produced file.






### Configure Firebase within application




```
firebase-vkarinje ▼
                                                          Search for resources, docs, products, and more (/)
                  CLOUD SHELL
                  Terminal
                                (firebase-vkarinje) X (firebase-vkarinje) X + ▼
          vkazinje@cloudshell:~/codelab-friendlychat-web/web-start (firebase-vkarinje)$ npm install
         added 244 packages, and audited 245 packages in 15s
         20 packages are looking for funding
           run 'npm fund' for details
         found 0 vulnerabilities
         vkarinjeβcloudshell:~/codelab-friendlychat-web/web-start (firebase-vkarinje)$ npm run start
         > friendlychat@1.0.0 start
         > webpack --watch --progress
 >
          asset main.js 4.21 MiB [emitted] (name: main)
          runtime modules 617 bytes 3 modules
         modules by path ./node_modules/ 1.58 MiB
modules by path ./node_modules/@firebase/ 1.56 MiB
              modules by path ./node_modules/@firebase/auth/dist/esm2017/*.js 378 KiB 2 modules
 >
            modules by path ./node_modules/firebase/ 1.17 KiB
              ./node_modules/firebase/app/dist/index.esm.js 827 bytes [built] [code generated]
            modules by path ./node_modules/idb/build/*.js 10.4 KiB
              ./node_modules/idb/build/index.js 3.09 KiB [built] [code generated]
            ./node_modules/idb/build/wrap-idb-value.js 7.32 KiB [built] [code generated]
./node_modules/tslib/tslib.es6.js 12 KiB [built] [code generated]
         modules by path ./src/*.js 11.1 KiB
./src/index.js 10.4 KiB [built] [code generated]
./src/firebase-config.js 719 bytes [built] [code generated]
         webpack 5.75.0 compiled successfully in 1751 ms
          asset firebase-messaging-sw.js 1.74 KiB [emitted] (name: main)
          ./src/firebase-messaging-sw.js 55 bytes [built] [code generated]
         webpack 5.75.0 compiled successfully in 180 ms
         asset main.js 4.21 MiB [emitted] (name: main)
         cached modules 1.59 MiB [cached] 22 modules
          runtime modules 617 bytes 3 modules
          ./src/firebase-config.js 998 bytes [built] [code generated]
          webpack 5.75.0 compiled successfully in 143 ms
         assets by status 4.21 MiB [cached] 1 asset
          cached modules 1.59 MiB (javascript) 617 bytes (runtime) [cached] 25 modules
 >
          ./src/firebase-config.js 998 bytes [built]
          webpack 5.75.0 compiled successfully in 84 ms
```

### Initialize Firebase within application




Test application




### Add authentication

- What missing functions deal with user authentication?
  - initFirebaseAuth(), signIn, isUserSignedIn, signOut, deal with user authentication.
- What missing functions deal with sending and receiving messages?

saveMessage, loadMessages, deleteMessage, displayMessage, saveImageMessage deal with sending and receiving messages.



### **Update UI**




Answer the following questions:

What are the names of the elements that are hidden when the user is signed out?


userNameElement, userPicElement, signOutButtonElement are hidden when the user is signed out.

What is the name of the element that is not hidden when the user is signed out?


signInButtonElement




### Test application with authentication




## Add text messaging






Test application with text messaging





Include a screenshot of the message and its fields in the database for your lab notebook



## Manual message insertion

• Include a screenshot of the application with its two messages for your lab notebook






## Add image messaging

In examining the code, answer the following question for your lab notebook:

What is the URL of the image that is first shown in the UI as the message is loading?

https://lh3.googleusercontent.com/a/ALm5wu2RgEPyN4e5L3uRdAO1yz6Bdw6dXyfX8Ui66AVR=s96-c

Test application with image messaging




Answer the following questions:

• How do the fields in an image document differ from that of the text document?

There are extra fields such as imageUrl, name, profilePicUrl, storageUri, timestamp for image document.

For text documents the fields are name, profilePicUrl,text, timestamp.

What URL and storage location can the image be found at?




#### The image can be found at


"https://firebasestorage.googleapis.com/v0/b/firebase-vkarinje.appspot.com/o/l0iTwi0iUZhuxjGfbR lAnkeX4xe2%2FaBJ67z5cTl6H9USZO1LP%2Fphoto-1587402092301-725e37c70fd8.jpg?alt=media&token=0ab6f191-01f5-4345-bd4b-1255ab74a644"

#### Storage location is

"IOiTwiOiUZhuxjGfbRlAnkeX4xe2/aBJ67z5cTl6H9USZO1LP/photo-1587402092301-725e37c70fd8.j pg"

• Take a screenshot of the image in the storage bucket for your lab notebook.





## **Deploy application**

Answer the following questions:

What directory is the application going to be served from?

The application is going to be served from the public directory.

What does the Cache-Control setting configured for the HTML and Javascript files do?

The max-age =0 setting in the Cache-Control setting will fetch the latest versions of HTML and Javascript files. If no-cache attribute is defined it will always fetch the latest version of the files. The Cache-Control tell the browser not to store anything.

```
vkarinje@cloudshell:~/codelab-friendlychat-web/web-start (firebase-vkarinje) $ firebase deploy --except functions

== Deploying to 'firebase-vkarinje'...

i deploying hosting
i hosting[fir-vkarinje-f2548]: beginning deploy...
i hosting[fir-vkarinje-f2548]: found 8 files in ./public

/ hosting[fir-vkarinje-f2548]: file upload complete
i hosting[fir-vkarinje-f2548]: version finalized
i hosting[fir-vkarinje-f2548]: version finalized
i hosting[fir-vkarinje-f2548]: releasing new version...
/ hosting[fir-vkarinje-f2548]: release complete

/ Deploy complete!

Project Console: https://console.firebase.google.com/project/firebase-vkarinje/overview
Hosting URL: https://fir-vkarinje-f2548.web.app
vkarinje@cloudshell:~/codelab-friendlychat-web/web-start (firebase-vkarinje)$ | |
```

• Take a screenshot of the message including the URL for your lab notebook.

