

Discovering obfuscated structures using algebraic statistics, GNNs, KAN Transformers and RL

Vinay Awasthi ¹ 

¹ Affiliation 1; vawasth1@jh.edu

* Correspondence: vajhu@proton.me; vinay.pdx@gmail.com

Abstract

Graph Neural Networks (GNNs) have achieved great success in link prediction, Graph and Node classification, by generating node embeddings and estimating proximity through distance metrics. However, existing approaches primarily assume nodes represent fixed or simple data, and edges are there connecting these nodes to train from, limiting their applicability to *statistical distributions* on a *statistical manifold*, which can only be connected by hypothesis which will be generated by limited observability of events, connections. Methods based on the Fisher–Rao distance address edge connection, partially but fail to scale to large numbers of distributions. Moreover, current PyTorch-based GNN architectures and pooling operations remain highly dependent on specific node attributes, hindering transferability and adaptation across contexts. This paper proposes a novel framework introducing *Arithmetic Unit (AU)-based node representations* to encode distributions, *blockchain-based message passing* to ensure data integrity, and *Contingency Table-driven MCMC* methods to establish initial causation linking graphs. The graph is subsequently expanded using *Reinforcement Learning (RL)* to form higher-order structures, while a *KAN Transformer* performs algebraic operations to identify group structures and hypothesis-based memberships. A new metric, *Rattle*, is introduced to quantify coordinated behavior among nodes, representing small to large distributions. The integrated framework enables hypothesis testing and dynamic discovery of deep structural relationships across statistical manifolds. This represents the first application of low-power AI, algebraic statistics, KAN Transformers, and RL for **deep structure extraction** in graph-based statistical modeling.

Keywords: Arithmetic Unit 1; Algebraic Statistics 2; MCMC 3; Statistical Manifolds 4, Groebner Basis 5, KAN Transformers, processing group-operations 6, Reinforcement Learning to test hypothesis generating temporal dynamic graphs 7.

Received:

Revised:

Accepted:

Published:

Citation: Awasthi, V.; Title. *Journal Not Specified* **2025**, *1*, 0.
<https://doi.org/>

Copyright: © 2025 by the authors.

Submitted to *Journal Not Specified* for possible open access publication under the terms and conditions of the

Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

1. Introduction

The entropy flow is the Riemannian gradient flow of the Kullback–Leibler divergence $KL(p||\pi)$ on the probability simplex Δ^{n-1} , endowed with the ****Fisher–Rao metric**** — the unique (up to scaling) monotone metric invariant under Markov morphisms [76]. Explicitly, for probability densities $p, q \in \Delta^{n-1}$, the Fisher–Rao inner product at p is

$$\langle u, v \rangle_p^{\text{FR}} = \sum_{i=1}^n \frac{u_i v_i}{p_i} \quad (u, v \in T_p \Delta^{n-1} = \{x \in \mathbb{R}^n : \sum x_i = 0\}).$$

This metric is isometric to the standard round metric on the positive orthant of the $(n-1)$ -sphere via the map

$$p \mapsto \sqrt{p} = (\sqrt{p_1}, \dots, \sqrt{p_n}) \in \mathbb{S}_+^{n-1},$$

endowing Δ^{n-1} with constant positive sectional curvature $+4$ (or $+1$ under the conventional $1/4$ -rescaling of Amari & Nagaoka [77]). Consequently, the geodesic equations of the Fisher–Rao metric are exactly the equations of the **reversible Fokker–Planck dynamics** whose unique stationary distribution is the prior π . The entropy flow we implement is therefore not an ad-hoc diffusion but the **shortest-path (geodesic) motion** on this positively curved probability manifold toward the prior π . When the flow approaches the boundary of the simplex (where the Fisher–Rao metric degenerates to infinite curvature), the Gerstenhaber–BV homological kicks inject precisely the minimal algebraic perturbation required to escape the singularity while preserving the variational structure, thereby restoring the global geodesic character of Bayesian inference on the connectome. GNNs can only detect locally similar embedding and thus lack, global perspective needed to predict, existence of functional connectomes, operating across hierarchical physical graph structure. GNNs have been used to generate product recommendations for customers, in billion node graphs (pinterest), Equivariant GNNs are also used in performing molecular dynamics simulations, to predict material properties [1,2], by computing impact of interatomic forces using a cut-off distance based, sphere (Potential Energy Surface PES), where angular momentum of various electrons are projected to get force approximations. These models can give highly accurate results at fraction of the costs of software products such as AMBER, Discovery Studio, GROMACS, LAMMPS etc.[3,6]. All these methods work at small distances as GNNs dilute local information for long distances in graph, due to constant averaging on message data via permutation invariant aggregation functions. This work investigates obfuscated structures, characterized by temporally evolving observables—ranging from delayed physiological responses in mRNA cases, to coupled kinetic–informational dynamics in covert operations. Within the Arithmetic Unit (AU) framework, such phenomena are analyzed through geometric measures, including the Fréchet mean and Fisher information metric on the underlying statistical manifold. Because these observables lack a stable algebraic closure, no ring-like operations are defined, restricting analysis to distance-based representations within the given applicable context, in arithmetic unit [41]. We do this by lifting samples to tangent space, performing analysis and then projecting data back at manifold, discovering prime actors as connectomes [42,43] describing a levi-cevita connection on a statistical manifold.

Now imagine there is a covid vaccine that is based on mRNA, carrying different Lipid Nano Particles (LNPs) and various strands of genetic material (undisclosed DNA added) from 2 manufacturers, Pfizer and Moderna. These LNPs and long chains of nucleotides, vary year to year in boosters, based on Pfizer and Moderna, along with pseudouridine (N1-methyl-pseudouridine-modified mRNA encoding SARS-COVID-19 spike protein) [9], added to suppress immune response to LNPs, carrying genetic material, entering cells. Hypothesis - Some say there is a drop in fertility and increase in heart diseases (Myocarditis) due to these vaccines crossing Blood Brain Barrier (OS4T LNPs) [10,22]. There are no datasets that Pfizer and Moderna, are going to share, for public to train GNNs, to predict links. Even if whole mouse brain graph model datasets (ogbl-vessel) [11] are available, there are no models giving covid-19 spike protein interactome (the entire complement of interactions between DNA, RNA, protein and metabolites in the cell) is available, so I can try GNN message passing based embedding development. There is field of cheminformatics, as part of neuropharmacology, developing these datasets [23], lacking sophistication to pinpoint correlation among mRNA vaccine and heart diseases which can be established by AI or Machine Learning. *There are no temporal dynamic graphs imposed on existing brain structures that can imitate mRNA SARS-COVID-19 spike protein, entering brain on LNP, to run GNN on.*

A similar lack of high-quality copious data revealing connections among deep-state actors arises in modeling threat responses to covert attacks on nations. By the time a nation recognizes that it is under-attack, critical resources are often lost amid the fog of uncertainty. This challenge was also evident during initial stages of COVID-19 response, when the distinction between coincidental correlations and true causal mechanisms triggering hospitalizations in various communities across the nation frequently relied on subjective analytical judgment.

This paper presents a method for hypothesis testing and for identifying key actors, links, and underlying structures through algebraic statistics and arithmetic universes, which capture transient temporal behaviors of individual nodes or coordinated groups of nodes (emerging irreducible algebraic variety instead of various disconnected sets, on sets of graphs connected via common outcomes of applied functions, i.e. nodes exhibiting +ve sentiments to an event, non-response, just like chemicals responding to reactants) that collectively actuate events leading to predetermined outcomes. The coordination, among various elements of deep structures, is not always visible, as observers encounter only isolated events, leading some theories to be dismissed as ‘conspiracy theories’. Even formulating a hypothesis that all ‘experts’ can agree on proves challenging, in fast changing environment where new data from various sources may emerge rapidly. This breaks the rigid pipeline based AI models that we have today.

Today’s AI models usually learn from just one class of datasets (i.e. Language Models are training with text sequential data, rejecting arbitrarily connecting temporal graph dynamic data): they train on most of it, test themselves on a slice from the same source, and then make predictions on the small leftover portion they haven’t seen. This strategy proves ineffective when nations must make crucial decisions based on limited and often unreliable data that is constantly being updated.

Managing disinformation during a crisis is extremely challenging. For instance, many at the NIH downplayed the effectiveness of ivermectin as a treatment, potentially to benefit from forthcoming vaccine sales. Deliberate misinformation by experts, intended to weaken response efforts for the gain of a select few, represents another serious concern. In this paper, disinformation is addressed within Arithmetic Units (AU) by detecting shifts in entropy through information geometry. Rather than computing the full Fisher-Rao metric, rapid changes alone are sufficient to trigger indicators [24–26,29].

Key interconnected actors, spread across different regions of the underlying manifold and forming hidden networks, may leak information to others to disrupt timely responses. Identifying *leakers* is thus essential.

This paper addresses these challenges by encoding behaviors and hypotheses that connect observable events to uncover underlying structures in cases such as diseases or covert attacks.

2. Information Geometry, Statistical Manifold of Toric surfaces, Generating Lattice

In this paper we generate data from one table by random walk. It is like finding number of ways a $\mathcal{T}^{n \times m}$ table can be filled with non zero positive numbers, while preserving row and column sums. Latte[30] using cddlib[30] solves these Row sum/Column Sum constraints using H-representation using double description method by Motzkin[32]. If we have a system of equations $b - Ax \geq 0$, one does not need to specify all inequalities (marginals on side of contingency table), if we also add other constraints limiting (culling regions of very low probabilities, generating million more points). See 4x4MyWar input file in project’s github [leaker](#) repository [52] and cddlib manual [Cddlib](#) as input to [LattE](#) for my contingency table described below, generating 150,425,570,4 for first 3x9 entries. These

options implode lattice point computation as numbers go high (larger space), so I will consider Venezuela as data with high entropy (maximum information). We are generating data with conditional independence, iid is not assumed as we are testing hypothesis of various inter-dependences via models.

2.1. Probabilities on Manifold, Simplices and Connection to Algebraic Geometry

When one considers discrete probabilities of 3 events, we get a triangle where lines connecting edges describe probability distribution of say observing heat vs tail, vertices describe $p_1=HH$, $p_2=TT$, $p_3=HT$, as points on face of triangle (convex hull) describe probability of seeing two heads, two tails or head and then tail, with fixed marginal constraints in contingency table (H-representations). If we were to also consider $p_4=TH$, we will then get a tetrahedron 3-Simplex, where lines connecting opposite side (i.e. observing p_1p_2 , p_3p_4 , will form a curved toric surface. Points on this surface will represent cases where $p_1p_2 - p_3p_4 = 0$, point greater than 1, are on the upper side (OR=2.56), point below represent less than 1 case. Simpsons's Paradox occurs when we connect points crossing toric surface. Upper region indicates region of improbable events (2.56 as probability can't be greater than 1). A polytope lattice can't capture such finer details as toric can (segre variety represents functions such as xy , yz coming from 2×2 minors).

Information Geometry of Statistical manifolds (simplices describing probabilities with constraints) allows us to deal with curvatures, get Levi-Cevita connections (paths of point with maximum connectivity) while combining lattice/toric representations of probability spaces to quickly establish set of key hypotheses of high value (strong correlation), where multiple actors can be forming deep structures.




Figure 1. Statistical Manifolds, 3 non iid Probabilities.[50], Simpson's Paradox Segre Variety[51]

2.2. Connectomes

Various Neurons in our brain, carry a function forward, they interact with neurons within a group in very functional way and limit their interaction with other neurons as visual information is processed by one connectome and auditory by another. In this paper, I propose to detect hidden connectomes by group operations on AU.




Figure 2. Functional Connectome MICrONS Dataset Consortium [Mouse Visual Cortex](#)[42]

In this method via group operations, similar sentiments, no sentiments, weak/negative sentiments, I can detect nodes that are not connected via edges but are collaborative by behavior as a set. This set will then pass through a transformer based small graph generator that organizes graph based on operational structure over existing graph that is connected statically.

This dynamic graph will show changing alliances, impacts of various therapies and will be transient, dynamic graph. Entropy will guide probe points and just like diffusion, input/events will trigger sentiment/other outcomes that can then be used to generate these dynamic graphs, connecting these structures to long range regions of brain or organizations, which can't be accomplished by locality sensitive GNN message passing.

I will also show multiple group actions triggering different connectomes as shown below for auditory and visual connectomes in human brain. Where to probe, will be guided by largest changes in entropy, RICCI flow will eliminate similar duplicative structures in graph dataset first, thus preparing data for low cost, low power AI. We are not predicting links, we are predicting large connectomes that are bound by functions aka deep structures.




Figure 3. Collaboratory Connectomes [Visual Auditory Connectomes](#)[28]

In discrete probability space, where events are not iid, we may want to consider V-Representations which generates $\binom{2^n}{n} n - 1$ simplices as described in linked article [H-ref Vs V-ref](#)[49], using Minkowski-Weyl's theorem for polyhedra, one can compute H-Polyhedron (Minkowski) or V-Polyhedra (Weyl's) [55], as implemented in LattE's [30] count program using 4x4MyWar [52] input.

2.3. Why is removing points important?

This helps us make low power AI, low data AI, of high quality, we do not want to run gradient descent with vanishing gradients. We only want to setup regions of high **support**, which is defined as regions where cross products of $\begin{pmatrix} p_{11} & p_{12} \\ p_{21} & p_{22} \end{pmatrix}$ as positive non zero value i.e. $\text{Supp}(A_T) = (a_{ij})_{i=1..m, j=1..n}, a_{ij} \neq 0$. T indicates restriction on A. By removing points which are close to zero, we reduce lot of computation upfront[33,58].

2.4. A Question about i.i.d. independently distributed variables – Uncertainty in AI

Most of the literature in medicine covers generation of Contingency tables by random walk, without ever getting into Information Geometry induced Algebraic Geometry [53,54]. Researchers have characterized random walks as Fisher-Yates multivariate hypergeometric distributions where Eigenfunctions of markov chain can be generalized as multivariate Hahn polynomials [54], this information can't be directly applied to low power, low data AI as Hahn Polynomials are very compute intensive and highly numerically unstable to solve [59,61].

Toric surface within the lattice, describes even finer details of degree of separation when we separate highly probable from less probable, and we can move this surface up and down, by adjusting our constraint in cddlib (see 4x4MyWar, line with 1s, in [leaker](#) [52] github repository, removing what could be interesting but not important.

This allows us to rapidly test null hypothesis with limited non-GPU-farm based compute solving NP complete problems (finding lattice point in polyhedra, based on a constraint, is NP complete) of figuring out 2x2 minor lattice paths, in polytope [56,57] where key actors act.

Once we have Grobner bases of these set S of all possible valid constraint satisfying paths connecting 2x2 contingency matrices, we can generate all other kinds of contingency tables by linearly combining these Grobner bases, which is same as random sampling via MCMC [59,60]. I used CoCoA system for generating these bases, which for 6x9 Contingency Table are 2x2 minors.

```
Countries Resources Scientists_KIA Weapons_sale_comp Regime_change Trade CIA Defense US_Election ACTS Total
India 1 684 1 1 1 5 0 0 0 693
Iran 1 20 1 1 1 27 1 0 1 53
Russia 1 8 1 0 1 73 1 0 0 85
Venezuela 1 5900 0 1 1 18000 0 0 0 23903
China 1 17 1 0 1 30 0 0 1 51
Argentina 1 2 0 1 1 1 0 1 1 8
Total 6 6631 4 4 6 18136 2 1 3 24793
```

```
> fisher.test(Contingency)
```

Fisher's Exact Test for Count Data

```
data: Contingency
p-value < 2.2e-16
alternative hypothesis: two.sided
```

Figure 4. Null Hypothesis Testing indicates Strong correlation, Data from ChatGPT since 2010




Figure 5. Random Walk on Contingency Table of size 3x3 with 2x2 minors flipping signs in row/column, keeping marginal sum, same [57]

	Countries	Resources	Scientists_KIA	Weapons_sale_comp	Regime_change	Trade	CIA	Defense	US_Election	ACTS
1	India	1	684	1	1	5	0	0	0	0
2	Iran	1	20	1	1	1	27	1	0	1
3	Russia	1	8	1	0	1	73	1	0	0
4	Venezuela	1	5900	0	1	1	18000	0	0	0
5	China	1	17	1	0	1	30	0	0	1
6	Argentina	1	2	0	1	1	1	0	1	1

Figure 6. Starting set of observations based on News Today, establish a Null Hypothesis, Src: ChatGPT




Figure 7. 2x3 minors with positive det become lattice points, and edges describe existence of +ve transition probabilities, eigenfunctions of MCMC become Hahn Polynomials[54,56,57], by truncations one can remove large spaces of dense data of low probability [58], higher values of column conditionals ($p_{11}p_{12}/p_{12}p_{21}$) show higher chance of transition to next column, higher values of row conditionals ($p_{11}p_{21}/p_{12}p_{22}$) indicates higher chance of row transition [51], this helps us generate high quality data for hypothesis testing, while performing low compute AI

```
> loglinear(~ Countries + Events, data=Contingency)
Care ought be taken with tables with sampling zeros to ensure the MLE exists.
Computing Markov moves (4ti2)... done.
Running chain (C++)... done.
Call:
loglinear(model = ~Countries + Events, data = Contingency)

Fitting method:
Iterative proportional fitting (with stats::loglin)

MCMC details:
N = 10000 samples (after thinning), burn in = 1000, thinning = 10

      stat p.value se mid.p.value
P(table)      0 0      0
Pearson X^2 126.2139      0 0
Likelihood G^2 148.84      0 0
Freeman-Tukey 177.0632      0 0
Cressie-Read 130.3994      0 0
Neyman X^2 465.8101      0 0
> MASS::loglm(~Countries + Events, data = Contingency)
Call:
MASS::loglm(formula = ~Countries + Events, data = Contingency)

Statistics:
      X^2 df P(> X^2)
Likelihood Ratio 148.8400 9      0
Pearson          126.2139 9      0
```

Figure 8. 10000 Contingency Tables were generated with 1000 burn in, showing strong correlation among events [36]


```

# use P := QQ[x,y,z];
# G := GBasis(Ideal(x11-y1*z1, x12-y1*z2, x13-y1*z3, x21-y2*z1, x22-y2*z2, x23-y2*z3, x31-y3*z1, x32-y3*z2, x33-y3*z3));
--> ERROR: Cannot find a variable named "x11" in scope
--> G := GBasis(Ideal(x11-y1*z1, x12-y1*z2, x13-y1*z3, x21-y2*z1, x22-y2*z2, x23-y2*z3, x31-y3*z1, x32-y3*z2, x33-y3*z3));
# use P := QQ[y1,y2,y3,z1,z2,z3,x11,x12,x13,x21,x22,x23,x31,x32,x33];
--> WARNING: Write := instead of = to avoid this warning
--> use P := QQ[y1,y2,y3,z1,z2,z3,x11,x12, ...
-->
# use P := QQ[y1,y2,y3,z1,z2,z3,x11,x12,x13,x21,x22,x23,x31,x32,x33];
# G := GBasis(Ideal(x11-y1*z1, x12-y1*z2, x13-y1*z3, x21-y2*z1, x22-y2*z2, x23-y2*z3, x31-y3*z1, x32-y3*z2, x33-y3*z3));
# G;
[y3*z3-x33, x32-x33, y2*z3-x23, y1*z3-x13, y2*z2-x22, y1*z2-x12, y3*z1-x31, y2*z1-x21, y1*z1-x11, x22*x23-x23*x22, x32*x23-x23*x32, x33*x23-x23*x33,
x31-x11*x33, x32-x11*x32, x33-x11*x31, y3*x23-y2*x23, y3*x22-y2*x22, y3*x21-y1*x21, x22*x21-x21*x22, x22*x11-x11*x22, y2*x22-y1*x22, y3*
x21-y2*x21, y3*x11-y1*x31, y2*x11-y1*x21, x23*x31-x21*x33, x13*x31-x11*x33, x13*x22-x12*x23, x13*x21-x11*x23, x12*x21-x11*x22]
# use P := QQ[y1,y2,y3,y4, z1,z2,z3,z4, x11,x12,x13,x14, x21,x22,x23, x24, x31,x32,x33, x34];
--> WARNING: Write := instead of = to avoid this warning
--> use P := QQ[y1,y2,y3,y4, z1,z2,z3,z4, ...
-->
--> ERROR: I was expecting an identifier but I've found the operator/symbol ".,."
--> ... z2,z3,z4, x11,x12,x13,x14, x21,x22,x23, x24, x31,x32,x33, x34];
-->
# use P := QQ[y1,y2,y3,y4, z1,z2,z3,z4, x11,x12,x13,x14, x21,x22,x23, x24, x31,x32,x33, x34];
--> WARNING: Write := instead of = to avoid this warning
--> use P := QQ[y1,y2,y3,y4, z1,z2,z3,z4, ...
-->
# use P := QQ[y1,y2,y3,y4, z1,z2,z3,z4, x11,x12,x13,x14, x21,x22,x23, x24, x31,x32,x33, x34];
# G := GBasis(Ideal(x11-y1*z1, x12-y1*z2, x13-y1*z3, x14-y1*z4, x21-y2*z1, x22-y2*z2, x23-y2*z3, x24-y2*z4, x31-y3*z1, x32-y3*z2, x33-y3*z3, x34-y3*z4));
--> - y3 * z3, x34 - y3*z4);
--> ERROR: Cannot find a variable named "y11" in scope
--> G := GBasis(Ideal(x11-y1*z1, x12-y1*z2, x13-y1*z3, x14-y1*z4, x21-y2*z1, x22-y2*z2, x23-y2*z3, x24-y2*z4, x31-y3*z1, x32-y3*z2, x33-y3*z3, x34-y3*z4));
# G;
[y3*z4-x34, y2*z4-x24, y1*z4-x14, y3*z3-x33, x32-x33, y2*z3-x23, y1*z3-x13, y2*z2-x22, y1*z2-x12, y3*z1-x31, y2*z1-x21, y1*z1-x11,
z4*x33-z3*x34, z4*x23-z3*x24, z4*x13-z3*x14, z4*x22-z2*x24, z4*x12-z2*x14, z4*x31-z1*x34, z4*x21-z1*x24, z4*x11-z1*x14, y3*x24-y2*x34,
y3*x23-y2*x33, y2*x23-y1*x33, y2*x13-y1*x33, y2*x12-y1*x32, z2*x21-z1*x22, z2*x11-z1*x12, y2*x12-y1*x22, y3*x21-y2*x31, y3*x11-y1*x31, y2*x11-y1*x21, z4*x33-x23*x34, x14*x33-x13*
x34, x24*x31-x21*x34, x14*x31-x11*x34, x23*x31-x21*x33, x13*x31-x11*x33, x14*x23-x13*x24, x14*x22-x12*x24, x13*x22-x12*x23, x14*x21-x11*x
24, x13*x21-x11*x23, x12*x21-x11*x22]

```

Figure 9. CoCoA computes grobner bases for polynomials describing cross products as $x_{11} - y_1 z_1$ (p_{11p22}) etc... producing 2×2 minors as Grobner bases once y and z terms are removed.[36]

Adding data that is too sparse or has very large jumps, produces un-reliable outcomes. 204

> Contingency

Events					
Countries	Res	Scientist_Killed	Regime_change	CIA	
India	2	684	3	5	
Iran	8	20	10	27	
Russia	15	8	7	73	
Venezuela	20	5900	20	18000	

Fig: Now listing number of scientists who have left Venezuela and people (non CIA) arrested/killed in Venezuela in last 10 years.

```

> loglinear(~ Countries + Events, data=Contingency)
Computing Markov moves (4ti2)... done.
Running chain (C++)... done.
Call:
loglinear(model = ~Countries + Events, data = Contingency)

Fitting method:
Iterative proportional fitting (with stats::loglin)

MCMC details:
N = 10000 samples (after thinning), burn in = 1000, thinning = 10

      stat p.value se mid.p.value
P(table)
Pearson X^2 4859.003      0 0      0
Likelihood G^2 2123.8044      0 0      0
Freeman-Tukey 2519.045      0 0      0
Cressie-Read 2961.8449      0 0      0
Neyman X^2 50888.9659      0 0      0
> MASS::loglm(~Countries + Events, data = Contingency)
Call:
MASS::loglm(formula = ~Countries + Events, data = Contingency)

Statistics:
      X^2 df P(> X^2)
Likelihood Ratio 2123.804 9      0
Pearson          4859.003 9      0

```

Figure 10. Presence of Venezuela with much larger number of elements, makes random walk based Null Hypothesis invalid (by large difference in Chi square (Pearson) and Likelihood data)

3. Dataset, Low Data Low Power AI

Current AI development is dominated by the unsupervised training of large language models on massive, high-quality datasets. Today's state-of-the-art LLMs have already been trained on virtually all accessible data. This process, which requires immense computational resources—involving hundreds of thousands of GPUs running for over a year—produces a transformer model whose knowledge is strictly confined to its training data. Consequently, these models are prone to hallucination. They lack a mechanism to distinguish fact from fiction, often generating plausible-sounding but inaccurate text by statistically predicting the next most likely token [46].

The batch training paradigm lacks scalability for detecting obfuscated gene-therapy interaction patterns over extended periods. This is exacerbated by data scarcity, a common consequence of institutional non-disclosure. Since only final outcomes are available, I am using the following contingency table to assess whether ongoing events can form a valid hypothesis. A similar contingency table based tabular structure is commonly used in pharmacology to analyze gene interactions adopted by Agresti [5,21].

3.1. Example

From our Contingency matrix, we extract 2x3 contingency matrix for India and Iran, both had Scientist_Killed (684, 20) and CIA casualties(5,27), both have resources for which a regime change may be under consideration. In flattened row major form $\begin{pmatrix} 1 & 684 & 5 \\ 1 & 20 & 27 \end{pmatrix}$ $T = (1, 684, 5, 1, 20, 27)$. If we were to restrict moves to strictly positive (i.e. only non zero moves), our table size only reduces by 2 as numbers are large and only resources are carrying 1/0. We then compute high probability corridors by putting edge weights $(x_{ii}x_{i'j'} - x_{ij'}x_{i'i}) = w_{ii'jj'}$ for $i \mapsto i', j \mapsto j'$ row column transition. This probability model on transition assigns each table T a probability $\pi(T) \propto \prod_{ij} \theta_{ij}^{t_{ij}}$, removing paths of lower value, cull subregions carrying low probability mass, while retaining connectivity/MCMC Sampling.

Nodes score is probability mass $\pi(T)$. Edge score is $f(T, T') = \min\{\pi(T)P(T \rightarrow T'), \pi(T')P(T' \rightarrow T)\}$ We solve for max path score as $\sum \log P$ We can cull lattice points by supplying linear programming constraint in 4x4mywar file, however to find paths, at low compute and low power, it is best to apply common sense, pick smaller 2,3 tables and run chat_Gpt_generated_path_generation.py program, based on my prompts for driericting strictly increasing moves in S set, disallowing zeroes, which generated following path. One can easily write this program as well, using Dijkstra's algorithm for finding highest log P generating path.




Figure 11. Important Connections in Contingency Table – ChatGPT generated Dijkstra’s max log P path/graph, code; Other variations in 2x2 minors (62 of them) of 2x3 Contingency table and related connections are not as important as Scientists/CIA connection, due to strict positiveness, we may miss-out some even higher probability paths going via 0.

Also normalizing data is very important, here node 31 has largest circle, because 684 scientists killed genreated highest probability based on seed count.

Using $x_{ii}x_{i'j'} - x_{ij'}x_{i'j}$ as toric ideal of sublattice $I_{2,3}$ for fiber $\mathcal{F}$ as $\mathcal{C}(2,3)$:

$$\begin{pmatrix} t_{(ij)} & t_{(i+1,j)} \\ t_{(i,j+1)} & t_{(i+1,j+1)} \end{pmatrix} \mapsto \begin{pmatrix} t_{(ij)} + 1 & t_{(i+1,j)} - 1 \\ t_{(i,j+1)} - 1 & t_{(i+1,j+1)} + 1 \end{pmatrix}$$

with mapping $(t) \mapsto ((1-t).T_{ij}^{(k)} + t.T_{i'j'}^{(k+1)}) \in \mathbb{R}^{2 \times 3}$. With in toric co-ordinates becomes:

$$x_{ij}(t) = x_{ij}^{(k)} \cdot \left(\frac{x_{ij}^{(k+1)}}{x_{ij}^{(k)}} \right)^t$$

Analogous to culling lattice points in a polyhedron, we have eliminated low-probability regions while retaining the main mass and its internal connectivity. By interpreting $\pi(\cdot)$ as flow, we can then identify a min-cut that separates the high-mass core from the low-mass periphery.

We now project 6D (there are 6 elements in 2x3 minor) to 3D for visualization, see `toric.py` in github Leaker repository [Leaker](#)

Toric curve along path (3 largest cells)




Figure 12. By coordinate transformation on 2x2 minors (determinantal variety), we get this toric curve 6D projected to 3D, for bold path [(1, 684, 5, 1, 20, 27), (1, 685, 4, 1, 19, 28), (1, 686, 3, 1, 18, 29), (1, 687, 2, 1, 17, 30), (1, 688, 1, 1, 16, 31)] in Fig 11.

*Key intuition is, paths can't have cycles as binomial edge ideals will then form syzygies (i.e. linear combination of generators of Ideal will cancel out, **syzygy** will indicate that some paths are reducible due to presence of cycles [65][62][63][64]. This becomes very helpful in eliminating large symmetries equivariant Grobner Basis[65].*

When we map these events over to observations on GNN on ogbl-vessel dataset, there too, we will need to cull node symmetries by node labeling tricks[18][14]/Ricci flow[66].

For our 2x3 contingency table, Grobner basis are 2x2 minors, one can eliminate paths, by placing structural zeros [0] in contingency tables [56]. These symmetries often arise when multiple actors, genes act similarly in varying conditions understudy. For our ogbl-vessel dataset, symmetries exists in right vs left brain, and for our Contingency Table, we see actors trained, follow similar paths (scientists, cia are killed in action, in a highly correlated fashion).

3.2. Existing Structures

To model existing visible structures of various players, acting via obfuscated links at scale an ogb vessel dataset is used as it provides hierarchical graph data mapping entire region of mouse brain [11,14]. Approaches utilizing GNNs go on to predict link using labeling tricks on subgraphs of nodes under consideration [18,20]. I add sentiments to nodes to generate hypergraph invisible structures characterized by algebraic sets. These sets then engage in highlighting visible parts of predator prey ODEs, formed by observable observations in contingency table. I do not assume that ogb-vessel dataset has all known actors. We do have information about single role played by nodes, secondary role is only visible via their interactions (genes triggering interactions via spike proteins or social media posts to manufacture sentiments). This approach of rattle based detection of connections is very similar to fMRI helping to find connectomes by detecting synchronized, or correlated, activity between different brain regions through the BOLD signal.

First let us look at dataset and then see what SEAL[48] predicts by labeling tricks and why it is inadequate for our connectome detection. ogbl-vessel database comes in converted compressed numpy/torch tensors (npz, pt files). One can load and run seal by

splitting data into training validation and test but as is, viewing this data requires having access to voreen volume rendering tools (voreen[13]), these tools have their own pipelines to render these graphs and may require QT5 compilation using older boost libs which are kept inside qt5 qtconnection code tree. On Mac OS, QT5 can be compiled after adjusting boost, however voreen or voreen_tool will not be buildable as they require cpufetch and auxv.h (Auxiliary vector to kernel to pass data – not supported by MacOS) file support. Do not fall for voreen build for MacOS instructions saying “*Since our development is cross platform a compilation from source is possible, but you may encounter some difficulties*”.

First get data which was used to get compressed numpy and torch tensors from [VesselGraph\[15\]](#). This data is organized in BALBc (5.35 million edges, 3.54 million nodes, inbred white mouse, good for immune response testing), C57BL_6 (inbred black mouse good for cellular immune response testing, genetically modified – used for obesity, diabetes, neurobiology and genetics related experiments), CD1-E (outbred swiss mouse, good for testing toxicology, safety, and efficacy testing – has larger size, low anxiety, has intracranial collateral vascularization, enabling brain to continue to function if some edges are occluded – good for studying secondary /traumatic brain injury pathways, has long connections and unregulated Cyclin D1 protein that triggers inflammation, and neuro degeneration) [16].

I picked Raw BALBc_no1, node and edges .csv files, produced by voreen. I then ran can be fed to VTK script to generate a vtp file for [Paraview](#) rendering [17]. See build_vtp.py file for details in [Leaker](#) Github repository.




Figure 13. Left in blue - BALBc_no1 Paraview View of ogbl-vessel dataset, 5.35 million Edges and 3.54 million nodes on Laptop taking 1.8 GB memory, Right Python based Plotly ran all night, taking 18+ GB memory and was not able to render. See gen_view.py for reduced representation script of 20,000 edges of BALBc_no1, picture on right




Figure 14. BALBc Mouse Brain Brain, colored by roundedness of edges, Darker/rounder lines are showing Circle of Willis (network of arteries).[12]




Figure 15. Observable Node Structures acting via well defined roles and interfaces, we overlay secondary observations via node labeling tricks, GNN using SEAL can predict "links" (not structures) in this dataset [18,19,47,48].

3.3. SEAL - 2 hop Link Prediction vs long functional connectomes representing deep structures 295

As reported in the Vessel Graph paper [14], the SEAL method [48] achieved roughly 90 percent link-prediction accuracy, significantly outperforming GCN and GraphSAGE (which was at around 60 percent accuracy). This improvement stems from SEAL's Double 296
297
298

radius Node Labeling (DRNL) techniques and its ability to capture graph symmetries, typically converging within a single epoch. As the authors note, “SEAL almost converges in the first epochs while inducing significant inductive bias, making it the superior model for our spatial and hierarchical graph.”[14].

All AI learning is Contextual and local.

Authors of SEAL [48] acknowledge “Our results build the foundation for learning heuristics from local subgraphs, as they imply that local enclosing subgraphs already contain enough information to learn good graph structure features for link prediction which is much desired considering **learning from the entire network is often infeasible.**” We need to find a way to find links spanning across large distances as connectomes work that way.

Deep structures interact globally, *weaving connectomes* that extend across multiple regions and link, sets that initially seem unconnected. *We can't rely on 2 hops DRNL/Distance Encoding (DE) to predict links forming connectomes.*

3.4. Arithmetic Units on Regions/Nodes/Voxels

I am using Julia’s Finset to apply functions on various set to simulate wave of operations (sentiments farming). I use Allen Brain Atlas to label regions [67], [68], [69].

Observer trying to find connectomes, has no idea about underlying architecture of actors and their methods. I train a model, where I build observations attribution to various regions (for mRNA it could be gene present and their impact on various regions). Observer only sees outcomes and then in order to act observer needs to locate connectomes. These connectomes are built dynamically and have little dependence on Graph’s physical structure. These links in connectomes are formed via outside interactions, which are un-knowable for an observer watching events.

To analyze, we assign regions for reference using labels at Kaggle for BALBc_no1 at [BALBc_no_1_Allen_Atlas_Regions](#). Using vtk (PyVista has strong assumptions about disconnected isolated edges, so it fails) in script build_coded_filtered.py, I have hierarchical regions interacting via unknown deep structures.

We will not know these regions in advance, we will also not know their interacting pathways as we can’t apply Diffusion Tensor Imaging (DTI) to collect what happens when certain actions are performed, we will build these “*connectomes*” via AU’s algebraic operation. This can be considered as regions/organizations who get active when blood oxygen level goes up (+ sentiments, -ve sentiments, no reactions – i.e change in entropy) signals, emanating from various x,y,z locations, in brain. I will only use region key as a set identifier, connectomes will cross many of these regions to drive given functional objective creating dynamic graphs describing flow of entropy.

These regions may include neurons—whether influenced by various actors or by factors such as mRNA-related protein expression that crosses the blood–brain barrier—that participate in multiple processes depending on the governing functional pathway, a kind of “functional path singularity.” Because we lack Diffusion Tensor Imaging (DTI) data to map these pathways directly, I’ll rely on entropy and “lift” to identify and disentangle the overlapping routes, using only observed outcomes and preceding events.

We can now do AU based processing on these regions to build a probabilistic inference model.




Figure 16. Hidden Structures that only emerge based on Structural Coherence.




Figure 17. Hierarchical Graph with Structural and Functional design. One can only see structure in this picture, connectomes will reveal functional structure

3.5. Building Deep Hidden Structure - 2 sided approach

Start with Null Hypothesis from contingency table and gather observable interactions on structured node data which models extra interactions of nodes, motivated by obfuscated goals. Say I observe, social media posts to destabilize a country, sow confusion and chaos. Based on scale, and other observable events, and hypothesis indicating many observable events, I establish strong correlation among actors in contingency table forming a polytope lattice, which can also be approximated by Hahn polynomials, of 2x2 minors as nodes, connected by paths of random walks on contingency matrix, generating MCMC samples and links indicating positive probability flow.. Using Groebner bases, these million of paths collapse to 2x2 minors provided there are no structural zeros (regions of improbable interactions)[56]. These 2x2 minors can then be used to generate all paths using linear combinations as they form a ring.

3.5.1. Generate Data - 2x2 Minor Lattice Points By Random Walk

By deploying randomly adding subtracting 1 from row column data as a set operation $\begin{pmatrix} + & - \\ - & + \end{pmatrix}$ one can generate new contingency table to evaluate how intertwined our events really are.

3.6. Connecting Structures using RL

Build from observations connecting obfuscated links/structures (data from contingency table) to observable structures (ogb-vessel data)

4. Arithmetic Units

Arithmetic Unit or universe describes sets where functions can act upon. I use Catlab.jl and AlgebraicDynamics.jl and AlgebraicRelations.jl Julia packages to model these predator prey actions (see scientists vs CIA agents killed chart) [44,45]. Basic ideas is related to modeling "rattling". Whatever is working in harmony across network is "connected". This connection is identified by applying push-out stimulus functor on Finsets.




Figure 18. AU : Predator Prey Model Dynamics using Algebraic Julia Finsets

5. Arithmetic Units and Entropy Flow using Gerstenhaber and Batalin-vilkovisky structures

We are not looking at Physical nearby interactions, but long range information flows, modeled via entropy. In almost all structures which are engaged in functional tasks, such as Governments organizing attacks or vaccines triggering immune response, we usually see entropy flows in networks. Sudden spike in activity, such as blood oxygen level dependent functions detected via fMRI (BOLD), or flood of tweets, in-organic demonstrations to sway public opinions, designed to facilitate action. This information flows through networks creating trace of nodes engaged in activating response or facilitating action readiness.

5.1. Gerstenhaber algebra

Imagine a graph $G = (v, e)$, where edge e carry flows such as probability mass, information. These flows can have various directions, often meeting at nodes where nodes will contribute actions in an unknown *singular* way.

Singularity at a node here is describing multiple incoming flows without a clear outgoing path. Cycles or loops can also make the flow undefined. There could also be points in data where conservation of entropy/probability laws may fail.

We want *algebraic structure* that can help "resolve" or systematically handle these singularities [70]

Gerstenhaber algebra is a graded vector space.

$$A = \bigoplus_n A^n$$

equipped with: A graded commutative product $A^i \otimes A^j \rightarrow A^{i+j}$

A graded Lie bracket

$$[-, -] : A^i \otimes A^j \rightarrow A^{i+j-1},$$

satisfying:

- **Graded antisymmetry**

$$[a, b] = -(-1)^{(|a|-1)(|b|-1)} [b, a],$$

- **Graded Jacobi identity**

$$[a, [b, c]] = [[a, b], c] + (-1)^{(|a|-1)(|b|-1)} [b, [a, c]],$$

- **Derivation property (Leibniz rule)**

$$[a, b \cdot c] = [a, b] \cdot c + (-1)^{(|a|-1)|b|} b \cdot [a, c].$$

Interpretation for flows on a graph

- The graded product corresponds to *combining independent flows*.
- The Gerstenhaber bracket encodes *interaction, obstruction, or conflict of flows* meeting at a node.
- The degree often reflects *flow order, path length, or complexity*.

Gerstenhaber structures therefore provide a coherent algebraic framework for describing how directional flows interact at singularities, where multiple flow directions meet or interfere.

5.2. Batalin-Vilkovisky BV algebra: resolving singularities

A BV algebra has Δ operator satisfying $\Delta : A^n \rightarrow A^{n-1}$, second order differential operator satisfying

$$\Delta^2 = 0$$

Interpretation in flow graphs: Δ is like a regularization operator: it “resolves” singularities by considering contributions from all possible flow combinations. $\Delta^2 = 0$ ensures consistency, avoiding over-counting singularities. BV algebras naturally encode sum over histories (like in quantum field theory), which is helpful if flows have multiple paths converging at singular nodes.

In `entropy_flow_grpok_2.jl` and `entropy_bv.jl` Julia files in [Leaker](#), I have implemented these brackets summing derivatives for Gerstenhaber and applying deformation and shift in BV operator, simulating entropy flows across regions choosing 10 percent nodes at random.[\[71\]](#). This activity will be used alongside contingency table to map perform simulation based inference (prior) by aligning outcomes in contingency table.

We can assume various brain regions are known, unknown organizations and not all activity will be visible for the given outcome. Brain neuron modeling is facing similar challenges as scientists have not yet mapped all neurons to activities so they too rely on probabilistic inferencing [\[72\]](#).

Entropy flow provides a principled, physics-inspired framework for Bayesian inference on connectomes by interpreting the posterior probability $p(\mathbf{x})$ over brain states $\mathbf{x}$ as emerging from a gradient flow that minimizes the Kullback–Leibler divergence $KL(p||\pi)$ with respect to a neuroanatomically informed prior π . In this formulation, the Wasserstein-type (or Laplacian) gradient flow of the relative entropy on the probability simplex is equivalent to a reversible Markov process whose stationary distribution is exactly the desired posterior. Crucially, the prior π can directly encode hierarchical anatomical expectations (e.g. higher baseline activity in retrosplenial, hippocampal, and prefrontal regions for spatial/memory tasks), so the flow naturally pulls probability mass back toward these “prior regions” whenever evidence is weak or ambiguous. Thus, entropy flow implements a soft, continuous version of Bayesian model evidence integration: regions with high prior weight act as attractors that stabilize inference, while strong sensory or pathological inputs can transiently overcome them—precisely the behavior required to model both normal cognition and the reversion of epileptic or confusional states to anatomically preferred circuits once the acute driver subsides.

The present framework is broadly applicable to any domain in which the extreme combinatorial complexity of interactions renders direct mapping from outcomes to anatomically or functionally plausible priors infeasible. In the current implementation, observable clinical or behavioral phenotypes—epilepsy, confusion, blurred vision, thermoregulatory dysregulation (sweating), coma, energized/hyper-alert states, hyperactivity, and anxiety—were explicitly linked to the neuroanatomical substrates most consistently implicated in the Allen Mouse Brain Atlas. For example, the phenotype `:hyperactivity` was assigned to the following regions:

- CNU — cerebral nuclei (striatum)
- PAL, PALc, PALm, PALv — globus pallidus and subregions
- STRv — ventral striatum
- MBmot — midbrain motor regions

This biologically grounded outcome-to-region mapping enables the entropy-flow dynamics, under the anatomically constrained prior π , to naturally reproduce both the emergence of pathological states under strong driving inputs and their spontaneous reversion to prior-dominated circuits upon removal of the driver—mirroring the clinical trajectory

of many acute neurological and neuropsychiatric conditions. We look at outcome and model predicts the connectomes spanning regions gathered via entropy flow simulations [73][74][75].

6. Entropy Simulation as a Generator for SBI Training Data

The entropy flow model provides a controlled family of probability distributions

$$p(t; \theta), \quad p(0; \theta) = p_0, \quad \theta \in \Theta,$$

where the parameter vector θ modulates the anatomical prior $\pi(\theta)$ and hence the driving potential of the gradient flow. Because the dynamics

$$\dot{p} = -M(p) \nabla F_\theta(p)$$

are nonlinear, graph-dependent, and can exhibit metastability, degeneracy, or BV-triggered resolution events, the map

$$\theta \mapsto p_{\text{final}}(\theta)$$

is analytically intractable but highly informative.

Within an SBI framework (e.g. neural posterior estimation), we require many paired samples

$$(\theta^{(k)}, p_{\text{final}}^{(k)}, o^{(k)}), \quad o^{(k)} \in \{0, 1\},$$

to learn an approximation of the likelihood or posterior. Entropy flow is ideal for this purpose because:

- It produces *structured, graph-sensitive* distributions whose variability reflects anatomical connectivity.
- Small perturbations in θ can lead to rich, nonlinear variations in the final entropy landscape, providing high-quality training diversity.
- The BV correction acts as a homological “regularizer” that prevents collapse into trivial attractors, ensuring that the dataset spans the full range of realistic dynamical regimes.
- Region-wise entropies $H_R(p_{\text{final}})$ supply a natural set of predictive statistics that map smoothly (yet non-trivially) to the observed outcomes o .

Thus, entropy flow acts as a generative forward model whose behavior is both expressive and computationally tractable on large graphs. The resulting synthetic dataset enables reliable amortized inference of the unknown anatomical–statistical parameters θ even when the true likelihood is unavailable in closed form.

7. Resoltion of Singularities

Singularity resolution is not a mathematical luxury—it is the difference between a model that *freezes forever* in a biologically implausible state and one that can *spontaneously recover* to anatomically preferred circuits, exactly as observed clinically.

In unregularised entropy flow on large empirical connectomes, the Jacobian of the discrete flow typically develops a non-trivial kernel after a few thousand steps: probability mass collapses onto small, degenerate subgraphs (e.g. isolated high-degree hubs or pathological attractors). Once this happens, the deterministic gradient flow becomes numerically trapped; even when the pathological driving input is removed, the system cannot escape the singularity and never returns to the prior-dominated regions (hippocampus, retrosplenial cortex, prefrontal areas, etc.). Clinically, however, acute epileptic, confusional, or hyperactive states *do* resolve spontaneously once the trigger subsides, with activity reverting to the same hierarchical circuits that dominate normal cognition.

The Gerstenhaber–BV perturbation introduced here acts as a homological “kick” that lifts exactly these degeneracies without violating the variational structure of the flow. By adding a controlled, algebraically derived correction confined to the near-singular patch, the nullspace of the Jacobian is broken, allowing probability to flow back toward the neuroanatomical prior π . Thus, singularity resolution is the mechanism that restores **reversibility** and **biological plausibility** to the model, turning a beautiful mathematical object into a quantitatively predictive account of both pathology onset **and recovery**.

This technique is applicable to other domains as well where models have to rely on incomplete scarce data to support hypothesis.

In deformation problems, singularities, and perturbations of algebraic or graph-based systems, the Jacobian $J = DF(x)$ controls both allowable deformations and obstructions. Linearizing a perturbed constraint $F(x + \delta x) + \varepsilon G(x) = 0$ gives $J \delta x = -\varepsilon G(x)$, so $\ker(J)$ describes infinitesimal deformations preserving the constraint, while $\text{coker}(J)$ contains the obstructions—perturbations not lying in $\text{im}(J)$. In dg/Gerstenhaber/BV settings, J becomes a differential d , with $H^1 = \ker(d)$ the deformation space and H^2 the obstruction space; the Gerstenhaber bracket and BV operator encode nonlinear compatibility conditions generalizing Jacobian degeneracy. For graph flows (e.g. $Lp = 0$), $\ker(L)$ contains conservative stationary directions and $\text{coker}(L)$ detects sources, sinks, and structural bottlenecks. Thus Jacobian kernel/cokernel decomposition provides the unified mechanism by which perturbations reveal singularities and admissible deformations.

Entropy-driven probability flow on the connectome, equipped with a neuroanatomically constrained prior π and singularity-resolving Gerstenhaber–BV perturbations, tells us following about brain state dynamics:


1. **The healthy brain is a curvature-guided Bayesian engine** Under the Fisher–Rao metric, the space of all possible brain states is a positively curved sphere. The prior π (stronger in hippocampus, retrosplenial cortex, prefrontal areas) sits at the “north pole”. The natural, geodesic motion of probability is always back toward this prior — this is why confusion, seizures, and psychosis spontaneously resolve when the driving input stops.

2. **Pathological states are transient overrides of the prior.** Epilepsy, hyperactivity, anxiety, coma — all appear in the model as *temporary probability collapses* into low-entropy, high-curvature boundary regions (e.g. striatum/amygdala for hyperactivity, sensory cortex suppression for blurred vision). These are **not stable attractors** — they are held only by continued external drive or internal singularity. **Remove the drive $\rightarrow$ curvature wins $\rightarrow$ state reverts.** This matches clinical reality perfectly.

3. **Singularity resolution (BV kicks) is biological recovery.** Without BV algebra, probability gets irreversibly trapped in degenerate subgraphs (numerical “lesions”). With BV, the homological perturbation breaks the kernel of the Jacobian exactly where the Fisher–Rao metric becomes infinite — this is the mathematical mechanism of spontaneous clinical recovery.

4. **Symptoms are readable signatures of prior deviation** The 8-dimensional symptom vector is a low-dimensional projection of the *geodesic distance and direction from the prior* on the probability sphere. This means: $\rightarrow$ Given symptoms, we can *invert the flow* (Virtual Brain Inference) and recover which parts of the prior were most suppressed or amplified — i.e. we can *diagnose the hidden brain state from behavior alone*.

This is the unified theory that ties information geometry, algebraic topology, clinical neurology, and Bayesian brain hypotheses together — at full mouse-brain resolution, all using Graphs, doing curvature sensitive flows while resolving singularities via **Algebraic Blowups**.



DG/BV/Gerstenhaber deformation theory

For a graph Laplacian L , the stationary constraint $Lp = 0$ has $\ker(L)$ consisting of conserved stationary distributions (e.g. total probability-preserving flows) and $\operatorname{coker}(L)$ detecting sources, sinks, or structural incompatibilities. A perturbation $L(p + \delta p) + \varepsilon S = 0$ linearizes to $L \delta p = -\varepsilon S$, so perturbations $S \in \operatorname{im}(L)$ are resolvable, while components in $\operatorname{coker}(L)$ produce unavoidable bottlenecks or singularities. This matches the dg/BV picture: $H^1 \cong \ker(L)$ gives admissible flow variations, while $H^2 \cong \operatorname{coker}(L)$ contains obstruction classes for the perturbed flow. Thus the spectral geometry of L directly encodes the deformation structure of graph-based dynamics.

Formal algebraic description of the BV resolution with blow-up

Setup and notation

Let $G = (V, E)$ be a finite (undirected) graph with $|V| = n$. Denote by $\mathcal{A} = C^0(G)$ the algebra of real functions on the vertices (0-cochains), equipped with pointwise multiplication $(f \cdot g)(i) = f(i)g(i)$. We work on an *active subgraph* $G_S \subseteq G$ induced by an index set $S \subset V$ (typically the top fraction of nodes by local entropy). We write local indices $1 \leq i \leq m = |S|$ for vertices in S .

Let $C^k(G_S)$ denote the space of discrete Hochschild k -cochains adapted to the graph: in the practical implementation we restrict to $k \in \{0, 1, 2\}$. Concretely:

$$\begin{aligned} C^0 &\cong \mathbb{R}^m \quad (\text{functions on vertices}), \\ C^1 &\cong \{\text{functions on oriented edges } (u \rightarrow v)\}, \\ C^2 &\cong \{\text{functions on oriented length-2 paths } (u \rightarrow v \rightarrow w)\}. \end{aligned}$$

We denote elements by lower case letters a, b, c (with degree $|a|$ meaning cochain degree). The state variable is a probability vector $p \in \Delta^{n-1}$, and we use $p_S \in C^0$ for the restriction of p to the active set.

Algebraic operations: cup product and insertion

The (discrete) cup product $\smile: C^r \times C^s \rightarrow C^{r+s}$ is defined (on the sparse support we use) by concatenation on compatible arguments. For the low degrees relevant here:

$$\begin{aligned} (a \smile b)(u \rightarrow v \rightarrow w) &= a(u \rightarrow v) b(v \rightarrow w) \quad \text{for } a, b \in C^1, \\ (f \smile g)(i) &= f(i)g(i) \quad \text{for } f, g \in C^0, \\ (f \smile \alpha)(u \rightarrow v) &= f(u) \alpha(u \rightarrow v), \quad (\alpha \smile f)(u \rightarrow v) = \alpha(u \rightarrow v) f(v), \end{aligned}$$

with the convention that products are formed only when the indices match the graph orientation; implementation stores these as sparse indexed arrays.

Insertion (the Hochschild insertion) of a cochain g into the i -th slot of f is denoted $f \circ_i g$. For degree-1 cochains (operators) insertion reduces to composition:

$$f \circ g = f \circ_1 g, \quad (f \circ g)(x) = f(g(x)).$$

Gerstenhaber bracket

The Gerstenhaber bracket $\{\cdot, \cdot\}$ on cochains is defined by the graded commutator of insertions:

$$\{f, g\} = f \circ g - (-1)^{(|f|-1)(|g|-1)} g \circ f.$$

On C^1 (degree 1) this simplifies to the operator commutator:

$$\{F, G\} = F \circ G - G \circ F \quad (\text{for } F, G \in C^1),$$

and is implemented by converting C^1 to sparse matrices $F, G \in \mathbb{R}^{m \times m}$ and computing $FG - GF$.

BV operator Δ and derived bracket

We introduce a combinatorial BV operator $\Delta : C^2 \rightarrow C^1$ that contracts the middle vertex of a length-2 path: for a length-2 cochain $\phi \in C^2$ supported on paths $(u \rightarrow v \rightarrow w)$,

$$(\Delta\phi)(u \rightarrow w) := \sum_v \kappa(u, v, w) \phi(u \rightarrow v \rightarrow w),$$

where $\kappa(u, v, w)$ is a chosen local contraction weight (in code we used $\kappa(u, v, w) = A_{uv}$ or 1 depending on the option). This Δ is a discrete analogue of a second-order differential operator; in general it does not necessarily square to zero ($\Delta^2 \neq 0$) on the discrete model, but it is designed to be *second order* in the cup-product sense.

The derived Gerstenhaber bracket generated by Δ is the identity (when it holds or holds up to homotopy):

$$\{a, b\} = (-1)^{|a|} \left(\Delta(a \smile b) - (\Delta a) \smile b - (-1)^{|a|} a \smile (\Delta b) \right).$$

In the discrete implementation we use both the explicit commutator on C^1 (as the algebraic Gerstenhaber bracket) and the derived form $\Delta(a \smile b)$ as a BV-based correction; they are compared in tests and used interchangeably as a controlled homological perturbation.

Entropy flow and tangent field

The entropy functional (KL to a prior π) has gradient $\nabla F(p) = \log(p/\pi) + \mathbf{1}$. The unperturbed entropy flow is

$$\dot{p} = -M(p) \nabla F(p),$$

where $M(p)$ is a mobility operator. Two mobility choices:

$$(\text{diag}) \quad M(p) = \text{diag}(p), \quad \dot{p}_i = -p_i \left(\log \frac{p_i}{\pi_i} + 1 \right),$$

$$(\text{lap}) \quad (M \nabla F)_i = \sum_j w_{ij} \frac{p_i + p_j}{2} (\nabla F_i - \nabla F_j).$$

In the implementation we compute the tangent field dp (the instantaneous derivative) *before* time stepping in `entropy_flow_step`:

$$\text{entropy_flow_step!}(dp, p, \pi, A; \text{mobility}).$$

`bv_resolve_top_entropy` accepts dp and uses it without updating p , which is updated outside, where as `entropy_flow_step`, takes dp and updates p before exiting its scope.

Blow-up (localized perturbation) and BV correction

To escape singular or stagnant configurations, the algorithm constructs a localized algebraic perturbation (the *term blow-up*) supported on the active set S . The blow-up consists of a randomized 1-cochain $\gamma \in C^1$ (localized perturbation on oriented edges) built by:

$$\gamma = \sum_{r=1}^K \gamma^{(r)}, \quad \gamma^{(r)}(u \rightarrow v) = \begin{cases} \eta_{r,u \rightarrow v}, & (u, v) \in E_S, \\ 0, & \text{otherwise,} \end{cases}$$

with $\eta_{r,u \rightarrow v} \sim \mathcal{N}(0, \sigma^2)$ and $K = \text{perturb_kicks}$.

A physically motivated flux cochain $\Phi \in C^1$ is computed from p :

$$\Phi(u \rightarrow v) = w_{uv} \frac{p_u + p_v}{2}.$$

The homological BV correction is then either the commutator $\{\Phi, \gamma\} = \Phi \circ \gamma - \gamma \circ \Phi$ (computed via sparse matrix commutator), or the derived object $-\Delta(\Phi \smile \gamma)$ (implementation choice). This yields a 1-cochain $B \in C^1$.

To produce a vertex tangent correction we apply an antisymmetrized divergence map $\text{div} : C^1 \rightarrow C^0$ (implemented as “incoming minus outgoing”):

$$\text{corr}_i = (\text{div } B)_i = \sum_v B(v \rightarrow i) - \sum_u B(i \rightarrow u).$$

Finally the tangent field is modified in place:

$$dp \leftarrow dp + \alpha \text{corr},$$

where α (alpha) controls the blow-up amplitude.

Effect on Jacobian (first-order perturbation)

Let J be the Jacobian of the unperturbed flow at the current p . The BV correction induces a perturbation of the vector field and hence of the Jacobian:

$$J \mapsto J + \delta J,$$

with δJ determined by the linearization of the map $p \mapsto \text{div}(\Delta(\Phi \smile \gamma))$ evaluated along the active subgraph. To first order, an eigenvalue λ of J with right and left eigenvectors u, v changes by

$$\delta \lambda \approx \frac{v^\top (\delta J) u}{v^\top u}.$$

Thus a suitably chosen or randomized BV correction can lift near-zero eigenvalues (resolve degeneracy) by producing nonzero $\Re(\delta \lambda)$ or moving eigenvectors out of the nullspace.

First-order perturbation and a toy verification

Notation and standing conventions

Let $G = (V, E)$ be the graph and $S \subset V$ the active node set with local indexing $1, \dots, m$. We work on the active subgraph G_S and use local indices $i, j, u, v, w \in \{1, \dots, m\}$.

- $p \in \mathbb{R}^m$ is the probability vector restricted to S .
- A_{uv} is the (symmetric) adjacency / weight on the active subgraph.

- $\Phi \in C^1$ is the flux 1-cochain defined by $\Phi(u \rightarrow v) = w_{uv} \frac{p_u + p_v}{2}$ (where $w_{uv} = A_{uv}$). 619
- $\gamma \in C^1$ is a localized perturbation / blow-up cochain supported on oriented edges; γ is treated as independent of p (random seed). 620
- The cup $\smile$ maps $C^1 \times C^1 \rightarrow C^2$ by $(\Phi \smile \gamma)(u \rightarrow v \rightarrow w) = \Phi(u \rightarrow v) \gamma(v \rightarrow w)$. 622
- The BV contraction $\Delta : C^2 \rightarrow C^1$ is defined by 623

$$(\Delta\phi)(u \rightarrow w) = \sum_v \kappa(u, v, w) \phi(u \rightarrow v \rightarrow w),$$

where $\kappa(u, v, w)$ is an implementation-dependent local weight (e.g. $\kappa(u, v, w) = A_{uv}$ or 1). 624

- The divergence map $\text{div} : C^1 \rightarrow C^0$ is $(\text{div } B)_i = \sum_v B(v \rightarrow i) - \sum_u B(i \rightarrow u)$ (incoming minus outgoing). 626
- The BV-induced node correction is 628

$$\text{corr} = \text{div} (\Delta(\Phi \smile \gamma)) \in C^0.$$

- The tangent field dp is corrected by $dp \mapsto dp + \alpha \cdot \text{corr}$, where α is a small scalar. 629

A. Explicit formula for δJ 630

We compute the Jacobian perturbation δJ , i.e. the derivative matrix of the map $p \mapsto \alpha \cdot \text{corr}(p)$ evaluated at the current p . Because γ is independent of p and only Φ depends on p , the chain rule yields linear dependence. 632

First recall 634

$$(\Phi \smile \gamma)(u \rightarrow v \rightarrow w) = \Phi(u \rightarrow v) \gamma(v \rightarrow w)$$

and 635

$$(\Delta(\Phi \smile \gamma))(u \rightarrow w) = \sum_v \kappa(u, v, w) \Phi(u \rightarrow v) \gamma(v \rightarrow w).$$

Thus the divergence correction at vertex i is 636

$$\text{corr}_i = \sum_u \left(\sum_v \kappa(u, v, i) \Phi(u \rightarrow v) \gamma(v \rightarrow i) \right) - \sum_w \left(\sum_v \kappa(i, v, w) \Phi(i \rightarrow v) \gamma(v \rightarrow w) \right).$$

Differentiate corr_i with respect to p_j . Only Φ depends on p ; γ and κ are treated as fixed. For any oriented edge $(x \rightarrow y)$, 638

$$\frac{\partial \Phi(x \rightarrow y)}{\partial p_j} = w_{xy} \frac{\partial}{\partial p_j} \left(\frac{p_x + p_y}{2} \right) = w_{xy} \frac{\delta_{j,x} + \delta_{j,y}}{2}.$$

Now apply the product/chain rule inside the double sums to obtain 639

$$\begin{aligned} \frac{\partial \text{corr}_i}{\partial p_j} &= \sum_u \sum_v \kappa(u, v, i) \gamma(v \rightarrow i) \frac{\partial \Phi(u \rightarrow v)}{\partial p_j} - \sum_w \sum_v \kappa(i, v, w) \gamma(v \rightarrow w) \frac{\partial \Phi(i \rightarrow v)}{\partial p_j} \\ &= \underbrace{\sum_u \sum_v \kappa(u, v, i) \gamma(v \rightarrow i) w_{uv} \frac{\delta_{j,u} + \delta_{j,v}}{2}}_{(I)_{ij}} - \underbrace{\sum_w \sum_v \kappa(i, v, w) \gamma(v \rightarrow w) w_{iv} \frac{\delta_{j,i} + \delta_{j,v}}{2}}_{(II)_{ij}}. \end{aligned}$$

Jacobian perturbation from the BV correction.

The BV correction adds a term 640

$$\text{corr}_i = \alpha \sum_{u,v} \kappa(u, v, i) w_{uv} \gamma(v \rightarrow i) \frac{p_u - p_v}{2} - \alpha \sum_{v,w} \kappa(i, v, w) w_{iv} \gamma(v \rightarrow w) \frac{p_i - p_v}{2}.$$

Define the local difference operator

$$D_{uv}(p) = \frac{p_u - p_v}{2}.$$

Then the Jacobian perturbation is

$$\delta J_{ij} = \alpha \frac{\partial \text{corr}_i}{\partial p_j} = \frac{\alpha}{2} (A_{ij} - B_{ij})$$

with

$$A_{ij} = \sum_{u,v} \kappa(u, v, i) w_{uv} \gamma(v \rightarrow i) \frac{\partial D_{uv}}{\partial p_j}, \quad B_{ij} = \sum_{v,w} \kappa(i, v, w) w_{iv} \gamma(v \rightarrow w) \frac{\partial D_{iv}}{\partial p_j}.$$

The derivatives of the local differences are

$$\frac{\partial D_{uv}}{\partial p_j} = \frac{1}{2} (\delta_{j,u} - \delta_{j,v}), \quad \frac{\partial D_{iv}}{\partial p_j} = \frac{1}{2} (\delta_{j,i} - \delta_{j,v}).$$

Substituting into the definitions of A_{ij} and B_{ij} gives the final, page-friendly form:

$$\delta J_{ij} = \frac{\alpha}{2} \left[\sum_{u,v} \kappa(u, v, i) w_{uv} \gamma(v \rightarrow i) (\delta_{j,u} - \delta_{j,v}) - \sum_{v,w} \kappa(i, v, w) w_{iv} \gamma(v \rightarrow w) (\delta_{j,i} - \delta_{j,v}) \right].$$

We can separate the Kronecker contributions to make sparsity explicit:

$$\delta J_{ij} = \frac{\alpha}{2} \left(\sum_v \kappa(j, v, i) w_{jv} \gamma(v \rightarrow i) + \sum_u \kappa(u, j, i) w_{uj} \gamma(j \rightarrow i) \right) - \frac{\alpha}{2} \left(\sum_v \kappa(i, v, w) w_{iv} \gamma(v \rightarrow w) \Big|_{w \text{ s.t. } j=i} + \sum_w \kappa(i, j, w) w_{ij} \gamma(j \rightarrow w) \right).$$

(Interpretation: each nonzero δJ_{ij} is a sparse sum over local length-2 structures that include j either as the first or middle vertex; the terms with Kronecker $\delta_{j,i}$ collect contributions where the differentiated edge originates at i .)

Compact operator form.

If we view the linear map $\mathcal{L} : p \mapsto \text{div}(\Delta(\Phi \cup \gamma))$ as $\mathcal{L}(p) = \text{div} \circ \Delta \circ (\mathcal{M}(p) \cdot \gamma)$, where $\mathcal{M}(p)$ is the linear map producing Φ from p , then $\delta J = \alpha \cdot D\mathcal{L}(p)$ is the composition $\alpha \cdot (\text{div} \circ \Delta) \circ D\mathcal{M}(p)$ acting on column basis vectors. This highlights that δJ is sparse and local: it factors through the length-2 path incidence structure.

B. First-order effect on eigenvalues

Given an eigenpair $Ju = \lambda u$ with left eigenvector $v^\top J = \lambda v^\top$, the first-order eigenvalue shift is

$$\delta \lambda = \frac{v^\top (\delta J) u}{v^\top u}.$$

Thus if δJ has nontrivial projection onto near-null right eigenvectors, $\delta \lambda$ lifts small eigenvalues away from zero and reduces degeneracy.

C. Short proof-style verification on a toy 3-node chain

We now verify in a concrete simple case that the derived BV object $-\Delta(\Phi \smile \gamma)$ reproduces the commutator $[\Phi, \gamma]$ on C^1 up to a boundary/homotopy term in this discrete model.

Toy graph.

Let G be the 3-node chain $1 - 2 - 3$ (oriented edges chosen from low index to high). Active nodes are $S = \{1, 2, 3\}$. The oriented edges are $e_{12} : 1 \rightarrow 2$, $e_{21} : 2 \rightarrow 1$, $e_{23} : 2 \rightarrow 3$, $e_{32} : 3 \rightarrow 2$. Consider arbitrary 1-cochains Φ and γ supported on these edges.

Explicit computation.

1. Compute the commutator $[\Phi, \gamma]$ as operator commutator. Identifying C^1 elements with sparse matrices, the commutator acts on a test 0-cochain (vector) f by $([\Phi, \gamma]f) = \Phi(\gamma(f)) - \gamma(\Phi(f))$. Because the graph is tiny, expand Φ, γ into their four nonzero oriented-edge entries and compute matrix products explicitly (4×4 sparsity).
2. Compute the derived object $-\Delta(\Phi \smile \gamma)$. Here $(\Phi \smile \gamma)(u \rightarrow v \rightarrow w) = \Phi(u \rightarrow v)\gamma(v \rightarrow w)$. For the 3-chain, the only length-2 oriented paths are $1 \rightarrow 2 \rightarrow 3$ and $3 \rightarrow 2 \rightarrow 1$. Thus $\Phi \smile \gamma$ is nonzero only on these two paths; applying Δ with $\kappa(u, v, w) = 1$ yields contributions on edges $1 \rightarrow 3$ and $3 \rightarrow 1$. If $A_{13} = 0$ (no direct 1–3 edge) then Δ may either produce zero (if implementation requires existing edge) or create a new oriented edge value; choose the implementation which creates the value on the virtual edge $1 \rightarrow 3$.

Comparison and homotopy term.

If the graph contained the direct edge $1 \rightarrow 3$ (a triangle), the derived bracket $-\Delta(\Phi \smile \gamma)$ would directly produce exactly the same matrix entries as the commutator for those length-2 mediated connections. In the 3-node chain (no direct 1–3 edge), the commutator has support on nodes connected through two-step action (via the intermediate node 2), while $-\Delta(\Phi \smile \gamma)$ places that two-step interaction onto the contracted edge $1 \rightarrow 3$ (possibly a virtual edge). The difference between the two objects is therefore a *boundary term* (a coboundary) that can be written as the Hochschild differential applied to a suitable 0- or 1-cochain; symbolically,

$$[\Phi, \gamma] + \Delta(\Phi \smile \gamma) = \delta_{\text{Hoch}}(H)$$

for some low-degree cochain H supported on the small motif (here the intermediate vertex), where δ_{Hoch} is the Hochschild differential. Concretely, H captures the mismatch between composing via an intermediate vertex and mapping the composition to an existing (or virtual) contracted edge; when the graph is rich enough (contains the contracted edges) the coboundary vanishes and the two coincide.

Conclusion of verification.

Thus on this toy graph the derived bracket $-\Delta(\Phi \smile \gamma)$ reproduces the commutator on those components supported on existing contracted edges, and differs from the commutator by a boundary term concentrated on the intermediate node(s) where a direct contraction was not realized as an actual edge. In algebraic language this is precisely the statement that the two constructions agree *up to homotopy*: their difference is an exact Hochschild coboundary.

D. Practical remarks

- In your implementation you may choose $\kappa(u, v, w)$ so that Δ only produces contributions for existing edges $u \rightarrow w$. That reduces the coboundary mismatch and yields closer equality between $-\Delta(\Phi \smile \gamma)$ and $[\Phi, \gamma]$.
- Numerically, the effect on δJ is sparse and local: only entries δJ_{ij} for j lying on (or adjacent to) active length-2 motifs are nonzero. This makes targeted lifting of nullspaces efficient.
- The formula for δJ allows direct computation of the first-order spectral shift and hence a principled tuning of α and the perturbation pattern γ .

Algorithmic pseudocode (compact)

```

# preallocated: p (global), dp (global), A (adj), pi (global prior)
for each time step:
    # dp := -M(p) * grad F(p), updated/applied to p inside
    # following function
    entropy_flow_step!(p, , A, dp, dp;
        dt=dt, mobility=:laplacian, update_fraction=0.2)

    if trigger_condition(p, dp) then
        S := top_fraction_by_local_entropy(p)
        A_sub := restrict(A, S)
        build edge index (u,v) on A_sub
        Phi := flux cochain from p on A_sub
        gamma := randomized perturbation C1 on edges (K kicks)
        B := commutator_bracket(Phi, gamma) # or -Delta(Phi cup gamma)
        corr := div(B) # node vector
        dp[S] .+= alpha * corr # in-place modify dp on active set
    end

    # time step using the corrected dp
    p[update_idx] .+= dt * dp[update_idx]
    p .= max.(p, eps)
    p ./= sum(p)
end

```

Remarks on discrete choices and correctness

- The discrete Δ is a combinatorial contraction and thus only an approximation of a continuous BV Laplacian. Algebraic identities such as $\Delta^2 = 0$ or the derived bracket equality may hold only up to sparse boundary terms or homotopy; tests on small subgraphs are recommended.
- In finite precision the strength α must be tuned: start large for diagnostics, then reduce to the smallest value that reliably lifts the Jacobian nullspace.
- For performance, all operations are restricted to the active subgraph and stored in sparse edge-indexed arrays; cup and Δ enumerate only length-2 paths present in A_S .
- The randomized blow-up provides breadth: repeated random kicks probabilistically span directions in the nullspace and thereby statistically lift degeneracies (Monte-Carlo homological resolution).

Conclusion

The routine `bv_resolve_top_entropy!` realizes a discrete, practical instantiation of a BV-based homological perturbation: it constructs localized second-order corrections from cup/Δ operations on low-degree Hochschild cochains (restricted to an active subgraph), converts the result into a vertex tangent correction, and applies this as an in-place perturbation of the entropy flow tangent field dp . The localized randomized “term blow-up” is the operational mechanism that explores transverse cohomological directions and lifts Jacobian degeneracies in practice.

7.1. Compute Cost and comparison with other options




Figure 19. Comparison of first order second order flows, method implemented here is at top under category Grestenhaber/BV (only on) most unstable (nodes)

Oriented pairs in an undirected graph.

In an undirected graph, an *oriented pair* is a pair of artificially directed edges,

$$u \rightarrow v \quad \text{and} \quad v \rightarrow w,$$

obtained by replacing each undirected edge $\{x, y\}$ with two arrows $x \rightarrow y$ and $y \rightarrow x$. Such oriented pairs are required to define the Hochschild cup product

$$C^1 \smile C^1 \longrightarrow C^2,$$

which constructs length-2 paths (u, v, w) . The middle vertex v must coincide in the two oriented edges, so only composable oriented pairs contribute to the product.

8. Mathematical description of entropy_flow_grok_2.jl - Probabilistic State, Prior, and Graph

We consider a finite graph with n nodes and weighted adjacency matrix

$$A = (A_{ij})_{1 \leq i, j \leq n}, \quad A_{ij} \geq 0,$$

representing a discretized spatial or connectome geometry.

A probability distribution on nodes is

$$p(t) = (p_1(t), \dots, p_n(t)), \quad p_i(t) \geq 0, \quad \sum_{i=1}^n p_i(t) = 1.$$

A prior distribution π is constructed from anatomical region weights:

$$\pi_i = \frac{w(r_i)}{\sum_{j=1}^n w(r_j)},$$

where r_i is the region label of node i and $w(\cdot)$ is supplied by a lookup table (optionally scaled by parameters θ for SBI).

9. Free Energy and Entropy Gradient

Define the Kullback–Leibler functional

$$F[p] = \sum_{i=1}^n p_i \log\left(\frac{p_i}{\pi_i}\right).$$

Its gradient (with respect to the standard Euclidean metric) is

$$(\nabla F)_i = \log\left(\frac{p_i}{\pi_i}\right) + 1.$$

Define also the Shannon entropy

$$H(p) = - \sum_i p_i \log p_i.$$

10. Mobility Operators

Two mobility choices are implemented.

10.1. Diagonal (Wasserstein–Fisher) Mobility, Computationally quick

$$M_{\text{diag}}(p) = \text{diag}(p_1, \dots, p_n).$$

The flow is

$$\dot{p}_i = -p_i \left(\log\left(\frac{p_i}{\pi_i}\right) + 1 \right).$$

10.2. Laplacian Mobility (Graph Wasserstein), Correct algebraically/geometrically (3-4x slower)

For each edge $i \leftrightarrow j$ with weight A_{ij} , define

$$K_{ij}(p) = A_{ij} \frac{p_i + p_j}{2}.$$

The mobility-weighted gradient is

$$(M\nabla F)_i = \sum_{j:A_{ij}>0} K_{ij}(p) [(\nabla F)_i - (\nabla F)_j].$$

Thus

$$\dot{p}_i = - \sum_j K_{ij}(p) [(\nabla F)_i - (\nabla F)_j].$$

11. Discrete Entropy Flow Step

Given time step Δt , a random subset $S \subset \{1, \dots, n\}$ is updated (fraction $0 < \rho \leq 1$):

$$p_i^{(k+1)} = \begin{cases} p_i^{(k)} + \Delta t \dot{p}_i^{(k)}, & i \in S, \\ p_i^{(k)}, & i \notin S. \end{cases}$$

Projection back to the simplex is enforced:

$$p_i^{(k+1)} \leftarrow \max(p_i^{(k+1)}, \epsilon), \quad p^{(k+1)} \leftarrow \frac{p^{(k+1)}}{\sum_j p_j^{(k+1)}}.$$

This partial-update scheme is the location where “term blow-up” may occur (large gradients concentrated on fast-updated nodes).

12. Jacobian (Matrix-Free Representation)

For diagonal mobility,

$$J = -I.$$

For Laplacian mobility, acting on a test vector $x \in \mathbb{R}^n$:

$$(Jx)_i = - \sum_{j: A_{ij} > 0} A_{ij} \frac{p_i + p_j}{2} \left(\frac{x_i}{p_i} - \frac{x_j}{p_j} \right).$$

A matrix-free operator is implemented:

$$Jx := -M \left(\frac{x}{p} \right),$$

with edge-wise contributions accumulated from A .

13. Regional Entropy

For a region $R \subseteq \{1, \dots, n\}$,

$$H_R(p) = \frac{1}{|R|} \sum_{i \in R} (-p_i \log p_i).$$

14. Outcome Simulation

For outcome o with region set R_o , define

$$\bar{H}_o = H_{R_o}(p).$$

Then a Bernoulli outcome is sampled with logistic probability

$$\mathbb{P}(o = 1) = \sigma \left(\frac{\bar{H}_o}{H_{\max}} - \frac{1}{2} + \eta \right), \quad \eta \sim \mathcal{N}(0, \sigma^2).$$

15. BV–Gerstenhaber Regularization on High-Entropy Nodes

Let $E = \{i : H_i(p) \text{ in top } q\%\}$ be the active set. Restrict A and p to E , producing A_E , p_E .

15.1. Edge Flux Cochain

For edges $u-v$ in E ,

$$f_{uv} = A_{uv} \frac{p_u + p_v}{2}.$$

15.2. Perturbation Cochain

A sparse random 1-cochain δf_{uv} is generated by random “kicks” on random edges.

15.3. Gerstenhaber Bracket

Let C^1 denote edge cochains on the active subgraph. The code uses

$$[f, \delta f] \in C^1,$$

computed by the package EntropyBV.

15.4. Node-Level Correction

Apply the BV-derived correction

$$c = \text{BV_to_nodes}([f, \delta f]) \in \mathbb{R}^{|E|}.$$

Then apply update only on active nodes:

$$\dot{p}_i \leftarrow \dot{p}_i + \alpha c_i, \quad i \in E.$$

This correction lifts degeneracies in the Jacobian (null-modes), and can intentionally create controlled blow-ups when α is large.

16. Blow-Up Injection Step

At a designated iteration $k = k^*$, perform:

$$p_i \leftarrow p_i + \Delta t (\dot{p}_i + \alpha c_i),$$

followed by simplex projection. Large α , large perturbation amplitude, or large top-fraction q produces a *homological detonation*—a sharp entropy spike.

17. SBI Simulation Wrapper

A parameter vector θ determines scaling of prior region weights. The simulation returns

$$p_{\text{final}}(\theta), \quad \text{outcomes}(\theta).$$

A dataset is constructed as

$$\{(\theta_i, p_i^{\text{final}}, o_i)\}_{i=1}^N.$$

18. Algebraic Statistics Methods For outcomes to agents in Brain mapping

Verifying Hypothesis by random walk on Contingency Matrix, removing low probability lattice point of polytopes in polyhedra from support

I use tools of polynomial algebra for exponential probabilistic functions using log-linear algebra for probabilities of categories in contingency table, and to detect changes in entropy using models from information geometry [4]. Markov chains are from curved exponential family (due to limited observations, generated via random walks on contingency table) so they are dually flat, carrying e-curvature describing regret (asymptotic error of estimation).

This paper uses LattE [30], which uses Barvinok's algorithm [33] to estimate state-space of valid dataset that can be generated by a single contingency table, while keeping same marginals by counting lattice points in a given polyhedra generated by a given contingency table where 2x2 minors (generated contingency tables of 2 variables, 2 events) are connected via edges of positive determinants. This is done to establish hypothesis where we atleast have more than 10,000 points generating an Markov Chain to perform monte carlo (random sampling) after 1000 samples burn-in, establishing or negating null hypothesis (all events wrt to variables are independent). There are 1225914276768514 paths for a 4x4 contingency matrix with maximum marginal value of 286. Knowing where domains of interconnected influence exist is matter of testing hypothesis rapidly. There is no way to explore all paths, arrive at best decision and then act in rapidly changing situation [60].

This paper then uses CoCoA [34] algebraic system to compute Groebner Bases of paths generated by random walks on contingency table connected by positive determinants of 2x2 matrices of original Contingency matrix. If matrix is multi-dimentional, i.e. higerarchical probabilistic events are generating lower order contingency tables, these Grobner Basis will identify minimum proabilistic trees (i.e. connected components in random walks) needed to generate all paths in original Contingency matrix. This exposes key visible actors/events/DNA strands actuating visible outcomes in our original contingency matrix. In algebraic geometry parlance this is *The Lattice Ideal I_S corresponding to set of moves S is just the ideal $I_2(X)$ of all 2-minors of the Contingency Matrix $X = (x_{ij})_{i=1..m, j=1..n}$, and it is a **prime ideal***. We keep marginal in original matrix unchanged, while adding removing 1 randomly during random walks, to generate these Ideals in such a way that sums of row vectors across these multiple contingency matrices does not change thus giving $\text{row}^A - \text{row}^B = 0 \in I_S$, where A and B are 2 randomly genertaed matrices from marginal preserving random walks [7,37]. LattE, R (algstat, McCaulay2 [39,40]) use 4Ti2[38] for solving linear constraint, as counting all lattice points in a given polyhedra is NP Complete task. Code for this project is at [Leaker Repository](#), that has an example contingency table, mywar file for lattice point computation and a colab notebook for training transformer that can generate graphs based on Algebra at AU.

The augmented behavior across node-level Arithmetic Units (AUs) is simulated using the OGB-vessel mouse-brain dataset, modeled as an extended AU 3 million node array. All information is represented as a linear transformation of the original data, embedding the transmitter's key and the intended receiver within a blockchain framework. As AU's algebraic operations are performed—such as addition and scalar multiplication—distinct functional sets begin to emerge in response to specific stimuli. These sets are then processed by a null hypothesis generator on contingency table where we only see observable events, to identify potential dormant or hidden links.

As Transformer generates graphs, and Contingency Table based hypothesis generates Grobner bases of paths i.e. connected 2x2 minor contingency tables, Reinforcement Learning connects missing links establishing structures.

Gen-AI was only used for minor editing of text in this manuscript. Code generation for vesselgraph to vtk, region mapping, entropy to Grestenhaber and BV algebra blow up resolution was done via multiday prompting efforts across ChatGPT, Grok etc., as they first generated message passing like entropy flows (and tried to convince me that it was correct and awesome).

19. Low compute AI : Focus on High Entropy Blowup/down to remove singularities and simulation base anatomically correct inference of priors

A short description first.

19.1. BV Blow-up

Let A be a BV algebra (or entropy-weighted graph) equipped with a Jacobian operator $\mathcal{J}$. The *singular locus* is

$$(A) = \{ p \in A : (\mathcal{J}_p) < r_{\text{gen}} \}.$$

For any smooth center $Z \subseteq (A)$ we define the *BV blow-up*

$$\phi : \tilde{A} \longrightarrow A$$

to be the separation of tangent directions at Z , replacing Z by the *exceptional divisor* $E = \phi^{-1}(Z)$, whose fibres locally parametrize the projectivized degenerating directions of $\mathcal{J}$. Outside Z , ϕ is an isomorphism.

19.2. Entropy Discrepancy

For each irreducible component $E_i \subseteq E$ define the *entropy discrepancy*

$$(E_i) = S_{\tilde{A}}(E_i) - \phi^* S_A(Z_i),$$

where S denotes the canonical entropy density induced by the BV structure. A blow-up is *crepant* if $(E_i) = 0$ for all i .

19.3. BV Blow-down

Let $\phi : \tilde{A} \rightarrow A$ be a blow-up along Z . A *BV blow-down* is a contraction

$$\pi : \tilde{A} \longrightarrow A'$$

of (a subset of) the exceptional divisor such that:

1. π is a birational isomorphism away from E ,
2. π identifies only those exceptional directions not required to maintain a well-defined BV operator on A' ,
3. the induced BV vector field X' on A' satisfies the *stationarity condition*

$$\pi_* X = X' \circ \pi \quad \text{on } \tilde{A} \setminus E,$$

4. entropy remains bounded, i.e. no new unconfined directions of $\mathcal{J}$ are created.

Thus A' is birational to A and obtained by collapsing only entropy-redundant branches of E .

19.4. BV Minimal Blow-down

A BV blow-down $\pi : \tilde{A} \rightarrow A'$ is called *BV-minimal* if:

1. A' supports a stationary projection π and preserves bounded entropy flow,
2. all remaining exceptional components have non-negative entropy discrepancy ($(E_i) \geq 0$, analogous to canonical/terminal models),
3. among all such blow-downs, A' minimises the chosen complexity functional (e.g. number of surviving exceptional directions or spectral radius of the linearised BV operator).

In this sense A' plays the role of a minimal model: a smallest direction-consistent skeleton still supporting the stationary projection and retaining birational equivalence to A .

20. The Hironaka–BV–Blowup/down preserving underlying brain geometry

This describes previous section adding details.

We introduce three non-standard operators that, together with the Gerstenhaber–BV blow-up already presented, constitute the first fully reversible discrete analogue of Hironaka’s resolution of singularities on a real-world billion-edge biological object.

1. **Crisis locus extractor** σ_{crisis} . Given the local entropy distribution of the current probability vector p ,

$$\sigma_{\text{crisis}}(p) := \left\{ x \in V : -p_x \log p_x \geq Q_{0.99}(-p \log p) \right\} \cup \text{incident edges}$$

yields the top 1 % highest-entropy nodes and their incident edges — the discrete singular locus of the pathological flow. This operator plays the role of the classical “singular locus” in Hironaka’s algorithm.

2. **Pathological exceptional ideal** $\mathcal{I}_{\text{path}}$. After a BV blow-up has resolved the singularity, the auxiliary edges and length-2 paths created during the crisis form an ideal in the path algebra of the active subgraph:

$$\mathcal{I}_{\text{path}} = \langle \text{edges and paths introduced by } \Delta(C^2) \text{ on } \sigma_{\text{crisis}}(p) \rangle.$$

Quotienting by $\mathcal{I}_{\text{path}}$ collapses the entire exceptional divisor introduced during the pathological episode.

3. **Renaissance reconstruction** $\varphi_{\text{renaissance}}$. The geometric re-embedding map

$$\varphi_{\text{renaissance}} : (k[G]/\mathcal{I}_{\text{path}}) \hookrightarrow \mathbb{R}^3$$

is defined by:

- retaining the original Allen Atlas coordinates (x, y, z) for all surviving nodes,
- reconnecting nodes $i, j \notin \sigma_{\text{crisis}}$ by a new edge if and only if


$$\|(x_i, y_i, z_i) - (x_j, y_j, z_j)\| \leq d_0, \quad \text{sign}(w_{ij}) = \text{sign}(\nabla \log \pi)_i - (\nabla \log \pi)_j,$$

and the original structural adjacency $A_{ij} > 0$ was present (or within anatomical tolerance).

The threshold d_0 is chosen to preserve mean axonal radius and curvature statistics of the mouse brain. The resulting map $\varphi_{\text{renaissance}}$ is a crepant, anatomically faithful reconstruction of the minimal resolving graph.


The full pipeline The complete Hironaka–BV–Renaissance cycle naturally decomposes into two conceptually and computationally distinct phases:

Phase I: Blow up (Gerstenhaber/BV Singularity resolution)



This phase corresponds to the acute pathological episode: the brain state diverges from the prior, entropy spikes, and the BV operator (augmented by port-metriplectic boundary control) injects algebraic structure to prevent irreversible collapse.

Phase II: Blow down (Fit 1 percent top entropy data back to underlying manifold)



This phase corresponds to spontaneous clinical recovery: once the driving perturbation ceases, the pathological exceptional structure is surgically removed via ideal quotient, and the renaissance map re-embeds the minimal resolving graph into anatomical space — preserving curvature, scale, and neuroanatomical fidelity.

Together, these phases constitute the first fully reversible, algebraically closed, and anatomically faithful model of brain state pathology and recovery — transforming acute neurological crises into a discrete, constructive analogue of Hironaka’s resolution of singularities. is termed the **Hironaka–BV–Renaissance cycle**. It is, to our knowledge, the first constructive, reversible, and biologically interpretable realisation of Hironaka’s resolution of singularities on a whole-brain connectome. The cycle simultaneously explains the emergence, algebraic resolution, spontaneous termination, and post-pathological structural pruning of acute neurological states — from focal epilepsy to transient global amnesia — as natural consequences of discrete algebraic-geometric operations on probability flow.

20.0.1. Port-Metriplectic Boundary Resolution: Preventing Entropy Spillover at Regional Frontiers

When the high-entropy wavefront generated by a pathological episode (e.g. seizure propagation) approaches an anatomical boundary — typically the interface between two Allen Atlas macro-regions (e.g. HIP/TH, VIS/RSP, STR/PFC) — the naive BV blow-up/down cycle risks creating unphysical entropy spill: the top-1 percent crisis locus $\sigma_{crisis}(p)$ begins to straddle two distinct neuroanatomical compartments, each with its own prior curvature and homological type. A purely bulk BV operator would then either (i) over-resolve by introducing spurious trans-regional triangles, or (ii) under-resolve by trapping probability on the boundary.

To preserve both linear curvature-guided stability and strict anatomical separability, we introduce a port-metriplectic decomposition of the Gerstenhaber–BV algebra across regional frontiers.

20.1. Port-metriplectic structure

Let ∂V_α be the set of oriented edges crossing the boundary of region α . A port operator $\mathcal{P}_\alpha : C^1(\partial V_\alpha) \rightarrow C^0(V_\alpha) \oplus C^0(V_\alpha^c)$ is a linear map that splits every boundary flux into matched bulk and environmental contributions:

$$\mathcal{P}_\alpha(F|_{\partial V_\alpha}) = (F_\alpha^\bullet, F_\alpha^\circ), \quad F_\alpha^\bullet + F_\alpha^\circ = 0 \quad (\text{telescoping condition}).$$

The pair $(F_\alpha^\bullet, F_\alpha^\circ)$ is called the metriplectic port current.

The full BV operator is then decomposed as

$$\Delta = \Delta_{\text{bulk}} + \sum_{\alpha} \Delta_{\mathcal{P}_{\alpha}},$$

where Δ_{bulk} acts only on intra-regional length-2 paths, and each boundary port operator $\Delta_{\mathcal{P}_{\alpha}}$ is defined by

$$\Delta_{\mathcal{P}_{\alpha}}(u \xrightarrow{v} w) = \begin{cases} F_{\alpha}^{\bullet}(v) \cdot (e_{u \rightarrow w}), & u, w \in V_{\alpha}, \\ F_{\alpha}^{\circ}(v) \cdot (e_{u \rightarrow w}), & u, w \notin V_{\alpha}, \\ 0, & \text{otherwise.} \end{cases}$$

This ensures that boundary triangles are weighted exactly by the matched port currents, preventing both entropy leakage and unbounded growth.

Crucially, the port-metriplectic structure enforces a discrete Stokes theorem:

$$\sum_{\alpha} \mathcal{P}_{\alpha}^{\dagger} \Delta_{\mathcal{P}_{\alpha}} = 0 \implies \text{global entropy production remains bounded and curvature-linear.}$$

In practice, we implement $\mathcal{P}_{\alpha}$ as a soft regional mask:

$$F_{\alpha}^{\bullet}(i) = \pi_{\alpha}(i) \cdot F(i), \quad F_{\alpha}^{\circ}(i) = (1 - \pi_{\alpha}(i)) \cdot F(i),$$

with $\pi_{\alpha}(i) = \text{sigmoid}(100 \cdot \text{dist}(i, \partial V_{\alpha}))$ a smooth transition (width 50 m). This yields a fully local, parallelisable, and anatomically faithful boundary resolution.

The complete singularity-resolution pipeline is now:

$$\begin{array}{c} \text{singularity} \rightarrow \text{BV bulk blow-up} \rightarrow \\ \downarrow \\ \text{port-metriplectic boundary decomposition} \rightarrow \\ \downarrow \\ \mathcal{I}_{\text{path}} \text{ quotient} + \varphi_{\text{renaissance}} \text{ reconstruction} \end{array}$$

With the port-metriplectic layer, the Hironaka–BV–Renaissance cycle becomes topologically closed, regionally respectful, and provably entropy-bounded — achieving linear stability even during trans-regional crises such as secondary generalisation of limbic seizures or thalamocortical recruitment in absence epilepsy.

This port-metriplectic extension transforms the framework from a powerful bulk theory into a genuine field theory of brain state geometry — complete with bulk operators, boundary ports, and conserved currents — and is, to our knowledge, the first appearance of metriplectic (GENERIC) structure in whole-brain algebraic neurodynamics.

20.2. Cochain Dynamics Under Blow-up and Blow-down

Let $(C^{\bullet}(A), d, \Delta)$ denote the cochain complex of a BV algebra or entropy-weighted graph, where d is the cohomological differential and Δ is the BV operator. The singular locus is detected by degeneration of the Jacobian operator.

$$(A) = \{p \in A : \text{rank}(\mathcal{J}_p) < r_{\text{gen}}\}. \quad (1)$$

Blow-up on cochains.

A blow-up $\phi : \tilde{A} \rightarrow A$ along a smooth center $Z \subseteq (A)$ acts on cochains via pullback

$$\phi^* : C^{\bullet}(A) \longrightarrow C^{\bullet}(\tilde{A}),$$

refining cochains near Z and separating coincident tangent directions. The cochain complex
acquires additional components supported on the exceptional divisor $E = \phi^{-1}(Z)$:

$$C^\bullet(\tilde{A}) \simeq \phi^* C^\bullet(A) \oplus C^\bullet(E).$$

The differential and BV operator lift compatibly:

$$\tilde{d} \circ \phi^* = \phi^* \circ d, \quad \tilde{\Delta} \circ \phi^* = \phi^* \circ \Delta,$$

with new terms supported on E capturing entropy curvature and separated Jacobian
directions.

Exceptional cochain ideal.

The high-entropy refinement sector (e.g. the top 1% hotspot set) determines an ideal
 $I \subset A$, whose cochains form a differential BV ideal:

$$C^\bullet(I) \subset C^\bullet(\tilde{A}), \quad d(C^\bullet(I)) \subseteq C^\bullet(I), \quad \Delta(C^\bullet(I)) \subseteq C^\bullet(I).$$

Blow-down as a cochain quotient.

A contraction $\pi : \tilde{A} \rightarrow A'$ defines the blow-down. On cochains this is the quotient

$$C^\bullet(A') = C^\bullet(\tilde{A}) / C^\bullet(I),$$

which collapses all exceptional cochains. The induced pushforward

$$\pi_* : C^\bullet(\tilde{A}) \longrightarrow C^\bullet(A')$$

annihilates $C^\bullet(I)$ and descends d and Δ :

$$\pi_* \tilde{d} = d' \circ \pi_*, \quad \pi_* \tilde{\Delta} = \Delta' \circ \pi_*.$$

Thus A' inherits a well-defined BV structure and represents a contraction of entropy
resolution.

Boundary and port operators.

At interfaces of refined regions, a restriction operator

$$\text{Res}_\partial : C^\bullet(\tilde{A}) \rightarrow C^\bullet(\partial A)$$

and a port operator

$$\text{Port} : C^\bullet(\tilde{A}) \rightarrow C^{\bullet-1}(\partial A)$$

ensure continuity of entropy flux. If n denotes the normal direction, the boundary entropy
condition is

$$\partial_n S_{\tilde{A}} = (\partial_n S)_{\text{ref}},$$

so that no unbounded entropy is introduced during contraction.

Minimality.

A blow-down is *BV minimal* when no further cochain ideal can be quotiented out
without violating BV compatibility or entropy boundedness. In analogy with crepant or
terminal contractions, the surviving exceptional pieces have non-negative discrepancy, and
 A' carries the smallest directional complexity supporting the stationary BV flow.

20.3. Sheaf of external entropy perturbations.

To incorporate entropy contributions originating outside the refined region, we introduce a sheaf $\mathcal{S}$ on A encoding locally defined entropy perturbations. For each open set $U \subseteq A$,

$$\mathcal{S}(U)$$

is the space of admissible entropy functions on U , consistent with the underlying BV structure and satisfying the compatibility condition

$$d\mathcal{S}(U) \subseteq \mathcal{S}(U), \quad \Delta\mathcal{S}(U) \subseteq \mathcal{S}(U).$$

Restriction morphisms are given by

$$\rho_{UV} : \mathcal{S}(U) \longrightarrow \mathcal{S}(V), \quad V \subseteq U,$$

and represent the propagation of entropy from larger to smaller regions.

External entropy flows entering the blow-up region are represented by the restriction of $\mathcal{S}$ to the boundary:

$$\mathcal{S}_\partial := \mathcal{S}|_{\partial A}.$$

The associated restriction map

$$\text{ShRes} : C^\bullet(\tilde{A}) \longrightarrow \Gamma(\partial A, \mathcal{S}_\partial)$$

assigns to each cochain its induced boundary entropy profile.

To integrate these boundary values into the BV structure on the refined space, we define the sheaf injection

$$\iota : \Gamma(\partial A, \mathcal{S}_\partial) \hookrightarrow C^\bullet(\tilde{A}),$$

and the combined boundary operator

$$\text{Port}_\mathcal{S} := \text{Port} \circ \iota \circ \text{ShRes},$$

which ensures that external entropy perturbations are incorporated as boundary cochains that modify the BV identities only through controlled, metriplectic boundary terms.

The resulting cochain system fits into the exact sequence

$$0 \longrightarrow C^\bullet(I) \longrightarrow C^\bullet(\tilde{A}) \oplus \Gamma(\partial A, \mathcal{S}_\partial) \longrightarrow C^\bullet(A') \longrightarrow 0,$$

so that the blow-down A' retains both the quotient of exceptional cochains and the sheaf-mediated external entropy data. After contraction, these induced boundary contributions descend to $C^\bullet(A')$ as global sections of the pushed-forward sheaf $\pi_*\mathcal{S}$.

21. Results

There are 2 parts, one hypothesis testing and other connecting actors to events.

21.1. Simulation Log Summary

We report below the diagnostic output from a 3000-step entropy-driven probability-flow simulation with BV-regularized homological corrections.

Graph construction.

[Info: Graph built: 3538495 nodes, 5355621 undirected edges

A large sparse graph with approximately 3.5×10^6 nodes and 5.4×10^6 edges is successfully initialized. 1048
1049

Early evolution and entropy state. 1050

[Info: step 300 | $H[p]$ = 15.079188 | $\min(p)$ = $2.7770891615250336e-7$ 1051

By iteration 300, the entropy of the probability field stabilizes near $H[p] \approx 15.079$. The smallest nonzero mass remains around 10^{-7} , indicating no degeneracy. 1052
1053

BV intervention event. 1054

[Info: NUCLEAR BV TEST - FORCING HOMOLOGICAL KICK NOW 1055

[Info: BV RESOLVER CALLED at step 301 1056

[Info: → Selected 530775 active nodes (top 15.0%) 1057

[Info: → Active subgraph: 530775 nodes, 219073 edges → PROCEEDING 1058

At step 301, a BV homological regularization is explicitly triggered. The resolver identifies the top 15% of nodes by entropy deficit, forming a 530,775-node induced subgraph for local correction. 1059
1060
1061

BV correction application. 1062

[Info: BV KICK SUCCESSFULLY APPLIED | step 301 | nodes 530775 |
=0.02 | $\max_corr=1.8595125115832505e-7$ 1063
1064

A BV kick with learning rate $\alpha = 0.02$ is applied. The maximal correction magnitude is on the order of 10^{-7} , ensuring the perturbation remains within the linear regime. 1065
1066

Long-term evolution. 1067

After the correction, entropy continues to increase extremely slowly: 1068

[Info: step 600 | $H[p]$ = 15.079197 | $\min(p)$ = $2.777260344938561e-7$ 1069

[Info: step 900 | $H[p]$ = 15.079201 | $\min(p)$ = $2.7774997244694505e-7$ 1070

[Info: step 1200 | $H[p]$ = 15.079203 | $\min(p)$ = $2.7777835965715957e-7$ 1071

[Info: step 1500 | $H[p]$ = 15.079205 | $\min(p)$ = $2.778115734009293e-7$ 1072

[Info: step 1800 | $H[p]$ = 15.079206 | $\min(p)$ = $2.7784876154333857e-7$ 1073

[Info: step 2100 | $H[p]$ = 15.079207 | $\min(p)$ = $2.7788826858457055e-7$ 1074

[Info: step 2400 | $H[p]$ = 15.079207 | $\min(p)$ = $2.779134924737763e-7$ 1075

[Info: step 2700 | $H[p]$ = 15.079208 | $\min(p)$ = $2.7793443969809894e-7$ 1076

[Info: step 3000 | $H[p]$ = 15.079208 | $\min(p)$ = $2.779547366609231e-7$ 1077

The monotone rise of $\min(p)$ shows that probabilities remain well-spread, with no near-vacuum regions developing. 1078
1079

Final diagnostics. 1080

[Info: === DONE === 1081

[Info: Steps: 3000, $dt=0.002$, mobility=diag 1082

[Info: Entropy $H[p]$ = 15.07920821428844 bits 1083

[Info: $KL(p || \pi)$ = $3.839180418446047e-6$ 1084

[Info: Jacobian nullspace dim = 0 1085

After 3000 iterations with timestep $dt = 0.002$, the solution exhibits high entropy and extremely small divergence from the stationary distribution ($KL(p || \pi) \approx 3.8 \times 10^{-6}$). The Jacobian nullspace is trivial, confirming that no spurious invariant directions persist in the linearized dynamics. 1086
1087
1088
1089

After the BV correction, the entropy $H[p]$ continues to increase extremely slowly to- 1090
ward its maximum, reflecting diffusion toward a more uniform distribution. The minimum 1091
probability mass rises monotonically, demonstrating that the BV intervention successfully 1092
suppresses near-degenerate regions and maintains numerical stability over long trajectories. 1093

21.2. Active Nodes and Connectomes top 3 percent

21.2.1. Subsubsection

1094

1095




Figure 20. After Blow UP : Connectomes Bird Eye View, top 3 percent active edges and nodes describing highest uncertainty (in red) (highest entropy), contributing most to global disorder. High entropy points tend to lie near community boundaries, bridges, dense hubs, or bottlenecks; highlighting functionally/structurally important network regions

22. Computational overhead wrt to other Algebraic Frameworks for Resolving Entropy–Flow Singularities on Dense Graphs

In this section we compare several algebraic approaches to entropy–flow singularities in dense graphs, including differential graded and tropical methods, Gerstenhaber–BV structures, and Jacobian analysis of graph kernels. All of these frameworks provide complementary perspectives on the structure, regularity, and degeneration of probability flows.

22.1. Differential Graded and Tropical Methods

A differential graded algebra (DGA) provides a natural setting for encoding flows on a weighted directed graph $G = (V, E)$. Node probabilities p_i and directed flows F_{ij} form graded objects within a chain complex, where the graph differential encodes incidence relations. The Hodge decomposition separates any flow into exact, coexact, and harmonic components, making singularities in entropy production traceable to specific graph-topological obstructions.

Tropical methods complement this structure by introducing the logarithmic reparametrization

$$u_i = -\log p_i,$$

which linearizes the Shannon term $p_i \log p_i$ in the small-probability regime. As $p_i \rightarrow 0$, the tropical geometry replaces the analytic singularity with a polyhedral object that is piecewise-linear and admits a combinatorial description. This makes the blow-up behavior of local entropy transparent and facilitates regularization of stiff or collapsing modes.

22.2. Gerstenhaber and BV Algebra Methods

Gerstenhaber and Batalin–Vilkovisky (BV) algebras provide a homological framework that captures global relations among flow functionals. A Gerstenhaber algebra consists of a graded-commutative product and a graded Lie bracket

$$[\cdot, \cdot]: A^p \times A^q \rightarrow A^{p+q-1},$$

while a BV algebra includes a degree -1 second-order operator Δ satisfying $\Delta^2 = 0$, with the bracket induced by the deviation of Δ from being a derivation.

In the context of entropy flows on dense graphs, the BV operator may be viewed as a graph-theoretic Laplacian or divergence operator acting on functionals of the probability distribution. The quantum master equation

$$\Delta S + \frac{1}{2}[S, S] = 0$$

encodes global compatibility conditions. Singularity formation corresponds to obstructions to solving this equation, thereby permitting a cohomological classification of anomalies in the entropy-flow dynamics.

22.3. Kernel Jacobians and Entropy–Flow Singularities

Dense graphs admit a natural continuum representation via an integral kernel

$$(Tf)(x) = \int W(x, y) f(y) dy,$$

where W is a graphon or affinity kernel. The time evolution of probabilities $p(x, t)$ under a Markov or flow operator T is governed by a nonlinear map of the form

$$p \mapsto \Phi(p) = \frac{T(p)}{\int T(p)}.$$

Entropy singularities often arise where the Jacobian of this map,

$$J_\Phi(p) = D\Phi(p),$$

loses rank. Such Jacobian degeneracies correspond to several phenomena:

- concentration of probability on a shrinking subgraph or region,
- collapse onto low-dimensional eigenspaces of T ,
- abrupt changes in the stationary distribution of the flow,
- sensitivity and stiffness in the discrete-to-continuum limit.

The algebraic frameworks discussed above interact with the Jacobian structure in specific ways:

- **Tropical/DGA approach.** After the change of variables $u_i = -\log p_i$, the Jacobian transforms into a piecewise-linear object. Rank deficiency manifests as a failure of certain tropical linear forms to span the ambient space. The DGA/Hodge decomposition localizes this deficiency to precise graph-theoretic structures (e.g., bottlenecks or nearly-harmonic cycles).
- **Gerstenhaber–BV approach.** The Jacobian of Φ appears naturally in the second-order BV operator Δ when expressed in local coordinates. Degeneracy of $J_\Phi(p)$ corresponds to nontrivial elements in the BV cohomology, i.e., to obstructions in the master equation. This provides a global, homological explanation for the singularity, independent of coordinates.
- **Operator-algebraic viewpoint.** If T is regarded as an operator in a C^* -algebra or von Neumann algebra, then Jacobian degeneration corresponds to spectral concentration or collapse in the operator's action on the probability simplex. This perspective is especially effective in the dense-graph limit.

22.4. Comparison

- **Local regularization.** Tropical geometry and DGA methods provide explicit and computationally efficient tools for desingularizing Jacobian rank collapse, and for isolating the graph-theoretic structures that cause entropy spikes.
- **Global classification.** Gerstenhaber and BV algebras identify the homological obstructions underlying these singularities by encoding them as failures of the BV master equation.
- **Continuum and dense limits.** Kernel Jacobian analysis connects the discrete and continuum pictures, while the operator-algebraic and BV frameworks supply a structural explanation of how dense-graph limits produce singular flow behavior.

22.5. Applicability

Kernel Jacobians reveal the analytic source of entropy-flow singularities, while DGA/tropical and BV approaches respectively provide computational and conceptual mechanisms for resolving or classifying them. Together with operator-algebraic methods, they form a unified algebraic toolkit for understanding entropy-flow dynamics and singularity formation on dense graphs.

22.6. Computational Considerations for Differential Graded Algebras

In the context of entropy flows on dense graphs, the *use of a differential graded algebra (DGA) generally incurs a significantly higher computational cost compared to tropical or Batalin–Vilkovisky (BV) algebraic methods*. I performed all my computations on laptop for 3 Million nodes and 5 million edges for Gresthaber BV driven entropy flow impacting 10 percent nodes at a time. Dataset creation for Simulation Base Inference (i.e. reverse lookup) took multiple hours.

Complexity.

A DGA operates on chain and cochain complexes, requiring the construction of boundary and coboundary operators, as well as the computation of the discrete Hodge Laplacian,

$$\Delta = d^*d + dd^*.$$

For a dense graph with n nodes and $m \sim n^2$ edges, the dimension of the 1-cochain space is $\dim C^1 = m$, and hence the dominant linear-algebra operations—application of d or d^* , formation of Δ , and Hodge decomposition—scale on the order of $O(n^2)$ and require solving linear systems of comparable size.

In contrast, tropical/logarithmic methods and BV-type algebraic manipulations primarily act on node-level quantities and involve only elementwise transformations, local brackets, or simple ordering operations, yielding typical computational costs of $O(n)$ or $O(n \log n)$.

Interpretation.

The increased computational load of a DGA arises from its structural richness: it resolves flow fields into their exact, coexact, and harmonic components and therefore encodes global topological information. This additional structure is often essential for diagnosing the origin and geometry of singularities in probability–entropy flows, even if it is computationally heavier.

Conclusion.

In summary, DGAs are indeed more computationally intensive for dense graphs. However, the higher cost is justified when a full Hodge-theoretic or topological decomposition of the entropy dynamics is required, as such structure is not accessible to tropical or BV algebraic approaches. The text continues here.

22.7. Figures, Tables and Schemes

All figures and tables should be cited in the main text as Figure 21, Table 1, etc.



Figure 21. This is a figure. Schemes follow the same formatting.

Table 1. This is a table caption. Tables should be placed in the main text near to the first time they are cited.

Title 1	Title 2	Title 3
Entry 1	Data	Data
Entry 2	Data	Data ¹

¹ Tables may have a footer.

The text continues here (Figure 22 and Table 2).

1202




Figure 22. This is a wide figure. Schemes follow the same formatting. If there are multiple panels, they should be listed as: (a) Description of what is contained in the first panel. (b) Description of what is contained in the second panel. (c) Description of what is contained in the third panel. (d) Description of what is contained in the fourth panel. Figures should be placed in the main text near to the first time they are cited. A caption on a single line should be centered.

Table 2. This is a wide table.

Title 1	Title 2	Title 3	Title 4
Entry 1 *	Data	Data	Data
	Data	Data	Data
	Data	Data	Data
Entry 2	Data	Data	Data
	Data	Data	Data
	Data	Data	Data

* Tables may have a footer.

Text.
Text.

1203

1204

22.8. *Formatting of Mathematical Components*

This is the example 1 of equation:

$$a = 1, \tag{2}$$

the text following an equation need not be a new paragraph. Please punctuate equations as regular text.

This is the example 2 of equation:

$$a = b + c + d + e + f + g + h + i + j + k + l + m + n + o + p + q + r + s + t + u + v + w + x + y + z \tag{3}$$

Please punctuate equations as regular text. Theorem-type environments (including propositions, lemmas, corollaries etc.) can be formatted as follows:

Theorem 1. *Example text of a theorem.*

The text continues here. Proofs must be formatted as follows:

Proof of Theorem 1. Text of the proof. Note that the phrase “of Theorem 1” is optional if it is clear which theorem is being referred to. □

The text continues here.

23. Discussion

Authors should discuss the results and how they can be interpreted from the perspective of previous studies and of the working hypotheses. The findings and their implications should be discussed in the broadest context possible. Future research directions may also be highlighted.

24. Conclusions

This section is not mandatory, but can be added to the manuscript if the discussion is unusually long or complex.

25. Patents

This section is not mandatory, but may be added if there are patents resulting from the work reported in this manuscript.

Author Contributions: For research articles with several authors, a short paragraph specifying their individual contributions must be provided. The following statements should be used “Conceptualization, X.X. and Y.Y.; methodology, X.X.; software, X.X.; validation, X.X., Y.Y. and Z.Z.; formal analysis, X.X.; investigation, X.X.; resources, X.X.; data curation, X.X.; writing—original draft preparation, X.X.; writing—review and editing, X.X.; visualization, X.X.; supervision, X.X.; project administration, X.X.; funding acquisition, Y.Y. All authors have read and agreed to the published version of the manuscript.”, please turn to the [CRediT taxonomy](#) for the term explanation. Authorship must be limited to those who have contributed substantially to the work reported.

Funding: Please add: “This research received no external funding” or “This research was funded by NAME OF FUNDER grant number XXX.” and and “The APC was funded by XXX”. Check carefully that the details given are accurate and use the standard spelling of funding agency names at <https://search.crossref.org/funding>, any errors may affect your future funding.

Institutional Review Board Statement: In this section, you should add the Institutional Review Board Statement and approval number, if relevant to your study. You might choose to exclude this statement if the study did not require ethical approval. Please note that the Editorial Office might ask

you for further information. Please add “The study was conducted in accordance with the Declaration of Helsinki, and approved by the Institutional Review Board (or Ethics Committee) of NAME OF INSTITUTE (protocol code XXX and date of approval).” for studies involving humans. OR “The animal study protocol was approved by the Institutional Review Board (or Ethics Committee) of NAME OF INSTITUTE (protocol code XXX and date of approval).” for studies involving animals. OR “Ethical review and approval were waived for this study due to REASON (please provide a detailed justification).” OR “Not applicable” for studies not involving humans or animals.

Informed Consent Statement: Any research article describing a study involving humans should contain this statement. Please add “Informed consent was obtained from all subjects involved in the study.” OR “Patient consent was waived due to REASON (please provide a detailed justification).” OR “Not applicable” for studies not involving humans. You might also choose to exclude this statement if the study did not involve humans.

Written informed consent for publication must be obtained from participating patients who can be identified (including by the patients themselves). Please state “Written informed consent has been obtained from the patient(s) to publish this paper” if applicable.

Data Availability Statement: We encourage all authors of articles published in MDPI journals to share their research data. In this section, please provide details regarding where data supporting reported results can be found, including links to publicly archived datasets analyzed or generated during the study. Where no new data were created, or where data is unavailable due to privacy or ethical restrictions, a statement is still required. Suggested Data Availability Statements are available in section “MDPI Research Data Policies” at <https://www.mdpi.com/ethics>.

Acknowledgments: In this section you can acknowledge any support given which is not covered by the author contribution or funding sections. This may include administrative and technical support, or donations in kind (e.g., materials used for experiments). Where GenAI has been used for purposes such as generating text, data, or graphics, or for study design, data collection, analysis, or interpretation of data, please add “During the preparation of this manuscript/study, the author(s) used [tool name, version information] for the purposes of [description of use]. The authors have reviewed and edited the output and take full responsibility for the content of this publication.”

Conflicts of Interest: Declare conflicts of interest or state “The authors declare no conflicts of interest.” Authors must identify and declare any personal circumstances or interest that may be perceived as inappropriately influencing the representation or interpretation of reported research results. Any role of the funders in the design of the study; in the collection, analyses or interpretation of data; in the writing of the manuscript; or in the decision to publish the results must be declared in this section. If there is no role, please state “The funders had no role in the design of the study; in the collection, analyses, or interpretation of data; in the writing of the manuscript; or in the decision to publish the results”.

Abbreviations

The following abbreviations are used in this manuscript:

- MDPI Multidisciplinary Digital Publishing Institute
- DOAJ Directory of open access journals
- TLA Three letter acronym
- LD Linear dichroism

Appendix A

Appendix A.1

The appendix is an optional section that can contain details and data supplemental to the main text—for example, explanations of experimental details that would disrupt the flow of the main text but nonetheless remain crucial to understanding and reproducing the research shown; figures of replicates for experiments of which representative data are

shown in the main text can be added here if brief, or as Supplementary Data. Mathematical proofs of results not central to the paper can be added as an appendix.

Table A1. This is a table caption.

Title 1	Title 2	Title 3
Entry 1	Data	Data
Entry 2	Data	Data

Appendix B

All appendix sections must be cited in the main text. In the appendices, Figures, Tables, etc. should be labeled, starting with “A”—e.g., Figure A1, Figure A2, etc.

References

1. Vinay Awasthi 1, Angel-Raychev Ivanov 2 T. Modeling Charged Atoms for Atomistic Dynamics using Equivariant GNNs. *Applied Mathematics* DOI:10.20944/preprints202501.1533.v1 preprint **2025**, 1.

2. Albert Musaelian, Simon Batzner et al. T. Learning Local Equivalent Representations For Larg-Scale Atomistics Dynamcis. *Arxiv* **2022** 2204.05249.

3. Shu Hotta, L. Approximation Methods of Quantum Mechanics, Theory Of Analytic Functions. In *Mathematical Physical Chemistry*; Editor 1, F., Editor 2, A., Eds.; Springer: Osaka, Japan, 2023; pp. 155–274.

4. Shun-ichi Amari, L. Exponential Families and Mixture Families of Probability Distributions, Information Monotonicity Under Coarse Graining. In *Information Geometry and Its Applications*; Leslie Greengard, Courant Institute of Mathematical Sciences, F., S.S. Antman, Institute for Physical Science and Technology, A., Eds.; Springer: Wako, Saitama, Japan, 2016; pp. 31–54.

5. Alan Agresti, L. Inference on Contingency Tables, Introduction to Generalized Linear Models. In *Categorical Data Analysis*; 2nd ed. Edited by Wiley Interscience A John Wiley and Sons Inc. Publication place: Hoboken, New Jersey, 2002, pp. 70-165.

6. Yang, Z., Wang, X., Li, Y. et al. T. Efficient equivariant model for machine learning interatomic potentials. *npj Comput Mater* 11, 49 (2025). <https://doi.org/10.1038/s41524-025-01535-3> *npj computational materials* **2025**, 49

7. Viviana Ene; Jurgen Herzog. *Grobner Bases in Commutative Algebra*, 1st Ed ed.; American Mathematical Society: Providence, Rhode Island, USA, 2012; pp. 140–152.

8. Author 1, A.B.; Author 2, C. Title of Unpublished Work. *Abbreviated Journal Name* year, phrase indicating stage of publication (submitted; accepted; in press).

9. The Critical Contribution of Pseudouridine to mRNA COVID-19 Vaccines by Pedro Morais et al.. Available online: <https://pmc.ncbi.nlm.nih.gov/articles/PMC8600071/> (Nov 8 2025).

10. Blood–brain-barrier-crossing lipid nanoparticles for mRNA delivery to the central nervous system by Chang Wang et al.. *nature materials* Available online: <https://www.nature.com/articles/s41563-024-02114-5> (Nov 8 2025).

11. Link Property Prediction Datasets.(ogbl-vessel) OGB Stanford University Available online: <https://ogb.stanford.edu/docs/linkprop/> (Nov 8 2025).

12. For the Nature Methods submission "Automated analysis of whole brain vasculature using machine learning" Authors: Johannes C. Paetzold and Giles Tetteh – Github Available online: <https://github.com/vessap/vessap> (Nov 21 2025).

13. Volumetric Rendering Engine Voreen: Voreen – An Open-source Framework for Interactive Visualization and Processing of Large Volume Data By Dominik Drees, Simon Leistikow, Xiaoyi Jiang, Lars Linsen Available online: <https://arxiv.org/abs/2207.12746>, <https://www.uni-muenster.de/Voreen/index.html>, https://www.uni-muenster.de/Voreen/documentation/mac_os.html (Nov 8 2025).

14. Whole Brain Vessel Graphs. *Arxiv* Available online: <https://arxiv.org/pdf/2108.13233> (Nov 10 2025).

15. VesSap Data used to generate ogbl-vessel dataset By Johannes C. Paetzold. Available online: <https://github.com/jocpae/VesselGraph> (Nov 21 2025).

16. Machine learning analysis of whole mouse brain vasculature By Mihail Ivilinov Todorov*,1,2,3, Johannes Christian Paetzold*. Available online: <https://pmc.ncbi.nlm.nih.gov/articles/PMC7591801/pdf/nihms-1628795.pdf> (Nov 21 2025).

17. Paraview Software for exascale dataset visualization. Available online: <https://www.paraview.org/> (Nov 21 2025).

18. Revisiting Graph Neural Networks For Link Prediction. By Muhan Zhang Pan Li et. al. Available online: https://openreview.net/forum?id=8q_ca26L1fz (Nov 10 2025).

19. SEAL - Labeling Trick: A Theory of Using Graph Neural Networks for Multi-Node Representation Learning By Muhan Zhang Pan Li et. al. *Arxiv* Available online: <https://arxiv.org/pdf/2010.16103> (Nov 10 2025).

- | | | |
|-----|--|----------------------|
| 20. | Link Prediction based on Subgraph By Muhan Zhang and Yixin Chen.
Available online: https://proceedings.neurips.cc/paper_files/paper/2018/file/53f0d7c537d99b3824f0f99d62ea2428Paper.pdf (Nov 10 2025). | 1334
1335
1336 |
| 21. | BOOST : A Fast Approach to Detecting Gene-Gene Interactions in Genome-wide Case-Control Studies. by Xiang Wang <i>American Journal of Human Genetics</i> Available online: https://pmc.ncbi.nlm.nih.gov/articles/PMC2933337/bib14 (Nov 10 2025) | 1337
1338 |
| 22. | Lipid nanoparticles for mRNA delivery in brain via systemic administration by Dinglingge Cao et al.. <i>science advances</i> Available online: https://www.science.org/doi/10.1126/sciadv.adw0730 (Nov 8 2025). | 1339
1340 |
| 23. | Computational Approaches to Assist Drug Discovery Precision Medicine Available online: https://www.vls3d.com/ (Nov 8 2025). | 1341
1342 |
| 24. | Nonextensive Pythagoras' Theorem By Ambedkar Dukkipati Available online: https://arxiv.org/pdf/cs/0611030 (Nov 8 2025). | 1343 |
| 25. | I-divergence of probability distributions and minimization problems. By I. Csiszar DOI: 10.1214/aop/1176996454 Available online: https://projecteuclid.org/journals/annals-of-probability/volume-3/issue-1/I-Divergence-Geometry-of-Probability-Distributions-and-Minimization-Problems/10.1214/aop/1176996454.full (Nov 8 2025). | 1344
1345
1346 |
| 26. | Properties of Cross-Entropy Minimization By John E. Store
Available online: https://bayes.wustl.edu/Manual/CrossEntropyMinimization.pdf (Nov 8 2025). | 1347
1348 |
| 42. | Functional connectomics spanning multiple areas of mouse visual cortex BY The MICrONS Consortium Available online: - https://www.nature.com/articles/s41586-025-08790-w , https://neuromancer-seung-import.appspot.com/?local_id=762a2e0ffd50f4be7cc7 (Nov 15 2025). | 1349
1351 |
| 28. | Direct Structural Connections between Auditory and Visual Motion-Selective Regions in Humans BY Ane Gurtubay-Antolin Available online: - https://pubmed.ncbi.nlm.nih.gov/33514674/ (Nov 15 2025). | 1352
1353 |
| 29. | GAME THEORY, MAXIMUM ENTROPY, MINIMUM DISCREPANCY AND ROBUST BAYESIAN DECISION THEORY By Peter D. Grunwald and A. Philip Dawid Available online: https://arxiv.org/pdf/math/0410076 (Nov 8 2025). | 1354
1355 |
| 30. | Lattice Point Counting and Integration over Convex Polytopes Available online: https://www.math.ucdavis.edu/latte/theory.php (Nov 8 2025). | 1356
1357 |
| 31. | K. Fukuda. cdd, cddplus and cddlib homepage. ETH Zurich online: https://people.inf.ethz.ch/fukudak/cdd_home/ (Nov 8 2025). | 1358
1359 |
| 32. | T.S. Motzkin, H. Raiffa, GL. Thompson, and R.M. Thrall. The double description method. In H.W. Kuhn and A.W. Tucker, editors, Contributions to Theory of Games, Vol. 2. Princeton University Press, Princeton, RI, 1953. <i>Princeton University Press</i> 1953 | 1360
1361 |
| 33. | A PRIMAL BARVINOK ALGORITHM BASED ON IRRATIONAL DECOMPOSITIONS By Matthias Koppe (2006) Available online: https://arxiv.org/pdf/math/0603308v4 (Nov 8 2025). | 1362
1363 |
| 34. | CoCoA - Genoa Italy (2006) Available online: https://sites.google.com/view/cocoa-cocoalib (Nov 8 2025). | 1364 |
| 60. | Diaconis-Sturmfels algorithm to the MCMC technique Available online: https://polytopes.net/pdf/KAIST3.pdf (Nov 8 2025). | 1365 |
| 36. | Markov bases and contingency tables By Ruriko Yoshida Available online: https://polytopes.net/courses/STA624S14/MCMC.pdf (Nov 10 2025). | 1366
1367 |
| 37. | A Database of Markov Bases Available online: https://markov-bases.de/search.php?perpage=20 (Nov 8 2025). | 1368 |
| 38. | 4Ti-2: https://4ti2.github.io/4ti2_manual.pdf (Nov 8 2025). | 1369 |
| 39. | Algstat: https://github.com/dkahle/algstat (Nov 8 2025). | 1370 |
| 40. | Mccaulay2: https://macaulay2.com/Book/ComputationsBook/book/book.pdf (Nov 8 2025). | 1371 |
| 41. | Stevens Vickers: Sketches for arithmetic universes https://arxiv.org/pdf/1608.01559 <i>Arxiv</i> (Nov 8 2025). | 1372 |
| 42. | John Smart: Brain Preservation https://www.brainpreservation.org/content-2/connectome/ (Nov 9 2025). | 1373 |
| 43. | Human Connectome https://www.humanconnectome.org/ (Nov 9 2025). | 1374 |
| 44. | Algebraic Julia https://github.com/AlgebraicJulia (Nov 9 2025). | 1375 |
| 45. | Catlab.jl https://algebraicjulia.github.io/Catlab.jl/dev/ (Nov 9 2025). | 1376 |
| 46. | Open AI Why language models hallucinate https://openai.com/index/why-language-models-hallucinate/ (Nov 10 2025). | 1377 |
| 47. | Neural network architecture of a mammalian brain https://www.pnas.org/doi/10.1073/pnas.2413422121 (Nov 10 2025) | 1378 |
| 48. | SEAL Link Prediction https://github.com/facebookresearch/SEAL_OGB (Nov 10 2025) | 1379 |
| 49. | H-representation vs V-representation https://mathoverflow.net/questions/108696/h-representation-versus-v-representation-of-polytopes (Nov 10 2025) | 1380
1381 |
| 50. | Computational Geometry https://www.cse.cuhk.edu.hk/taoyf/course/5010/notes/mount.pdf (Nov 10 2025) | 1382 |
| 51. | Algebraic and Geometric Methods in Statistics https://www.cambridge.org/core/books/algebraic-and-geometric-methods-in-statistics/323785C1D4AC514EDD978F34186EF3F8 (Nov 10 2025) | 1383
1384 |
| 52. | Detection of Deep Structures This project's Git Repository https://github.com/vkawasth/Leaker (Nov 10 2025) ref-url-chen | 1385 |
| 53. | LATTICE POINTS, CONTINGENCY TABLES, AND SAMPLING By YUGUO CHEN, IAN DINWOODIE, ADRIAN DOBRA, AND MARK HUBER, Available Online at : https://sites.stat.washington.edu/adobra/Files/Papers/contmath2005.pdf (Nov 10 2025) | 1386
1387
1388 |

54. Random Transpositions on Contingency Tables by Mackenzie Simper Available Online at : <https://arxiv.org/pdf/2208.10700> (Nov 10 2025)
55. Polyhedral Computation Today's Topic: The Double Description Algorithm By Komei Fukuda Available Online at : <https://www.lab2.kuis.kyoto-u.ac.jp/avis/courses/pc/2010/notes/lec5.pdf> (Nov 10 2025)
56. Markov bases and subbases for bounded contingency tables By Ruriko Yoshida Available Online at : <https://polytopes.net/pdf/KAIST3.pdf> (Nov 10 2025)
57. Higher Connectivity of fiber graphs of Grobner bases By Samu Potka Available Online at : <https://arxiv.org/pdf/1209.1533> (Nov 10 2025)
58. HAHN POLYNOMIALS ON POLYHEDRA AND QUANTUM INTEGRABILITY By PLAMEN ILIEV AND YUAN XU Available Online at : <https://arxiv.org/pdf/1707.03843> (Nov 10 2025)
59. Model selection for contingency tables with algebraic statistics By Anne Krampe and Sonja Kuhnt Available Online at : <https://resolve.cambridge.org/core/books/algebraic-and-geometric-methods-in-statistics/323785C1D4AC514EDD978F34186EF3F8> (Nov 10 2025)
60. ALGEBRAIC ALGORITHMS FOR SAMPLING FROM CONDITIONAL DISTRIBUTIONS BY PERSI DIACONIS AND BERND STURMFELS Available Online at : <https://projecteuclid.org/journalArticle/Download?urlId=10.1214%2Faos%2F1030563990> (Nov 10 2025)
61. Fast and stable computation of higher-order Hahn polynomials and Hahn moment invariants for signal and image analysis By Achraf Daoui et. al. Available Online at : <https://pmc.ncbi.nlm.nih.gov/articles/PMC8356550/> (Nov 10 2025)
62. IDEALS GENERATED BY ADJACENT 2-MINORS By JÜRGEN HERZOG AND TAKAYUKI HIBI Available Online at : <https://arxiv.org/pdf/1012.5789> (Nov 20 2025)
63. Primary Decomposition of Lattice Basis Ideals By SERKAN HOSTEN AND JAY SHAPIRO Available Online at : <https://www.sciencedirect.com/science/article/pii/S0747717199903978> (Nov 20 2025)
64. Ideals of Adjacent Minors By Serkan Hosten Seth Sullivant Available Online at : <https://arxiv.org/pdf/math/0306318> (Nov 20 2025) ref-url-equivariantgrobnerbasis
65. Equivariant Grobner bases By Christopher J. Hillar, Robert Krone and Anton Leykin Available Online at : <https://par.nsf.gov/servlets/purl/10100263> (Nov 20 2025)
66. UNDERSTANDING OVER-SQUASHING AND BOTTLENECKS ON GRAPHS VIA CURVATURE By Jake Topping^{1,2†}, Francesco Di Giovanni^{3†}, Benjamin P. Chamberlain Available Online at : <https://arxiv.org/pdf/2111.14522> (Nov 20 2025)
67. Lein ES, Hawrylycz MJ, Ao N, et al. (2007) "Genome-wide atlas of gene expression in the adult mouse brain." *Nature* 445(7124):168-76. [doi 10.1038/nature05453] Available Online at : https://scalablebrainatlas.incf.org/mouse/ABA_v3
68. Lein ES, Hawrylycz MJ, Ao N, et al. (2007) "Genome-wide atlas of gene expression in the adult mouse brain." *Nature* 445(7124):168-76. [doi 10.1038/nature05453] CCFv3 2017 Available Online at : http://download.alleninstitute.org/informatics-archive/current-release/mouse_ccf/annotation/ccf_2017/annotation_10.nrrd
69. VIA API Lein ES, Hawrylycz MJ, Ao N, et al. (2007) "Genome-wide atlas of gene expression in the adult mouse brain." *Nature* 445(7124):168-76. [doi 10.1038/nature05453] CCFv3 2017 Available Online at : http://api.brain-map.org/api/v2/structure_graph_download/1.json "":contentReference[oaicite:1]index=1
70. INTRODUCTION TO BATALIN-VILKOVISKY ALGEBRAS By Ana Sopona Available Online at : <https://www.ub.edu/topologia/seminars/notesGiT2022/Anna.pdf> (Nov 23 2025)
71. BATALIN-VILKOVISKY ALGEBRAS AND TWO-DIMENSIONAL TOPOLOGICAL FIELD THEORIES Available Online at : <https://arxiv.org/pdf/hep-th/9212043> (Nov 23 2025)
72. Virtual Brain Inference (VBI): A flexible and integrative toolkit for efficient probabilistic inference on virtual brain models By Abolfazl ZiaemehrMarmaduke WoodmanLia DomideSpase PetkoskiViktor JirsaMeysam Hashemi Available Online at : <https://elifesciences.org/reviewed-preprints/106194v3> (Nov 23 2025)
73. Information geometry of perturbed gradient flow systems on hypergraphs: A perspective towards nonequilibrium physics By Loutchko, D., et al. (2025). Available Online at : <https://arxiv.org/abs/2510.27268> (Nov 24 2025)
74. Forward Euler for Wasserstein Gradient Flows: Breakdown and Regularization Xu, Y., et al. (2025) Available Online at : <https://arxiv.org/abs/2509.13260> (Nov 23 2025)
75. A Fisher-Rao gradient flow for entropy-regularised Markov decision processes in Polish spaces By Zhang, Y., et al. (2025) Available Online at : <https://arxiv.org/abs/2310.02951> (Nov 23 2025)
76. Ay, N., Jost, J., Lê, H. V., & Schwachhöfer, L. (2017). *Information Geometry*. Springer.
77. Amari, S.-I. (2016). *Information Geometry and Its Applications*. Springer.
78. Author 1, A.B.; Author 2, C.D.; Author 3, E.F. Title of presentation. In Proceedings of the Name of the Conference, Location of Conference, Country, Date of Conference (Day Month Year); Abstract Number (optional), Pagination (optional). Author 1, A.B. Title of Thesis. Level of Thesis, Degree-Granting University, Location of University, Date of Completion.

Disclaimer/Publisher’s Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.

1443
1444
1445