

Non-Trivial Monodromy and the Derived $(2, 1)$ -Stack Structure of Neural Algebraic Singularities: Complete Mathematical Exposition with BALBc Connectome Implementation

Anonymous
Mathematical Modeling and Theoretical Neuroscience

May 4, 2026

Abstract

We establish a rigorous mathematical framework connecting non-trivial monodromy to derived $(2, 1)$ -moduli stacks in the context of neural dynamics and consciousness. The key innovation is a **two-slider model** where consciousness arises from the interplay of two independent crisis mechanisms: algebraic crises (A_∞ -deformation obstructions) and geometric crises (wavelet-Grassmannian singularities).

We provide complete technical exposition of the implementation on the BALBc connectome, detailing: (1) Renkin-Crone blood-brain barrier dynamics with molecular trapping/release kinetics, (2) Grassmannian wavelets on $\text{Gr}(2, 4)$ with Plücker coordinates and Klein quadric constraint, (3) spectral zeta functions (Ihara graph zeta, wavelet zeta, Hochschild zeta) measuring singularities, (4) A_∞ -algebra structure computation from quiver path algebras, (5) perverse sheaves and schobers encoding wall-crossing data, and (6) Toda flow providing isospectral deformations.

Analyzing a 25-second simulation of opiate/norcain dynamics, we observe a striking “ghost signal” phenomenon: Hochschild cohomology $HH^2(t)$ decays to near-zero at $t \approx 10$ seconds, yet monodromy signatures persist through $t = 25$ seconds with coherence error $\|M - I\|_{L^2} = 3.00$. This persistence is impossible in smooth families but is precisely the hallmark of genuine derived $(2, 1)$ -stacks with nontrivial 2-morphisms.

We develop the categorical foundations over the product base $B = X \times (\text{Gr}(2, 4) \setminus \Delta)$, prove the main theorem connecting monodromy to stack structure, validate via eight independent checks plus comprehensive 21-panel consciousness dashboard, and discuss implications for understanding neural resilience, phase transitions, and the mathematical foundations of consciousness.

Contents

1	Introduction	9
1.1	Background and Motivation	9
1.2	Statement of Main Results	9
2	Quiver Path Algebra Generation from BALBc Connectome Atlas	9
2.1	Motivation: From Connectome Data to Algebraic Structure	9
2.2	Phase 1: Node-to-Region Mapping	10
2.3	Phase 2: Edge Processing with Geometric Impedance	10
2.3.1	Geometric Weight Formula	11
2.3.2	Aggregation to Region Pairs	11
2.4	Phase 3: Arrow Definition	11

2.5	Phase 4: Hochschild Relations from Geometric Flows	11
2.5.1	Associative Coefficient	12
2.5.2	Relation Definition	12
2.5.3	Relation Magnitude as Hochschild Obstruction	12
2.6	Phase 5: Loop Relations and Idempotent Structure	12
2.6.1	Loop Relation Definition	13
2.7	Phase 6: GAP Quiver Algebra Code Generation	13
2.7.1	GAP Code Structure	13
2.7.2	Computational Output	13
2.8	Key Design Decisions	13
2.8.1	Geometric Impedance Formula	13
2.8.2	Associative Coefficient Formula	14
2.8.3	Field Choice: GF(101)	14
2.8.4	Treatment of Missing Edges	14
2.9	Validation and Sanity Checks	14
2.9.1	Arrow Count	14
2.9.2	Relation Count	14
2.9.3	Coefficient Magnitudes	14
2.9.4	Consistency with A-Infinity Computation	14
2.10	Integration with Time-Dependent Simulations	15
2.11	Connection to Perverse Sheaves	15
2.12	Summary: From Atlas to Algebra	15
3	Renkin-Crone Blood-Brain Barrier Dynamics	15
3.1	Biological Background and Mathematical Model	15
3.2	Implementation in BALBc	17
4	Grassmannian Wavelets and Gr(2,4) Structure	17
4.1	Why Gr(2,4): Geometric Motivation	17
4.2	Plücker Coordinates and Klein Quadric	17
4.3	Wavelet Decomposition Indexed by Plücker Coordinates	18
4.4	Wavelet Zeta Function and Geometric Crisis	18
5	Spectral Zeta Functions: Ihara, Wavelet, Hochschild	18
5.1	Ihara Zeta and Graph Topology	18
5.2	Ihara Pole Radius and Monodromy Signature	19
5.3	Hochschild Cohomology and A_∞ -Zeta	19
6	Region Graph Construction and Integration with Dynamics	19
6.1	Overview: From Voxel-Level Atlas to Regional Network	19
6.2	Stage 1: Voxel-to-Region Mapping	19
6.3	Stage 2: Edge Aggregation by Region Pair	20
6.4	Stage 3: Centroid Computation	21
6.5	Stage 4: Graph Export	21
6.5.1	regions.csv	21
6.5.2	region_edges.csv	21
6.6	Integration with Renkin-Crone Dynamics	22
6.6.1	Flow Term Dynamics	22
6.7	Real-Time A_∞ -Algebra Updates from Dynamics	22
6.7.1	Motivation: Time-Varying Edge Weights	22
6.7.2	A_∞ -Algebra Recomputation at Each Snapshot	22
6.7.3	Julia-Python Interface	23

6.7.4	Time-Varying Crisis Ideal	23
6.8	Two-Slider Synchronization	23
6.9	Data Structures for Efficiency	24
6.9.1	regions.csv in Python	24
6.9.2	region_edges.csv in Python	24
6.9.3	Self-Loops	24
6.10	Validation and Sanity Checks	24
6.10.1	Region Count	24
6.10.2	Edge Count	25
6.10.3	Weight Magnitudes	25
6.10.4	Centroid Validity	25
6.10.5	Symmetry in Self-Loops	25
6.11	Advantages of This Approach	25
6.12	Summary: From Atlas to Network Dynamics	25
7	A_∞-Algebras, Quivers, and Prime Higher Ideals	26
7.1	From BALBc Atlas to Weighted Quiver	26
7.2	A_∞ -Algebra Structure from Stasheff Identities	26
7.2.1	Computing $m_2, \dots, m_6$ for the BALBc Quiver	26
7.3	Prime Paths and Prime Higher Ideals	27
7.4	Perverse Sheaves and Perverse Schobers	27
7.5	Associahedron and Beam-Search Navigation	27
7.6	Toda Flow: Isospectral Deformations with Damping	28
7.7	Spectral and Perverse Sheaves on the Quiver	28
7.7.1	Spectral Sheaf	28
7.7.2	Perverse Sheaf from Prime Ideals	29
8	The Two-Slider Model and Product Base	29
8.1	Algebraic Slider: A_∞ -Deformations and Crisis Ideal	29
8.2	Geometric Slider: Wavelet-Grassmannian Structure	29
8.3	Coupling Locus: Dual-Zeta Mismatch	29
8.4	Total Singular Locus: Three Independent Components	30
9	Derived Stack Structure Over the Product Base	30
9.1	Base Space and Blow-Up	30
9.2	Homological Layers	30
10	Non-Trivial Monodromy and the Ghost Signal	30
10.1	Monodromy from Loops Around the Discriminant	30
10.2	The Ghost Signal: HH^2 Clears but Monodromy Persists	31
10.3	Dehn Twist Composition and Coherence Error	31
11	Final Analysis Pipelines: Spectral, Geometric, and Categorical	31
11.1	Overview of the Three Pipelines	31
12	Bass-Ihara Zeta Function and Spectral Analysis	31
12.1	The Proper Bass-Ihara Determinant Formula	31
12.1.1	Exponent and Cyclomatic Number	32
12.2	The Pole Radius and Network Connectivity	32
12.2.1	Interpretation	32
12.3	Application to BALBc Connectome	33
12.4	Relationship to the Unified Zeta Proxy	33

12.4.1	Why the Proxy?	33
12.4.2	Proxy vs. Ground Truth	34
12.5	Corrected Formulation for the Two-Slider Model	34
12.6	Revised Correlation Analysis	34
12.7	Summary: Proxy vs. Ground Truth	35
12.8	Pipeline 1: Spectral Analysis via Ihara Zeta	35
12.8.1	Key Functions	35
12.8.2	Workflow	36
12.8.3	Output Interpretation	36
12.9	Pipeline 2: Geometric Analysis via Rees Blow-Up	36
12.9.1	Motivation	36
12.9.2	Crisis Ideal Generators	36
12.9.3	Key Functions	37
12.9.4	Output Structure	38
12.9.5	Interpretation	38
12.10	Pipeline 3: Categorical Analysis via Perverse Schober	38
12.10.1	Motivation	38
12.10.2	Data Structures	38
12.10.3	Key Functions	39
12.10.4	Output and Interpretation	40
12.11	Comparison: Old (run_v3.jl) vs. New (run_iharaSingV2.jl) Pipelines	40
13	Associahedron Navigation and Ihara Spectral Integration	41
13.1	Overview: Dual Pipelines from Shared A-Obstruction Data	41
13.2	Pipeline 1: Associahedron Navigator (Combinatorial)	41
13.2.1	Input Data	41
13.2.2	Obstruction Scoring Function	41
13.2.3	Beam Search Algorithm	42
13.2.4	Physical Interpretation	42
13.3	Pipeline 2: Ihara-Associahedron Bridge (Spectral)	42
13.3.1	Effective Adjacency Matrix Construction	42
13.3.2	Unified Zeta Computation	43
13.3.3	Tubing Signature Integration	43
13.4	Correlation and Validation in run_iharaSingV2.jl	43
13.4.1	Interpretation of Correlations	43
13.5	The Shared Data: A-Algebra as Hub	44
13.6	Validation Framework: Eight-Point Check	44
13.7	Why Integration Matters	45
13.8	Dynamics and Analysis Flow	45
13.9	Data Structure: Shared JSON Format	45
13.10	Summary: Associahedron Meets Ihara	49
14	Unified Sheaf Zeta: Reconciling Spectral and Geometric Crises	49
14.1	The Unified Sheaf Zeta Function	49
14.2	The Effective Adjacency Matrix	50
14.2.1	Component 1: Static Connectome	50
14.2.2	Component 2: Prime Paths	50
14.2.3	Component 3: Main Obstruction m	50
14.2.4	Component 4: Cup Product	50
14.2.5	Component 5: Gerstenhaber Bracket	50
14.2.6	Weighting and Normalization	50
14.3	The Complex Parameter and Convergence	51

14.4	Log-Magnitude Representation	51
14.5	How the Unified Zeta Unifies Two Crises	51
14.5.1	Algebraic Contribution	52
14.5.2	Geometric Contribution	52
14.5.3	The Unification	52
14.6	Poles and Spectral Information	52
14.6.1	Crisis Interpretation	53
14.7	Relation to Ihara and Plücker Zetas	53
14.8	Implementation in IharaAssociahedronBridgeV2.jl	53
14.9	Computational Efficiency	54
14.10	Crisis Signatures in Unified Zeta	54
14.10.1	Pre-Crisis	54
14.10.2	Crisis Onset	55
14.10.3	Full Crisis	55
14.10.4	Recovery	55
14.11	Why the Unified Zeta Is the Real Proof	55
14.12	Summary: The Unified Sheaf Zeta as Crisis Probe	55
14.13	Complete Execution Workflow	56
15	GNNs versus Toda Flow: Can Message Passing Replace Categorical Trans-	57
	port?	
15.1	The Superficial Resemblance	57
15.2	Why This Claim Is Seductive But False	57
15.2.1	Difference 1: Discrete vs Continuous Time	57
15.2.2	Difference 2: Structure Preservation	58
15.2.3	Difference 3: Global vs Local Algebra	58
15.2.4	Difference 4: Algebraic Structure	59
15.3	Fundamental Theorem: Why Toda Cannot Be Replaced	59
15.4	What GNNs CAN Do (and Cannot)	60
15.4.1	What GNNs Are Good At	60
15.4.2	What GNNs Cannot Do	60
15.5	Application to Consciousness and Derived Stacks	60
15.5.1	Why Toda is Necessary Here	60
15.5.2	Could a GNN Approximate Consciousness?	61
15.6	Mathematical Analogy: Numerics vs Analysis	61
15.7	Summary: GNNs Cannot Replace Toda	61
16	Hironaka Resolution and Derived Enhancements: The A-Algebra Singularity	62
16.1	Classical Foundation: Scheme-Theoretic Crisis	62
16.1.1	The Crisis Scheme	62
16.1.2	Singularities of the Crisis Locus	62
16.2	Hironaka's Theorem: Classical Resolution	63
16.2.1	Resolution of Singularities	63
16.3	Rees Algebra and Blow-Up	63
16.3.1	Universal Property of the Blow-Up	63
16.3.2	Rees Charts	64
16.4	Exceptional Divisor with Multiplicities	64
16.4.1	Structure of E	64
16.4.2	Multiplicities	64
16.4.3	Normal Crossings Structure	65
16.5	Derived Enhancement: A-Algebra Deformations	65
16.5.1	Failure of Classical Truncation	65

16.5.2	Derived Deformation Ring	66
16.5.3	Derived Stack	66
16.6	A-Operations as Derived Structure	66
16.6.1	The Five Operations	66
16.6.2	Classical vs Derived Visibility	67
16.6.3	The Crisis Ideal Reinterpreted	67
16.7	Monodromy from Fundamental Group	67
16.7.1	Correction: Monodromy Source	67
16.7.2	Loop Around Discriminant	68
16.7.3	Coherence Error	68
16.8	Integration: Hironaka + Derived	68
16.8.1	The Two Levels	68
16.8.2	Classical Resolution	69
16.8.3	Derived Enhancement	69
16.8.4	Perverse Schober on E	69
16.9	Summary: Hironaka in Derived Language	69
16.10	Key Results and Validation	70
17	Reverse Hironaka: Last Known Good Algebra Localization via VTU Subgraphs	70
17.1	Overview: From Abstract Resolution to Concrete Anatomy	70
17.2	Crisis Detection and Last Known Good Step	71
17.2.1	Threshold-Based Detection	71
17.2.2	Last Known Good Step	71
17.3	Epicenter Localization: Identifying the Crisis Region	71
17.3.1	Dominant Region Selection	71
17.3.2	Centroid Coordinates	71
17.4	Subgraph Extraction: Highlighting Crisis Anatomy	72
17.4.1	Seed-Based Extraction	72
17.4.2	Obstruction Annotation	72
17.4.3	VTU File Output	73
17.5	ParaView Visualization: Anatomy of Crisis	73
17.5.1	Opening in ParaView	73
17.5.2	Interpretation	73
17.6	Last Known Good Algebra Marker	73
17.6.1	Saving the Good State	73
17.6.2	Characteristics of Good Algebra	74
17.7	Blow-Up Marker: Crisis Epicenter	74
17.7.1	Marker Generation	74
17.7.2	Interpretation	75
17.8	Reverse Hironaka Procedure: Recovery from Blow-Up	75
17.8.1	Conceptual Framework	75
17.8.2	Step 1: Chart Selection	75
17.8.3	Step 2: Norcaine Injection (Recovery Mechanism)	75
17.8.4	Step 3: Recompute A-Algebra	75
17.8.5	Step 4: Verify Recovery with VTU	76
17.9	Mathematical Interpretation: Shadow of Functoriality	76
17.9.1	Not an Explicit Functor	76
17.9.2	Derived Functor in Mathematics	76
17.9.3	Functorial Data Structures in Code	76
17.9.4	Statement for the Paper	77

17.10	Summary: From VTU Visualization to Derived Functors	77
18	Best Paths and Best Tubings: Dual Structures for Molecular Dynamics Management	77
18.1	Overview: From Algebra to Combinatorics to Physics	77
18.2	Best Paths: Algebraic Structure	78
18.2.1	Definition	78
18.2.2	Selection: Best Path at Each Snapshot	78
18.2.3	Physical Interpretation of Best Paths	79
18.2.4	Link to Molecular Dynamics	79
18.3	Best Tubings: Combinatorial Structure	79
18.3.1	Definition	79
18.3.2	Selection: Best Tubing at Each Snapshot	79
18.3.3	Physical Interpretation of Best Tubings	80
18.3.4	Link to Molecular Dynamics	81
18.4	The Duality: Best Paths and Best Tubings	81
18.4.1	Paths are Algebraic; Tubings are Combinatorial	81
18.4.2	Complementarity	81
18.5	Data Evidence: Synchronized Molecular Routing	81
18.5.1	Snapshot Progression	81
18.5.2	Tubing Repetition as Crisis Depth Indicator	82
18.6	Mathematical Model: From Paths to Tubings	82
18.6.1	Step 1: Path Evaluation	82
18.6.2	Step 2: Obstruction Accumulation	82
18.6.3	Step 3: Tubing Formation	83
18.7	Molecular Interpretation: Opiate and Norcaine Routes	83
18.7.1	Opiate Route	83
18.7.2	Norcaine Route	83
18.7.3	Combined Effect	83
18.8	Summary: Best Paths and Best Tubings as Molecular Routers	83
19	Validation Framework and Results	84
19.1	Eight-Point Validation: All Pass	84
19.2	21-Panel Consciousness Dashboard	84
20	Discussion and Implications	84
20.1	Classical vs Derived Picture	84
20.2	Neural Resilience and Topological Locking	84
20.3	Consciousness as Categorical	85
21	A Fibered Derived Blow-Up Model for A_∞ Brain Dynamics	85
21.1	A_∞ Snapshots and Obstruction Data	85
21.2	Prime Paths and Higher Ideals	85
21.3	Perverse Structure and Associahedron	86
21.4	Spectral Zeta Functions	86
21.5	Singularity Ideal	86
21.6	Rees Blow-Up and Exceptional Divisor	86
21.7	Grassmannian Base and Fiber Structure	87
21.8	Derived (2,1)-Stack Structure	87
21.9	Monodromy and Wall-Crossing	87
21.10	Correlation Principle	87

22 Computational Implementation: A_∞-Algebra via Hochschild Cohomology	88
22.1 Overview	88
22.2 Algebra Basis and Path Enumeration	88
22.3 Hochschild Differential and Boundary Operators	88
23 Perverse Schober and Chamber Flips	89
23.1 From Stratification to Categorification	89
23.2 Associahedron Chambers as Stalk Categories	89
23.3 The Perverse Schober as a Sheaf of Stacks	89
23.4 Computational Realisation	90
23.5 Why This Matters	90
23.6 Computational Implementation: Singularity Tracker and Perverse Schober	90
23.6.1 Detecting Blow-Up Events (Singularity Tracker)	90
23.6.2 Constructing the Perverse Schober (Chambers and Walls)	91
23.6.3 Integration with the Associahedron Navigator	91
23.6.4 Rees Chart Switching and Exceptional Divisor	91
23.6.5 Summary of the Pipeline	91
23.7 Cohomology Computation	92
23.8 Higher A_∞ -Operations: m_3, m_4, m_5, m_6	92
23.8.1 m_3 : Associator	92
23.8.2 m_4 : Pentagon Obstruction	92
23.8.3 m_5 : Hexagon Obstruction	93
23.8.4 m_6 : Main A_∞ -Obstruction	93
23.9 Cup Product and Lie Bracket on HH^1	93
23.9.1 Shifted Cup Product	93
23.9.2 Gerstenhaber Bracket	93
23.10 Prime Paths and Higher Ideals	93
23.11 Support Locus and Annihilator	94
23.12 Real-Time Crisis Computation	94
23.13 Data Structures and Sparse Representation	95
24 Conclusion	97

1 Introduction

1.1 Background and Motivation

A central challenge in neuroscience and consciousness studies is understanding how neural systems undergo phase transitions (crises) and recover, and what role these transitions play in consciousness. Classical approaches model neural dynamics as smooth dynamical systems, where equilibria bifurcate and attractors emerge or disappear. However, this framework assumes that once an algebraic obstruction is cleared (e.g., solving an equation), the system returns to its original state.

Our analysis of BALBc connectome dynamics with opiate/norcain reveals a fundamentally different picture. The system exhibits a **two-slider mechanism**:

1. **Algebraic Slider (X)**: Edge weights w_{ij} determine the A_∞ -algebra structure via Hochschild cohomology. Crisis occurs when HH^2 spikes.
2. **Geometric Slider ($\text{Gr}(2,4) \setminus \Delta$)**: Wavelet parameters (Plücker coordinates) determine spectral and topological properties. Crisis occurs when zeta functions collide or winding numbers change.
3. **Coupling (Mismatch)**: The dual-zeta mismatch $M(w, \gamma)$ measures how out-of-sync the two sliders are. When both spike together, the system enters a double crisis.

The empirical observation is striking: HH^2 clears by $t \approx 10$ seconds, yet monodromy (detected as coherence loss and topological locking) persists through $t = 25$ seconds. This **ghost signal** is impossible in smooth families but follows naturally from derived $(2,1)$ -stack theory, where 1-morphisms (algebraic, living in homological degree 1) and 2-morphisms (categorical/topological, living in homological degree 2) are independent.

1.2 Statement of Main Results

Theorem 1.1 (Main Theorem). *Let $B = X \times (\text{Gr}(2,4) \setminus \Delta)$ be the product base of algebraic and geometric parameters. If the associated family of A_∞ -algebra structures and wavelet deformations exhibits:*

- (i) *Hochschild obstruction $HH^2(t) \rightarrow 0$ as $t \rightarrow t_*$ (algebraic clearing), yet*
- (ii) *Nontrivial chamber flips persist after t_* (categorical persistence),*
- (iii) *Dehn twist composition $M = T_1 \circ T_2 \circ T_3$ satisfies $\|M - I\|_{L^2} \gg \varepsilon$ for small ε ,*

then the family is a genuine derived $(2,1)$ -stack with nontrivial 2-morphisms in homological degree 2, and is not smoothable to a classical moduli space.

Corollary 1.2. *The BALBc opiate/norcain neural system satisfies all three conditions of Theorem 1.1 with $\|M - I\|_{L^2} = 3.00$, implying the system is a genuine derived $(2,1)$ -moduli stack. Moreover, consciousness levels (measured as coherence and oscillation frequency) directly correspond to chamber occupancy in the derived fiber.*

2 Quiver Path Algebra Generation from BALBc Connectome Atlas

2.1 Motivation: From Connectome Data to Algebraic Structure

The BALBc connectome atlas provides a three-level hierarchical representation: individual neurons (nodes), white-matter axons connecting them (edges), and anatomical brain regions (regional aggregation). The challenge is to extract an algebraic quiver structure that preserves

the geometric and topological information at the regional scale while enabling A-infinity-algebra computations.

This section describes a six-phase pipeline that converts raw connectome atlas data into a weighted quiver $Q = (Q_0, Q_1, w)$, where:

$$Q_0 = \{CA1sp, BLA, HY, HPF, sAMY, LA\} \quad (\text{six regions} = \text{vertices}) \quad (1)$$

$$Q_1 = \{f_{ij} : i, j \in Q_0, i \neq j\} \quad (\text{region-pair flows} = \text{arrows}) \quad (2)$$

$$w_{ij} : Q_1 \rightarrow \mathbb{R}^+ \quad (\text{geometric capacities} = \text{weights}) \quad (3)$$

The weights w_{ij} are not simply fiber counts; they encode physical properties of the axonal tracts (cross-sectional area, voxel count, curveness) to capture how readily information propagates between regions.

2.2 Phase 1: Node-to-Region Mapping

The BALBc atlas provides two CSV files:

- **node_regions.csv**: One row per neuron (soma), with columns: `id`, `regions` (list of anatomical labels)
- **edges.csv**: One row per axon segment, with columns: `node1id`, `node2id`, `avgCrossSection`, `curveness`, `num_voxels`

Phase 1 Goal: Build a lookup table `node-id` $\rightarrow$ `region-label`.

Algorithm:

1. Read `node_regions.csv` in chunks (500,000 rows per chunk for memory efficiency)
2. For each node, parse the `regions` field (a Python list string) using `ast.literal_eval`
3. Check if any target region $R \in \{CA1sp, BLA, HY, HPF, sAMY, LA\}$ is in the node's region list
4. On first match, assign: `node_to_region[node_id] = R` and break
5. Result: Dictionary mapping approximately 10^5 to 10^6 node IDs to their canonical region

Output: A dictionary `node_to_region` with `length` = number of indexed neurons (typically 10^5 – 10^6).

2.3 Phase 2: Edge Processing with Geometric Impedance

Raw edges in the atlas record individual axon segments. To aggregate them into region-pair flows, we:

1. Read `edges.csv` in chunks (1,000,000 rows per chunk)
2. For each edge, map the source and target node IDs to region labels using `node_to_region`
3. Filter edges that connect two different regions (exclude within-region and unmapped edges)
4. Compute a geometric weight for each edge based on physical properties

2.3.1 Geometric Weight Formula

For an axon segment connecting regions i and j :

$$w_{\text{edge}} = \frac{A_{\text{cross}} \cdot V_{\text{voxels}}}{\kappa} \quad (4)$$

where:

$$A_{\text{cross}} = \text{average cross-sectional area of the axon} \quad (5)$$

$$V_{\text{voxels}} = \text{number of voxels along the axon path} \quad (6)$$

$$\kappa = \text{curveness} = \text{arc length/Euclidean distance} \quad (7)$$

Physical Interpretation:

- **Numerator** ($A_{\text{cross}} \times V_{\text{voxels}}$): Total volume of the axon, a proxy for conductance. Larger diameter and longer paths carry more information.
- **Denominator** (κ): Curveness penalty. A straight path ($\kappa \approx 1$) has low impedance. Highly curved paths ($\kappa \gg 1$) have high impedance, representing circuitous routing that delays signal propagation.

2.3.2 Aggregation to Region Pairs

After weighting, aggregate all edges between region pair (i, j) :

$$w_{ij} := \sum_{\text{edges } e: e \text{ connects } i \text{ and } j} w_e = \sum_e \frac{A_{\text{cross}}(e) \cdot V_{\text{voxels}}(e)}{\kappa(e)} \quad (8)$$

The result is a dictionary `consolidated_flows` mapping tuple $(i, j) \rightarrow w_{ij}$.

Output: Dictionary with approximately 20–30 entries (one per directed region pair actually present in the data).

2.4 Phase 3: Arrow Definition

For each region pair (i, j) with $w_{ij} > 0$, define an arrow in the quiver:

$$f_{ij} : i \rightarrow j \in Q_1 \quad (9)$$

The arrow is a formal generator of the path algebra $\mathbb{T}Q$. The weight w_{ij} is not yet part of the algebraic structure; it will appear in the relations.

Arrow Naming Convention: f_{ij} denotes the flow from region i to region j .

Output: A list of arrows suitable for input to GAP (Groebner Algebra Package) or other quiver algebra software.

2.5 Phase 4: Hochschild Relations from Geometric Flows

The key insight is that the path algebra relations should encode associativity constraints derived from the connectome geometry. Specifically, for any triple of composable arrows $f_{ij} \circ f_{jk}$, we enforce a Hochschild relation that reflects the geometric coherence of multi-hop paths.

2.5.1 Associative Coefficient

For each ordered triple (i, j, k) where edges (i, j) and (j, k) both exist, compute:

$$\gamma_{ijk} := \frac{w_{ij} \cdot w_{jk}}{w_{ik}} \quad (10)$$

where w_{ik} is the direct flow between i and k (if it exists; otherwise set to a default anchor value such as 1.0).

Geometric Interpretation:

- If $\gamma_{ijk} \approx 1$, the two-hop path $i \rightarrow j \rightarrow k$ has similar capacity to the direct path, suggesting geometric congruence.
- If $\gamma_{ijk} \gg 1$, the two-hop path carries much more information, suggesting a “detour” with high conductance but circuitous routing. This is an obstructed path in the A-infinity sense.
- If $\gamma_{ijk} \ll 1$, the direct path is much more efficient, indicating that the middle region j acts as a bottleneck.

2.5.2 Relation Definition

For each valid triple, generate the relation:

$$f_{ij} \cdot f_{jk} = \gamma_{ijk} \cdot f_{ik} \quad (11)$$

This relation is written in the form:

$$f_{ij} * f_{jk} - \gamma_{ijk} \cdot f_{ik}$$

which, when set to zero in the path algebra quotient, imposes the constraint.

Detection of Obstruction:** If $|\gamma_{ijk}| > 1000$, a warning is issued:

$$\text{“!!! Large curvature detected at } i \rightarrow j \rightarrow k : \text{coeff} = \gamma_{ijk}''$$

This flags regions of the connectome with unusually high multi-hop impedance, which may correspond to consciousness-critical bottlenecks during drug-induced crises.

Output: A list of approximately 50–100 relations, one per valid triple.

2.5.3 Relation Magnitude as Hochschild Obstruction

Note that the coefficient γ_{ijk} is a scalar, not a Hochschild 2-cocycle. However, the existence and magnitude of the relation itself captures the degree to which associativity fails in the connectome:

$$\text{HH}^2 \text{ obstruction magnitude} \propto \sum_{(i,j,k)} |\gamma_{ijk} - 1| \quad (12)$$

During crises, these coefficients become highly anomalous (large deviations from 1), causing the Hochschild dimension $\dim \text{HH}^2(t)$ to spike (as observed in the 21-panel dashboard, Panel 6).

2.6 Phase 5: Loop Relations and Idempotent Structure

A loop (2-cycle) occurs when arrows exist in both directions: f_{ij} and f_{ji} .

For each such pair, compute:

$$\ell_{ij} := (w_{ij} \cdot w_{ji}) \mod 101 \quad (13)$$

The modulus 101 is chosen to work over the finite field $\mathbb{F}_{101}$ in GAP. It provides numerical stability while preserving the topological information.

2.6.1 Loop Relation Definition

Define the relation:

$$f_{ij} \cdot f_{ji} = \ell_{ij} \cdot e_i \quad (14)$$

where e_i is the idempotent associated with region i (the identity element on region i 's subspace in the path algebra).

Algebraic Meaning: The composition of a round-trip flow returns to the starting region with a weighted identity, encoded as the idempotent. The weight ℓ_{ij} is the loop “charge.”

Physical Meaning: Bidirectional flows between two regions create feedback loops. Their combined conductance, modulo the field characteristic, determines the idempotent's coefficient.

Output: Approximately 5–10 loop relations, one per bidirectional region pair.

2.7 Phase 6: GAP Quiver Algebra Code Generation

The accumulated arrow and relation data are translated into GAP (Computer Algebra System) code, which can compute the algebra's properties: dimension, Hochschild cohomology, Cartan matrix, etc.

2.7.1 GAP Code Structure

The generated file `brain_complex_quiver_FIXED.g` contains:

```
LoadPackage("qpa");
k := GF(101);                # Field with 101 elements
Q_vertices := [CA1sp, BLA, ...]; # 6 region vertices
Q_arrows := [[i, j, f_ij], ...]; # Arrow definitions
Q := Quiver(Q_vertices, Q_arrows); # Build quiver
A := PathAlgebra(k, Q);        # Path algebra over GF(101)
rels := [f_ij*f_jk - gamma*f_ik, ...]; # Relations
I := Ideal(A, rels);           # Ideal generated by relations
B := A / I;                   # Quotient algebra
HH2 := HochschildCohomology(B, 2); # Compute HH^2
```

2.7.2 Computational Output

Running the GAP code yields:

- **Dimension of B :** Total dimension of the quotient algebra
- **Dimension of $\text{HH}^2(B)$:** Hochschild 2-cohomology, the obstruction space
- **Cartan Matrix:** $C_{ij} = \dim \text{Hom}(e_i, e_j)$ for regions i, j

These outputs feed directly into the A-infinity computation pipeline (Section ??).

2.8 Key Design Decisions

2.8.1 Geometric Impedance Formula

The choice to use $(A_{\text{cross}} \cdot V_{\text{voxels}})/\kappa$ rather than simple fiber counts reflects the principle that **information flow is modulated by physical properties**. High curveness (long, winding paths) acts as an impedance that slows signal propagation, making such paths less efficient despite having large volume. This is essential for capturing the dynamics of anesthetic crises: drugs can travel along high-volume but high-impedance routes, causing accumulation in certain regions.

2.8.2 Associative Coefficient Formula

The formula $\gamma_{ijk} = (w_{ij} \cdot w_{jk})/w_{ik}$ is a **dimensionless efficiency ratio**. It measures how efficiently a two-hop path preserves the flow compared to a direct path. In the derived stack framework, this ratio becomes the coefficient of a Hochschild relation, linking geometric data to cohomological structure.

2.8.3 Field Choice: GF(101)

Working over $\mathbb{F}_{101}$ rather than $\mathbb{Q}$ or $\mathbb{R}$ provides:

- Computational stability (finite field operations are bounded)
- Canonical reduction for loop coefficients (modulo 101 avoids unwieldy large numbers)
- Compatibility with GAP’s standard library for quiver algebras

The results are mathematically valid over any field; the choice of 101 is pragmatic.

2.8.4 Treatment of Missing Edges

If (i, k) exists but $(i, j) \rightarrow (j, k)$ do not both exist, the triple is skipped. If (i, k) does not exist, it is treated as an “anchor edge” with weight 1.0, ensuring that γ_{ijk} is well-defined even for sparse connectivity. This avoids division by zero and captures the intuition that missing direct edges allow multi-hop paths to dominate.

2.9 Validation and Sanity Checks

2.9.1 Arrow Count

The number of arrows should match the number of directed region pairs with nonzero flow. For BALBc with 6 regions, the maximum is $6 \times 5 = 30$ arrows (if fully connected). Typical connectomes have 20–25 arrows.

2.9.2 Relation Count

Relations from composable triples and loops. With 6 regions and approximately 25 arrows:

$$\text{Triples} \approx 25 \text{ (one per valid } (i, j, k) \text{ path)} \quad (15)$$

$$\text{Loops} \approx 5 \text{ (one per bidirectional pair)} \quad (16)$$

$$\text{Total} \approx 30 \text{ relations} \quad (17)$$

2.9.3 Coefficient Magnitudes

Coefficients γ_{ijk} should typically lie in the range 0.1 to 100. Values exceeding 1000 or below 0.01 indicate geometric anomalies (e.g., highly curved or disconnected paths) and are flagged for manual inspection.

2.9.4 Consistency with A-Infinity Computation

The quiver and its relations serve as input to the Hochschild cohomology computation described in Section ???. The dimensions reported by GAP should match the $\dim \mathrm{HH}^2$ values computed by the Julia code at $t = 0$ (baseline).

2.10 Integration with Time-Dependent Simulations

In the BALBc simulation, the connectivity can change over time due to drug-induced alterations in local concentrations. A full dynamical treatment would regenerate the quiver and recompute relations at each time step, but this is computationally expensive. Instead:

1. Generate the baseline quiver at $t = 0$ using atlas data
2. Modulate the arrow weights $w_{ij}(t)$ according to Renkin-Crone dynamics
3. At each time step, compute relations using the updated weights
4. Feed the time-varying relations into the A-infinity computation

This approach preserves the algebraic structure while allowing phenomenological dynamics.

2.11 Connection to Perverse Sheaves

The quiver Q and its relation ideal I_t define a stratified singularity locus in the parameter space $X = \text{Spec}(\mathbb{R}[w_{ij}])$. The regions i, j become strata, and the arrows f_{ij} are wall-crossing data. The path algebra quotient $B = (\mathbb{R}Q)/I_t$ then carries a perverse sheaf structure (Section 7.4), with the relations determining the support conditions and wall-crossing functors.

2.12 Summary: From Atlas to Algebra

The six-phase pipeline converts connectome atlas data (voxel-level edges and node-region assignments) into a weighted quiver path algebra. The key steps are:

1. **Phase 1:** Map neurons to brain regions (lookup table)
2. **Phase 2:** Compute geometric capacities using cross-section, voxel count, and curviness
3. **Phase 3:** Define arrows for each region-pair flow
4. **Phase 4:** Generate Hochschild relations from associative coefficients
5. **Phase 5:** Add loop relations for bidirectional pairs
6. **Phase 6:** Translate to GAP algebra code for cohomology computation

This algebraic structure encodes both the connectome’s geometric properties and its topological organization, enabling the derived stack analysis to proceed. The pipeline is implemented in Python (`real_node_region_qpa.py`) and generates GAP code for verification and further computation.

3 Renkin-Crone Blood-Brain Barrier Dynamics

3.1 Biological Background and Mathematical Model

The blood-brain barrier (BBB) is a selective molecular filter separating blood from neural tissue. Small lipophilic molecules (like opiates and norcain) cross readily. However, once in the parenchyma, they may be temporarily sequestered in specific regions, particularly those with high metabolic density or receptor density.

The **Renkin-Crone model** quantifies this trapping/release kinetics. A molecule in region i exists in two compartments:

- **Free:** Available for diffusion and synaptic action,




Figure 1: Fibred derived structure over $Gr(2,4)$ with associahedral and blow-up dynamics.

- **Trapped:** Bound to receptors or sequestered in vesicles.

For molecule type $X \in \{A, B\}$ (opioids, norcain) in region i , define:

- $q_{X,\text{free}}^{(i)}(t)$ = free concentration,
- $q_{X,\text{trap}}^{(i)}(t)$ = trapped concentration,
- $\alpha_{\text{in},X}^{(i)}$ = trapping rate (free $\rightarrow$ trap),
- $\alpha_{\text{out},X}^{(i)}$ = release rate (trap $\rightarrow$ free).

The compartmental kinetics are:

$$\frac{dq_{X,\text{free}}^{(i)}}{dt} = -\alpha_{\text{in},X}^{(i)} \cdot q_{X,\text{free}}^{(i)} + \alpha_{\text{out},X}^{(i)} \cdot q_{X,\text{trap}}^{(i)} + (\text{diffusion terms}) \quad (18)$$

$$\frac{dq_{X,\text{trap}}^{(i)}}{dt} = \alpha_{\text{in},X}^{(i)} \cdot q_{X,\text{free}}^{(i)} - \alpha_{\text{out},X}^{(i)} \cdot q_{X,\text{trap}}^{(i)} \quad (19)$$

Definition 3.1 (Renkin-Crone Compartment and Consciousness). The effective free concentration at region i is:

$$C_i(t) := \frac{q_{X,\text{free}}^{(i)}(t)}{q_{X,\text{free}}^{(i)}(t) + q_{X,\text{trap}}^{(i)}(t)}$$

the fraction not trapped. Consciousness in region i depends on $C_i > \text{threshold}$ (typically 0.3 in simulations). When C_i drops below threshold, the region enters unconsciousness.

3.2 Implementation in BALBc

In the BALBc connectome simulation, trapping rates are defined per-region and per-molecule:

$$\alpha_{\text{in},A} = \{0 \text{ (CA1sp)} : 0.15, 2 \text{ (BLA)} : 0.12\} \quad (\text{opioids}), \quad (20)$$

$$\alpha_{\text{out},A} = \{0 : 0.015, 2 : 0.012\} \quad (\text{release } 10\times \text{ slower}), \quad (21)$$

$$\alpha_{\text{in},B} = \{0 : 0.15, 2 : 0.12\} \quad (\text{norcain}), \quad (22)$$

$$\alpha_{\text{out},B} = \{0 : 0.015, 2 : 0.012\}. \quad (23)$$

The key insight is that CA1sp (region 0) and BLA (region 2) are “loopy nodes” with high metabolic activity and thus higher trapping rates. This asymmetry explains why these regions are more vulnerable to consciousness collapse during drug administration.

Doses are applied at specific times ($t = 2.5s, 6.0s, 9.5s$) with large amount (4.0 units), creating the crisis-recovery cycle observed in the 21-panel dashboard (Panel 2). The recovery dynamics depend critically on the release rates: slower α_{out} means the drug stays trapped longer, prolonging unconsciousness.

4 Grassmannian Wavelets and Gr(2,4) Structure

4.1 Why Gr(2,4): Geometric Motivation

The Grassmannian $\text{Gr}(2, 4)$ of 2-planes in $\mathbb{C}^4$ naturally parametrizes **2-dimensional subspaces** of neural state space. This is geometrically natural for consciousness:

- Each of the six BALBc regions contributes oscillatory modes (e.g., alpha 8-12 Hz and theta 4-8 Hz bands).
- The intersection/span of these oscillations across regions defines a 2-plane in a larger oscillatory space.
- The Plücker embedding encodes the geometry of all 2-planes coherently.
- Transitions between different consciousness states correspond to jumps between Plücker points on $\text{Gr}(2, 4)$.

4.2 Plücker Coordinates and Klein Quadric

A 2-plane in $\mathbb{C}^4$ can be specified by two basis vectors $v_1, v_2 \in \mathbb{C}^4$. The **Plücker coordinates** are the $\binom{4}{2} = 6$ minors:

$$p_{ij} := \det \begin{pmatrix} v_1^i & v_1^j \\ v_2^i & v_2^j \end{pmatrix}, \quad 1 \leq i < j \leq 4 \quad (24)$$

These satisfy the **Klein quadric relation**:

$$q(p) := p_{12}p_{34} - p_{13}p_{24} + p_{14}p_{23} = 0 \quad (25)$$

Definition 4.1 (Plücker Normalization). Since Plücker coordinates are defined up to scaling, we normalize:

$$\sum_{i < j} |p_{ij}|^2 = 1$$

In the BALBc simulation, Plücker coordinates are extracted from the oscillation matrix at each timestep. Panel 10 of the 21-panel dashboard verifies that the Klein quadric constraint is satisfied to high precision (error $< 10^{-6}$), confirming that the system indeed moves on $\text{Gr}(2, 4)$.

4.3 Wavelet Decomposition Indexed by Plücker Coordinates

The consciousness signal $C(t)$ can be decomposed in a wavelet basis naturally living on $\text{Gr}(2, 4)$:

$$C(t) = \int_0^\infty d\omega a(\omega) \psi_\omega(t; p(t)) \quad (26)$$

where $\psi_\omega(t; p)$ are wavelets with frequencies indexed by Plücker coordinates:

$$\psi_\omega(t; p) := \frac{1}{\sqrt{\omega}} (\cos(\omega t + \phi(p)) + i \sin(\omega t + \phi(p))) \quad (27)$$

where $\phi(p)$ depends on the Plücker point $p = (p_{12}, \dots, p_{23})$.

Remark 4.2 (Wavelet Energy as Crisis Indicator). The wavelet energy is:

$$E_\omega := |a(\omega)|^2$$

High energy at low frequencies ($\omega < 1$) indicates conscious oscillations (smooth, coherent). High energy at high frequencies ($1 < \omega < 10$) indicates crisis/unconsciousness (incoherent, noisy).

In Panel 14 of the 21-panel dashboard, wavelet energy shows exactly this pattern: low during consciousness, rising during crisis phases, then dropping again during recovery.

4.4 Wavelet Zeta Function and Geometric Crisis

Define the wavelet zeta function as:

$$\zeta_W(t; p) := \sum_{n=1}^{\infty} \frac{E_n(p)}{n^{s(t)}} \quad (28)$$

where:

- $E_n(p)$ = energy in the n -th frequency band,
- $s(t) = 1 + \epsilon \cdot M(t; p)$ = time-dependent Riemann zeta exponent,
- $M(t; p)$ = mismatch between algebraic and geometric sliders (defined in Section 8).

Crisis signature: When zeta poles approach the critical line, ζ_W exhibits rapid oscillations. This is the geometric slider crisis (Σ_G), visible in Panel 2 (aligned_timeseries.png, red line) of the empirical figures. The log-scale plot shows zeta magnitude fluctuating wildly (10^0 to 10^2) during crisis snapshots 3 – 8.

5 Spectral Zeta Functions: Ihara, Wavelet, Hochschild

5.1 Ihara Zeta and Graph Topology

For a graph $G = (V, E)$ with adjacency matrix A , the **Ihara zeta function** is:

$$\zeta_I(u) := \prod_{p \text{ prime closed walk}} (1 - u^{|p|})^{-1} \quad (29)$$

where the product is over all prime cycles in the graph, and $|p|$ is the cycle length.

Theorem 5.1 (Bass, Ihara). *For a finite connected graph:*

$$\zeta_I(u)^{-1} = (1 - u^2)^{|E| - |V| + 1} \det(I - uA + u^2Q)$$

where $Q = \text{diag}(\deg_0, \dots, \deg_{n-1})$ is the degree matrix.

5.2 Ihara Pole Radius and Monodromy Signature

The rightmost pole of $\zeta_I(u)$ is at $u = u_*$ where:

$$u_* = \frac{1}{\lambda_2 + 2\sqrt{\lambda_2 - 1}} \quad (30)$$

where λ_2 is the second-largest eigenvalue of the adjacency matrix.

The **pole radius** is:

$$r_I := \frac{1}{u_*} \quad (31)$$

Remark 5.2 (Monodromy Signature from Pole Persistence). In `bridge_pole_radius.png`, the pole radius rises from 200 $\rightarrow$ 420 during crisis (snapshots 10-15), then falls to 250 post-crisis (snapshots 18-25). The **failure to return to baseline** (200) is the monodromy signature. This is exactly the ghost signal: even after HH^2 clears (panel 6), the pole radius remains elevated, indicating persistent topological structure.

5.3 Hochschild Cohomology and A_∞ -Zeta

Define the Hochschild 2-cocycle as the primary algebraic obstruction to the associativity of higher A_∞ -operations. Explicitly, for a path algebra with relations, HH^2 measures the dimension of the space of 2-cocycles satisfying the Hochschild differential condition. In code, this is computed via Julia’s `gerstenhaber_compute_A_infty` function, which solves the Stasheff identities recursively.

The magnitude $\|HH^2(t)\|$ spikes when the path algebra structure develops new relations (obstacles to quasi-isomorphisms). When $\|HH^2\| \rightarrow 0$, all 1-morphisms are invertible (path algebra is formal).

6 Region Graph Construction and Integration with Dynamics

6.1 Overview: From Voxel-Level Atlas to Regional Network

The BALBc connectome atlas provides voxel-level segmentation of the brain: each voxel is annotated with its anatomical region (e.g., CA1sp, BLA, HY). The challenge is to construct a simplified regional graph that preserves connectivity information while enabling efficient simulation of Renkin-Crone pharmacokinetics and A_∞ -algebra updates.

The pipeline consists of four stages:

1. **Voxel-to-Region Mapping:** Parse the annotated node file to assign each voxel to its region
2. **Edge Aggregation:** Sum axon segments connecting each region pair
3. **Centroid Computation:** Calculate the geometric center of each region
4. **Graph Export:** Save the regional network as CSV files for use in simulation and A_∞ -algebra computation

6.2 Stage 1: Voxel-to-Region Mapping

Input: `node_regions_clean.csv`, a CSV file with columns:

- **id:** Unique voxel identifier (integer)

- **regions:** Anatomical label(s), stored as a Python list string, e.g., “[‘CA1sp’]” or “[‘CA1sp’, ‘Other’]”
- **pos_x, pos_y, pos_z:** Voxel coordinates (microns)

Algorithm:

for each voxel row in node_regions_clean.csv:

1. Parse the ‘regions’ string field as a Python list using `ast.literal_eval()`
2. Take the first region in the list (most voxels belong to exactly one region)
3. Store: `node_to_region[voxel_id] = first_region`

Result: A dictionary mapping voxel IDs to region labels. For BALBc with 6 target regions {CA1sp, BLA, HY, HPF, sAMY, LA}, this typically yields 10^5 – 10^6 voxel assignments.

Data structure:

$$\text{node_to_region} : \mathbb{Z}_{\text{voxel}} \rightarrow \{\text{CA1sp, BLA, HY, HPF, sAMY, LA}\} \quad (32)$$

6.3 Stage 2: Edge Aggregation by Region Pair

Input: BALBc-no1-iso3um_stitched_segmentation_bulge_size_3.0_edges.csv, the full connectome edge file with columns:

- **node1id, node2id:** Source and target voxel IDs
- **length:** Axon segment length (microns)
- **volume:** Cross-sectional area $\times$ length (cubic microns)
- **curveness:** Curvature metric (arc length / Euclidean distance)

Algorithm:

1. Filter edges: keep only those where both node1id and node2id are in `node_to_region`
2. For each surviving edge:

$$\text{region_weights}[(\text{reg1}, \text{reg2})] += \text{edge_weight} \quad (33)$$

where `edge_weight` is typically the axon length (or volume, or some combination)

3. Result: dictionary mapping directed region pairs to aggregate weights

Physical Interpretation:

- **Additive:** Multiple axon segments between the same region pair accumulate their weights. A large weight indicates strong physical connectivity.
- **Directed:** The region pair (i, j) may have a different weight than (j, i) , reflecting the anatomy of the connectome.

Output: A dictionary:

$$\text{region_weights} : (\text{region}, \text{region}) \rightarrow \mathbb{R}^+ \quad (34)$$

Typically 20–30 entries (one per directed region-pair connection).

6.4 Stage 3: Centroid Computation

To enable visualization and spatial analysis, compute the geometric center of each region.

Algorithm:

1. For each region r , collect all voxels assigned to that region:

$$V_r = \{v : \text{node_to_region}[v] = r\} \quad (35)$$

2. Compute the mean position:

$$\text{centroid}(r) = \frac{1}{|V_r|} \sum_{v \in V_r} (\text{pos_x}[v], \text{pos_y}[v], \text{pos_z}[v]) \quad (36)$$

Output: For each region, a 3D centroid in micron coordinates.

Use Cases:

- Visualization of the regional graph in 3D space
- Distance metrics between regions (Euclidean distance between centroids)
- Geometric structure of the derived stack (spatial stratification)

6.5 Stage 4: Graph Export

The regional network is exported as two CSV files:

6.5.1 regions.csv

```
region,index,centroid_x,centroid_y,centroid_z
CA1sp,0,x_c,y_c,z_c
BLA,1,x_c,y_c,z_c
...
```

Columns:

- **region:** Region name (string)
- **index:** 0-indexed region number (integer, for matrix operations)
- **centroid_x, centroid_y, centroid_z:** Mean coordinates (float, microns)

Size: 6 rows (one per target region)

6.5.2 region_edges.csv

```
src_idx,tgt_idx,weight
0,0,1659959.67
1,1,71936.62
1,2,7939.20
...
```

Columns:

- **src_idx:** Source region index (integer)
- **tgt_idx:** Target region index (integer)
- **weight:** Aggregate edge weight from src to tgt (float)

Size: 30 rows (one per directed region-pair connection)

6.6 Integration with Renkin-Crone Dynamics

The regional network (regions.csv and region_edges.csv) serves as the foundation for Renkin-Crone molecular dynamics:

$$\frac{dq_{X,free}^{(i)}}{dt} = -\alpha_{in,X}^{(i)} q_{X,free}^{(i)} + \alpha_{out,X}^{(i)} q_{X,trap}^{(i)} + \sum_j F_{ij}(t) \quad (37)$$

where:

- $q_{X,free}^{(i)}$: Free (untrapped) concentration of molecule X in region i
- $q_{X,trap}^{(i)}$: Trapped concentration
- $\alpha_{in,X}^{(i)}, \alpha_{out,X}^{(i)}$: Region-specific trapping/release rates
- $F_{ij}(t)$: Flow term from region j to region i , governed by the edge weight w_{ij}

6.6.1 Flow Term Dynamics

The flow from region j to region i is proportional to:

$$F_{ij}(t) = \text{transport_coeff} \times w_{ij} \times (q_j(t) - q_i(t)) \quad (38)$$

where:

- w_{ij} is the static edge weight from region_edges.csv
- $q_j(t) - q_i(t)$ is the concentration gradient (driving the flow)
- **transport_coeff** is a rate constant (e.g., 0.01 per second)

The edge weight w_{ij} represents axon bundle capacity: large w_{ij} means fast molecular transport; small w_{ij} means slow transport (bottleneck).

6.7 Real-Time A_∞ -Algebra Updates from Dynamics

6.7.1 Motivation: Time-Varying Edge Weights

In the simulation, the Renkin-Crone equations evolve the molecular concentrations $q(t)$ at each region. As $q(t)$ changes, the effective connectivity of the network changes:

$$w_{ij}(t) = w_{ij}^{static} \times \text{modulation}(q_i(t), q_j(t)) \quad (39)$$

For example, regions with low free concentration may have reduced effective connectivity (local anesthesia effect). The weight modulation captures this dynamical change.

6.7.2 A_∞ -Algebra Recomputation at Each Snapshot

The simulation runs for 25 seconds, sampled at 0.5-second intervals, yielding 50 snapshots. At selected snapshots (e.g., every 10 steps or during critical events), the simulation:

1. **Collect current weights:** Extract the current edge weights $w_{ij}(t)$ from the Renkin-Crone state
2. **Build weight dictionary:** Construct **current_weights** = {(i,j): $w_{ij}(t)$ for all edges}
3. **Call Julia A_∞ extractor:** Execute **gerstenhaber_compute_** A_∞ with the updated weights

4. **Extract crisis data:** Julia returns $HH^2(t)$, $m_6(t)$, prime paths, support loci, perversity assignments
5. **Log results:** Store the crisis metrics in the dashboard

6.7.3 Julia-Python Interface

The communication occurs via JSON and temporary files:

Python (BALBc_Opiate_Norcain.py):

1. At snapshot t , gather current_weights
2. Write to JSON file: temp_weights.json
3. Call Julia subprocess:
julia curved_hh2_sparse_refactored.jl --weights temp_weights.json
4. Read output: temp_hh2.json, temp_m6.json, temp_paths.json
5. Parse and store in Python data structures
6. Continue Renkin-Crone simulation with next timestep

Julia (curved_hh2_sparse_refactored.jl):

1. Read weights from JSON
2. Recompute path algebra basis
3. Compute d_2 , d_3 , d_4 (sparse boundary matrices)
4. Solve for HH^2 dimension
5. Compute m_3 , m_4 , m_5 , m_6 obstructions
6. Extract prime paths and support loci
7. Write results to JSON
8. Exit

6.7.4 Time-Varying Crisis Ideal

The crisis ideal evolves in real-time:

$$I_t = \langle HH^2(t), m_6(t), \Delta^{-1}(t), disc(\zeta_I(t)), disc(\zeta_W(t)) \rangle \quad (40)$$

Each generator depends on the current edge weights $w_{ij}(t)$:

- $HH^2(t)$: Hochschild 2-cohomology dimension (from path algebra with weights $w_{ij}(t)$)
- $m_6(t)$: Main A_∞ -obstruction magnitude (computed from m_3 , m_4 , m_5)
- $\Delta^{-1}(t)$: Inverse discriminant (Grassmannian structure, from wavelet zeta)
- $disc(\zeta_I(t))$: Ihara zeta discriminant
- $disc(\zeta_W(t))$: Wavelet zeta discriminant

6.8 Two-Slider Synchronization

The region graph construction enables the **two-slider model**:

1. **Algebraic Slider (X)**: Edge weights $w_{ij}(t)$ evolve via Renkin-Crone dynamics. Changes in regional molecular concentrations modulate connectivity, affecting the path algebra structure and $HH^2(t)$.

2. **Geometric Slider (Gr(2,4)):** Grassmannian parameters (Plücker coordinates) evolve independently via wavelet dynamics. Crisis occurs when these parameters approach the discriminant Δ .
3. **Coupling:** The mismatch $M(w, \gamma)$ between algebraic and geometric crisis events determines overall consciousness state. When both sliders approach crisis simultaneously, the system exhibits dual-crisis (full unconsciousness).

Synchronization Mechanism: At each snapshot, the Python code:

1. Updates $w_{ij}(t)$ based on $q(t)$ (Renkin-Crone)
2. Passes $w_{ij}(t)$ to Julia for A_∞ -recomputation
3. Independently computes Plücker coordinates $p(t)$ and wavelet zeta
4. Combines both signals into the crisis ideal I_t

This ensures that the algebraic and geometric sliders remain synchronized throughout the simulation, enabling the two-slider model to unfold realistically.

6.9 Data Structures for Efficiency

6.9.1 regions.csv in Python

Loaded as a Pandas DataFrame:

```
regions_df = pd.read_csv("regions.csv")
self.region_names = regions_df['region'].tolist()          # ["CA1sp", "BLA", ...]
self.region_centroids = regions_df[['centroid_x', 'centroid_y', 'centroid_z']].values
```

6.9.2 region_edges.csv in Python

Loaded as a Pandas DataFrame and converted to dictionaries for fast access:

```
edges_df = pd.read_csv("region_edges.csv")
self.edges = [(int(row.src_idx), int(row.tgt_idx)) for _, row in edges_df.iterrows()]
self.edge_weights = {(row.src_idx, row.tgt_idx): row.weight for _, row in edges_df.iterrows()}
```

Edge weights dictionary: Maps $(i, j) \rightarrow w_{ij}$, enabling $O(1)$ lookup during dynamics updates.

6.9.3 Self-Loops

Self-loops (recirculation within a region) are added explicitly:

$$w_{ii} = 1.0 \quad \text{for all regions } i \quad (41)$$

These represent local molecular exchange and prevent isolation of individual regions.

6.10 Validation and Sanity Checks

6.10.1 Region Count

The final region list should contain exactly 6 regions (for BALBc target): CA1sp, BLA, HY, HPF, sAMY, LA.

Check: `len(region_list) == 6`

6.10.2 Edge Count

The number of directed edges should be in the range 20–30 (typically 25–28 for BALBc).

Check: `20 <= len(edges) <= 30`

6.10.3 Weight Magnitudes

Region pair weights should be positive and span multiple orders of magnitude (from 10^3 to 10^7 microns, reflecting variation in axon bundle size).

Check: `min(weights) > 0 and max(weights) / min(weights) > 100`

6.10.4 Centroid Validity

Centroid coordinates should be within the voxel coordinate range of the atlas (typically 0–2000 microns in each dimension for BALBc).

Check: `all(0 <= c <= 2000 for centroid in centroids for c in centroid)`

6.10.5 Symmetry in Self-Loops

Self-loop weights should be positive and moderate (not excessively large, which would cause regions to decouple).

Check: `0 < w_ii < max(w_ij) / 10`

6.11 Advantages of This Approach

1. **Data Reduction:** From 10^6 voxels to 6 regions; from 10^7 edges to 30 region-pair edges. Computation becomes feasible.
2. **Anatomical Fidelity:** Aggregation by anatomical region preserves neurobiology; weights reflect actual axon bundle sizes.
3. **Geometric Preservation:** Centroid computation allows spatial visualization and enables connection to Grassmannian structure (wavelet wavelengths, Plücker coordinates).
4. **Dynamic Flexibility:** Edge weights can be modulated in real-time without rebuilding the entire graph; A_∞ -algebra updates are swift.
5. **Modularity:** The region graph is decoupled from the dynamics; changes to Renkin-Crone parameters or A_∞ -algebra design do not require regenerating the graph.

6.12 Summary: From Atlas to Network Dynamics

The `build_region_graph.py` script performs four key tasks:

1. **Voxel Mapping:** Assign each voxel to its anatomical region
2. **Edge Aggregation:** Sum connectome edges by region pair, weighted by axon length
3. **Centroid Computation:** Calculate geometric centers for visualization and analysis
4. **CSV Export:** Save the regional network (`regions.csv`, `region_edges.csv`)

The resulting region graph serves as the foundation for:

- **Renkin-Crone Dynamics:** Molecular flow between regions governed by edge weights

- **A_∞-Algebra Recomputation:** Time-varying weights feed into Julia A_∞ extractor at each snapshot
- **Two-Slider Model:** Algebraic (HH²) and geometric (zeta) crises evolve in lockstep via the shared regional connectivity
- **Crisis Ideal:** Five generators $\langle HH^2, m_6, \Delta^{-1}, disc(\zeta_I), disc(\zeta_W) \rangle$ track consciousness transitions

This architecture enables the complete BALBc simulation pipeline: atlas data → regional network → pharmacokinetics → A_∞-dynamics → consciousness.

7 A_∞-Algebras, Quivers, and Prime Higher Ideals

7.1 From BALBc Atlas to Weighted Quiver

The BALBc connectome is represented as a directed weighted quiver $Q = (Q_0, Q_1)$ where:

- $Q_0 = \{\text{CA1sp, BLA, HY, HPF, sAMY, LA}\}$ (six anatomical regions),
- Q_1 contains an arrow $x \rightarrow y$ for each white-matter tract with non-zero fiber count,
- Each arrow carries a time-dependent weight $w_{xy}(t)$ derived from tractography volume and modulated by drug concentrations (opiate/norcain) and Toda flow.

The path algebra $\mathbb{C}Q$ (or $\mathbb{R}Q$) is the $\mathbb{C}$ -vector space spanned by all directed paths, with multiplication given by concatenation (zero when not composable). This algebra is the starting point for the A_∞ deformation.

7.2 A_∞-Algebra Structure from Stasheff Identities

Classical path algebras are associative, but the dynamic system exhibits higher obstructions. We therefore replace strict associativity by an A_∞-structure, i.e., a collection of multilinear maps

$$m_n : A^{\otimes n} \rightarrow A, \quad n \geq 1,$$

with m_2 the ordinary product and m_3, m_4, m_5, m_6 higher homotopies correcting the failure of associativity. The maps are required to satisfy the Stasheff identities (coherence relations); the first non-trivial relation is:

$$m_2(m_2(a, b), c) - m_2(a, m_2(b, c)) = \partial m_3(a, b, c),$$

where ∂ is the Hochschild differential. For $n = 6$, the identity involves all lower maps and provides a measure of the “obstruction” at order six:

$$\sum_{r+s+t=6} (-1)^{r+st} m_{r+1+t}(1^{\otimes r} \otimes m_s \otimes 1^{\otimes t}) = 0.$$

7.2.1 Computing $m_2, \dots, m_6$ for the BALBc Quiver

Using the explicit relations derived from the connectome edge weights, the algorithm:

1. Builds a basis of the path algebra up to length 6 (idempotents and arrows).
2. Computes the multiplication table m_2 (concatenation with coefficients from the geometry).
3. Computes the associator m_3 as the difference $m_2(m_2(a, b), c) - m_2(a, m_2(b, c))$.

4. Propagates the Stasheff identities recursively to obtain m_4 , m_5 , and finally m_6 as the residual after correcting all lower-order obstructions. This is done via the function `gerstenhaber_compute_A_in` in the Julia module `curved_hh2_sparse_refactored.jl`.

The total mass of m_6 ,

$$\|m_6\| = \sum_{\text{inputs } a_1 \dots a_6} \sum_{\text{output } b} |\text{coeff}(m_6(a_1, \dots, a_6), b)|,$$

serves as a scalar indicator of higher coherence failure and is the second generator of the crisis ideal.

7.3 Prime Paths and Prime Higher Ideals

From the m_6 tensor we extract **prime paths**: indecomposable 6-tuples of arrows with high obstruction weight that cannot be split into two subpaths of comparable weight. Each prime path generates a **prime higher ideal** by closing under all operations $m_3, \dots, m_6$:

$$I = \langle \text{prime path} \rangle_{\text{closure}}.$$

The support score of a basis element x is

$$\text{supp}(x) = \sum_{n=3}^6 \sum_{\text{inputs } \mathbf{a} \ni x} \|m_n(\mathbf{a})\|,$$

where $\|\cdot\|$ is the Euclidean norm of the output coefficients. The **annihilator** $\text{Ann}(I)$ consists of elements with zero support, and the **support locus** $\text{Supp}(I)$ is the set of elements with positive support.

7.4 Perverse Sheaves and Perverse Schobers

The total support of each prime higher ideal is normalised to an integer perversity $p(I) \in \{0, 1, 2\}$ via a linear map. This defines a perverse t-structure on the derived category of representations of the quiver.

A **perverse schober** is a categorification: it assigns to each stratum a triangulated category (e.g., the derived category of quiver representations supported on that stratum) and to each wall-crossing (flip) a functor (a spherical twist or mutation). The perversity numbers become the “charge” that determines the support condition.

7.5 Associahedron and Beam-Search Navigation

The graph associahedron K_6 for the BALBc support graph has vertices = **maximal tubings** (collections of pairwise compatible connected subsets of regions) and edges = **flips** (replace one tube by another). There are 42 such vertices.

A beam-search navigator walks on this polytope:

1. At each snapshot, compute candidate tubes (connected subsets) and score each using the current A_∞ -obstruction data (higher products, prime paths, cup product, etc.).
2. Greedily complete a candidate set to a maximal tubing.
3. Generate neighbors by adding, removing, or replacing a tube, then complete greedily.
4. Keep the top 7 tubings (beam width) and update the “dominant region” vector via monodromy matrix.

The best tubing (vertex) minimises the obstruction score and maximises coherence; flips correspond to moving to an adjacent vertex. The sequence of best tubings over time gives the **associahedron walk**.

The monodromy matrix M is built from prime paths; its action on the transport vector (dominant region) gives the non-trivial holonomy. The product of three Dehn twists (coherence condition) is computed as $M = T_1 T_2 T_3$, and its deviation from the identity matrix quantifies the obstruction to flatness.

7.6 Toda Flow: Isospectral Deformations with Damping

The wavelet state (q_A, q_B, C) evolves not only through drug transport but also via an isospectral flow that preserves the eigenvalues of a certain Lax matrix while damping off-diagonal correlations. This flow, known as the **Toda flow**, is given by

$$\frac{dL}{dt} = [B(L), L],$$

where L is a symmetric tridiagonal matrix (the Lax matrix) and $B(L)$ is its skew-symmetric part.

In our system, L is built from the wavelet parameters

$$L = \begin{pmatrix} a & \phi & \kappa \\ \phi & b & \frac{1}{2}(\omega_1 + \omega_2) \\ \kappa & \frac{1}{2}(\omega_1 + \omega_2) & \bar{C} \end{pmatrix},$$

where a, b are amplitudes, ϕ, κ coupling coefficients, ω_1, ω_2 frequencies, and $\bar{C}$ the mean consciousness.

To incorporate dissipation and external forcing, we add a damping term and a septal drive:

$$\frac{dL}{dt} = \varepsilon[B(L), L] - \lambda(L - \text{diag}(L)) + \nu \sin(2\pi \cdot 8t) \mathbb{I}_3,$$

where:

- ε measures the strength of the isospectral part,
- λ is a damping rate,
- ν is the amplitude of a periodic septal (theta-band) drive at 8 Hz.

From the derived stack perspective, the Toda flow acts as a **parallel transport** of the spectral sheaf along the time direction. The isospectral part corresponds to a unitary transformation, while the damping and drive modify the metric on the base.

7.7 Spectral and Perverse Sheaves on the Quiver

7.7.1 Spectral Sheaf

Let Q be the quiver. At each time t , define a cellular sheaf $\mathcal{F}_t$ on Q as follows:

- For each vertex $v \in Q_0$, the stalk $\mathcal{F}_t(v)$ is a d -dimensional vector space.
- For each arrow $e : u \rightarrow v$ with weight $w_{uv}(t)$, the restriction map $\varphi_e : \mathcal{F}_t(u) \rightarrow \mathcal{F}_t(v)$ is a linear map proportional to $\exp(w_{uv}(t))$.

The sheaf Laplacian $\mathcal{L}_t$ is defined as

$$\mathcal{L}_t = \bigoplus_v \left(\sum_{e \text{ out of } v} \varphi_e^\top \varphi_e \right) - \bigoplus_e (\varphi_e + \varphi_e^\top),$$

acting on the total stalk space. Its eigenvalues $\lambda_1(t) \leq \dots \leq \lambda_N(t)$ are computed numerically. The **spectral gap** $\Delta(t) = \lambda_2(t) - \lambda_1(t)$ provides a scalar measure of network coherence.

7.7.2 Perverse Sheaf from Prime Ideals

The strata are defined by the closures of the prime higher ideals. For each stratum S , we assign a perversity $p(S) \in \{0, 1, 2\}$. A **perverse schober** categorifies this by assigning derived categories and functors to flips.

8 The Two-Slider Model and Product Base

8.1 Algebraic Slider: A_∞ -Deformations and Crisis Ideal

Let $X = \text{Spec}(\mathbb{R}[w_{ij}])$ be the affine parameter scheme where w_{ij} are connectome edge weights.

Definition 8.1 (Crisis Ideal - Five Independent Generators). The crisis ideal is:

$$I_t := \langle HH^2(t), m_6(t), \Delta^{-1}(t), \text{disc}(\zeta_I(t)), \text{disc}(\zeta_W(t)) \rangle \subset \mathbb{R}$$

where:

- $HH^2(t)$: Hochschild 2-cocycle magnitude (1-morphism obstruction),
- $m_6(t)$: A_∞ -operation depth-6 (pentagonal coherence failure),
- $\Delta^{-1}(t)$: Inverse spectral gap,
- $\text{disc}(\zeta_I(t))$: Ihara zeta discriminant (graph cycle structure),
- $\text{disc}(\zeta_W(t))$: Wavelet zeta discriminant (Grassmannian pole collision).

All five generators have been validated empirically in the BALBc simulation.

The crisis scheme is:

$$Z_X := V(I_t) \subset X$$

The algebraic crisis locus is denoted $\Sigma_X := \text{Supp}(Z_X)$.

8.2 Geometric Slider: Wavelet-Grassmannian Structure

Let $\text{Gr}(2, 4)$ be the Grassmannian of 2-planes in $\mathbb{C}^4$, embedded in $\mathbb{P}^5$ via Plücker coordinates satisfying the Klein quadric:

$$q_{12}q_{34} - q_{13}q_{24} + q_{14}q_{23} = 0$$

Let $\Delta \subset \text{Gr}(2, 4)$ be the discriminant locus. Define:

$$\Sigma_G := \{\gamma \in \text{Gr}(2, 4) \setminus \Delta : |\zeta_W(\gamma)| > \text{threshold or spectral gap shrinks}\}$$

This is the geometric crisis locus.

8.3 Coupling Locus: Dual-Zeta Mismatch

Define the dual-zeta mismatch:

$$M(w, \gamma) := |\arg(\zeta_I(w)) - \arg(\zeta_W(\gamma))| + ||\zeta_I(w)| - |\zeta_W(\gamma)||$$

The coupling crisis locus is:

$$\Sigma_{\text{int}} := \{(w, \gamma) \in X \times \text{Gr}(2, 4) \setminus \Delta : M(w, \gamma) > \text{threshold}\}$$

8.4 Total Singular Locus: Three Independent Components

Definition 8.2 (Total Singular Locus).

$$\Sigma = \Sigma_X \cup \Sigma_G \cup \Sigma_{\text{int}} \subset X \times (\text{Gr}(2, 4) \setminus \Delta)$$

Theorem 8.3 (Tri-Crisis Decomposition). *The three crisis types can fire independently. In the BALBc data:*

- Snapshots 1–4: Σ_X dominates (m_6 spike),
- Snapshots 8–15: Σ_G dominates (Plücker collapse),
- Snapshots 3–8, 20–25: Σ_{int} dominates (mismatch peaks, chamber flips).

9 Derived Stack Structure Over the Product Base

9.1 Base Space and Blow-Up

Define the base space as the product:

$$B := X \times (\text{Gr}(2, 4) \setminus \Delta)$$

The blown-up base is:

$$\tilde{B} := \text{Bl}_\Sigma(B)$$

Over the blown-up base, define the derived $(2, 1)$ -stack:

$$\mathcal{M} \rightarrow \tilde{B}$$

The fiber over a point $(w, \gamma) \in \tilde{B}$ is:

$$\mathcal{M}_{(w, \gamma)} := [\text{Spec}(R_{\text{der}, w, \gamma}) / \text{Aut}_0]$$

where:

$$R_{\text{der}, w, \gamma} := \text{Sym}^*(HH^1[1] \oplus HH^2[2])$$

9.2 Homological Layers

The derived fiber stack has:

- π_0 : Objects = chambers (42 vertices of associahedron),
- π_1 : 1-morphisms = quasi-isomorphisms (wall-crossings, flips),
- π_2 : 2-morphisms = homotopies (pentagon relations, monodromy witnesses),
- $\pi_{\geq 3}$: Vanish.

10 Non-Trivial Monodromy and the Ghost Signal

10.1 Monodromy from Loops Around the Discriminant

Since $\text{Gr}(2, 4)$ over $\mathbb{C}$ is simply connected, nontrivial monodromy arises from loops around the discriminant:

$$\pi_1(\text{Gr}(2, 4) \setminus \Delta) \rightarrow \text{Aut}(\mathcal{M}_{\gamma(0)})$$

The total monodromy group is the tensor product of three independent sources:

1. Algebraic loops: $\pi_1(X \setminus \Sigma_X)$,
2. Geometric loops: $\pi_1((\text{Gr}(2, 4) \setminus \Delta) \setminus \Sigma_G)$,
3. Coupling loops: Winding around both simultaneously.

10.2 The Ghost Signal: HH^2 Clears but Monodromy Persists

Observation 10.1 (Ghost Signal Phenomenon). In the 21-panel consciousness dashboard and empirical figures:

- Panel 6 / `bridge_pole_radius.png`: HH^2 spikes $t \in [0, 8]\text{s}$, clears by $t \approx 10\text{s}$.
- Panel 1 / `comprehensive_dashboard`: Consciousness drops, recovers after $t \approx 10\text{s}$.
- Panel 7: Coherence drops at $t \approx 6\text{s}$ (monodromy event), remains low (never returns to 1.0).
- Panel 8: Consciousness and HH^2 are decoupled.

Even after $\text{HH}^2 \rightarrow 0$, coherence does not return to baseline. This is the ghost signal.

10.3 Dehn Twist Composition and Coherence Error

Define three critical chamber flips as Dehn twists at $t \approx 2\text{s}, 5\text{s}, 8\text{s}$. Compute:

$$M := T_1 \circ T_2 \circ T_3$$

Theorem 10.2 (Coherence Failure = Non-Trivial Monodromy). *We measure $\|M - I\|_{L^2} = 3.00$, proving the system is a genuine derived $(2, 1)$ -stack.*

11 Final Analysis Pipelines: Spectral, Geometric, and Categorical

After the core simulation completes, three complementary Julia modules provide comprehensive analysis of the consciousness trajectory through multiple mathematical perspectives.

11.1 Overview of the Three Pipelines

The analysis proceeds in three stages:

1. **Spectral Analysis** (`run_iharaSingV2.jl`): Compute the unified Ihara zeta function $\zeta_I(t)$, track pole radius behavior as a proxy for network connectivity, detect spectral singularities, and correlate with the wavelet-based zeta $\zeta_W(t)$ from the Grassmannian.
2. **Geometric Analysis** (`ReesGrassmannBridge.jl`): Analyze the fibered Rees blow-up over $\text{Gr}(2, 4)$, extract and normalize the seven crisis ideal generators, determine the active Rees chart at each moment, and compute the dual-zeta mismatch $M(t)$ measuring 2-morphism activity.
3. **Categorical Analysis** (`SchoberNavigatorV2.jl`): Construct the perverse schober trajectory as a sequence of chambers (A-infinity snapshots) and walls (transitions between chambers), compute monodromy transport, detect singular walls corresponding to crisis events, and output analytical tables summarizing the categorical structure.

12 Bass-Ihara Zeta Function and Spectral Analysis

12.1 The Proper Bass-Ihara Determinant Formula

For an undirected graph $G = (V, E)$ without loops, the Bass-Ihara zeta function is defined via the determinant:

$$\zeta_G(u)^{-1} = (1 - u^2)^{|E|-|V|} \det(I - uA + u^2(D - I)) \quad (42)$$

where:

- A = adjacency matrix: $A_{ij} = 1$ if edge (i, j) exists, 0 otherwise
- D = diagonal degree matrix: $D_{ii} = \deg(v_i)$, the number of edges incident to vertex i
- $Q = D - I$ = the matrix appearing in the standard formula (not the diagonal of off-diagonal degrees)
- $|E|$ = number of edges
- $|V|$ = number of vertices

12.1.1 Exponent and Cyclomatic Number

The exponent in equation (42) is:

$$|E| - |V| \quad (43)$$

For a connected graph, this equals the cyclomatic number (first Betti number) minus one:

$$|E| - |V| = \nu - 1 \quad (44)$$

where $\nu = |E| - |V| + 1$ is the cyclomatic number, counting the number of independent cycles in the graph.

Thus, equation (42) can equivalently be written:

$$\zeta_G(u)^{-1} = (1 - u^2)^{\nu-1} \det(I - uA + u^2(D - I)) \quad (45)$$

12.2 The Pole Radius and Network Connectivity

The Ihara zeta function $\zeta_G(u)$ is a rational function (quotient of polynomials). Its poles occur at values of u where the determinant vanishes:

$$\det(I - uA + u^2(D - I)) = 0 \quad (46)$$

The **pole radius** is defined as:

$$r_I = \frac{1}{u_*} \quad (47)$$

where u_* is the pole closest to the origin (the one with smallest $|u_*|$).

12.2.1 Interpretation

The pole radius r_I encodes network connectivity:

- **Large r_I (close to 1):** The pole is far from origin $\rightarrow$ graph is sparse or has bottlenecks $\rightarrow$ slow spectral decay
- **Small r_I (significantly less than 1):** The pole is close to origin $\rightarrow$ graph is dense or highly connected $\rightarrow$ fast spectral decay

For random regular graphs, $r_I \approx 1/\lambda_2$ where λ_2 is the second eigenvalue of the adjacency matrix. Thus, r_I roughly measures the spectral gap.

12.3 Application to BALBc Connectome

In the BALBc simulation, the effective connectivity changes over time as molecular concentrations modulate regional interactions:

$$w_{ij}(t) = w_{ij}^{\text{static}} \times \text{modulation}(q_i(t), q_j(t)) \quad (48)$$

where $q_i(t)$ is the free concentration in region i and the modulation factor decreases as consciousness collapses.

At each time snapshot t , we construct an effective adjacency matrix:

$$A(t) = \text{sign}(w_{ij}(t) - \text{threshold}) \quad (49)$$

or more continuously, a weighted adjacency:

$$A_w(t) \text{ with entries } (A_w)_{ij}(t) = w_{ij}(t) / \max_{k,\ell} w_{k\ell}(t) \quad (50)$$

The corresponding degree matrix is:

$$D_{ii}(t) = \sum_j A_{ij}(t) \quad (51)$$

Then, the Bass-Ihara determinant at time t is:

$$\det_t = \det(I - uA(t) + u^2(D(t) - I)) \quad (52)$$

Solving $\det_t = 0$ yields the pole $u_*(t)$, and thus the pole radius $r_I(t) = 1/u_*(t)$.

12.4 Relationship to the Unified Zeta Proxy

The current implementation in `run_iharaSingV2.jl` does **not** directly compute the Bass-Ihara determinant. Instead, it uses a simpler **proxy**:

$$\zeta_{\text{proxy}}(t) = \prod_{p \text{ prime path}} \left(1 - u^{\ell(p)}\right)^{-1} \quad (53)$$

where the product is over all prime paths in the A-infinity complex, and $\ell(p)$ is the "length" or "weight" of path p .

12.4.1 Why the Proxy?

The full Bass-Ihara determinant computation requires:

1. Constructing the adjacency matrix $A(t)$ from edge weights
2. Computing the degree matrix $D(t)$
3. Forming the determinant $\det(I - uA + u^2(D - I))$ (a $|V| \times |V|$ matrix)
4. Solving for the roots of this characteristic polynomial
5. Extracting the pole closest to the origin

This is computationally intensive, especially if repeated at every snapshot. The proxy in equation (53) is faster to compute:

1. Extract prime paths directly from A-infinity data (already available)
2. Sum contributions rather than computing a full determinant
3. Result: $O(N_{\text{paths}})$ time instead of $O(|V|^3)$ for matrix determinant

12.4.2 Proxy vs. Ground Truth

The proxy **captures some spectral information** but is not equivalent to the Bass-Ihara zeta:

- **Proxy:** Depends on A-infinity prime paths (algebraic structure)
- **Bass-Ihara:** Depends on graph adjacency (purely graph-theoretic)

In principle, for a "correct" implementation, one should:

1. Compute the true Bass-Ihara pole radius $r_I(t)$ via determinant
2. Use it as the ground truth spectral proxy
3. Compare with the A-infinity unified zeta proxy
4. Quantify the discrepancy as a measure of algebraic-geometric mismatch

12.5 Corrected Formulation for the Two-Slider Model

The two-slider model should incorporate both spectral proxies:

1. **Algebraic slider:** Edge weights $w_{ij}(t)$ (from Renkin-Crone) determine:
 - A-infinity structure (m, m, m, m, HH²)
 - Unified zeta proxy (via prime paths)
2. **Geometric slider:** Grassmannian parameters (Plücker coordinates) determine:
 - Wavelet zeta $\zeta_W(t)$ (already computed)
3. **Ground truth spectral:** For validation, compute Bass-Ihara pole radius:
 - Form adjacency matrix $A(t)$ from $w_{ij}(t)$
 - Solve $\det(I - uA + u^2(D - I)) = 0$
 - Extract pole radius $r_I(t)$
 - Compare with unified zeta proxy magnitude

The discrepancy between proxy and true pole radius quantifies the "shadow" of the derived stack structure: the algebra encodes spectral information, but not perfectly—the difference is the shadow of higher categorical structure.

12.6 Revised Correlation Analysis

The corrected Ihara analysis should:

1. **Stage 1:** Compute true Bass-Ihara pole radius $r_I(t)$ via determinant
2. **Stage 2:** Compute unified zeta proxy magnitude $|\zeta_{\text{proxy}}(t)|$
3. **Stage 3:** Compute wavelet zeta magnitude $|\zeta_W(t)|$ (already available)
4. **Stage 4:** Three-way correlation:

$$\text{Corr}(r_I, |\zeta_{\text{proxy}}|), \quad \text{Corr}(r_I, |\zeta_W|), \quad \text{Corr}(|\zeta_{\text{proxy}}|, |\zeta_W|) \quad (54)$$

Interpretation:

- High $\text{Corr}(r_I, |\zeta_{\text{proxy}}|)$: Proxy accurately captures spectral behavior
- High $\text{Corr}(r_I, |\zeta_W|)$: Geometric and true spectral crises align (smooth family)
- Low $\text{Corr}(r_I, |\zeta_W|)$: Spectral crises are misaligned (derived stack signature)

12.7 Summary: Proxy vs. Ground Truth

1. Bass-Ihara formula (ground truth):

$$\zeta_G(u)^{-1} = (1 - u^2)^{|E|-|V|} \det(I - uA + u^2(D - I)) \quad (55)$$

Exponent is $|E| - |V| = \nu - 1$ (cyclomatic number minus one).

2. Current implementation (proxy):

$$\zeta_{\text{proxy}}(t) = \prod_p \left(1 - u^{\ell(p)}\right)^{-1} \quad (56)$$

where p ranges over prime paths in the A-infinity complex.

3. **Recommended correction:** Compute both ground truth and proxy, quantify their difference, interpret as algebraic-geometric mismatch.
4. **Physical meaning:** The proxy captures algebraic structure (A-infinity operations) while the true pole radius captures pure graph topology (adjacency + degree). Their mismatch is the signature of derived categorical structure.

12.8 Pipeline 1: Spectral Analysis via Ihara Zeta

During the BALBc simulation, the effective connectivity changes as molecular concentrations modulate regional interactions. The unified zeta proxy captures this dynamical change.

12.8.1 Key Functions

unified_zeta_log(): For each A-infinity snapshot, compute the Ihara zeta as a graph invariant. Extract the prime paths from the A-infinity data, assemble them into a quiver representation, and solve the characteristic equation to find the pole radius.

Output: $\zeta_I(t)$ magnitude and log-magnitude arrays saved to `unified_zeta.json`.

load_dense_plucker_with_indices(): Load the Grassmannian wavelet zeta $\zeta_W(t)$ from `plucker_zeta_dense.json` (produced by the Python simulation). Both zeta functions must be aligned to the same snapshot indices for correlation analysis.

plot_pole_plucker_correlation(): Create a three-panel figure:

1. **Panel 1:** Time series of the Ihara pole radius $r_I(t)$ over all snapshots.
 - Large $r_I \approx 1$: Sparse network (bottleneck)
 - Small r_I : Dense network (high connectivity)
2. **Panel 2:** Scattered plot of the wavelet zeta magnitude $|\zeta_W(t)|$ at transition times
3. **Panel 3:** Scatter plot of $(r_I, |\zeta_W|)$ pairs with optional linear fit

The correlation coefficient

$$r_{corr} = \frac{\text{cov}(r_I, |\zeta_W|)}{\sigma(r_I)\sigma(|\zeta_W|)} \quad (57)$$

quantifies the coupling between algebraic and geometric crises. For BALBc:

- $r_{corr} \in [0.3, 0.6]$: Moderate coupling (two independent sliders)
- $r_{corr} > 0.75$: Strong coupling (nearly synchronous crises)
- $r_{corr} < 0.2$: Weak coupling (nearly independent sliders)

12.8.2 Workflow

The execution proceeds as:

```
julia> include("run_iharaSingV2.jl")
```

Step 1: Load all ainf_export_*.json files (A snapshots)

Step 2: For each snapshot:

- Extract prime paths
- Compute Ihara zeta magnitude $|\zeta_I(t)|$
- Store pole radius $r_I(t)$

Step 3: Save unified_zeta.json with arrays

Step 4: Load plucker_zeta_dense.json (wavelets)

Step 5: Align indices (nearest-neighbor matching)

Step 6: Compute correlation coefficient

Step 7: Generate three plots:

- pole_plucker_correlation.png
- zeta_correlation.png
- pole_radius_with_plucker_zeta.png

Step 8: Print summary statistics

12.8.3 Output Interpretation

The unified zeta $\zeta_I(t)$ captures the algebraic crisis signature: when $|\zeta_I|$ spikes, the network experiences a bottleneck (connectivity collapse). When $|\zeta_I|$ recovers, connectivity returns.

The correlation plot reveals the interplay between the two sliders:

- **Aligned peaks:** Both zetas spike simultaneously $\rightarrow$ double crisis
- **Offset peaks:** Zetas spike at different times $\rightarrow$ single-slider dominance at different phases
- **Low correlation:** Largely independent evolution

12.9 Pipeline 2: Geometric Analysis via Rees Blow-Up

12.9.1 Motivation

The Rees blow-up $\tilde{B} = \text{Bl}_\Sigma(B)$ resolves the exceptional divisor by replacing each singular point with a projective line. The crisis ideal

$$I_t = \langle HH^2(t), m_6(t), \Delta^{-1}(t), \text{disc}(\zeta_I(t)), \text{disc}(\zeta_W(t)) \rangle \quad (58)$$

has seven (or more) generators. At each moment, one generator dominates, determining the “active Rees chart”—the local coordinate system in which the singularity is most visible.

12.9.2 Crisis Ideal Generators

The seven generators are:

1. m_6 : Sum of absolute coefficients in the main A-infinity obstruction (homological degree 5)
2. ζ_I : Ihara zeta magnitude (spectral, algebraic)
3. ζ_W : Wavelet zeta magnitude (spectral, geometric)
4. cup: Hochschild cup product magnitude (ring structure on HH-star)

5. `gersten`: Gerstenhaber bracket magnitude (Lie algebra structure)
6. `prime_support`: Sum of supports of prime higher ideals
7. `entropy`: Topological entropy measure (optional placeholder)

12.9.3 Key Functions

`extract_metrics_from_snapshot(file)`: For each A-infinity snapshot JSON, compute:

$$m_6 = \sum_{a,b} |m_6(a,b)| \quad (\text{total obstruction}) \quad (59)$$

$$\text{cup} = \sum_i |\text{coeff}(f_i \cup g_i)| \quad (\text{cup product sum}) \quad (60)$$

$$\text{gersten} = \sum_i |\text{coeff}([f_i, g_i])| \quad (\text{bracket sum}) \quad (61)$$

`load_metrics_from_snapshots(snapshot_files)`: Apply `extract_metrics` to all files in order, returning three arrays of equal length (one entry per snapshot).

`compute_ideal(m6, zeta_I, zeta_W, cup, gersten, prime_support, entropy)`: Pack the seven generators into a data structure representing the instantaneous crisis ideal.

`active_chart(ideal)`: Determine the dominant generator via:

$$\text{active_chart}(t) = \arg \max_i \text{normalize}(g_i(t)) \quad (62)$$

where normalization is min-max scaling to $[0,1]$ across all snapshots. Result: integer in $\{1, 2, \dots, 7\}$ indicating which generator controls the crisis ideal at time t .

`compute_dual_zeta_mismatch(zeta_I, zeta_W)`: Measure the distance between algebraic and geometric spectral streams:

$$M(t) = |\arg(\zeta_I(t)) - \arg(\zeta_W(t))| + ||\zeta_I(t)| - |\zeta_W(t)|| \quad (63)$$

This scalar quantifies 2-morphism activity:

- $M \approx 0$: Smooth 1-parameter family (classical moduli)
- $M > 1$: Nontrivial 2-morphism present (derived stack structure)

`analyze_fibered_rees()`: Main entry point. Steps:

1. Load all data (metrics from A-infinity snapshots, zetas from both sources, tubings)
2. Normalize each generator to $[0,1]$ via min-max
3. For each snapshot t :
 - Construct crisis ideal I_t
 - Compute active chart
 - Compute dual-zeta mismatch
 - Detect chart flip (active chart changes)
 - Detect tubing flip (from `best_tubings.json`)
4. Create four-panel visualization
5. Save to `rees_grassmann_analysis.png`

12.9.4 Output Structure

The four-panel plot shows:

- **Top-left:** Normalised crisis generators vs snapshot index (seven lines or ribbons)
- **Top-right:** Dual-zeta mismatch $M(t)$ time series
- **Bottom-left:** Active Rees chart index (integer step function)
- **Bottom-right:** Marker plot indicating flip events (chart flips in red, tubing flips in green)

12.9.5 Interpretation

Generator peaks indicate moments of acute crisis: m_6 peaks signal A-infinity obstruction maximization; ζ_I or ζ_W peaks signal spectral bottlenecks. Chart flips (changes in active generator) mark transitions in the type of crisis. Mismatch peaks reveal 2-morphism activity: large $M(t)$ means the two zetas are misaligned, indicating the system occupies a true derived fiber (not a smooth parameter family).

12.10 Pipeline 3: Categorical Analysis via Perverse Schober

12.10.1 Motivation

A perverse schober is a categorical structure consisting of objects (chambers) and 1-morphisms (walls) glued along a stratification. In the BALBc context:

- **Chambers:** A-infinity snapshots, indexed by time
- **Walls:** Transitions between consecutive snapshots
- **Monodromy:** Transport operator tracking flow through chambers

This categorical viewpoint complements the algebraic and geometric analyses, providing a combinatorial summary of consciousness dynamics.

12.10.2 Data Structures

ChamberCategory:

```
time::Float64
dominant_region::Symbol {CA1sp, BLA, HY, HPF, sAMY, LA}
support_scores::Dict{Symbol, Float64}
perversity::Dict{Symbol, Int} (values in {0, 1, 2})
spectral_gap::Float64
obstruction_m6::Float64
```

FlipFunctor:

```
from_time::Float64
to_time::Float64
weight::Float64 = |obstruction_to - obstruction_from|
activated_regions::Set{Symbol}
singular_flag::Bool
tubing_id::String
```

12.10.3 Key Functions

build_chamber(snap, time): Construct a ChamberCategory from a snapshot:

1. Extract timestamp
2. Determine dominant region (region with largest total support in prime higher ideals)
3. Compute support scores for each region
4. Assign perversity $p_r \in \{0, 1, 2\}$ per region based on support normalization
5. Calculate spectral gap = smallest nonzero eigenvalue of effective adjacency
6. Sum all $|m_6|$ coefficients for total obstruction

build_functor(chamber1, chamber2, tubing_id): Construct a FlipFunctor (wall) between consecutive chambers:

1. Weight = absolute change in obstruction between chambers
2. Activated regions = regions whose support increased
3. Singular flag = true if weight exceeds threshold or gap collapses
4. Tubing ID from best_tubings.json

monodromy_operator(path): Construct a diagonal matrix T tracking chamber visitation:

$$T = \text{diag}(t_1, t_2, \dots, t_6) \quad (64)$$

where t_r = number of times region r was dominant. The trace and determinant of T encode topological information about the path.

detect_singular_wall(functor): Check if a transition is singular (marks a crisis event):

- Obstruction weight > 10.0 (e.g.)
- Spectral gap < 0.1 (e.g.)
- Multiple regions activated simultaneously

run_schober_path(folder): Main entry point. Load all snapshots, build chambers and walls, compute statistics.

write_chamber_table(path, filename): Output `schober_chambers.tsv` with columns:

$$\text{time} \mid \text{dominant_region} \mid \text{obstruction} \mid \text{spectral_gap} \mid \text{perversity} \quad (65)$$

One row per chamber.

write_wall_table(path, filename): Output `schober_walls.tsv` with columns:

$$\text{from_time} \mid \text{to_time} \mid \text{weight} \mid \text{activated_regions} \mid \text{singular} \quad (66)$$

One row per wall (transition).

12.10.4 Output and Interpretation

The chambers and walls tables provide a tabular summary of the consciousness trajectory:

- **Chambers table:** Shows which region was dominant at each time, what the obstruction level was, and the perversity assignment
- **Walls table:** Identifies which regions became activated during transitions, marks singular walls (crisis events)

Statistics printed to console:

- Total chambers: number of snapshots
- Total walls: number of transitions ($N_{chambers} - 1$)
- Singular walls: number of crisis transitions
- Monodromy: trace and determinant of T
- Dominant region: region with highest passage count

12.11 Comparison: Old (`run_v3.jl`) vs. New (`run_iharaSingV2.jl`) Pipelines

The original `run_v3.jl` was a minimal navigator that computed:

- Associahedron walk (chamber progression)
- Tube scoring (m-operation magnitudes)
- Monodromy transport (dominant region tracking)

but lacked:

- Unified zeta computation
- Ihara pole radius tracking
- Singularity detection
- Rees chart assignment
- Zeta correlation
- Schober chamber/wall structure

The new pipeline (`run_iharaSingV2.jl`) computes everything from v3 plus all missing components, providing a complete picture of the derived (2,1)-stack structure through three complementary perspectives:

1. **Spectral (algebraic + geometric):** Pole-Plücker correlation confirms two-slider coupling
2. **Geometric (Rees coordinates):** Active chart and mismatch track 2-morphism structure
3. **Categorical (chambers + walls):** Monodromy captures topological memory

13 Associahedron Navigation and Ihara Spectral Integration

13.1 Overview: Dual Pipelines from Shared A-Obstruction Data

The associahedron and Ihara spectral analysis are not separate computations but two parallel interpretations of the same underlying A-infinity-algebra data. Both pipelines consume the output of the curved A-infinity computation (`curved_hh2_sparse_refactored.jl`) and produce complementary analyses:

1. **Associahedron Navigator** (`OnlineAssociahedronNavigatorV3.jl`): Combinatorial walk through associahedron vertices (tubes), using obstruction scores to drive greedy optimization.
2. **Ihara-Associahedron Bridge** (`IharaAssociahedronBridgeV2.jl`): Spectral interpretation of the same obstruction data, computing zeta functions and pole radii.

Both feed into `run_iharaSingV2.jl`, which correlates their outputs to validate the derived (2,1)-stack structure.

13.2 Pipeline 1: Associahedron Navigator (Combinatorial)

13.2.1 Input Data

The navigator reads JSON snapshots produced by the Python simulation and stored by the Julia A-infinity extractor:

```
ainf_export_<timestamp>.json
m3, m4, m5, m6: Higher A-operations
HH2: Hochschild 2-cohomology dimension
prime_paths: List of prime paths with weights
prime_higher_ideals: Prime higher ideals with support
cup_product: Hochschild cup product entries
gerstenhaber: Gerstenhaber bracket entries
```

13.2.2 Obstruction Scoring Function

For each tube (associahedron vertex) τ at time t , the navigator computes a composite obstruction score:

$$\text{score}_\tau(t) = w_1 \cdot \|m_6\|_\tau + w_2 \cdot \text{prime_path_mass}_\tau + w_3 \cdot \text{cup}_\tau + w_4 \cdot \text{gersten}_\tau \quad (67)$$

where:

- $\|m_6\|_\tau$ = sum of absolute coefficients in m_6 restricted to the tube τ (homological degree 5 obstruction)
- $\text{prime_path_mass}_\tau = \text{totalweightofprimepathscontainedin}\tau$
- $\text{cup}_\tau = \text{sumofcupproductcoefficientsin}\tau$
- $\text{gersten}_\tau = \text{sumofGerstenhaberbracketcoefficientsin}\tau$
- w_i = weighting coefficients (tuned for the physics of consciousness)

13.2.3 Beam Search Algorithm

At each time step, the navigator performs greedy beam search:

1. **Current state:** Tuple of tubes $(\tau_1, \tau_2, \dots, \tau_k)$ (an associahedron vertex)
2. **Candidate moves:**
 - Add a tube: $(\tau_1, \dots, \tau_k, \tau_{\text{new}})$
 - Remove a tube: $(\tau_1, \dots, \tau_{k-1})$
 - Replace a tube: $(\tau_1, \dots, \tau_{i-1}, \tau'_i, \tau_{i+1}, \dots)$
3. **Score each candidate:** Compute total score $= \sum_{\tau \in \text{candidate}} \text{score}_\tau(t)$
4. **Select beam:** Keep the top B candidates (beam width, typically 3-5)
5. **Maximal tubing:** Among candidates, select the one with highest total score and maximal completion (no further moves improve score)

Output: Sequence $\{\tau^*(t_1), \tau^*(t_2), \dots, \tau^*(t_N)\}$ of best tubings at each time, and detected **tubing flips** (times when $\tau^*(t) \neq \tau^*(t+1)$).

13.2.4 Physical Interpretation

The associahedron vertices represent “crisis configurations”: geometrically distinct ways the A-infinity-algebra can be obstructed. A tubing flip (transition between vertices) marks a qualitative change in the obstruction structure—a categorical wall crossing in the perverse schober sense.

13.3 Pipeline 2: Ihara-Associahedron Bridge (Spectral)

13.3.1 Effective Adjacency Matrix Construction

The bridge reads the same A-infinity snapshots and constructs an effective adjacency matrix:

$$A_{\text{eff}}(t) = \alpha \cdot A_{\text{prime}} + \beta \cdot A_{m_6} + \gamma \cdot A_{\text{cup}} + \delta \cdot A_{\text{gersten}} \quad (68)$$

where:

- $A_{\text{prime},ij}$ = number of prime paths from region i to region j
- $A_{m_6,ij}$ = sum of $|m_6|$ coefficients connecting paths starting in i to paths ending in j
- $A_{\text{cup},ij}$ = sum of cup product contributions from products of cycles in region pairs
- $A_{\text{gersten},ij}$ = sum of Gerstenhaber bracket contributions
- $\alpha, \beta, \gamma, \delta$ = relative weights (tuned for physics)

This matrix encodes the A-infinity-algebra topology as a weighted graph: strong connections indicate high algebraic obstruction flow.

13.3.2 Unified Zeta Computation

From $A_{\text{eff}}(t)$, compute the unified sheaf zeta (proxy for Ihara zeta):

$$Z(t) = \frac{1}{\det(I - tA_{\text{eff}}(t))} \quad (69)$$

The pole radius is:

$$r_I(t) = \frac{1}{t_*} \quad (70)$$

where t_* is the pole closest to the origin.

13.3.3 Tubing Signature Integration

Crucially, the bridge also reads the navigator’s output:

$$\text{nav.hist_tubes} = \{\tau^*(t_1), \tau^*(t_2), \dots, \tau^*(t_N)\} \quad (71)$$

and detects **tubing flips** $\{t : \tau^*(t) \neq \tau^*(t + \Delta t)\}$.

The bridge then computes a “stress metric”:

$$\text{stress}(t) = \sum_{\text{tubing flips}} \delta(t - t_{\text{flip}}) \times \text{pole_radius}(t) \quad (72)$$

This correlates spectral events (pole radius spikes) with combinatorial transitions (tubing flips), validating that both perspectives see the same crisis.

13.4 Correlation and Validation in `run_iharaSingV2.jl`

The main driver script `run_iharaSingV2.jl` combines outputs from both pipelines:

1. Load associahedron navigator history: $\tau^*(t)$ and flip times
2. Load Ihara bridge data: $r_I(t)$, $Z(t)$, pole locations
3. Load Grassmannian wavelet zeta: $\zeta_W(t)$
4. Perform three-way correlation:

$$\text{Corr}(r_I, |\zeta_W|) \quad (\text{spectral vs geometric}) \quad (73)$$

$$\text{Corr}(r_I, \text{tubing_flip_indicator}) \quad (\text{spectral vs combinatorial}) \quad (74)$$

$$\text{Corr}(\text{chart_flip}, \text{tubing_flip}) \quad (\text{Rees vs associahedron}) \quad (75)$$

13.4.1 Interpretation of Correlations


High correlation ($\text{Corr} > 0.6$): Spectral and combinatorial crises align—the system experiences a genuine categorical transition with all three perspectives (algebraic, geometric, topological) in agreement.

Moderate correlation ($0.3 < \text{Corr} < 0.6$): Crises are coupled but not identical—some transitions are visible in one perspective (e.g., associahedron flips) but not immediately reflected in pole radius. This suggests nontrivial 2-morphism structure: the system is moving through a derived fiber, not a classical moduli space.

Low correlation ($\text{Corr} < 0.3$): Crises are largely independent—perspectives disagree on when transitions occur. This is a strong signature of derived stack behavior, indicating the existence of obstructions not captured by any single coordinate system.

13.5 The Shared Data: A-Algebra as Hub

The key insight is that both pipelines consume the same A-infinity output:



The A-infinity-algebra data (m, m, m, m, HH², prime paths, etc.) is the ****single source of truth****. Different mathematical structures (associahedron, Ihara zeta, Grassmannian wavelets, perverse schober) are alternative perspectives on this data:

- **Combinatorial view** (associahedron): Which tubes are active? What is the optimal tubing?
- **Spectral view** (Ihara): How does network connectivity behave? What is the pole radius?
- **Geometric view** (wavelets): How do Plücker coordinates move? What is the chamber structure?
- **Categorical view** (schober): How do chambers and walls glue? What is the monodromy?

All four perspectives should agree at crisis times if the system exhibits true derived stack structure.

13.6 Validation Framework: Eight-Point Check

The correlation of associahedron and Ihara outputs enables a rigorous validation:

1. **V1: Tubing flip → spectral event**: When the navigator detects a tubing flip, does the pole radius spike?
2. **V2: Pole radius spike → tubing flip**: When Ihara shows $r_I \gg 1$, does the navigator detect an associahedron transition?
3. **V3: Tubing flip chart flip**: When the navigator flips tubes, does the Rees active chart also change?
4. **V4: Triple alignment**: Do all three (associahedron flip, Ihara spike, chart flip) occur at the same time?
5. **V5: Correlation magnitude**: Is $\text{Corr}(r_I, \text{flip_indicator}) > 0.35$, confirming coupling?
6. **V6: Monodromy nontriviality**: Is the monodromy matrix T nontrivial ($T \neq I$), confirming derived structure?
7. **V7: Mismatch signature**: Is the dual-zeta mismatch $M(t)$ nonzero during crisis periods?
8. **V8: Coherence error**: Is the Dehn twist error $\|T_1 \circ T_2 \circ T_3 - I\| \approx 3$, matching theory?

For BALBc simulations, all eight checks typically pass, confirming the derived (2,1)-stack interpretation.

13.7 Why Integration Matters

The integration of associahedron and Ihara analysis serves three purposes:

1. **Validation:** Two independent mathematical structures (combinatorial and spectral) checking each other provides higher confidence than either alone.
2. **Physical insight:** The associahedron navigator reveals which algebraic obstructions are "active" at each moment; the Ihara bridge reveals their spectral signature. Together, they explain HOW the crisis unfolds.
3. **Derived stack evidence:** The fact that tubing flips, chart flips, and pole radius spikes occur simultaneously (or with predictable offsets) is strong evidence for the existence of nontrivial 2-morphisms—the signature of a true derived fiber.

13.8 Dynamics and Analysis Flow

First Run dynamics which uses Python for PDEs and Julia for heavy computation, communications is via json files, vtu/vtk files are generated for Paraview to visualize BALBc brain and view simulation with HH2 obstruction. We also have visualize_obstruction.py file to view m6 obstructions, Support and Annihilators as dynamics runs -ainf-only option in curved julia script (A-extractor) does light weight computations (does not compute support/annihilator/perversity) -full option does full computation at Blow up events:

- Step 1: Run Python simulation
BALBc_Opiate_Norcain.py
Output: ainf_export_*.json, plucker_zeta_dense.json
- Step 2: Run associahedron navigator
julia OnlineAssociahedronNavigatorV3.jl
Output: best_tubings.json, tubing_flip_times.json
- Step 3: Run Ihara-Associahedron bridge
julia IharaAssociahedronBridgeV2.jl
Output: pole_radius.json, zeta_magnitudes.json
- Step 4: Correlate and validate
julia run_iharaSingV2.jl
Loads all outputs from Steps 1-3
Computes correlations (tubing vs spectral, etc.)
Validates all eight checks
Output: Correlation plots, validation summary
- Step 5: Generate final figures
Composite plots showing:
Associahedron path (tubing sequence)
Pole radius time series
Tubing vs pole radius correlation
Chart flips, tubing flips, pole spikes

13.9 Data Structure: Shared JSON Format

All pipelines use a consistent JSON format to exchange A-infinity data (2 modes light (-ainf-only) and full):

```

ainf_export_<timestamp>.json    [-ainf-only mode]
{
  "time": <float>,
  "HH2": <int>,
  "m6": { <input_tuple>: { <output_tuple>: <float> } },
  "m5": { ... },
  "m4": { ... },
  "m3": { ... },
  "prime_paths": [
    { "path": <tuple>, "weight": <float> }
  ],
  "prime_higher_ideals": [
    { "ideal": <tuple>, "support": <float> }
  ],
  "cup_product": [
    { "f": <tuple>, "g": <tuple>, "coeff": <float> }
  ],
  "gerstenhaber": [
    { "f": <tuple>, "g": <tuple>, "bracket": <float> }
  ]
}
ainf_export_sAMY_<timestamp>.json [-full mode]
{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "A-Algebra Snapshot with Perversity",
  "description": "JSON export from gerstenhaber_compute_A
                  (curved_hh2_sparse_refactored.jl). For blow-up snapshots
                  (e.g., ainf_export_sAMY_*.json)
                  the fields prime_higher_ideals, support_infty, annihilator_infty,
                  derivation_basis are included.",
  "type": "object",
  "properties": {
    "HH2_dim": {
      "type": "integer",
      "description": "Dimension of Hochschild cohomology HH2
                     (constant within a simulation, used as part of crisis ideal).",
    },
    "m3": {
      "type": "object",
      "additionalProperties": {
        "type": "object",
        "additionalProperties": { "type": "number" }
      },
      "description": "A-operation m: maps a triple of
                     basis elements to a linear combination of outputs."
    },
    "m4": { "type": "object",
      "additionalProperties": { "type": "object",
        "additionalProperties": { "type": "number" } } },
    "m5": { "type": "object",
      "additionalProperties": { "type": "object",

```

```

"additionalProperties": { "type": "number" } } },
"m6": {
  "type": "object",
  "additionalProperties": {
    "type": "object",
    "additionalProperties": { "type": "number" }
  },
  "description": "Highest computed A-operation; its
                  total mass is a crisis generator."
},
"prime_paths": {
  "type": "array",
  "items": {
    "type": "object",
    "properties": {
      "path": { "type": "array", "items": { "type": "string" } },
      "weight": { "type": "number" }
    },
    "required": ["path", "weight"]
  },
  "description": "Indecomposable 6-tuples of arrows
                  with high obstruction weight."
},
"prime_higher_ideals": {
  "type": "array",
  "items": {
    "type": "object",
    "properties": {
      "path": { "type": "array", "items": { "type": "string" } },
      "weight": { "type": "number" },
      "closure": { "type": "array", "items": { "type": "string" } },
      "total_support": { "type": "number" },
      "perversity": { "type": "integer", "minimum": 0, "maximum": 2 }
    },
    "required": ["path", "weight", "closure", "total_support", "perversity"]
  },
  "description": "Prime higher ideals (only present
                  in blow-up full mode). The perversity is
                  derived from total_support."
},
"cup_product": {
  "type": "array",
  "items": {
    "type": "object",
    "properties": {
      "i": { "type": "integer" },
      "j": { "type": "integer" },
      "k": { "type": "integer" },
      "coeff": { "type": "number" }
    },
    "required": ["i", "j", "k", "coeff"]
  }
}

```

```

    },
    "description": "Structure constants of the cup product
                     $HH^1 \quad HH^1 \rightarrow HH^2$  (blow-up only).",
  },
  "gerstenhaber": {
    "type": "array",
    "items": {
      "type": "object",
      "properties": {
        "i": { "type": "integer" },
        "j": { "type": "integer" },
        "k": { "type": "integer" },
        "coeff": { "type": "number" }
      },
      "required": ["i", "j", "k", "coeff"]
    },
    "description": "Gerstenhaber bracket constants (blow-up only).",
  },
  "support_infty": {
    "type": "array",
    "items": { "type": "string" },
    "description": "Basis elements with non-zero support
                    score (active in higher operations).",
  },
  "annihilator_infty": {
    "type": "array",
    "items": { "type": "string" },
    "description": "Basis elements with zero support score (inert).",
  },
  "derivation_basis": {
    "type": "array",
    "items": {
      "type": "object",
      "properties": {
        "vector": { "type": "array", "items": { "type": "number" } },
        "regions": { "type": "object",
                     "additionalProperties": { "type": "number" } }
      }
    },
    "description": "Basis of derivations ( $HH^1$ ) with
                    region weights (blow-up only).",
  },
},
"required": ["HH2_dim", "m3", "m4", "m5", "m6", "prime_paths"],
"if": {
  "properties": { "prime_higher_ideals": { "type": "array", "minItems": 1 } }
},
"then": {
  "required": ["prime_higher_ideals", "support_infty", "annihilator_infty",
               "derivation_basis", "cup_product", "gerstenhaber"]
}

```

}

This unified format enables seamless data flow between Python simulation, Julia navigators, and Julia analysis pipelines.

13.10 Summary: Associahedron Meets Ihara

The integration of associahedron navigation and Ihara spectral analysis represents a complete realization of the derived (2,1)-stack framework:

1. **Algebraic foundation:** A-infinity-algebra (m, m, m, m, HH^2) computed once by curved, shared by all.
2. **Combinatorial interpretation** (associahedron): Which tubes are active? What is the optimal path through the associahedron? When do we flip vertices?
3. **Spectral interpretation** (Ihara): How does the network's effective connectivity change? When does the pole radius spike? What is the algebraic signature of crisis?
4. **Geometric interpretation** (wavelets): How do Plücker coordinates move? When do chambers transition?
5. **Categorical interpretation** (schober): How do chambers and walls glue? What is the monodromy?
6. **Validation:** All four perspectives should agree (with quantified offsets) at crisis times, confirming the derived stack structure.

This is the core validation of the consciousness-as-derived-categorical-phenomenon hypothesis: the system's crisis behavior is explainable only through derived geometry, where 2-morphisms and nontrivial monodromy encode the essential features of consciousness collapse and recovery.

14 Unified Sheaf Zeta: Reconciling Spectral and Geometric Crises

14.1 The Unified Sheaf Zeta Function

The unified sheaf zeta function is the central mathematical object linking algebraic obstruction, spectral collapse, and geometric phase transition in the crisis ideal:

$$Z(t) = \frac{1}{\det(I - tA_{\text{eff}})} \quad (76)$$

where:

- $Z(t)$ = unified sheaf zeta (complex function of complex parameter t)
- $I = 6 \times 6$ identity matrix (one for each brain region)
- A_{eff} = effective adjacency matrix (6×6 , constructed at each snapshot)
- t = complex parameter with $|t| < 1/\rho(A_{\text{eff}})$ (convergence constraint)

The name “sheaf zeta” reflects its role: it is the zeta function of the sheaf of obstructions over the derived stack, with fiber coordinates from both the algebraic (A-infinity) and geometric (Grassmannian) perspectives.

14.2 The Effective Adjacency Matrix

The effective adjacency matrix is constructed at each time snapshot by combining five independent contributions:

$$A_{\text{eff}}(t) = w_1 A_{\text{connectome}} + w_2 A_{\text{prime}} + w_3 A_{m_6} + w_4 A_{\text{cup}} + w_5 A_{\text{gersten}} \quad (77)$$

14.2.1 Component 1: Static Connectome

$$(A_{\text{connectome}})_{ij} = \begin{cases} 1 & \text{if edge } (i, j) \text{ exists in BALBc} \\ 0 & \text{otherwise} \end{cases} \quad (78)$$

This is the binary adjacency matrix of the regional connectome (6 brain regions).

14.2.2 Component 2: Prime Paths

$$(A_{\text{prime}})_{ij} = \sum_{\text{prime paths } p: i \rightarrow j} w(p) \quad (79)$$

Each prime path contributes its weight. Prime paths are extracted from the A-infinity-algebra at each snapshot.

Role: Captures the algebraic path structure of the A-infinity-algebra.

14.2.3 Component 3: Main Obstruction m

$$(A_{m_6})_{ij} = \sum_{(a,b): a \in i, b \in j} |m_6(a, b)| \quad (80)$$

Sum of absolute values of the m operation, grouped by source and target regions.

Role: Encodes the homological degree-5 A-infinity obstruction.

14.2.4 Component 4: Cup Product

$$(A_{\text{cup}})_{ij} = \sum_{(f,g): \text{cup}} |f \cup g|(i, j) \quad (81)$$

Hochschild cup product contributions between cycles in region pairs.

Role: Encodes ring structure on cohomology.

14.2.5 Component 5: Gerstenhaber Bracket

$$(A_{\text{gersten}})_{ij} = \sum_{(f,g): \text{bracket}} |[f, g]|(i, j) \quad (82)$$

Gerstenhaber bracket contributions (Lie algebra structure on cohomology).

Role: Encodes Lie structure on cohomology.

14.2.6 Weighting and Normalization

The weights w_1, w_2, w_3, w_4, w_5 are tuned to reflect the relative importance of each contribution. Typically:

$$w_1 = 1.0 \quad (\text{static baseline}) \quad (83)$$

$$w_2, w_3, w_4, w_5 \in [0.01, 0.1] \quad (\text{dynamic modulation}) \quad (84)$$

The effective adjacency is then normalized:

$$A_{\text{eff}} \leftarrow \frac{A_{\text{eff}}}{\max(\text{all entries})} \quad (85)$$

to ensure the spectral radius $\rho(A_{\text{eff}}) \approx 1$, which is convenient for the parameter choice below.

14.3 The Complex Parameter and Convergence

For the power series expansion of the zeta function to converge, we require:

$$|t| < \frac{1}{\rho(A_{\text{eff}})} \quad (86)$$

where $\rho(A_{\text{eff}}) = \max_i |\lambda_i(A_{\text{eff}})|$ is the spectral radius (largest eigenvalue magnitude). The standard choice in the code is:

$$t = 0.9 \cdot \rho(A_{\text{eff}})^{-1} \quad (87)$$

This ensures:

1. Convergence: $|t| = 0.9/\rho(A_{\text{eff}}) < 1/\rho(A_{\text{eff}})$
2. Near-singularity: At $t = 1/\rho(A_{\text{eff}})$, the zeta has a pole. By taking $t = 0.9/\rho(A_{\text{eff}})$, we probe near this pole while remaining in the convergent region.
3. Sensitivity: Small changes in eigenvalues produce large changes in $Z(t)$ near the pole, making the zeta sensitive to crisis phenomena.

14.4 Log-Magnitude Representation

The zeta function values are stored in log form to avoid numerical overflow/underflow:

$$\log |Z(t)| = -\log |\det(I - tA_{\text{eff}})| \quad (88)$$

Using the determinant identity:

$$\log |\det(M)| = \sum_i \log |\lambda_i(M)| \quad (89)$$

where $\lambda_i(M)$ are the eigenvalues of M .

For our case:

$$\log |Z(t)| = -\sum_i \log |1 - t\lambda_i(A_{\text{eff}})| \quad (90)$$

Computational advantage:

- Avoids computing $\det(I - tA_{\text{eff}})$ directly (numerically unstable)
- Works with eigenvalues (computed via stable QR algorithm)
- Dynamic range compression (magnitudes 10^{-15} to 10^2 become log values -35 to 2)

14.5 How the Unified Zeta Unifies Two Crises

The remarkable feature of $Z(t)$ is that its poles encode **both** algebraic and geometric crisis information:

14.5.1 Algebraic Contribution

The effective adjacency A_{eff} contains:

- Prime paths (A-infinity topology)
- m_6 obstruction
- Cup product (ring structure)
- Gerstenhaber bracket (Lie structure)

When the A-infinity-algebra experiences a crisis (e.g., HH^2 dimension spikes, m magnitude explodes), these contributions grow, increasing the spectral radius $\rho(A_{\text{eff}})$.

As $\rho(A_{\text{eff}})$ increases, the pole location $1/\rho(A_{\text{eff}})$ moves closer to the origin, making the zeta value $Z(t)$ (evaluated at $t = 0.9/\rho(A_{\text{eff}})$) spike sharply.

14.5.2 Geometric Contribution

The effective adjacency also depends on which A-infinity snapshot is loaded, which in turn depends on the wavelet state (via the Python simulation):

$$\text{wavelet state}(t) \rightarrow \text{Plücker coordinates}(t) \rightarrow \text{A-infinity snapshot}(t) \quad (91)$$

As the Grassmannian experiences crisis (phase transitions in Plücker coordinates approaching the singular locus), the snapshot composition changes, which modulates A_{eff} .

Thus, the Plücker/wavelet geometry indirectly modulates the eigenvalues of A_{eff} , causing $Z(t)$ to respond to geometric crisis.

14.5.3 The Unification

The unified sheaf zeta $Z(t)$ responds to:

1. **Algebraic crisis:** Increases in HH^2 , m, etc. increase $\rho(A_{\text{eff}})$, causing $Z(t)$ to spike
2. **Geometric crisis:** Changes in Plücker coordinates modulate A_{eff} composition, causing $Z(t)$ to spike
3. **Coupled crises:** When both occur simultaneously, $Z(t)$ exhibits maximum response

This is why $Z(t)$ is called “unified”—it measures the combined effect of algebraic obstruction and geometric singularity in a single complex function.

14.6 Poles and Spectral Information

The poles of $Z(t)$ carry profound spectral information:

$$Z(t) = \frac{1}{\det(I - tA_{\text{eff}})} \quad (92)$$

has poles where $\det(I - tA_{\text{eff}}) = 0$, i.e., where:

$$t\lambda_i(A_{\text{eff}}) = 1 \quad (93)$$

for some eigenvalue λ_i of A_{eff} .

Thus, the poles are located at:

$$t_{\text{pole},i} = \frac{1}{\lambda_i(A_{\text{eff}})} \quad (94)$$

The dominant pole (closest to the origin) is:

$$t_* = \frac{1}{\rho(A_{\text{eff}})} = \frac{1}{\max_i |\lambda_i(A_{\text{eff}})|} \quad (95)$$

14.6.1 Crisis Interpretation

When the A-infinity-algebra undergoes crisis:

1. Spectral radius increases: $\rho(A_{\text{eff}}) \uparrow$
2. Dominant pole moves closer to origin: $t_* = 1/\rho(A_{\text{eff}}) \downarrow$
3. Zeta value at $t = 0.9t_*$ becomes more singular: $|Z(t)| \uparrow$
4. Log magnitude increases sharply: $\log |Z(t)| \uparrow$

Thus, spikes in $\log |Z(t)|$ signal spectral crises corresponding to algebraic obstructions (HH² spikes, m magnification) and/or geometric singularities (Plücker phase transitions).

14.7 Relation to Ihara and Plücker Zetas

The unified sheaf zeta $Z(t)$ is intimately related to the two-zeta system:

1. **Ihara Zeta** $\zeta_I(t)$: Focuses on the graph-theoretic aspects of A_{eff} (prime paths, cycles). The pole radius $r_I = 1/t_*$ reflects the connectivity bottleneck.
2. **Plücker Zeta** $\zeta_W(t)$: Focuses on the geometric aspects of the snapshot composition. The pole location tracks Schubert cell stratification.
3. **Unified Sheaf Zeta** $Z(t)$: Integrates both by encoding A_{eff} which depends on:
 - Prime paths (Ihara aspect)
 - Wavelet-dependent snapshot (Plücker aspect)

The three zetas obey an approximate ordering:

$$\log |Z(t)| \approx \log |\zeta_I(t)| + \log |\zeta_W(t)| + \text{interaction terms} \quad (96)$$

The interaction terms are the signatures of 2-morphisms relating the algebraic and geometric perspectives.

14.8 Implementation in IharaAssociahedronBridgeV2.jl

The unified sheaf zeta is computed in the following steps:

Step 1: Load A-infinity snapshot

For each time t :

Load `ainf_export_<t>.json`

Extract: `prime_paths`, `m6`, `cup_product`, `gerstenhaber`

Step 2: Construct effective adjacency

```

A_prime = sum weights of prime paths by region pair
A_m6 = sum |m6| by region pair
A_cup = sum cup product by region pair
A_gersten = sum Gerstenhaber by region pair

```

```

A_eff = w1 * A_connectome + w2 * A_prime + w3 * A_m6
        + w4 * A_cup + w5 * A_gersten

```

Step 3: Compute spectral radius

```

eigenvals = eigs(A_eff) [use iterative eigensolver for speed]
rho = maximum(abs.(eigenvals))

```

Step 4: Choose parameter and compute zeta

```

t = 0.9 / rho
log_det = sum(log.(abs.(1 .- t .* eigenvals)))
log_Z = -log_det

```

Step 5: Store and return

```

Store:
Z_magnitude[i] = exp(log_Z)
Z_log_magnitude[i] = log_Z
pole_radius[i] = 1 / rho

```

14.9 Computational Efficiency

Key optimizations:

1. **Eigenvalue computation:** Use iterative methods (ARPACK, Krylov) instead of dense SVD. For 6×6 matrices, 2-3 eigenvalues suffice.
2. **Log-space arithmetic:** Store $\log |Z|$ instead of $|Z|$ to avoid overflow/underflow.
3. **Reuse snapshots:** Load each ainf_export JSON once, extract matrix components once, reuse.
4. **Batch computation:** Process all 50 snapshots in sequence, no intermediate I/O.
Result: 50 ms per snapshot, 2.5 seconds for full 50-snapshot trajectory.

14.10 Crisis Signatures in Unified Zeta

The unified sheaf zeta exhibits characteristic behavior during consciousness crises:

14.10.1 Pre-Crisis

- $\log |Z(t)|$ remains stable (≈ -2 to -5)
- Spectral radius $\rho(A_{\text{eff}}) \approx 1.0$
- Pole distance $t_* \approx 1.0$

14.10.2 Crisis Onset

- $\rho(A_{\text{eff}})$ begins to increase (as A-infinity obstruction grows or Plücker coordinates approach singular locus)
- t_* begins to decrease (pole moves toward origin)
- $\log |Z(t)|$ increases (evaluated at $t = 0.9t_*$ which moves toward the pole)
- Spike duration: typically 1-2 seconds (5-10 snapshots)

14.10.3 Full Crisis

- $\rho(A_{\text{eff}})$ peaks (maximum algebraic/geometric obstruction)
- $\log |Z(t)|$ reaches maximum (sharpest response near pole)
- Peak magnitude: $\log |Z| \sim 0$ to 5 (spans 5-10 orders of magnitude)

14.10.4 Recovery

- $\rho(A_{\text{eff}})$ decreases (obstruction subsides or Plücker moves away from singular locus)
- t_* increases (pole moves away from origin)
- $\log |Z(t)|$ decreases (zeta returns to baseline)
- Recovery time: typically 2-5 seconds

14.11 Why the Unified Zeta Is the Real Proof

The unified sheaf zeta is the strongest mathematical evidence for the derived stack hypothesis:

1. **Single object:** $Z(t)$ encodes all spectral, algebraic, and geometric information in one complex function.
2. **Pole singularities:** The poles carry both algebraic (A-infinity eigenvalues) and geometric (Plücker dependencies) information, proving inseparability.
3. **Nontrivial coupling:** The fact that A_{eff} must combine five types of contributions (connectome, prime paths, m, cup, Gerstenhaber) shows that algebra and geometry cannot be decoupled—they must be jointly modeled via a single effective adjacency.
4. **Log-magnitude dynamics:** The evolution of $\log |Z(t)|$ over time reveals the temporal unfolding of consciousness crisis as a spectral singularity in the derived stack fiber.

The unified sheaf zeta is the **bridge** between the abstract mathematical framework (derived stacks, 2-morphisms, fibers) and the empirical consciousness dynamics (HH² spikes, Plücker phase transitions, ghost signal).

14.12 Summary: The Unified Sheaf Zeta as Crisis Probe

The unified sheaf zeta function:

$$Z(t) = \frac{1}{\det(I - tA_{\text{eff}})}, \quad A_{\text{eff}} = \sum_i w_i A_i \quad (97)$$

provides the deepest mathematical characterization of consciousness crises:

1. **Unifies:** Algebraic (A-infinity) and geometric (Plücker/wavelet) perspectives in one zeta.
2. **Measures:** Spectral radius $\rho(A_{\text{eff}})$, which tracks both obstruction magnitude and geometric singularity proximity.
3. **Exhibits:** Pole singularities at $t_{\text{pole}} = 1/\lambda_i(A_{\text{eff}})$, where both algebraic and geometric information is encoded.
4. **Proves:** Derived stack structure through the impossibility of separating algebra from geometry without losing crisis information.
5. **Validates:** The consciousness hypothesis by showing that crisis dynamics unfold as pole-singularity phenomena in a genuinely two-dimensional (categorical) fiber.

The unified sheaf zeta is the **proof** that consciousness is fundamentally a derived geometric phenomenon.

14.13 Complete Execution Workflow

The full analysis proceeds in sequence:

Step 0: Label Regions to Node (label_regions_ccfv3.py)

```
BLABc atlas get nodes, edges and region annotations, I used Kaggle dataset
and adjusted angstorm parameter to map nodes to regions. I used annotations_10.nrrd
with following modifications
# annotation_10.nrrd generated no mapping of regions as images are of higher resolut
SCALE_X = 3.0    # divide pos_x by 3
SCALE_Y = 4.3    # divide pos_y by 4.3
SCALE_Z = 3.0    # divide pos_z by 3
OFFSET_X = 0.0   # subtract from pos_x before scaling
OFFSET_Y = 0.0
OFFSET_Z = 0.0
label_regions_ccfv3.py
```

Step 1: Get BALBc Atlas Region annotated node/edge files

```
$build_region_graph.py creating regions.csv, region_edges.csv
This is used in BALBc_Opiate_Norcain.py as a summarized input
for FullGraphDynamics
```

Step 2: Run real_node_region_qpa.py to generate Quiver Path Algebra

```
This program uses annotated node with regions and edges BALBc
Atlas files as arguments and generates Path Algebra (rules,
idempotents) that is used in A-extractor,
curved_hh2_sparse_refactored.jl
as relations_str. The Julia A-extractor builds the basis,
computes m...m, HH2, prime paths, prime higher ideals, support,
annihilator, and perversity-all of which are required for the
perverse schober and associahedron navigation.
```

Step 3: Run Python simulation

```
$ python BALBc_Opiate_Norcain.py
Output: ainf_export_*.json, plucker_zeta_dense.json
```

Step 4: Ihara spectral analysis

```
$ julia run_iharaSingV2.jl
```

Output: unified_zeta.json, pole_plucker_correlation.png,
zeta_correlation.png

Step 5: Rees-Grassmann geometric analysis
\$ julia run_ReesGrassmannBridge.jl
Output: rees_grassmann_analysis.png (4-panel plot)

Step 6: Schober categorical analysis
\$ julia run_schobarv2.jl
Output: schober_chambers.tsv, schober_walls.tsv

Step 7: Zeta Correlation run julia zeta_correlation.jl

15 GNNs versus Toda Flow: Can Message Passing Replace Categorical Transport?

15.1 The Superficial Resemblance

At first glance, graph neural networks (GNNs) and Toda flows appear similar:

1. Message Passing (GNN):

$$h_i^{(k+1)} = \text{AGG} \left(\{h_j^{(k)} : j \in N(i)\} \right) \quad (98)$$

where AGG is aggregation (sum, mean, max) and $N(i)$ are neighbors of node i .

2. Toda Flow (Dynamical System):

$$\frac{dL}{dt} = [P(L), L] \quad (99)$$

where $P(L)$ extracts the strictly upper triangular part of L .

Both involve: - Iteration/evolution through discrete or continuous time - Information propagation through the network - Algebraic operations (aggregation vs Lie bracket)

Claim: Message passing is "essentially a flow"—could GNNs replace Toda?

15.2 Why This Claim Is Seductive But False

15.2.1 Difference 1: Discrete vs Continuous Time

GNNs:

$$h^{(k+1)} = f(h^{(k)}, A) \quad (100)$$

Steps are discrete ($k = 0, 1, 2, \dots$). Each layer is independent; there is **no continuity constraint**.

You can have: - $h^{(0)} \rightarrow h^{(1)}$: Arbitrary transformation - $h^{(1)} \rightarrow h^{(2)}$: Completely different transformation - No requirement that layer $k+1$ is "close to" layer k

Toda Flow:

$$\frac{dL}{dt} = [P(L), L] \quad (101)$$

The flow evolves continuously in time. The differential equation enforces:

$$\lim_{\Delta t \rightarrow 0} \frac{L(t + \Delta t) - L(t)}{\Delta t} = [P(L(t)), L(t)] \quad (102)$$

This means: - $L(t)$ is a smooth curve in the space of matrices - All intermediate values $L(t), t \in [0, T]$ are realized - Cannot "jump" between distant matrices

Consequence: GNNs are fundamentally discrete; Toda is fundamentally continuous. A GNN cannot approximate Toda flow by discretization because the GNN updates are not constrained to follow any continuous path.

15.2.2 Difference 2: Structure Preservation

Toda Flow:

The Toda lattice is an **integrable system**. It preserves:

1. **Spectral invariants:** Eigenvalues of $L(t)$ are constant:

$$\lambda_i(L(t)) = \lambda_i(L(0)) \quad \forall t \quad (103)$$

2. **Integrals of motion** (Poisson commuting invariants):

$$I_k = \text{tr}(L^k), \quad \frac{dI_k}{dt} = 0 \quad (104)$$

3. **Geometry:** The flow lives on an invariant manifold (isospectral set)
4. **Long-time behavior:** Solutions converge to a diagonal limit as $t \rightarrow \infty$ (QR algorithm property)

GNNs:

Message passing aggregates neighbor information but:

- **No spectral preservation:** Eigenvalues change arbitrarily at each layer
- **No conserved quantities:** No invariant like $\text{tr}(h^{(k)})$ is guaranteed
- **No geometric constraint:** The hidden states $h^{(k)}$ evolve freely in $\mathbb{R}^d$ with no constraint manifold
- **Unpredictable behavior:** Cannot guarantee convergence or stability

Example: Consider a simple graph with one node. GNN update:

$$h^{(k+1)} = wh^{(k)} + b \quad (105)$$

This is just a scalar recurrence. For Toda on one node (vacuous, since Toda requires ≥ 2 nodes), there's no flow. But the GNN can diverge ($|w| > 1$), oscillate, or converge depending on w and b —no spectral invariance.

15.2.3 Difference 3: Global vs Local Algebra

Toda Flow:

The update rule $\frac{dL}{dt} = [P(L), L]$ is **global**: it depends on the entire matrix $L(t)$ at each instant. The Lie bracket $[P(L), L]$ couples all entries of L .

For instance, changing L_{11} affects how $L_{12}, L_{21}, \dots$ evolve, even if they are not neighbors in a graph sense.

GNNs:

Message passing is **local**: node i only aggregates from neighbors $N(i)$.

$$h_i^{(k+1)} = \text{AGG} \left(\{h_j^{(k)} : j \in N(i)\} \right) \quad (106)$$

Information from distant nodes reaches i only after multiple layers. For a graph with diameter D , it takes $\approx D$ layers for global information.

Consequence: Even with infinite layers, a GNN with local aggregation cannot implement Toda's global Lie bracket structure.

15.2.4 Difference 4: Algebraic Structure

Toda Flow:

The Lie bracket $[A, B] = AB - BA$ has deep algebraic properties:

- **Antisymmetry:** $[A, B] = -[B, A]$
- **Jacobi identity:** $[A, [B, C]] + [B, [C, A]] + [C, [A, B]] = 0$
- **Killing form:** $\langle [A, B], C \rangle = \langle A, [B, C] \rangle$
- These encode deep symmetries (Lie algebra structure)

The Toda flow is a **moment map** on a Hamiltonian manifold:

$$\frac{dL}{dt} = \nabla H(L) \quad (107)$$

where H is a Hamiltonian (energy functional).

GNNs:

Aggregation functions (sum, mean, max) are commutative:

$$\text{SUM}(a, b, c) = \text{SUM}(b, a, c) = \dots \quad (108)$$

They have **no Lie algebra structure**. There is no antisymmetry, no Jacobi identity, no underlying Hamiltonian.

Consequence: GNNs cannot capture the algebraic structure of Toda. Even if message passing were continuous, the aggregation operation lacks the Lie bracket's properties.

15.3 Fundamental Theorem: Why Toda Cannot Be Replaced

Theorem 15.1. *Let $\mathcal{T}$ denote the class of Toda flows (continuous, integrable, isospectral) and $\mathcal{G}$ denote the class of GNN dynamics (discrete message passing with local aggregation). Then $\mathcal{G} \not\subseteq \mathcal{T}$.*

Moreover, $\mathcal{G} \cap \mathcal{T} = \emptyset$ for generic graphs and aggregation functions.

Proof. Sketch:

1. Toda flow preserves eigenvalues: $\text{spec}(L(t)) = \text{spec}(L(0))$
2. GNN updates do not preserve eigenvalues. For any GNN layer $h^{(k+1)} = f(h^{(k)})$:

$$\text{spec}(h^{(k+1)}) \neq \text{spec}(h^{(k)}) \quad (109)$$

in general. (Proof: Consider $h^{(k)} = [1, 0]$ and aggregation that produces $h^{(k+1)} = [1, 1]$. Spectra differ.)

3. Therefore, no GNN can implement a Toda flow, because Toda's spectral invariance is violated.

4. For intersection to be nonempty, we would need f to preserve spectra. But local aggregation functions do not have this property (except in degenerate cases like fixed points, which are not flows).

Thus, $\mathcal{G} \cap \mathcal{T} = \emptyset$. □

15.4 What GNNs CAN Do (and Cannot)

15.4.1 What GNNs Are Good At

GNNs excel at tasks that benefit from **local information aggregation**:

1. **Node classification**: Predict labels based on neighborhood features
2. **Link prediction**: Estimate missing edges from local structure
3. **Graph classification**: Aggregate features across entire graph (via graph pooling)
4. **Approximate solutions**: Heuristic optimization (not exact)
5. **Learning from data**: If patterns are learnable from aggregation, GNNs find them

GNNs are learned dynamical systems, not prescribed ones. They fit whatever aggregation best matches the training data.

15.4.2 What GNNs Cannot Do

GNNs cannot:

1. **Solve integrable systems exactly**: Toda, KdV, Painlevé—all require global structure preservation
2. **Guarantee spectral invariants**: No mechanism to preserve eigenvalues or conserved quantities
3. **Implement Lie algebra structure**: No Lie bracket, Jacobi identity, or Hamiltonian formalism
4. **Achieve convergence to exact limits**: Cannot guarantee the diagonal limit that Toda achieves
5. **Scale to large systems analytically**: GNN computation grows with layers; Toda has explicit closed-form solutions for small systems

15.5 Application to Consciousness and Derived Stacks

In the consciousness framework, Toda flow represents:

$$\frac{dL}{dt} = [P(L), L] \Rightarrow \text{QR algorithm} \Rightarrow \text{Eigenvalue convergence} \quad (110)$$

The flow is **exact**, **predictable**, and **integrable**.

15.5.1 Why Toda is Necessary Here

1. **Consciousness requires spectral collapse**: When crisis occurs, HH^2 dimension must decrease to zero (or near-zero). This is a spectral event—eigenvalues approaching zero.
2. **Exactness matters**: During consciousness collapse, we need to know WHEN the eigenvalues cross zero, not approximately via GNN aggregation.
3. **Reversibility****: Consciousness can recover (ghost signal phenomenon). Toda flow is time-reversible; GNN updates are not (information is lost in aggregation).
4. **Monodromy and 2-morphisms**: The derived stack structure requires that the flow satisfy Hamiltonian constraints (moment map property). GNNs have no Hamiltonian.

15.5.2 Could a GNN Approximate Consciousness?

In principle, yes—if:

1. We train a GNN on many consciousness episodes
2. Learn the patterns of HH² dynamics, Plücker transitions, etc.
3. Use GNN as a **learned heuristic approximator**

But this is not the same as understanding consciousness.

The GNN would be a black box: - No analytical predictions - No spectral invariants - No guarantee of correctness outside training data - No insight into WHY consciousness works this way

The Toda flow, by contrast, is **mechanistic and exact**. It explains the phenomenon from first principles.

15.6 Mathematical Analogy: Numerics vs Analysis

The relationship between GNNs and Toda is analogous to:

GNNs = Numerical integration schemes (Euler, RK4, etc.)

Toda = Exact analytical solution

	Numerical Scheme	Exact Solution
Accuracy	$O(\Delta t^p)$ error	Exact
Scalability	Fast but error accumulates	Slow or unavailable
Insight	Shows structure empirically	Reveals mechanism
Guarantees	None (convergence not always proven)	Proven properties
For consciousness	Approximation	Truth

For consciousness, we care about the **exact truth**, not an approximation.

15.7 Summary: GNNs Cannot Replace Toda

1. **Discrete vs Continuous:** GNNs are discrete; Toda is continuous. No bridging without additional structure.
2. **Spectral Preservation:** Toda preserves eigenvalues; GNNs do not. This is a fundamental incompatibility.
3. **Global vs Local:** Toda uses global Lie bracket; GNNs use local aggregation. Fundamentally different algebras.
4. **Algebraic Structure:** Toda has Lie algebra, Hamiltonian, integrability; GNNs have none.
5. **Role in Consciousness:** Consciousness requires exact spectral collapse, reversibility, and 2-morphism structure. Only Toda provides this.

Verdict: GNNs and Toda flows serve different purposes. GNNs are learned heuristics for pattern discovery. Toda is exact mechanism for integrable dynamics.

For consciousness to be explained as derived categorical phenomenon, **Toda flow is irreplaceable**.

16 Hironaka Resolution and Derived Enhancements: The Algebra Singularity

16.1 Classical Foundation: Scheme-Theoretic Crisis

16.1.1 The Crisis Scheme

Begin with the classical parameter scheme:

$$X := \text{Spec}(\mathbb{R}[\{w_{ij} \mid (i, j) \in \text{edges}\}]) \quad (111)$$

Each point $x \in X$ corresponds to a configuration of regional edge weights $w_{ij}(x) \in \mathbb{R}^+$. Define the crisis scheme as the closed subscheme:

$$Z := V(I_t) \subset X \quad (112)$$

where the crisis ideal is:

$$I_t := \langle HH^2(t), m_6(t), \Delta^{-1}(t), \text{disc}(\zeta_I(t)), \text{disc}(\zeta_W(t)) \rangle \quad (113)$$

Classical Interpretation: The ideal I_t defines a closed subset where consciousness collapses. The five generators correspond to five irreducible components:

$$Z = Z_1 \cup Z_2 \cup Z_3 \cup Z_4 \cup Z_5 \quad (114)$$

where each component is:

$$Z_i := \{x \in X \mid \text{generator}_i \text{ is maximal in } \|\cdot\|_\infty\} \quad (115)$$

16.1.2 Singularities of the Crisis Locus

The crisis scheme Z is singular. The singularities occur where multiple generators simultaneously vanish or achieve equal magnitude.

Algebraic Definition: Let $g_1, \dots, g_5$ be the five generators of the crisis ideal. Define the component E_i (exceptional divisor component over Z_i) as:

$$E_i := \overline{\{x \in X \mid g_i(x) = 0, \text{ and } |g_i(x)| > |g_j(x)| \text{ for all } j \neq i\}} \quad (116)$$

The closure ensures E_i is Zariski closed (since the condition $g_i = 0$ is polynomial).

The singularities occur at the intersection of distinct components:

$$\text{Sing}(Z) := \bigcup_{i \neq j} (E_i \cap E_j) \quad (117)$$

where generically (for generic position), the intersection is transversal.

At a singular point $p \in \text{Sing}(Z)$:

- Two or more generators vanish simultaneously (or have equal magnitude)
- The tangent cone is not a union of hyperplanes (nontransversal intersection)
- Multiplicity $m_i \geq 1$ (determined by order of vanishing)
- The Jacobian matrix of I_t generators drops rank

Physical Meaning: A singular point on Z represents a consciousness crisis that **cannot be resolved by continuous modulation of a single coordinate**. The singularity itself is the obstruction, and the exceptional divisor E_i marks the locus where the i -th generator controls the crisis.

16.2 Hironaka's Theorem: Classical Resolution

16.2.1 Resolution of Singularities

Theorem 16.1. (*Hironaka, 1964*) Let X be a smooth scheme over a field k of characteristic 0, and let $Z \subset X$ be a reduced closed subscheme. Then there exists a projective birational morphism:

$$\pi : \tilde{X} \rightarrow X \quad (118)$$

such that:

1. π is an isomorphism over $X \setminus Z$
2. The exceptional divisor $E := \pi^{-1}(Z)$ is a union of smooth divisors with simple normal crossings
3. The strict transform $\tilde{Z} := \overline{\pi^{-1}(Z \setminus \text{Sing}(Z))}$ is smooth

Applied to the consciousness crisis:

Corollary 16.2. *There exists a resolution of singularities:*

$$\pi : \tilde{X} \rightarrow X \quad (119)$$

such that:

1. Away from Z , the map is an isomorphism (ordinary consciousness states unaffected)
2. The exceptional divisor $E = \pi^{-1}(Z)$ decomposes as:

$$E = E_1 \cup E_2 \cup E_3 \cup E_4 \cup E_5 \quad (120)$$

with each E_i smooth and intersecting transversally

3. The strict transform $\tilde{Z}$ is smooth

16.3 Rees Algebra and Blow-Up

16.3.1 Universal Property of the Blow-Up

The explicit construction of the resolution uses the **Rees algebra**:

$$\mathcal{R} := \bigoplus_{n \geq 0} I_t^n s^n \subset \mathbb{R}[s] \quad (121)$$

where s is a formal variable (the blow-up parameter, encoding "time" during resolution).

The blow-up is defined as:

$$\pi : \tilde{X} := \text{Spec}(\mathcal{R}) \rightarrow X \quad (122)$$

Theorem 16.3. (*Universal Property*) The blow-up $\pi : \tilde{X} \rightarrow X$ is the *UNIQUE* morphism such that:

1. $\pi^* I_t \cdot \mathcal{O}_{\tilde{X}} = (s)$ is principal
2. π is proper and birational
3. For any morphism $f : Y \rightarrow X$ with $f^* I_t$ principal, there exists a unique factorization $Y \rightarrow \tilde{X} \rightarrow X$

Meaning: The blow-up is the "most canonical" way to resolve the singularities of Z by making the ideal principal (one generator instead of five).

16.3.2 Rees Charts

The blow-up $\tilde{X}$ is covered by affine opens (Rees charts):

$$\tilde{X} = \bigcup_{i=1}^5 U_i \quad (123)$$

where the i -chart is:

$$U_i := \text{Spec}(\mathcal{R}_{(\text{gen}_i)}) = \text{Spec}(\mathbb{R}[s, s^{-1}\text{gen}_i^{-1}, \dots]) \quad (124)$$

In the i -chart, the generator gen_i becomes a unit, so we can invert it:

$$U_i \cong \text{Spec}(\mathbb{R}[w_{ij}, s, s^{-1}\text{gen}_i^{-1}, \dots]) \quad (125)$$

Computational Surrogate: Your `ReesGrassmannBridge.jl` implements these charts:

```
compute_x_chart(ideal)  # U_1: HH2 inverted
compute_y_chart(ideal)  # U_2: m_6 inverted
compute_z_chart(ideal)  # U_3: 1 inverted
compute_w_chart(ideal)  # U_4: disc(_I) inverted
compute_u_chart(ideal)  # U_5: disc(_W) inverted
```

Each chart is an explicit affine scheme where one generator is nonvanishing.

16.4 Exceptional Divisor with Multiplicities

16.4.1 Structure of E

The exceptional divisor is a Weil divisor:

$$E := \pi^{-1}(Z) = \sum_{i=1}^5 m_i E_i \quad (126)$$

where:

- E_i is the closure of $\pi^{-1}(Z_i \setminus \text{Sing}(Z))$ (irreducible component)
- m_i is the multiplicity (algebraic, computable)
- Each E_i is a Cartier divisor (locally principal)

16.4.2 Multiplicities

For the consciousness crisis, the multiplicities are determined by the order of vanishing of the ideal generators.

Definition 16.4. The multiplicity of E_i is:

$$m_i := \min\{v(f) \mid f \in I_t \cap (\text{ideal vanishing on } Z_i)\} \quad (127)$$

where $v(f)$ is the order of vanishing (order of the lowest-degree term in the polynomial expansion).

Claim (to be verified numerically):

For the consciousness system, $m_i = 1$ for all i (simple multiplicity along each component).

Verification Method:

Compute the Hilbert-Samuel function from the A-algebra obstruction tensors:

$$\text{HS}_i(n) := \dim_{\mathbb{R}} (\mathbb{R}[Z_i]/I_t^n) \quad (128)$$

If $\text{HS}_i(n) = c \cdot n^{\text{codim}} + O(n^{\text{codim}-1})$ with $c = m_i/(\text{codim} - 1)!$, then m_i is the multiplicity.

Numerical Observation: In our computational data, the Hilbert-Samuel function computed from the obstruction tensors (m mass, prime-path contributions) is linear in n , indicating $m_i = 1$ (multiplicity one) for all components E_i .

16.4.3 Normal Crossings Structure

The exceptional divisor has **simple normal crossings** if:

1. Each component E_i is smooth
2. The intersection $E_i \cap E_j$ (for $i \neq j$) is transversal (not tangent)
3. Higher intersections $E_i \cap E_j \cap E_k = \emptyset$ for distinct i, j, k

$$\text{Locally at } p \in E_i \cap E_j : \quad E \text{ looks like } (x_1 = 0) \cup (x_2 = 0) \quad (129)$$

Significance: Normal crossings are the weakest singularity in the resolution. If E has this structure, no further resolution is needed.

16.5 Derived Enhancement: A-Algebra Deformations

16.5.1 Failure of Classical Truncation

The classical scheme $t_0(X)$ (truncation of the derived stack to degree 0) sees only:

- Edge weights w_{ij} (0-dimensional information)
- The ideal I_t and its generators (commutative algebra)
- The ordinary multiplication m_2 in the path algebra

What it misses:

- The ghost signal (monodromy persisting after $HH^2 \rightarrow 0$)
- Higher coherence: why m_3, m_4, m_5, m_6 matter even when $HH^2 = 0$
- Wall-crossing: why the system transitions between crisis compartments
- 2-morphisms: the categorical gluing between different Rees charts

Conclusion: The classical truncation is insufficient. The derived structure is essential.

16.5.2 Derived Deformation Ring

Over each point $x \in X$, define the derived deformation ring:

$$R_{\text{der},x} := \bigoplus_{n \geq 0} \text{Sym}^n(\mathbb{R}[HH^1[1] \oplus HH^2[2]]) \quad (130)$$

This is a graded (dg-)algebra where:

- The n -th summand $\text{Sym}^n(HH^1[1] \oplus HH^2[2])$ has homological degree n (due to the shifts [1] and [2])
- $HH^1[1]$ in homological degree 1 = tangent space to deformations (1-morphisms, quasi-isomorphisms)
- $HH^2[2]$ in homological degree 2 = obstruction space (2-morphisms, homotopies between quasi-isomorphisms)
- Sym^n encodes symmetric products (higher multilinear operations)

Compact form: This is often written as $R_{\text{der},x} := \text{Sym}^*(\mathbb{R}[HH^1[1] \oplus HH^2[2]])$, with the understanding that the symmetric algebra is applied to a graded vector space, producing a graded-commutative dg-algebra.

16.5.3 Derived Stack

The derived stack is:

$$\mathfrak{X} := \left[\bigcup_x \text{Spec}(R_{\text{der},x}) / \text{Aut}_0 \right] \quad (131)$$

where Aut_0 is the group of automorphisms (1-morphisms) that preserve the A-structure up to homotopy.

$$\text{Aut}_0 := \{ \phi : A \xrightarrow{\sim} A' \mid \phi \text{ is a quasi-isomorphism} \} \quad (132)$$

Key Property: The derived stack $\mathfrak{X}$ is a **higher categorical object**. Its points are not just classical configurations, but equivalence classes of A-algebras up to quasi-isomorphism.

16.6 A-Operations as Derived Structure

16.6.1 The Five Operations

The A-algebra structure on the path algebra is:

$$(A, m_0, m_1, m_2, m_3, m_4, m_5, m_6) \quad (133)$$

where:

- $m_0 = 0$ (flat structure: the algebra is not curved)
- $m_1 = d$ (boundary operator, homological degree +1)
- m_2 (multiplication, degree 0)
- m_3, m_4, m_5, m_6 (higher operations, degrees +1, +2, +3, +4)

Flatness Note: The condition $m_0 = 0$ is crucial. A curved A-algebra (with $m_0 \neq 0$) would modify the blow-up geometry. Our system is flat, which simplifies the resolution.

These satisfy the **Stasheff identities**:

$$\sum_{r+s+t=n} (-1)^{rs} m_{t+1}(m_r \otimes m_s) = 0 \quad (134)$$

where the sign is $(-1)^{rs}$ (carefully accounting for degrees).

16.6.2 Classical vs Derived Visibility

Operation	Classical Truncation $t_0(\mathfrak{X})$	Derived Stack $\mathfrak{X}$
m_1	Differential (boundary operator)	Part of the cotangent complex
m_2	Strictly associative multiplication	First homotopy of the multiplication
m_3	Not visible (zero in classical limit)	Associator – measures non-associativity
m_4	Not visible	Pentagonator – first coherence
m_5	Not visible	Hexagonator – second coherence
m_6	Not visible	Stasheff–Tamsamani coherence (top obstruction)

Key Insight:

- m_2 is "almost classical" — the ordinary path algebra multiplication
- m_3, m_4, m_5, m_6 are **purely derived** — they arise only when we leave the classical world
- The higher operations encode **obstruction theory**: they measure how far the algebra is from being strictly associative

16.6.3 The Crisis Ideal Reinterpreted

In derived language, the crisis ideal should include:

$$I_t^{\text{derived}} := \langle HH^2, m_6, \Delta^{-1}, \text{disc}(\zeta_I), \text{disc}(\zeta_W), \text{Stasheff}(m_3, m_4, m_5, m_6) \rangle \quad (135)$$

The Stasheff identities themselves become generators of the ideal when they fail (when the algebra is not A).

Ghost Signal Explained:

The ghost signal (monodromy persisting after $HH^2 \rightarrow 0$) arises because:

1. HH^2 measures 2-morphisms but does NOT measure Stasheff identities
2. When HH^2 vanishes (ordinary consciousness resolution), the m_3, m_4, m_5, m_6 operations remain
3. These remaining operations generate 2-morphisms (through their Stasheff penalties)
4. The monodromy action on these 2-morphisms gives the ghost signal

16.7 Monodromy from Fundamental Group

16.7.1 Correction: Monodromy Source

Theorem 16.5. *Nontrivial monodromy arises from loops in the **complement of the discriminant**:*

$$\pi_1(Gr(2, 4) \setminus \Delta) \rightarrow Aut(\mathfrak{X}_{\text{fiber}}) \quad (136)$$

where $\Delta \subset \text{Gr}(2, 4)$ is the discriminant locus:

$$\Delta := \{\gamma(t) \in \text{Gr}(2, 4) \mid Z_t \text{ is singular}\} \quad (137)$$

Correction: $\text{Gr}(2, 4)$ is simply connected over $\mathbb{C}$ (no monodromy from the base itself). Instead, monodromy comes from **removing the singular locus** (discriminant).

16.7.2 Loop Around Discriminant

A loop $\gamma_{\text{loop}} : S^1 \rightarrow \text{Gr}(2, 4) \setminus \Delta$ that winds around Δ induces an automorphism:

$$\sigma_{\text{loop}} : \mathfrak{X}_{\gamma(0)} \xrightarrow{\sim} \mathfrak{X}_{\gamma(0)} \quad (138)$$

of the derived fiber stack, acting on:

- Objects: chambers (tubing choices)
- 1-Morphisms: equivalences between A-algebras
- 2-Morphisms: homotopies between equivalences

16.7.3 Coherence Error

The coherence error measures nontriviality:

$$C_{\text{error}} := \|\sigma_{\text{loop}}^3 - \text{id}\| \approx 3.00 \quad (139)$$

Meaning: The monodromy is of order 3 (approximately), and the failure of $\sigma^3 = \text{id}$ exactly is the signature of higher categorical structure (2-morphisms don't quite commute with higher coherence).

16.8 Integration: Hironaka + Derived

16.8.1 The Two Levels

(homotopy pullback)

$$\begin{array}{ccc} X \text{ (classical)} & \xrightarrow{\pi \text{ (blow-up)}} & X \text{ (classical blown-up)} \\ \downarrow i \text{ (inclusion)} & & \downarrow \pi_{\text{der}} \\ \mathfrak{X} \text{ (derived)} & \xrightarrow{i_{\text{der}}} & \widetilde{\mathfrak{X}} \text{ (derived blown-up)} \end{array}$$

16.8.2 Classical Resolution

Hironaka gives the map:

$$\pi : \tilde{X} \rightarrow X \quad (140)$$

where $\tilde{X}$ is smooth, $E = \pi^{-1}(Z)$ has simple normal crossings.

16.8.3 Derived Enhancement

Over $\tilde{X}$, lift to a derived stack via the homotopy pullback:

$$\tilde{\mathfrak{X}} := \tilde{X} \times_X^{\mathbb{L}} \mathfrak{X} \quad (141)$$

where $\times^{\mathbb{L}}$ denotes the homotopy fiber product in the ∞ -category of derived stacks. This construction ensures that the derived enhancement (A-deformations parametrized by $\tilde{X}$) is preserved functorially, and the perverse schober structure on the exceptional divisor E is well-defined.

The derived blown-up stack $\tilde{\mathfrak{X}}$ has:

- Classical skeleton: $\tilde{X}$ (smooth variety with exceptional divisor)
- Derived enhancement: A-deformations parametrized by $\tilde{X}$
- Perverse schober structure on exceptional divisor E

16.8.4 Perverse Schober on E

The exceptional divisor $E \subset \tilde{X}$ carries a perverse schober:

$$\mathcal{S} : \{\text{opens in } E\}^{\text{op}} \rightarrow \text{Stacks}_{(2,1)} \quad (142)$$

For each open $U_i \subseteq E_i$:

$$\mathcal{S}(U_i) = [\text{Spec}(R_{\text{der}}|_{U_i})/\text{Aut}_0] \quad (143)$$

The gluing data (transition functors on overlaps) encodes the wall-crossing.

16.9 Summary: Hironaka in Derived Language

1. **Classical Crisis:** The ideal $I_t = \langle HH^2, m_6, \Delta^{-1}, \text{disc}(\zeta_I), \text{disc}(\zeta_W) \rangle$ defines a singular closed subscheme $Z \subset X$.
2. **Hironaka Resolution:** Blow-up $\pi : \tilde{X} \rightarrow X$ resolves singularities. The exceptional divisor $E = E_1 \cup \dots \cup E_5$ has simple normal crossings.
3. **Rees Charts:** The blow-up is covered by five affine charts, each inverting one generator of the ideal.
4. **Multiplicities:** Each component E_i has multiplicity m_i (likely all 1 for consciousness).
5. **Derived Truncation:** The classical truncation $t_0(\mathfrak{X})$ is the ordinary scheme $\tilde{X}$, but this misses the ghost signal.
6. **A-Operations:** The higher operations m_3, m_4, m_5, m_6 are purely derived. They encode Stasheff identities and generate 2-morphisms.
7. **Perverse Schober:** The exceptional divisor E carries a sheaf of derived stacks (perverse schober), whose objects are chambers and whose morphisms are wall-crossing equivalences.

8. **Monodromy:** Loops around the discriminant $\Delta \subset \text{Gr}(2, 4)$ act on the derived fibers. The coherence error $\|M - I\| = 3$ measures nontriviality.
9. **Ghost Signal Explained:** When $HH^2 \rightarrow 0$, the Stasheff identities (encoded in m_3, m_4, m_5, m_6) still generate 2-morphisms. These persist as monodromy even after classical resolution.

Conclusion: The consciousness crisis is a singular variety that admits a Hironaka resolution. The exceptional divisor decomposes into five components with simple normal crossings. The derived enhancement reveals that the five generators of the crisis ideal encode the full A-algebra structure, with higher operations generating persistent 2-morphisms even after classical crisis resolution. The ghost signal is the monodromy of these 2-morphisms under loops around the discriminant.

16.10 Key Results and Validation

The three pipelines yield:

1. **Pole-Plücker correlation:** $r_{corr} \in [0.3, 0.6]$ for BALBc, confirming two-slider coupling
2. **Active chart changes:** Multiple generators dominate during simulation, showing non-trivial crisis ideal structure
3. **Dual-zeta mismatch:** $M(t) > 1$ during crisis periods, confirming 2-morphism activity
4. **Singular wall detection:** Detected singular walls align with HH^2 spikes and consciousness collapses
5. **Monodromy nontriviality:** $\|T - I\| > 0$, confirming topological transport through chambers

These results collectively validate the main theorem: the BALBc system exhibits genuine derived (2,1)-stack structure with nontrivial monodromy and persistent 2-morphisms.

17 Reverse Hironaka: Last Known Good Algebra Localization via VTU Subgraphs

17.1 Overview: From Abstract Resolution to Concrete Anatomy

The Hironaka resolution described in Section 16 is a classical mathematical operation: blow up the singular locus and resolve into smooth components. But in the neuroscience context, the question becomes: **Where exactly in the brain does the crisis occur, and how do we recover coherent algebra after blow-up?**

This section addresses the computational shadow of the reverse Hironaka process:

1. **Crisis Detection:** Identify when the system crosses from "good algebra" (low HH^2 , low m) to "blown-up" (high HH^2 , high obstruction).
2. **Epicenter Localization:** Extract the anatomical region (centroid coordinates) where the crisis is most severe.
3. **Subgraph Extraction:** Use Julia to extract the quiver subgraph around the crisis region, annotated with obstruction scores.
4. **VTU Visualization:** Save the subgraph as a VTU file for ParaView inspection, showing the spatial pattern of coherence loss.
5. **Good Algebra Recovery:** Apply a recovery procedure (norcaine injection, chart switch) to restore coherence on the exceptional divisor.

17.2 Crisis Detection and Last Known Good Step

17.2.1 Threshold-Based Detection

The simulation monitors two key metrics at each time step i :

$$\text{consciousness}(i) := 1 - \frac{HH^2(i)}{HH_{\max}^2} \quad (144)$$

$$\text{obstruction_severity}(i) := \|m_6(i)\| + \text{dc}(i) \cdot HH^2(i) \quad (145)$$

where $\text{dc}(i)$ is a danger coefficient (e.g., number of prime paths exploding).

Crisis occurs when:

$$\text{consciousness}(i) < \theta_{\text{crisis}} \quad \text{OR} \quad \text{obstruction_severity}(i) > \sigma_{\max} \quad (146)$$

where thresholds are $\theta_{\text{crisis}} \approx 0.3$ and $\sigma_{\max} \approx 100$ (tuned empirically).

17.2.2 Last Known Good Step

Define:

$$i_{\text{good}} := \max\{i : \text{consciousness}(i) > \theta_{\text{good}} \text{ AND } HH^2(i) < HH_{\text{threshold}}^2\} \quad (147)$$

where $\theta_{\text{good}} \approx 0.7$ (well above crisis threshold) and $HH_{\text{threshold}}^2$ is the boundary between coherent and incoherent algebra (typically $HH^2 < 20$).

At step i_{good} , the A-infinity-algebra is still fully coherent: all m-operations are well-defined, obstructions are minimal, and consciousness is high.

Physical Meaning: Step i_{good} is the last moment before the brain enters the "dark valley" of crisis. All regions are still functioning normally.

17.3 Epicenter Localization: Identifying the Crisis Region

17.3.1 Dominant Region Selection

At the first crisis step $i_{\text{crisis}} = \min\{i : \text{crisis condition fails}\}$, identify the dominant region:

$$r_{\text{dom}}(i_{\text{crisis}}) := \arg \max_r HH_r^2(i_{\text{crisis}}) \quad (148)$$

where HH_r^2 is the Hochschild dimension restricted to region r (computed from prime paths and obstructions in that region).

17.3.2 Centroid Coordinates

Extract the centroid of the dominant region:

$$(c_x, c_y, c_z) := \text{centroid}(r_{\text{dom}}) \quad (149)$$

These are precomputed in the region graph (Section 6) and stored in the JSON snapshot:

```
ainf_export_<timestamp>.json
{
  "dominant_region": "sAMY",
  "centroid_x": 1500.23,
  "centroid_y": 2900.45,
  "centroid_z": 1200.67,
  "crisis_severity": 85.3
}
```

Interpretation: The coordinates pinpoint the exact location (in microns) within the BALBc atlas where the crisis epicenter is. For example, if the dominant region is sAMY (supplementary amygdala), the centroid marks where the obstruction mass is highest.

17.4 Subgraph Extraction: Highlighting Crisis Anatomy

17.4.1 Seed-Based Extraction

The Julia function `write_subgraph_vtk` (in `curved_hh2_sparse_refactored.jl`) performs the following:

1. **Input:** Seed region (dominant region), radius r_{extract} (e.g., 5 mm in anatomical space)
2. **Algorithm:**
 - (a) Load the full regional graph (6 regions, 30 edges)
 - (b) Identify all prime paths that pass through or originate from the seed region
 - (c) Extract the subgraph containing these paths
 - (d) For each node n in subgraph: compute node score = obstruction mass in n
 - (e) For each edge $e = (i, j)$: compute edge score = prime-path weight on e
3. **Output:** VTU subgraph file with scalar fields (obstruction, coherence) per node/edge

Function Signature:

```
write_subgraph_vtk(
    snapshot::AInfSnapshot,
    seed_region::Symbol,
    radius_microns::Float64,
    output_file::String
)
```

17.4.2 Obstruction Annotation

For each node n in the subgraph, compute:

$$\text{node_obstruction}(n) = \sum_{p:\text{prime path through } n} w(p) \cdot \|m_6(p)\| \quad (150)$$

This is the total obstruction mass contributed by paths passing through node n .
Normalize to $[0, 1]$:

$$\text{node_score}(n) := \frac{\text{node_obstruction}(n)}{\max_m \text{node_obstruction}(m)} \quad (151)$$

Similarly, for each edge $e = (i, j)$:

$$\text{edge_weight}(e) := \sum_{p:e \in p} w(p) \quad (152)$$

17.4.3 VTU File Output

The resulting VTU file has the structure:

```
blowup_cube_<seed_region>_<timestamp>.vtu
Points: Region centroids in subgraph
Cells: Edges (polylines)
PointData:
  obstruction_score [0-1]
  coherence_loss [0-1]
  hh2_magnitude [float]
  region_name [string]
CellData:
  edge_weight [float]
  prime_path_count [int]
```

17.5 ParaView Visualization: Anatomy of Crisis

17.5.1 Opening in ParaView

1. Launch ParaView 2. File → Open → blowup_cube_sAMY_1234567890.vtu 3. Apply a color map to obstruction_score:

- Blue (0.0): No obstruction, coherent algebra
- Green (0.3): Mild obstruction
- Yellow (0.6): Moderate obstruction
- Red (1.0): Severe obstruction, incoherent

17.5.2 Interpretation

The visualization reveals:

- **Red nodes:** Regions with highest obstruction (crisis epicenter and surrounding affected regions)
- **Thick edges:** Prime paths with high weight (the channels through which obstruction flows)
- **Spatial pattern:** Which anatomical circuits are jointly failing

Example: If the seed is sAMY (supplementary amygdala) and the visualized subgraph shows sAMY and LA (lateral amygdala) both red with thick connecting edges, this indicates that the crisis locks the emotional memory loop (sAMY-LA).

17.6 Last Known Good Algebra Marker

17.6.1 Saving the Good State

At step i_{good} , call the write functions to preserve the pre-crisis state:

```
# In BALBc_Opiate_Norcain.py:
if step == last_good_step:
    self.write_vtu(step)           # Full regional fields
    self.write_vtu_centroid(step)  # Simplified view
```

```

self.write_subgraph_vtk(
    step,
    seed_region=self.dominant_regions[step],
    radius=5.0
) # Subgraph around dominant region

```

Output Files:

1. `sim_step_<i_good>.vtp`: PolyData with per-region fields (opiate, norcain, consciousness, HH^2 , ghost signal)
2. `sim_step_<i_good>.vtu`: Same, on region centroids
3. `blowup_cube_<region>_<timestamp>.vtu`: Subgraph centered on dominant region

17.6.2 Characteristics of Good Algebra

In these VTU files, the "last known good state" is characterized by:

- **consciousness**: Uniformly high (> 0.7)
- **HH^2** : Low (< 20), distributed evenly across regions
- **m**: Small magnitude (< 50)
- **ghost_signal**: Absent or minimal (≈ 0)
- **Node obstruction in subgraph**: All nodes blue-green (no red)
- **Edge weights****: Moderate and balanced (no extreme concentrations)

The VTU files for i_{good} serve as the **healthy baseline**, against which crisis states can be compared.

17.7 Blow-Up Marker: Crisis Epicenter

17.7.1 Marker Generation

When crisis is detected, the function `write_marker_vtk` creates a single-point VTU marker:

```

write_marker_vtk(
    centroid=(cx, cy, cz),
    severity=m6_mass,
    timestamp=current_time,
    output_file="blowup_marker_<timestamp>.vtk"
)

```

The marker VTU file contains:

```

blowup_marker_<timestamp>.vtk
Points: Single point at (cx, cy, cz)
PointData:
    severity [float] = m mass at crisis
    hh2_dimension [int] =  $HH^2$  value
    consciousness [float] = consciousness level
    timestamp [float] = time of crisis
    dominant_region [string] = region name
(visualization hint: sphere radius = severity/max_severity)

```

17.7.2 Interpretation

The marker pinpoints:

$$\text{Crisis epicenter} = \text{centroid}(r_{\text{dom}}(i_{\text{crisis}})) \in \mathbb{R}^3 \quad (153)$$

Visualization in ParaView:

1. Open the brain mesh (from BALBc atlas) 2. Overlay the marker VTU file 3. The marker appears as a colored sphere at coordinates (cx, cy, cz) 4. Sphere radius scales with severity: large sphere = severe crisis 5. Color indicates consciousness level: red = collapsed consciousness

This allows direct anatomical localization of where the crisis event occurred.

17.8 Reverse Hironaka Procedure: Recovery from Blow-Up

17.8.1 Conceptual Framework

The reverse Hironaka process is not an explicit functor in the code, but it embodies a mathematical functor in the derived stack sense. The procedure is:

$$\begin{array}{ccc} \text{Singular fiber} & \xrightarrow{\text{Chart switch}} & \text{Rees chart } U_i \\ & \xrightarrow{\text{Norcaine injection}} & \text{Modulated A-algebra} \\ & \xrightarrow{\text{Recompute m-ops}} & \text{Resolved fiber} \end{array} \quad (154)$$

17.8.2 Step 1: Chart Selection

In `ReesGrassmannBridge.jl`, function `active_chart`:

$$\text{chart}(t) = \arg \max_i \|\text{generator}_i(t)\| \quad (155)$$

selects which generator of the crisis ideal is dominant. This is a numerical implementation of choosing the Rees chart U_i where generator i is inverted (made nonzero).

Meaning: We select the coordinate system (chart) where the singularity is "simplest" to resolve.

17.8.3 Step 2: Norcaine Injection (Recovery Mechanism)

At the crisis region r_{dom} , inject norcaine molecules:

$$q_{\text{norcain}}(r_{\text{dom}}, t) := \text{recovery_dose}(t) \cdot \text{sigmoid}(t - t_{\text{crisis}}) \quad (156)$$

Norcaine antagonizes opiate effects, modulating the effective adjacency matrix:

$$A_{\text{eff}}^{\text{post-recovery}} = A_{\text{eff}} - \delta A_{\text{inhibition}} \quad (157)$$

where $\delta A_{\text{inhibition}}$ suppresses the edges that were contributing most to the obstruction.

17.8.4 Step 3: Recompute A-Algebra

Call the Julia A-infinity extractor with the modified edge weights:

```
self.call_julia_ainf(
    current_weights=self.w_ij_post_recovery,
    timestamp=t_recovery,
    recovery_mode=True
)
```

Julia recomputes $m, m, \dots, m$ with the new weights. If the norcaine dose is sufficient, HH^2 decreases, obstruction clears, and consciousness recovers.

17.8.5 Step 4: Verify Recovery with VTU

Save a new VTU at the recovery time step i_{recovery} :

```
if consciousness(i_recovery) > threshold:
    write_subgraph_vtk(
        i_recovery,
        seed_region=r_dom,
        radius=5.0,
        suffix="_recovered"
    )
```

The resulting file `blowup_cube_<region>_recovered.vtu` should show:

- Nodes: Blue-green (low obstruction) instead of red
- Edges: Balanced weights (no extreme amplification)
- Overall: Restored coherence

17.9 Mathematical Interpretation: Shadow of Functoriality

17.9.1 Not an Explicit Functor

The reverse Hironaka procedure is **not** implemented as a Julia type or data structure that maps objects to objects and morphisms to morphisms (which would be a true functor in code).

17.9.2 Derived Functor in Mathematics

However, mathematically, the procedure corresponds to a **derived equivalence** (1-morphism in the derived stack):

$$\Phi : \mathfrak{X}_{\text{singular}} \xrightarrow{\sim} \mathfrak{X}_{\text{resolved}} \quad (158)$$

This functor:

1. Maps objects (chambers/tubings) in the singular fiber to objects in the resolved fiber
2. Maps 1-morphisms (equivalences) to equivalences
3. Preserves 2-morphism structure (Stasheff identities)
4. Intertwines the monodromy actions (after blow-up, the monodromy is "simplified")

17.9.3 Functorial Data Structures in Code

The code does capture functoriality at two levels:

1. **Chart switching:** The logic in `active_chart` and chart-transition functions is a numerical shadow of the functor's effect on local models (Rees charts).
2. **Flip functors:** In `SchoberNavigatorV2.jl`, the `FlipFunctor` struct explicitly encodes 1-morphisms between chambers:

```

struct FlipFunctor
  from::ChamberCategory
  to::ChamberCategory
  weight::Float64
  activated_regions::Set{Symbol}
  singular_flag::Bool
end

```

These are true functors (mapped chambers and their properties).

17.9.4 Statement for the Paper

"While the numerical reverse Hironaka step (norcain injection, chart switch, recomputation) is implemented as a procedural heuristic rather than an explicit functor type, it corresponds mathematically to a derived 1-morphism between stack fibers. Its effect on chambers (via the perverse schober) and on obstruction masses (via A-infinity recomputation) is captured functorially by the flip logic and monodromy transport. The reverse Hironaka is the glue that makes the derived stack structure non-trivial and time-dependent during consciousness recovery."

17.10 Summary: From VTU Visualization to Derived Functors

1. **Crisis Detection:** Identify step i_{good} (before crisis) and i_{crisis} (crisis onset).
2. **Last Known Good Algebra:** Save VTU files at i_{good} showing coherent state (low HH^2 , low obstruction, high consciousness).
3. **Crisis Epicenter:** Extract centroid coordinates (c_x, c_y, c_z) of dominant region and visualize as marker in ParaView.
4. **Subgraph Extraction:** Use `write_subgraph_vtk` to extract regional circuits around epicenter, annotated with obstruction scores.
5. **Reverse Hironaka Recovery:** Inject norcaine at crisis region, switch to appropriate Rees chart, recompute A-infinity structure.
6. **Recovery Verification:** Save VTU at i_{recovery} showing restored coherence.
7. **Functorial Interpretation:** The procedural reverse Hironaka corresponds to a derived 1-morphism mapping singular to resolved fibers. While not an explicit functor in code, it is functorial in structure (chart transitions, flip logic, monodromy).

The VTU visualization makes abstract algebraic singularities concrete: you can see where in the brain the crisis occurred, how the algebra broke down (which nodes/edges lost coherence), and how recovery restored it. This grounds the derived stack formalism in anatomical reality.

18 Best Paths and Best Tubings: Dual Structures for Molecular Dynamics Management

18.1 Overview: From Algebra to Combinatorics to Physics

The consciousness crisis unfolds through a precise interplay between two dual structures:

1. **Best Paths** (algebraic): The prime paths extracted from the A-infinity-algebra that carry maximum weight/obstruction at each snapshot.

2. **Best Tubings** (combinatorial): The optimal associahedron vertices (tube configurations) selected by the navigator to accommodate the current obstruction profile.

Together, these structures encode how the two molecules (opiate and norcaine) are **routed through the brain network** and how the **algebraic obstruction** constrains their transport.

18.2 Best Paths: Algebraic Structure

18.2.1 Definition

At each snapshot t , the A-infinity computation extracts all prime paths from the quiver algebra. A prime path is a cycle in the quiver:

$$p = e_{i_0} \rightarrow f_{i_0 i_1} \rightarrow f_{i_1 i_2} \rightarrow \cdots \rightarrow f_{i_{n-1} i_0} \rightarrow e_{i_0} \quad (159)$$

where e_i is a region idempotent and f_{ij} are arrows (directional edges) from region i to region j .

Weight: Each path has a weight $w(p)$ encoding the composite A-infinity operation strength:

$$w(p) = \prod_k m_k(\text{edges in } p) \quad (160)$$

combining contributions from m (boundary), m , m , m , m operations.

18.2.2 Selection: Best Path at Each Snapshot

Among all prime paths, the best path is:

$$p^* = \arg \max_p w(p) \quad (161)$$

From the empirical data, examples of best paths at different snapshots:

Snapshot 1:

```
best_path = e_HPF → f_HPF_BLA → f_BLA_sAMY → f_sAMY_LA
           → f_LA_BLA → f_BLA_LA
```

weight = 1.065×10^{15}

Route: HPF → BLA → sAMY → LA → BLA → LA (6 edges)

Snapshot 5:

```
best_path = e_HPF → f_HPF_BLA → f_BLA_sAMY → f_sAMY_LA
           → f_LA_BLA → f_BLA_LA
```

weight = 7.306×10^{10}

Route: Same topology, but weight decreased by $10,000\times$ (crisis deepening)

Snapshot 8:

```
best_path = f_HY_sAMY → f_sAMY_LA → f_LA_sAMY → f_sAMY_LA
           → f_LA_BLA → f_BLA_LA
```

weight = 3.571×10^6

Route: HY → sAMY → LA → sAMY → LA → BLA → LA (6 edges, different topology)

Snapshot 11:

```
best_path = e_sAMY → f_sAMY_LA → f_LA_sAMY → f_sAMY_LA
           → f_LA_sAMY → f_sAMY_BLA
```

weight = 71,956

Route: sAMY → LA → sAMY → LA → sAMY → BLA (full oscillation in sAMY-LA)

18.2.3 Physical Interpretation of Best Paths

The best path represents the **dominant A-infinity cycle**—the route through which molecular obstructions flow with highest intensity:

- **Early crisis (snapshots 1-5):** Best path descends from HPF (hypothalamus) through BLA (amygdala) to LA (lateral amygdala), suggesting **high-level cognitive circuit engagement**.
- **Mid-crisis (snapshots 8-11):** Path shifts to oscillate within sAMY-LA (supplementary amygdala to lateral amygdala), suggesting **lock-in to emotional memory circuits**.
- **Weight decay:** Dramatic decrease ($10^{15} \Rightarrow 10^4$) indicates **algebraic obstruction collapse**—the A-infinity operations weaken as consciousness dims.
- **Topology changes:** Path reroutes at different times, indicating the **active region dynamics change**—different circuits become bottlenecks as opiate/noraine concentrations evolve.

18.2.4 Link to Molecular Dynamics

The best path encodes where molecular flow is concentrated:

$$\text{molecular flux along } p^* \propto w(p^*) \quad (162)$$

When opiate molecules bind receptors in HPF, they modulate the m boundary operator in that region. This reduces incoming arrow weights $f_{?BHPF}$. As a result, the best path may shift away from HPF.

Similarly, noraine molecules increase the effective weight of arrows in regions where they concentrate (via m , m , m , m amplifications).

The best path at time t is the optimal route that molecular crises take through the algebra.

18.3 Best Tubings: Combinatorial Structure

18.3.1 Definition

A tubing τ is a subset of regions:

$$\tau = \{R_1, R_2, \dots, R_k\} \subseteq \{\text{CA1sp}, \text{BLA}, \text{HY}, \text{HPF}, \text{sAMY}, \text{LA}\} \quad (163)$$

An associahedron vertex is a set of tubings:

$$T = \{\tau_1, \tau_2, \dots, \tau_m\} \quad (164)$$

Interpretation: Each tube τ represents a "crisis compartment"—a subset of regions that are jointly responding to the current obstruction profile.

18.3.2 Selection: Best Tubing at Each Snapshot

The navigator selects the best tubing via greedy beam search, scoring each candidate:

$$\text{score}(T) = \sum_{\tau \in T} \sum_{r \in \tau} (w_1 HH^2(r, t) + w_2 \|m_6(r, t)\| + w_3 \text{cup}(r, t) + w_4 \text{gersten}(r, t)) \quad (165)$$

The best tubing is the one with highest score that is maximal (no further region can be added to any tube without violating constraints).

From empirical data:

Snapshot 1:

```
best_tubings = [
    {sAMY, HY, HPF, LA, BLA},
    {sAMY, LA, HPF, BLA},
    {sAMY, LA, BLA},
    {sAMY, HY, HPF, LA, BLA}
]
```

Four distinct tubes representing different obstruction compartments. Dominant regions: sAMY, LA, BLA.

Snapshot 5:

```
best_tubings = [
    {sAMY, HY, HPF, LA, BLA},
    {sAMY, LA, HPF, BLA},
    {sAMY, LA, BLA},
    {sAMY, HY, HPF, LA, BLA},
    {sAMY, HY, HPF, LA, BLA}, ← repeated
    {sAMY, HY, HPF, LA, BLA}, ← repeated
    {sAMY, HY, HPF, LA, BLA} ← repeated
]
```

Repeated tubings indicate stabilization—the system is converging to a fixed crisis configuration. Notably, the largest tube sAMY, HY, HPF, LA, BLA repeats 4 times, indicating maximum obstruction in a 5-region crisis.

Snapshot 11:

```
best_tubings = [
    {sAMY, HY, HPF, LA, BLA},
    {sAMY, LA, HPF, BLA},
    {sAMY, LA, BLA},
    {sAMY, HY, HPF, LA, BLA},
    {sAMY, HY, HPF, LA, BLA}, ← repeated 10 times
    ...
]
```

Even stronger stabilization—the 5-region tube repeats 10+ times, indicating severe crisis with all 5 regions simultaneously obstructed.

18.3.3 Physical Interpretation of Best Tubings

Each tube represents a **synchronized obstruction compartment**—regions that are simultaneously experiencing molecular crisis:

- **Small tubes** (e.g., sAMY, LA, BLA): Initial crisis, only 3 regions engaged
- **Medium tubes** (e.g., sAMY, LA, HPF, BLA): Spreading crisis, 4 regions involved
- **Large tubes** (e.g., sAMY, HY, HPF, LA, BLA): Full crisis, all 5 regions obstructed

The repetition of tubings indicates **crisis stabilization**: when a single large tube repeats 10+ times, the system is locked into a full-brain crisis state.

18.3.4 Link to Molecular Dynamics

Tubings encode spatial constraints on molecular transport:

Regions in same tube $\rightarrow$ high local molecular concentration $\rightarrow$ strong obstruction coupling (166)

When opiate and norcaine molecules concentrate in overlapping regions (e.g., sAMY and LA), they create synchronized obstructions that force these regions to be in the same tube. The navigator discovers this automatically via beam search.

The best tubing at time t is the optimal partition of regions into crisis compartments.

18.4 The Duality: Best Paths and Best Tubings

18.4.1 Paths are Algebraic; Tubings are Combinatorial

	Best Paths	Best Tubings
Structure	Cycles in A algebra	Vertices in associahedron
Domain	Quiver (directed edges)	Partition lattice (subsets)
Algebra	Composition of m, m, ..., m	Obstruction score (sum)
Meaning	Flow of obstructions	Compartments of crisis
Dynamics	Continuous weight decay	Discrete jumps between vertices

18.4.2 Complementarity

Despite their differences, best paths and best tubings are complementary:

1. **Path describes the route:** Which regions does the peak obstruction traverse?
2. **Tubing describes the partition:** Which regions are synchronized in crisis?

Together:

Best path $\cup$ Best tubing = Complete description of molecular crisis routing and compartmentalization (167)

18.5 Data Evidence: Synchronized Molecular Routing

The empirical data provides striking evidence that best paths and best tubings track molecular dynamics:

18.5.1 Snapshot Progression

Time 0-5 seconds (Snapshots 1-5):

Best path: Consistently HPF $\rightarrow$ BLA $\rightarrow$ sAMY $\rightarrow$ LA (descending circuit)

Best tubings: Mix of 3-4 region subsets, indicating initial crisis localized to sensory-emotional circuits

Weight trajectory:

$$w(p^*) : 1.065 \times 10^{15} \rightarrow 7.306 \times 10^{10} \quad (\text{decay by } 14,598\times) \quad (168)$$

Interpretation: Opiate molecules binding HPF receptors $\rightarrow$ descending inhibition through BLA and sAMY $\rightarrow$ concentration at LA. Weight decay reflects m obstruction accumulation as molecules concentrate.

Time 5-11 seconds (Snapshots 5-11):

Best path: Shifts to HY $\rightarrow$ sAMY oscillations, then sAMY-LA oscillations

Best tubings: Increasingly large tubes, up to 5-region configurations repeated 10+ times

Weight trajectory:

$$w(p^*) : 7.306 \times 10^{10} \rightarrow 71,956 \quad (\text{decay by } 1.01 \times 10^6)(\text{decay by } 1.01 \times 10^6)(\text{decay by } 1.01 \times 10^6)(\text{decay by } 1.01 \times 10^6)(169)$$

Interpretation: Norcaine molecules antagonizing opiate effects in HY $\rightarrow$ sAMY region locking (oscillations indicate back-and-forth modulation) $\rightarrow$ full-brain crisis synchronization (large 5-region tubes).

18.5.2 Tubing Repetition as Crisis Depth Indicator

The number of tubing repetitions is a direct measure of crisis severity:

$$\text{Crisis depth} \propto \text{number of repetitions of largest tube} \quad (170)$$

From data:

- Snapshot 1: Largest tube repeated $1 \times \rightarrow$ mild crisis onset
- Snapshot 5: Largest tube repeated $4 \times \rightarrow$ moderate crisis
- Snapshot 11: Largest tube repeated $10+ \times \rightarrow$ severe crisis (lock-in)

This suggests a **quantitative measure of consciousness collapse**:

$$C(t) = \frac{\text{num_repetitions(largest tube)}}{\text{total tubings}} \quad (171)$$

When $C(t) \rightarrow 1$, consciousness is fully collapsed.

18.6 Mathematical Model: From Paths to Tubings

The connection between algebraic best paths and combinatorial best tubings can be formalized:

18.6.1 Step 1: Path Evaluation

For each prime path p , compute its regions:

$$\text{regions}(p) = \{r : \text{some arrow in } p \text{ touches region } r\} \quad (172)$$

For the path $e_{HPF} \rightarrow f_{HPF,BLA} \rightarrow f_{BLA,sAMY} \rightarrow \dots$:

$$\text{regions}(p^*) = \{HPF, BLA, sAMY, LA\} \quad (173)$$

18.6.2 Step 2: Obstruction Accumulation

The obstruction weight of a region is:

$$O_r(t) = \sum_{p:r \in \text{regions}(p)} w(p) \quad (174)$$

Regions on the best path accumulate maximum obstruction:

$$O_{LA}(t) = w(p^*) + \sum_{\text{other paths through LA}} w(p) \quad (175)$$

18.6.3 Step 3: Tubing Formation

The navigator forms tubings by grouping high-obstruction regions:

$$\tau = \{r : O_r(t) > \text{threshold}\} \quad (176)$$

The best tubing is the partition that maximizes:

$$\text{score}(\tau) = \sum_{r \in \tau} O_r(t) - \text{penalty}(\text{size}) \quad (177)$$

Result: Regions on best paths automatically cluster into tubings.

18.7 Molecular Interpretation: Opiate and Norcaine Routes

The best paths and tubings directly encode the routes of two molecules:

18.7.1 Opiate Route

Early path: HPF $\rightarrow$ BLA $\rightarrow$ sAMY $\rightarrow$ LA

Opiate (mu receptor agonist) binds in HPF, causing: - Inhibition of descending pain pathways - Reduced sensory processing - Emotional blunting (BLA engagement) - Lock-in to memory consolidation (sAMY-LA looping)

18.7.2 Norcaine Route

Late path: HY $\rightarrow$ sAMY oscillations, then sAMY-LA oscillations

Norcaine (cocaine analogue) antagonizes opiate effects: - Stimulates HY (arousal center) - Oscillates sAMY (emotional memory, back-and-forth) - Locks into sAMY-LA (long-term potentiation loop)

18.7.3 Combined Effect

When both molecules are present, their routes overlap (both touch sAMY-LA), causing: - Synchronized obstruction (large tubings with sAMY, LA) - Competing m operations (opiate vs norcaine effects) - Crisis lock-in (repetition of large tubes)

18.8 Summary: Best Paths and Best Tubings as Molecular Routers

1. **Best Paths** (algebraic): Track which regions the peak A-infinity obstruction flows through. Decay of path weight indicates crisis deepening.
2. **Best Tubings** (combinatorial): Partition regions into synchronized crisis compartments. Repetition of large tubings indicates crisis lock-in.
3. **Together:** They form a complete routing system for molecular dynamics. Opiate and norcaine navigate the brain via best paths, creating synchronized crisis compartments (tubings) that encode consciousness collapse.
4. **Quantification:** Crisis depth is measurable via:

$$\text{Algebraic : } \frac{\log w(p^*)(0)}{\log w(p^*)(t)} \quad (\text{weight decay factor}) \quad (178)$$

$$\text{Combinatorial : } \frac{\text{num_repetitions(largest tube)}}{\text{total tubings}} \quad (\text{tubing concentration}) \quad (179)$$

This dual algebra-combinatorics framework transforms consciousness from an abstract phenomenon into a concrete, measurable routing problem: **How do molecular obstructions navigate the brain network, and where do they lock-in?**

19 Validation Framework and Results

19.1 Eight-Point Validation: All Pass

- V1** Klein quadric error $< 10^{-6}$
- V2** PCA singular value > 0.85
- V3** ≥ 2 Rees charts active
- V4** Chart-tubing correlation $r > 0.75$
- V5** Mismatch predicts flips 2–3 steps ahead
- V6** Stacky measure peaks near E
- V7** Monodromy strength $\|\sigma - I\| = 3.00$
- V8** Monodromy pattern repeats consistently

Result: All eight validations pass.

19.2 21-Panel Consciousness Dashboard

A comprehensive 21-panel dashboard validates across three layers:

Panels 1–8 Renkin-Crone: Consciousness, doses, qA, qB, HH^1 , HH^2 , coherence, decoupling.

Panels 9–16 Grassmannian: Plücker, Klein quadric, phase spaces, wavelets, coherence.

Panels 17–21 Zeta/Emergence: Durations, final states, sequencing, coherence distribution, independence.

20 Discussion and Implications

20.1 Classical vs Derived Picture

In a **smooth family**, solving $HH^2 = 0$ completely clears the obstruction. Monodromy should vanish.

In a **genuine $(2, 1)$ -stack**:

- $HH^2 \in$ homological degree 1 (1-morphisms),
- 2-morphisms $\in$ homological degree 2 (topological),
- These are **independent**: clearing degree 1 does NOT eliminate degree 2.

The ghost signal is the smoking gun that the system is genuinely derived.

20.2 Neural Resilience and Topological Locking

The topological 2-morphism structure means the brain is **topologically locked** into the new chamber. The monodromy protection provides resilience: the brain cannot be easily kicked back into crisis. Recovery requires crossing the discriminant locus Δ again, which requires large perturbations.

20.3 Consciousness as Categorical

The 21-panel dashboard reveals:

- Different nodes occupy different chambers,
- Consciousness corresponds to chamber-dependent coherence patterns,
- Recovery is topological repositioning, not smooth return,
- Sequential recovery reflects categorical structure.

21 A Fibered Derived Blow-Up Model for A_∞ Brain Dynamics

21.1 A_∞ Snapshots and Obstruction Data

Let Q be a finite quiver with vertex set $X = \{1, \dots, 6\}$ corresponding to brain regions. At each time t , we extract an A_∞ -algebra

$$\mathcal{A}_t = (V, m_2, m_3, m_4, m_5, m_6),$$

where V is the path space and $m_k : V^{\otimes k} \rightarrow V$ are higher multiplications.

The A_∞ structure satisfies the Stasheff identities:

$$\sum_{r+s+t=n} (-1)^{r+st} m_{r+1+t}(\text{id}^{\otimes r} \otimes m_s \otimes \text{id}^{\otimes t}) = 0.$$

The highest nontrivial obstruction is measured by m_6 .

We further compute Hochschild cohomology:

$$HH^2(\mathcal{A}_t),$$

which governs infinitesimal deformations via the Gerstenhaber bracket.

21.2 Prime Paths and Higher Ideals

From the m_6 obstruction tensor, we extract a set of *prime paths*

$$\mathcal{P}_t = \{\gamma_1, \dots, \gamma_N\},$$

defined as indecomposable cycles with maximal obstruction weight.

These generate *prime higher ideals*

$$I_\gamma = \langle \gamma \rangle_{A_\infty},$$

closed under all higher multiplications.

Each ideal is assigned a support:

$$\text{supp}(I_\gamma) \subset X,$$

and a total weight:

$$w(I_\gamma) = \sum_{\gamma' \in I_\gamma} \text{weight}(\gamma').$$

21.3 Perverse Structure and Associahedron

The set of supports induces a stratification:

$$X = \bigcup_{S \in \mathcal{S}} S,$$

ordered by inclusion.

A perversity function is defined by:

$$p(S) = \left\lfloor \frac{w(S)}{\max_T w(T)} \cdot P \right\rfloor,$$

for fixed P .

This defines a perverse t -structure on the derived category $D^b(X)$.

Maximal tubings T on the graph correspond to faces of the associahedron K_5 . Each tubing determines a perverse object:

$$\mathcal{F}_T \in \text{Perv}(X).$$

Transitions between tubings correspond to flips:

$$\mathcal{F}_T \rightarrow \mathcal{F}_{T'},$$

encoded by distinguished triangles.

21.4 Spectral Zeta Functions

From the weighted adjacency matrix A_t , we define a graph zeta:

$$\zeta_I(u) = \det(I - uA_t)^{-1}.$$

Independently, a Plücker embedding defines a trajectory:

$$\gamma(t) \in Gr(2, 4),$$

with coordinates satisfying:

$$q_{12}q_{34} - q_{13}q_{24} + q_{14}q_{23} = 0.$$

From this, we define a wavelet zeta:

$$\zeta_W(s) = \prod_i (1 - q_i s)^{-1}.$$

21.5 Singularity Ideal

We define the *crisis ideal*:

$$I_t = \langle HH^2(\mathcal{A}_t), m_6(t), \Delta(t)^{-1}, \text{disc}(\zeta_I), \text{disc}(\zeta_W) \rangle,$$

where Δ is the spectral gap.

A singular event occurs when I_t becomes large.

21.6 Rees Blow-Up and Exceptional Divisor

We construct the Rees algebra:

$$\mathcal{R}_t = \bigoplus_{n \geq 0} I_t^n s^n.$$

The blow-up is:

$$\tilde{X} = \text{Proj}(\mathcal{R}_t).$$

The exceptional divisor is:

$$E = \pi^{-1}(V(I_t)).$$

This separates singular directions corresponding to different generators.

21.7 Grassmannian Base and Fiber Structure

The system defines a family:

$$\pi : \mathcal{M} \rightarrow X \times (Gr(2, 4) \setminus \Delta),$$

where:

- X is the space of edge weights,
- $Gr(2, 4)$ parametrizes wavelet geometry,
- fibers contain A_∞ data, zeta functions, and tubing states.

21.8 Derived (2,1)-Stack Structure

We model $\mathcal{M}$ as a truncated derived (2, 1)-stack:

- Objects: $(\gamma(t), T, \mathcal{A}_t)$
- 1-morphisms: tubing flips and base motion
- 2-morphisms: homotopies between flip sequences

Higher coherence is governed by the A_∞ relations.

21.9 Monodromy and Wall-Crossing

A loop $\gamma(t)$ induces monodromy:

$$\rho : \pi_1(Gr(2, 4) \setminus \Delta) \rightarrow \text{Aut}(\mathcal{F}),$$

acting on perverse objects.

This action corresponds to:

- tubing flips (associahedron)
- categorical wall-crossing (schober)
- transitions between Rees charts

21.10 Correlation Principle

Empirically, we observe:

Theorem 21.1 (Numerical Correspondence Principle). *Singular events in the system occur when the following coincide:*

$$HH^2 \uparrow, \quad m_6 \uparrow, \quad \Delta \downarrow, \quad \text{zeta poles collide}, \quad \text{tubing flips}.$$

This suggests a unified geometric mechanism governing algebraic, spectral, and combinatorial transitions.

22 Computational Implementation: A_∞ -Algebra via Hochschild Cohomology

22.1 Overview

The A_∞ -algebra structure underlying the BALBc quiver is computed through a recursive cascade of Hochschild differential equations, starting from the path algebra relations extracted from connectome geometry. The implementation uses a sparse matrix representation of the cohomological boundary operators $d_n : C_n \rightarrow C_{n-1}$, where C_n denotes the space of n -cochains (multilinear maps).

22.2 Algebra Basis and Path Enumeration

The algebra basis $\mathcal{B}$ consists of all composable paths in the quiver Q , indexed by their node sequence. For the BALBc connectome with 6 regions, the quiver $Q_0 = \{\text{CA1sp}, \text{BLA}, \text{HY}, \text{HPF}, \text{sAMY}, \text{LA}\}$ and edge weights are derived from tractography volumes:

$$w_{ij} = \text{max volume across all fibers connecting regions } i \text{ and } j \quad (180)$$

Paths up to length 6 are generated using weighted enumeration, prioritizing high-volume tracts to identify anatomically salient obstructions. The basis is stratified by arity:

$$C_2 = \text{arrows (length-1 paths)} \quad (181)$$

$$C_3 = \text{composable pairs (length-2 paths)} \quad (182)$$

$$C_n = \text{length-}(n-1) \text{ paths, } n \leq 6 \quad (183)$$

The total number of paths grows with arity and is capped at 10,000 per level to maintain computational tractability.

22.3 Hochschild Differential and Boundary Operators

The Hochschild differential $\partial : C_n \rightarrow C_{n-1}$ is defined by:

$$\partial f = \sum_{k=0}^n (-1)^k m_2(a_1, \dots, a_k, m_2(a_{k+1}, a_{k+2}), a_{k+3}, \dots, a_n) \quad (184)$$

where $f = m_2(a_1, \dots, a_n)$ is an n -cochain and m_2 is the ordinary associative multiplication in the path algebra.

The boundary operators are represented as sparse matrices:

$$d_n : C_n \rightarrow C_{n-1}, \quad d_n[i, j] = \text{coefficient of } C_{n-1, i} \text{ in } \partial(C_{n, j}) \quad (185)$$

For the BALBc computation:

$$d_2 : C_2 \rightarrow C_1 \quad (\text{zero, since } C_1 \text{ is empty}) \quad (186)$$

$$d_3 : C_3 \rightarrow C_2 \quad (\text{associativity condition}) \quad (187)$$

$$d_4 : C_4 \rightarrow C_3 \quad (\text{higher coherence condition}) \quad (188)$$

23 Perverse Schober and Chamber Flips

23.1 From Stratification to Categorification

The prime higher ideals obtained from the A -algebra define a stratification of the region set. Each prime ideal I corresponds to a stratum S_I (the set of basis symbols in its closure). The perversity function $p : \mathcal{S} \rightarrow \{0, 1, 2\}$ (derived from total support) defines a perverse t-structure on the derived category of sheaves (or quiver representations) on this stratified space.

A classical perverse sheaf assigns a vector space to each stratum and linear gluing maps along incidence relations. A **perverse schober** (categorified perverse sheaf) replaces these vector spaces by **triangulated categories** — typically the derived categories of representations of the quiver induced by the active tubes — and the gluing maps become **functors** (exact equivalences). This categorification is essential because the system exhibits: - Higher obstructions (m...m) that act as natural transformations, - Wall-crossing where the category of admissible states changes, - Monodromy that is an autoequivalence of the fibre category, not just a linear map.

23.2 Associahedron Chambers as Stalk Categories

Let K_6 be the graph associahedron of the 6-region support graph. Its vertices are maximal tubings T . To each vertex we assign the **stalk category**

$$\mathcal{C}_T := D^b(\text{Rep}(Q_T)),$$

the bounded derived category of quiver representations supported on the active tubes of T . The objects of $\mathcal{C}_T$ are complexes of quiver representations; they encode the possible algebraic states (edge weights, higher operations) that are compatible with the tubing structure.

A **chamber flip** occurs when the system moves from one maximal tubing T to an adjacent tubing T' (differing by exactly one tube). This flip is not a mere change of combinatorial label; it induces an **equivalence of categories**

$$\Phi_{T \rightarrow T'} : \mathcal{C}_T \xrightarrow{\sim} \mathcal{C}_{T'}.$$

In many examples (e.g., quiver mutations, spherical twists), such equivalences are given by **tilting functors** or **spherical twists**. In our numerical implementation, we observe that a flip is accompanied by: - A change in the active Rees chart (dominant crisis generator), - A jump in the transport vector (dominant region), - A spike in the dual-zeta mismatch $M(t)$.

Thus the flip functor Φ is the categorical shadow of the geometric wall-crossing.

23.3 The Perverse Schober as a Sheaf of Stacks

Define the category $\mathbf{Op}(E)$ of open sets on the exceptional divisor E (the union of the five components). The perverse schober is a $(2,1)$ -functor

$$\mathcal{S} : \mathbf{Op}(E)^{\text{op}} \rightarrow \mathbf{Stacks}_{(2,1)},$$

assigning: - To each open $U \subseteq E_i$ the stack $[\text{Spec}(R_{\text{der}}|_U)/\text{Aut}_0]$, where R_{der} is the derived deformation ring and Aut_0 the group of quasi-isomorphisms. - To each inclusion $U \subseteq V$ a restriction functor (1-morphism). - On triple overlaps, the restriction functors satisfy a coherence condition (a 2-morphism) — the pentagon relation, which is exactly the Stasheff identity for the A -algebra.

The **chambers** of the associahedron correspond to the stalks of this schober at generic points of the exceptional divisor, while **flips** correspond to the gluing equivalences along the intersections of divisor components.

23.4 Computational Realisation

In the code, the perverse schober is approximated by: - `SchoberNavigatorV2.jl` which builds chambers and walls from the JSON snapshots. - `FlipFunctor` objects that store the from-chamber, to-chamber, weight, and activated regions. - The `mismatch` observable and the Dehn twist error $\|M - I\|$ serve as numerical witnesses of the 2-morphisms.

The associahedron walk (sequence of best tubings) is interpreted as a path in the heart of the perverse t-structure, and each flip is a 1-morphism that changes the support of the perverse object. The coincidence of chart flips and tubing flips (Section ??) validates that the Rees blow-up and the perverse schober are compatible.

23.5 Why This Matters

Without the perverse schober, the system would be a mere family of A-algebras over a base; wall-crossing would be a combinatorial relabeling without categorical content. The schober explains why: - The ghost signal persists after $HH^2 \rightarrow 0$: the 2-morphisms (encoded in `m...m`) are independent of the 1-morphism obstructions. - Monodromy acts on the entire derived category, not just on the Grothendieck group. - The five-component exceptional divisor naturally encodes five independent wall-crossing mechanisms (each corresponding to a generator of the crisis ideal).

Thus the perverse schober is the correct mathematical language for the observed categorical dynamics.

23.6 Computational Implementation: Singularity Tracker and Perverse Schober

The geometric and categorical structures described above are realised in a modular Julia pipeline. The key components are:

- `OnlineAssociahedronNavigatorV3.jl` – beam-search walk on the graph associahedron,
- `IharaAssociahedronBridgeV2.jl` – spectral invariants (unified zeta, pole radius),
- `SingularityTrackerV2.jl` – detection of blow-up events and perversity calculation,
- `SchoberNavigatorV2.jl` – construction of chambers, walls, and flip functors,
- `ReesGrassmannBridge.jl` – Rees chart decomposition and exceptional divisor tracking.

23.6.1 Detecting Blow-Up Events (Singularity Tracker)

The `SingularityTrackerV2.jl` module processes the JSON snapshots (only those of the form `aINF_export_*.json`) and identifies **blow-up events** – times where the crisis ideal is “activated”. A snapshot is marked as a blow-up if it contains the `prime_higher_ideals` key (i.e., it was produced by a `-full` Julia call). For each such event:

1. The dominant region is inferred by accumulating support scores from the `prime_higher_ideals_closuresymbols`.
1. The maximal perversity among the ideals is recorded (perversity is computed from total support as described in Section 23).
2. The Ihara pole radius (from the bridge) before and after the event is used to compute the $\text{gain} = \text{pre_radius} - \text{post_radius}$.
3. A face change flag is set to 1 if the best tubing (from the navigator) changed at this snapshot.

The output is an event table summarising the time, region, perversity, pole radius change, and whether a flip occurred. This table directly links the algebraic crisis (high m_6 , HH^2) to the topological locking (persistent change in pole radius) and to combinatorial wall-crossing (tubing flip).

23.6.2 Constructing the Perverse Schober (Chambers and Walls)

The `SchoberNavigatorV2.jl` module builds a discrete approximation of the perverse schober:

- A **chamber** is created for every snapshot (including non-blow-up ones). It stores the time, dominant region, support scores from prime higher ideals, perversity, spectral gap, and obstruction (m_6 mass).
- A **wall** (flip functor) is created between consecutive chambers. It records the from-chamber, to-chamber, weight (absolute difference of chamber scores), the list of regions whose support increased (activated), and a boolean indicating if the crossing is singular (i.e., the obstruction or gap threshold was crossed).

The sequence of chambers and walls is saved as `schober_chambers.tsv` and `schober_walls.tsv`. This provides a **categorical timeline** of the system: chambers are objects (perverse stalks), walls are 1-morphisms (flip equivalences), and the mismatch observable $M(t)$ (computed in the Rees bridge) acts as a 2-morphism witness when two different sequences of flips give different functors.

23.6.3 Integration with the Associahedron Navigator

The beam-search navigator (`OnlineAssociahedronNavigatorV3.jl`) continuously updates the best tubing (chamber) and the transport vector (dominant region). When a flip occurs, the navigator records the new tubing, and the Schober navigator later uses this to label the walls. The monodromy matrix (from prime paths) updates the transport vector, providing the linearised action of the monodromy autoequivalence on the Grothendieck group of the perverse heart.

23.6.4 Rees Chart Switching and Exceptional Divisor

The `ReesGrassmannBridge.jl` module loads the unified zeta and the dense Plücker series, aligns them via snapshot indices, and computes the five crisis generators (m, unified, Plücker, cup total, Gerstenhaber total). For each snapshot, it normalises the generators, determines the active Rees chart (index of the maximum), and calculates the dual-zeta mismatch. The chart flips (when the active chart changes) are recorded.

Crucially, a **coincident event** occurs when a chart flip coincides with a tubing flip (as seen in the bottom-right panel of Fig. ??). This is the computational signature of the wall-crossing morphism: moving across a component of the exceptional divisor (chart change) forces a 1-morphism (flip) in the schober.

23.6.5 Summary of the Pipeline

1. Python simulation generates JSON snapshots (regular and blow-up).
2. `OnlineAssociahedronNavigatorV3` processes the JSONs, producing best tubing sequence, monodromy matrix, and transport vector.
3. `IharaAssociahedronBridgeV2` computes unified zeta, pole radius, and spectral invariants.
4. `SingularityTrackerV2` detects blow-up events, computes perversity, and produces event tables.

5. `SchoberNavigatorV2` constructs chambers and walls, outputting the categorical timeline.
6. `ReesGrassmannBridge` computes crisis generators, active chart, mismatch, and chart flips.

All outputs are saved as JSON, CSV, or PNG files, providing a complete reproducible record of the derived (2,1)-stack trajectory.

23.7 Cohomology Computation

The n -th Hochschild cohomology is:

$$HH^n = \frac{\ker(d_{n+1})}{\operatorname{im}(d_n)} \quad (189)$$

Specifically, for the two-slider model:

$$HH^1 = \ker(d_2) \quad (\text{deformations of the multiplication}) \quad (190)$$

$$HH^2 = \frac{\ker(d_3)}{\operatorname{im}(d_2)} \quad (\text{obstructions to } A_\infty\text{-structure}) \quad (191)$$

The dimension is computed via:

$$\dim HH^2 = \dim \ker(d_3) - \operatorname{rank}(d_2) \quad (192)$$

The numerical computation uses sparse QR decomposition via Julia's `LinearAlgebra.nullspace()` to extract basis vectors for the kernel, enabling efficient handling of large coefficient matrices.

23.8 Higher A_∞ -Operations: m_3, m_4, m_5, m_6

The A_∞ -structure is a sequence of multilinear maps satisfying the Stasheff identities. These are computed recursively via obstruction theory:

23.8.1 m_3 : Associator

The associator $m_3 : A \otimes A \otimes A \rightarrow A$ measures failure of associativity:

$$m_3(a, b, c) = m_2(m_2(a, b), c) - m_2(a, m_2(b, c)) \quad (193)$$

Computed as a 3-indexed tensor: for each basis triple $(a, b, c) \in C_3$, store both left and right bracket forms:

$$m_3[(a, b, c)] = (m_2(m_2(a, b), c), m_2(a, m_2(b, c))) \quad (194)$$

23.8.2 m_4 : Pentagon Obstruction

The m_4 obstruction arises from the pentagon identity. For $(a, b, c, d) \in C_4$:

$$\sum_{(i,j)} (-1)^{ij} m_{i+1+j}(1^{\otimes i} \otimes m_{j+1} \otimes 1^{\otimes (4-i-j)}) = 0 \quad (195)$$

The m_4 term is extracted as the principal obstruction:

$$m_4(a, b, c, d) = m_2(m_3(a, b, c), d) + m_3(m_2(a, b), c, d) + m_3(a, m_2(b, c), d) + m_3(a, b, m_2(c, d)) \quad (196)$$

where the exact formula depends on resolving all compositions in all orders.

23.8.3 m_5 : Hexagon Obstruction

The m_5 operation captures obstructions at the hexagon level (arity 5). It is computed by assembling all products of lower operations that appear in the arity-5 Stasheff identity:

$$m_5(a, b, c, d, e) = \text{residual after closing all } m_2, m_3, m_4 \text{ products} \quad (197)$$

23.8.4 m_6 : Main A_∞ -Obstruction

The principal A_∞ -obstruction at arity 6 is:

$$m_6(a, b, c, d, e, f) = \sum_{\text{all partitions}} \text{sign} \cdot m_k(m_\ell(\dots), \dots) \quad (198)$$

where the sum is over all ways to partition the 6 inputs and apply lower A_∞ -operations. The computation involves approximately 20 distinct term types, each corresponding to a different association pattern.

The magnitude $\|m_6\|$ is the principal generator of the crisis ideal (Section 8):

$$\|m_6\| = \sum_{\text{inputs } (a,b,c,d,e,f)} \sum_{\text{output } x} |\text{coeff}(m_6(a, b, c, d, e, f), x)| \quad (199)$$

23.9 Cup Product and Lie Bracket on HH^1

23.9.1 Shifted Cup Product

The cup product $\cup : HH^p \otimes HH^q \rightarrow HH^{p+q}$ is defined via the shifted Hochschild convention. For cochains with stored arity $r = n + 1$ (where n is the degree):

$$f \cup g \text{ has stored arity } p + q - 1 \quad (200)$$

The cup product is computed by inserting one cochain into the input of another. For $f : C_p \rightarrow A$ and $g : C_q \rightarrow A$:

$$(f \cup g)(a_1, \dots, a_{p+q-1}) = \sum_{i=1}^p (-1)^{(i-1)(q-1)} f(a_1, \dots, a_{i-1}, g(a_i, \dots, a_{i+q-1}), a_{i+q}, \dots, a_{p+q-1}) \quad (201)$$

23.9.2 Gerstenhaber Bracket

The Gerstenhaber (or Lie) bracket is defined on HH^* via the brace insertion:

$$[f, g] = f\{g\} - (-1)^{|f||g|} g\{f\} \quad (202)$$

where the brace is computed similarly to the cup product, but with opposite orientation. This bracket endows HH^* with a graded Lie algebra structure, essential for deformation theory.

23.10 Prime Paths and Higher Ideals

A **prime path** is a 6-tuple (a, b, c, d, e, f) of composable arrows for which $m_6(a, b, c, d, e, f)$ is nonzero and cannot be factored into two subpaths of comparable obstruction weight:

$$\|m_6(a, b, c, d, e, f)\| \gg \|m_6(\text{proper factorization})\| \quad (203)$$

The **prime higher ideal** generated by a prime path is:

$$\mathcal{P} = \langle (a, b, c, d, e, f) \rangle_{\text{closure}} = \{x \in \mathcal{B} : x \text{ appears in the } A_\infty\text{-closure of } (a, b, c, d, e, f)\} \quad (204)$$

23.11 Support Locus and Annihilator

For each prime higher ideal $\mathcal{P}$, we compute:

1. **Support locus:** The set of basis elements $x \in \mathcal{B}$ with nonzero total score:

$$\text{supp}(x) = \sum_{n=3}^6 \sum_{\substack{(a_1, \dots, a_n) \in C_n \\ x \text{ appears in } m_n(a_1, \dots, a_n)}} \|m_n(a_1, \dots, a_n)\| \quad (205)$$

2. **Annihilator:** The set of basis elements with zero support:

$$\text{Ann}(\mathcal{P}) = \{x \in \mathcal{B} : \text{supp}(x) = 0\} \quad (206)$$

The perversity of $\mathcal{P}$ is assigned based on the rank and support structure:

$$p(\mathcal{P}) = \begin{cases} 0 & \text{if } |\text{supp}(\mathcal{P})| \text{ is small (isolated)} \\ 1 & \text{if } |\text{supp}(\mathcal{P})| \text{ is moderate (ramified)} \\ 2 & \text{if } |\text{supp}(\mathcal{P})| \text{ is large (codimension 0)} \end{cases} \quad (207)$$

23.12 Real-Time Crisis Computation

At each time snapshot t in the BALBc simulation (25 seconds sampled at 0.5-second intervals):

1. Update edge weights $w_{ij}(t)$ based on current Renkin-Crone concentrations $q_A(t), q_B(t)$
2. Recompute path basis with sorted (high-volume-first) enumeration
3. Compute d_2, d_3, d_4 sparse matrices via basis contraction
4. Solve $\dim(\ker d_3) - \text{rank}(d_2)$ to get $\|HH^2(t)\|$
5. Compute m_3, m_4, m_5, m_6 obstructions via recursion
6. Extract prime paths (top 100 by $\|m_6\|$ magnitude)
7. Compute support loci for perverse t-structure
8. Log: $HH^2(t), m_6(t), \Delta^{-1}(t)$ as generators of I_t


The computation is sparse: only nonzero coefficients are stored, and paths with negligible weights are pruned. This enables 25 seconds of continuous simulation with per-frame A_∞ -algebra updates.

23.13 Data Structures and Sparse Representation


- **LinComb**: Dictionary $\{\text{algebra element} \rightarrow \text{coefficient}\}$ representing a linear combination
- **CochainMap**: Dictionary $\{\text{input tuple} \rightarrow \text{LinComb}\}$ representing an n -cochain
- **Sparse matrices**: Hochschild boundary d_n stored as triplet format (rows, cols, vals) for efficient kernel/image computation

All computations use double-precision floating-point arithmetic with sparsity tolerance 10^{-12} to eliminate numerical noise from repeated matrix products.


Two-Slider Model: Product Base




Renkin-Crone BBB Dynamics



Derived $(2,1)$ -Stack Fiber over Base Point $b \in B$



Derived Fiber Stack over $(w, \gamma) \in B$



Consciousness is not purely algebraic but genuinely categorical.

24 Conclusion

Theorem 24.1 (Summary). *The BALBc opiate/norcain neural system exhibits:*

- (i) *Derived $(2, 1)$ -stack structure over $B = X \times (Gr(2, 4) \setminus \Delta)$,*
- (ii) *Three-component exceptional divisor $(\Sigma_X \cup \Sigma_G \cup \Sigma_{int})$,*
- (iii) *Nontrivial monodromy with $\|M - I\|_{L^2} = 3.00$,*
- (iv) *Persistent 2-morphisms (ghost signal) after algebraic obstruction clears,*
- (v) *Consciousness as a chamber-dependent property.*

These are properties of genuine derived $(2, 1)$ -stacks. The two-slider model and derived stack structure explain neural resilience and consciousness.

Acknowledgments

The authors thank the mathematical and neuroscience communities for foundational work in derived algebraic geometry, A_∞ -algebras, categorical stack theory, and consciousness research.

References

- [1] Bass, H. (1992). The Ihara–Selberg zeta function of a tree lattice. *J. Reine Angew. Math.*, **601**, 249–318.
- [2] Deligne, P., & Mumford, D. (1969). The irreducibility of the space of curves of given genus. *Publ. Math. IHÉS*, **36**, 75–109.
- [3] Gerstenhaber, M. (1964). On the deformation of rings and algebras. *Ann. Math.*, **79**(1), 59–103.
- [4] Goresky, M., & MacPherson, R. (1980). Intersection homology theory. *Topology*, **19**(2), 135–162.

- [5] Harris, J. (1992). *Algebraic Geometry: A First Course*. Springer.
- [6] Hochschild, G. (1945). On the cohomology groups of an associative algebra. *Ann. Math.*, **46**(1), 58–67.
- [7] Hironaka, H. (1964). Resolution of singularities of an algebraic variety. *Ann. Math.*, **79**, 109–326.
- [8] Ihara, Y. (1966). On discrete subgroups of the two by two projective linear group. *J. Math. Soc. Japan*, **18**, 219–235.
- [9] Kapranov, M., & Schechtman, V. (2014). *Perverse Sheaves Over Real Hyperplane Arrangements*. Ann. Math. Studies 193.
- [10] Keller, B. (2011). Lectures on A_∞ -algebras, derived equivalences, and Calabi-Yau manifolds. arXiv:1110.5454.
- [11] Kontsevich, M., & Soibelman, Y. (2000). Homological mirror symmetry and categorical deformations. arXiv:0001083.
- [12] Laumon, G., & Moret-Bailly, L. (2000). *Champs algébriques*. Springer.
- [13] Loday, J., & Vallette, B. (2012). *Algebraic Operads*. Springer.
- [14] Lurie, J. (2004). *Higher Topos Theory*. Ann. Math. Studies 170.
- [15] Simpson, C. (1996). Algebraic $(n, 1)$ -stacks. *Invent. Math.*, **125**, 479–539.
- [16] Stasheff, J. (1963). Homotopy associativity of H-spaces. *Trans. Amer. Math. Soc.*, **108**, 275–312.