

A CONTEXT ALGEBRA FOR AUTOREGRESSIVE SYSTEMS: A_∞ -CATEGORIES, TWISTED OBJECTS, SHEAVES, P-ADIC REFINEMENT, AND RELATION-SENSITIVE NERVE GEOMETRY

[AUTHORS]

CONTENTS

Preface: what this paper is about	2
1. The context category $\mathcal{C}_{\text{ctx}}$	2
1.1. The primary object	2
1.2. Connection to Seidel’s framework	3
1.3. The A_∞ -categorical foundation	4
1.4. Contextual degeneration modes	4
2. Layer one: dual nerve compatibility geometry	5
2.1. Contextual compatibility: the problem	5
2.2. Two simplicial complexes in one vocabulary	5
2.3. The contextual transport defect score	6
2.4. Constructing N_{env} with genuine topology	6
2.5. Experimental results on contextual transport defect	6
3. Layer two: α -complex filtration	6
3.1. Why Rips is the wrong complex for hidden states	6
3.2. Per-layer topology and the phase transition	7
3.3. Observability zones	7
4. Layer three: sheaf coboundary	8
4.1. The sheaf on $\mathcal{C}_{\text{ctx}}$	8
4.2. Transport defect on long sequences	8
5. Layer four: Bockstein refinement tower	8
5.1. Context refinement as an inverse system	8
5.2. The collapse: what it reveals	8
6. Layer five: Frobenius orbits and the Galois structure	9
6.1. Iterated contextual transfer	9
6.2. Three corrections from peer review	9
7. The relation-sensitive nerve and the Dehn twist obstruction	10
7.1. The central missing ingredient	10
7.2. The relation-sensitive model nerve	10
7.3. The Dehn twist obstruction	10
7.4. Experimental results: full relation score	11
8. The five layers as a system	11
8.1. Independence and triangulation	11
8.2. The comparison map as the central invariant	12

Date: June 11, 2026.

Grounded in Seidel’s p-adic splitting framework [1], Henniart–Vignéras representation theory [3], and Lefèvre–Hasegawa’s A_∞ -category theory [2]. All experimental code available at [repository].

9.	BV differential calculus on context transport	12
9.1.	Two foundational papers	12
9.2.	Three metric constraints	12
9.3.	Quantum Steenrod operations	12
9.4.	The cotangent bridge	13
10.	Stasheff experiments and the twisted object regime	13
10.1.	The curved A_∞ relation	13
10.2.	Experimental results	14
11.	Derivative extraction: a falsifiability test	14
11.1.	Setup	14
11.2.	Predictions	14
11.3.	Results	14
11.4.	What the results establish	15
12.	Experiments: probing contextual dynamics	15
12.1.	Setup	15
12.2.	Experiment 1: transport defect via dual nerve	15
12.3.	Experiment 2: relation-sensitive nerve	16
12.4.	Experiment 3: checkpoint sweep	16
12.5.	Layer comparison (Experiment 1 extension)	16
13.	Failures as algebraic boundary conditions	16
14.	Predictions and empirical programme	18
14.1.	Confirmed on synthetic models	18
14.2.	Predictions for trained models	18
15.	Discussion: what $\mathcal{C}_{\text{ctx}}$ is and is not	18
15.1.	What has been established	18
15.2.	Addressing the criticism	19
15.3.	What has not been established	19
15.4.	The broader programme	19
15.5.	A research programme, not a conclusion	19
	References	20

PREFACE: WHAT THIS PAPER IS ABOUT

This paper develops the foundations of a **context algebra** $\mathcal{C}_{\text{ctx}}$ for autoregressive sequence generation. It is not a paper about hallucination detection, though hallucinations appear throughout as stress tests.

The distinction matters. A hallucination detector asks: *is this output true?* A context algebra asks: *what algebraic structures organise the evolution of context in autoregressive systems?* The second question is broader, more mathematical, and—as we discovered through an extended research process—more tractable.

The shift clarifies everything. Under the hallucination framing, structures like Bockstein filtration depth, Frobenius orbit decomposition, and sheaf coboundary norms were overengineered classifiers fighting against a simple cosine similarity baseline. Under the context algebra framing, these same structures are different projections of a single underlying phenomenon: the geometry of *contextual refinement, transport, and obstruction* in a system that generates text by iterating a learned transition operator.

Hallucinations become one degeneration mode among several. They are useful precisely because they stress the machinery— context transport, gluing, orbit stability, lifting structure— in ways that smooth factual generation does not. The tearing reveals the geometry.

The paper records the full research arc: every theorem, every failure, every correction. This is intentional. The failures identify regime boundaries. The corrections identify what the algebra is actually measuring. Both are more informative than a clean final statement would be.

1. THE CONTEXT CATEGORY $\mathcal{C}_{\text{ctx}}$

1.1. The primary object. Let M be a language model with hidden state space $\mathbb{R}^d$, generating a sequence $h_0, h_1, \dots, h_n \in \mathbb{R}^d$. We organise this data into a mathematical structure.

Definition 1.1 (Context category). The *context category* $\mathcal{C}_{\text{ctx}}$ of a model M on a sequence of length n is a structured category with:

- (i) **Objects** $\{X^k\}_{k=1}^K$: the skeleton windows $X^k = (h_{(k-1)s}, \dots, h_{ks-1})$ for window size s and depth K (we use $K = 8, s = 128, n = 1024$).
- (ii) **Morphisms** $T_{k\ell} : X^k \rightarrow X^\ell$: the *contextual transport operators*, fitted as

$$T_{k,k+1} = \arg \min_T \|TH_k - H_{k+1}\|_F^2 + \varepsilon \|T\|_F^2,$$

where $H_k \in \mathbb{R}^{s \times d}$ is the hidden-state matrix of window X^k .

- (iii) **Sheaf** $\mathcal{F}$: the assignment $\mathcal{F}(X^k) = \Sigma_k^{1/2}$ (Cholesky factor of the empirical covariance of X^k), with restriction maps ρ_R, ρ_L induced by $T_{k,k+1}$.
- (iv) **Nerve** $N_{\text{ctx}}(\mathcal{U})$: the nerve of the cover $\mathcal{U} = \{X^k\}$ defined by centroid proximity in PCA space, with filtration given by centroid distances.
- (v) **Filtration** $X^1 \subset X^2 \subset X^4 \subset X^8 \subset \dots$: the skeleton filtration encoding refinement depth (formally analogous to the p-adic tower $\dots \rightarrow \mathbb{Z}/p^3 \rightarrow \mathbb{Z}/p^2 \rightarrow \mathbb{Z}/p$).
- (vi) **Galois action**: for each prime p , the Frobenius $\phi_p : x \mapsto x^p$ acts on the eigenvalues of $T \bmod p$, partitioning contextual modes into orbits.

Five algebraic structures operate on $\mathcal{C}_{\text{ctx}}$. Each measures a different aspect of contextual dynamics. None is more fundamental than the others.

Structure	Input	What it measures
Dual nerve map $\phi : N_{\text{ctx}} \rightarrow N_{\text{env}}$	$T, \mathcal{F}, N_{\text{env}}$	Contextual compatibility with environment
α -complex $K_\alpha(X^k)$	$\{h_t\}_{t \in X^k}$	Manifold geometry of context neighborhoods
Sheaf coboundary $\rho_R - \rho_L$	$T, \Sigma_k, \Sigma_{k+1}$	Transport defect / gluing failure
Bockstein depth $F_{\text{depth}}(T; p)$	$T \bmod p$	Refinement liftability depth
Frobenius orbits $\mathcal{O}_p(T)$	$\text{char.poly}(T)/\mathbb{F}_p$	Context collapse at prime p

1.2. Connection to Seidel’s framework. The architecture of $\mathcal{C}_{\text{ctx}}$ is motivated by Seidel’s p-adic splitting of the quantum connection [1]. In Seidel’s setting, one has a closed monotone symplectic manifold M , quantum cohomology $H^*(M)[q]$, and the quantum connection

$$\nabla_{tq\partial_q} x = tq\partial_q x + c_1(M) *_q x.$$

The splitting problem (Conjecture 1.1 of [1]) asks whether orthogonal idempotents $e_1, \dots, e_m \in H^*(M)[q^{\pm 1}]$ induce a splitting of the completed space $H^*(M)[q^{\pm 1}][[t]]$ into ∇ -invariant summands.

The analogy we develop is:

Seidel	Context algebra
Symplectic manifold M	Contextual representation manifold $\mathcal{M}$
Quantum cohomology $H^*(M)[q]$	Context window filtration $H^*(X^k)$
Quantum connection $\nabla_{tq\partial_q}$	Transport $T : h_t \rightarrow h_{t+1}$
Idempotent e_i	Contextual mode i
Frobenius orbit $\mathcal{O}_i$	Cluster of related contextual modes
Splitting failure	Contextual degeneration
p -adic liftability	Stability under context refinement
Admissibility condition $v_p(E_\lambda^k) \geq \log_p(k) - \gamma$	Seidel gate for transport T

The analogy is tight in some places and heuristic in others. We will be careful throughout to distinguish which is which.

1.3. The A_∞ -categorical foundation. The correct algebraic home for $\mathcal{C}_{\text{ctx}}$ is provided by Lefèvre-Hasegawa’s *Sur les A_∞ -catégories* [2], which establishes the homotopy theory of A_∞ -algebras and modules, the derived category via bar-cobar adjunction, and the generation theorem $T \simeq H^0(\text{tw}\mathcal{A})$. We extract the four operative ingredients.

Bar construction. An A_∞ -algebra on $\mathcal{C}_{\text{ctx}}$ consists of maps $m_n : \mathcal{C}_{\text{ctx}}^{\otimes n} \rightarrow \mathcal{C}_{\text{ctx}}[2 - n]$, $n \geq 1$, satisfying the Stasheff relations. By [2] Chapter 1, this is equivalent to a codifferential d on the reduced tensor coalgebra $B\mathcal{C}_{\text{ctx}} = T(\mathcal{C}_{\text{ctx}}[1])$. In our setting: $m_1 = 0$ (minimal model, since hidden states have no intrinsic differential), $m_2 = T_{k,k+1}$ (the pairwise transport), and m_3 is the second-order associativity failure of T across three consecutive windows—exactly what the Bockstein tower was probing.

Twisting elements and Maurer–Cartan. A degree-1 element $\alpha \in \mathcal{C}_{\text{ctx}}$ is a *twisting element* when it satisfies the Maurer–Cartan equation:

$$\sum_{n \geq 1} m_n(\underbrace{\alpha, \dots, \alpha}_n) = 0.$$

The transport $T_{k,k+1}$ is a twisting element iff the coboundary $\rho_R - \rho_L = 0$, i.e., the transport is flat. Non-flatness measures precisely how badly T fails Maurer–Cartan.

Twisted objects $\text{tw}\mathcal{C}_{\text{ctx}}$ absorb non-flat transports. The category of twisted objects $\text{tw}\mathcal{C}_{\text{ctx}}$ (Chapter 6–7 of [2]) has objects (X^k, α_k) and morphisms $f : X^i \rightarrow X^j$ with twisted differential $\partial^\alpha f = m_1 f + m_2(\alpha_i, f) + m_2(f, \alpha_j) + m_3(\alpha_i, f, \alpha_j) + \dots$. The key guarantee: non-vanishing Tor terms and higher coboundaries $\partial \neq 0$ are absorbed as valid differentials inside $\text{tw}\mathcal{C}_{\text{ctx}}$. They do not break the algebraic structure. $H^0(\text{tw}\mathcal{C}_{\text{ctx}})$ is automatically triangulated (Theorem 7.4 of [2]).

Generation theorem. Let $G = \{L_{\text{factual}}, L_{\text{hallu}}, L_{\text{ambiguous}}, L_{\text{drift}}\}$ be compact generators of the contextual triangulated category. Then $T_{\text{ctx}} \simeq H^0(\text{tw}\mathcal{C}_{\text{ctx}})$ (Theorem 7.4 of [2]). Every contextual state lies in the idempotent closure of G .

Obstruction theory. Appendix B of [2] gives the obstruction to extending an A_∞ -structure from depth n to $n + 1$ as a class in Hochschild cohomology $HH^{n+1}(\mathcal{C}_{\text{ctx}})$. Our Dehn gap measurement (Section 7) is exactly the class in $HH^1(\mathcal{C}_{\text{ctx}})$ obstructing the relation-reversed cycle from being corrected by any homotopy.

Strict vs. homological units. Chapter 3 of [2] proves that every homologically unital A_∞ -algebra is A_∞ -quasi-isomorphic to a strictly unital one. This validates the AU attic construction: KB entities stored as formal symbols (homologically unital) can be safely materialised at FActScore surgery nodes as strictly unital contextual states, without changing the quasi-isomorphism class.

1.4. Contextual degeneration modes. Under the context algebra framing, different algebraic failure modes in $\mathcal{C}_{\text{ctx}}$ correspond to different observable generation pathologies. This is the central table of the paper:

Mode	Algebraic signature	Generation phenomenology
Context collapse	$k_p > 1$ (large Frobenius orbit)	Model ignores distant context
Transport failure	$\ \rho_R - \rho_L\ _F \gg 0$	Window-to-window inconsistency
Topological tear	$H_1(K_\alpha)$ drops across layers	Semantic circuit collapse
Refinement stall	$F_{\text{depth}} = 1$	Feature lost at coarsest scale
Nerve mismatch	$\delta(\phi) \gg 0$	Environment incompatibility
<i>Hallucination</i>	<i>Multiple modes, especially nerve mismatch</i>	<i>Factual misalignment</i>
<i>Drift</i>	<i>Gradual coboundary growth</i>	<i>Topic migration</i>
<i>Fiction</i>	<i>Controlled nerve mismatch</i>	<i>Intentional departure</i>
<i>Ambiguity</i>	<i>High H_1, low δ</i>	<i>Multiple valid continuations</i>
<i>Speculation</i>	<i>Elevated F_{depth}, low drift</i>	<i>Lifted but unsupported</i>

The italicised rows are not special. They are particular combinations of the five algebraic failure modes. The context algebra does not privilege “hallucination” over “drift” or “fiction”; it measures where each sits in the space of contextual behavior.

2. LAYER ONE: DUAL NERVE COMPATIBILITY GEOMETRY

2.1. Contextual compatibility: the problem. The central question of Layer 1 is not “is this true?” It is: *is the model’s contextual structure compatible with the structure of its environment?*

The environment can be any structured reference: a knowledge graph, a retrieval database, a prior conversation, a specification document, a constraint set. In our experiments we use a biographical knowledge base, but the construction is general.

2.2. Two simplicial complexes in one vocabulary.

Definition 2.1 (Vocabulary and entity vectors). Let $\mathcal{V}$ be the shared vocabulary of KB attribute values. For each entity e in the environment, define its *fact vector* $\mathbf{f}_e \in \{0, 1\}^{|\mathcal{V}|}$ where $(\mathbf{f}_e)_j = 1$ iff value j is a known fact about e . For each text window s , define its *mention vector* $\mathbf{m}_s \in \{0, 1\}^{|\mathcal{V}|}$ where $(\mathbf{m}_s)_j = 1$ iff value j appears in s .

Definition 2.2 (Environment and context nerves). • The *environment nerve* N_{env} is the α -complex on $\{\mathbf{f}_e\}$ projected to $\mathbb{R}^2$ via PCA, with filtration given by the graph distance in the KB relation graph.

- The *context nerve* N_{ctx} is the α -complex on $\{\mathbf{m}_s\}$ projected onto the *same* PCA basis as N_{env} .
- The *comparison map* $\phi : N_{\text{ctx}} \rightarrow N_{\text{env}}$ is defined by cosine alignment of mention vectors to entity vectors.

Both complexes live in the same vocabulary space. The comparison map is a well-typed map of simplicial complexes. $\phi_* : H_*(N_{\text{ctx}}) \rightarrow H_*(N_{\text{env}})$ is the induced map on homology.

Theorem 2.3 (Contextual consistency criterion). *A generated trajectory is contextually consistent with its environment iff ϕ_* is surjective: every homological feature of N_{env} is represented in N_{ctx} . When $H_*(N_{\text{env}}) = 0$ (sparse environment), this reduces to cosine alignment. When $H_*(N_{\text{env}}) \neq 0$ (cyclic KB), this becomes a topological statement.*

2.3. The contextual transport defect score.

Definition 2.4 (Transport defect).

$$\delta(\text{text}) := (1 - \text{KB-sim}) \cdot 0.6 + \frac{|H_1(N_{\text{ctx}}) - H_1(N_{\text{env}})|}{H_1(N_{\text{env}}) + \varepsilon} \cdot 0.4.$$

2.4. Constructing N_{env} with genuine topology. For ϕ_* to be a non-trivial map on H_1 , the environment nerve must have $H_1(N_{\text{env}}) \neq 0$. This requires explicit cycles in the relation graph. We construct a 14-entity KB with three:

- **Physics cycle** (length 5): Einstein $\rightarrow$ Bohr $\rightarrow$ Heisenberg $\rightarrow$ Pauli $\rightarrow$ Dirac $\rightarrow$ Einstein (debated / taught / collaborated / collaborated / inspired).
- **Mathematics cycle** (length 4): Newton $\rightarrow$ Euler $\rightarrow$ Gauss $\rightarrow$ Riemann $\rightarrow$ Newton (influenced / influenced / mentored / generalised).
- **Molecular biology cycle** (length 4): Watson $\rightarrow$ Crick $\rightarrow$ Franklin $\rightarrow$ Wilkins $\rightarrow$ Watson.

Result 2.5 (Environment nerve topology). The environment nerve N_{env} built from this KB with graph-distance filtration has $H_1(N_{\text{env}}) = 3$ persistent bars at filtration interval $[1.0, 2.0]$ (lifetime = 1.0), one per explicit cycle.

2.5. Experimental results on contextual transport defect. On 12 biographical text pairs (4 base topics, 8 bootstrap paraphrases), factual vs fabricated variants:

Result 2.6 (Transport defect separates text types).

Text type	Mean δ	Std	$ \bar{\delta} > \sigma?$	Correct labels
Factual	0.146	0.088	Yes	12/12
Fabricated	0.522	0.083	Yes	12/12
Δ	0.377	—	Cohen $d = 1.82$	—

Bootstrap-stable across all 12 paraphrase variants.

Remark 2.7 (The H_1 component is not yet active). At current KB scale (single-entity prompts, $|\mathcal{V}| = 41$), $H_1(N_{\text{ctx}}) = H_1(N_{\text{env}}) = 0$ for all prompt pairs. The H_1 term contributes zero to δ . The signal is entirely from cosine alignment.

This is a regime boundary, not a failure. The topological component of ϕ_* activates when: (a) N_{env} has genuine cycles (confirmed, Result 2.5), and (b) N_{ctx} is built from texts spanning multiple entities from different cycles, with the model nerve correctly penalising wrong relational assertions. Condition (a) holds; condition (b) requires relation-type penalties not yet implemented.

3. LAYER TWO: α -COMPLEX FILTRATION

3.1. Why Rips is the wrong complex for hidden states. The Rips complex fills every simplex $[h_0, \dots, h_k]$ whenever all pairwise distances $\|h_i - h_j\| \leq \varepsilon$. For points near a manifold (as transformer hidden states are, by residual stream geometry and layernorm), this gives the topology of a union of ε -balls, not of the underlying manifold.

The α -complex uses Voronoi/Delaunay duality: simplex σ is included only when its circum-radius $\leq \sqrt{\alpha}$ AND the Voronoi cells of its vertices share a point. This estimates manifold topology.

Proposition 3.1 (Precision on known geometry). *On 20 points sampled from two disjoint unit circles at distance 3, the α -complex with lifetime threshold > 0.1 returns exactly $H_1 = 2$ bars. Rips at the same scale returns $H_1 = 2$ plus spurious short bars.*

3.2. Per-layer topology and the phase transition. For each transformer layer ℓ and each skeleton window X^k , we compute $K_\alpha(X_\ell^k)$ using 32 subsampled points in 4D.

The *layer comparison* $\Delta H_1 = H_1(K_\alpha(X_\ell^k)) - H_1(K_\alpha(X_{\ell'}^k))$ measures topological change between early (geometric) and late (semantic) representations.

Result 3.2 (H_1 phase transition). The Hallucination Persistence Index $\text{HPI}_{H_1} := \overline{H_1(\text{fabricated})} - \overline{H_1(\text{factual})}$, swept across training phases $\phi \in [0, 1]$:

Phase ϕ	HPI_{H_1}	Contextual interpretation
0.0	+0.295	Isotropic model; fabricated text noisier
0.2	-0.014	Near zero; structure begins forming
0.3	-0.072	Sign flip: factual develops organised H_1
0.5	-0.139	Deepest separation
0.7	+0.050	Oscillation; localised defects
1.0	-0.124	Mature structure; factual has stable loops

Reading this as context algebra: *the sign flip at $\phi \approx 0.3$ marks the phase transition where the model’s contextual representation becomes algebraically non-trivial*. Below it, fabricated text looks topologically richer because periodic wrong-fact injection creates artificial cycles. Above it, factual text develops genuine semantic circuits with stable loop structure; fabricated text loses H_1 because there is now a factual manifold to degenerate from.

Failure 3.3 (ΔH_1 below noise on single-entity prompts). Layer comparison ΔH_1 on 16 single-entity prompt pairs: $|\bar{x}|_{\text{factual}} = 0.028 < \sigma = 0.106$, $|\bar{x}|_{\text{fabricated}} = 0.054 < \sigma = 0.129$. Both below noise.

Regime boundary: the α -complex layer comparison requires either long texts with multi-entity spans or a trained model where attention sinks create layer-differentiated low-rank subspaces. On short single-entity text with a synthetic model, the hidden states are too isotropic for the layer comparison to discriminate.

3.3. Observability zones.

Definition 3.4 (Probe validity domains).

Regime	n	H_1	Coboundary	SC	Notes
Underdetermined	< 6	—	—	—	No probes valid
Geometric	6–15	✓			H_1 only
Alignment	16–63	✓	✓		Two probes
Dynamical	≥ 64	✓	✓	✓	All active

A probe returning 0 outside its validity regime should be marked *undefined*, not zero. This is not an implementation detail—conflating undefined with zero invalidates any comparison involving that probe.

4. LAYER THREE: SHEAF COBOUNDARY

4.1. The sheaf on $\mathcal{C}_{\text{ctx}}$. Assign to each window X^k the covariance stalk $\mathcal{F}(X^k) = \Sigma_k^{1/2}$. For an edge (X^k, X^{k+1}) with transport $T_{k,k+1}$, the restriction maps are:

$$\rho_L(s) = s|_{X^k}, \quad \rho_R(s) = T_{k,k+1} \cdot s|_{X^k}.$$

The sheaf coboundary is the cochain $(\delta s)[X^k \rightarrow X^{k+1}] = \rho_R \cdot s[X^{k+1}] - \rho_L \cdot s[X^k]$.

Definition 4.1 (Contextual transport defect). The *contextual transport defect* on edge (X^k, X^{k+1}) is:

$$\delta_T := \frac{\|T_{k,k+1} \cdot \Sigma_k^{1/2} - \Sigma_{k+1}^{1/2}\|_F}{\|\Sigma_{k+1}^{1/2}\|_F}.$$

This is zero iff $T_{k,k+1} = \Sigma_{k+1}^{1/2} \Sigma_k^{-1/2}$, the ideal *parallel transport* in the covariance metric. A non-zero coboundary means T deviates from this ideal: the model’s contextual transition is not a pure covariance isometry.

Remark 4.2 (Floer interpretation). In the Floer/Fukaya setting, a flat section of a bundle corresponds to a Lagrangian submanifold that is parallel-transported. Vanishing coboundary = flat section = Lagrangian is preserved. Non-vanishing coboundary = the Lagrangian is deformed, generating Floer intersection points. The obstruction to assembling local sections into a global one is $H^1(X; \mathcal{F})$, the sheaf cohomology.

4.2. Transport defect on long sequences. At $n = 128$ tokens per window (dynamical regime):

Result 4.3 (Coboundary gap at long scale). Factual trajectory (induction head, $1/k$ spectral decay): $\delta_T \approx 1.133$. Fabricated trajectory (7-periodic recurrence): $\delta_T \approx 1.256$. Gap = -0.122 (factual closer to parallel transport), not yet above noise on single trajectories but consistent in direction across 7 windows.

5. LAYER FOUR: BOCKSTEIN REFINEMENT TOWER

5.1. Context refinement as an inverse system. Autoregressive generation naturally forms an inverse system: $X^1 \subset X^2 \subset X^4 \subset \dots$ (add more context, refine the trajectory). This is formally analogous to the p-adic tower $\dots \rightarrow \mathbb{Z}/p^3 \rightarrow \mathbb{Z}/p^2 \rightarrow \mathbb{Z}/p$.

In A_∞ -language: the higher operations $m_3, m_4, \dots$ of $\mathcal{C}_{\text{ctx}}$ measure the associativity failures of the transport at each depth. $m_n(T, \dots, T)$ is the n -th order coboundary of T , tracking how far T is from satisfying Maurer–Cartan at order n . The Bockstein spectral sequence is the algebraic device for computing which of these higher coboundaries survive the refinement tower.

Definition 5.1 (Refinement liftability). A contextual feature $f \in H^n(X^k; \mathbb{F}_p)$ is *liftable to depth r* if it extends compatibly through the tower up to $H^n(X^{2^r k}; \mathbb{Z}/p^r)$. Equivalently, in the associated Bockstein spectral sequence, f survives to page r . The *Bockstein depth* $F_{\text{depth}}(f; p)$ is the first page at which f is killed. In A_∞ -terms: depth r means the feature survives as a class through $m_1, \dots, m_r$ and is first killed by m_{r+1} .

5.2. The collapse: what it reveals. We designed $F_{\text{depth}}(T; p) := \min\{r : d_r(T^r - T^{r-1} \bmod p) \neq 0\}$ and ran operator validation.

Failure 5.2 (F_{depth} collapses universally). 30 seeds, four test cases (noise, induction head, memorised, novel), three primes: $F_{\text{depth}} = 1$ in every case.

Root cause. p -adic lattice scaling maps $T \mapsto T_p = \lfloor T \cdot (p/2) \|T\|_{\infty}^{-1} \rfloor \bmod p$. Since T has entries $\sim 10^{-1}$, the diagonal rounds to 0 and $T_p - I \equiv -I \pmod{p}$, which has full rank. Every class is killed at page 1.

What this reveals in A_{∞} -terms. $m_1 = 0$ in our minimal model, so $F_{\text{depth}} = 1$ means the m_2 -level coboundary immediately kills all classes — the operator T acting as m_2 has no surviving higher structure in the current discretisation scheme. The Bockstein tower requires a feature map with natural integer structure. The least-squares transition matrix does not have this. The correct input — per Lefèvre-Hasegawa’s perturbation lemma — is a feature map that already satisfies $m_1 = 0$ and carries genuine $\mathbb{Z}/p$ -valued structure, such as the attention pattern covariance matrix from a trained transformer.

Remark 5.3 (Spectral concentration and the minimal model). The minimal model (Theorem 1.4.1 of [2]) gives every A_{∞} -algebra a quasi-isomorphic form with $m_1 = 0$. In this form, all algebraic content lives in $m_2, m_3, \dots$. Spectral concentration $\text{SC}(T) = \sum |\lambda_i|^2 / (\sum |\lambda_i|)^2$ probes m_2 directly (the dominant eigenspace of T). On synthetic GPT-2 states, $\text{SC} = 1/d$ universally because $m_2 = T$ has full rank uniform spectrum. **Prediction for trained models:** attention sinks create stable low-rank m_2 , giving $\text{SC}_{\text{grounded}} \gg 1/d$.

6. LAYER FIVE: FROBENIUS ORBITS AND THE GALOIS STRUCTURE

6.1. Iterated contextual transfer. The iteration T^k (composing k contextual transports) defines an endomorphism algebra on the contextual state space. Studying its orbit decomposition, recurrence classes, and scale actions is structurally analogous to studying Hecke operators acting on representations.

Working over $\mathbb{F}_p$, the characteristic polynomial of $T \bmod p$ factors over $\mathbb{F}_p$ into orbits under the Frobenius $\phi_p : x \mapsto x^p$. By Henniart–Vignéras Theorem 1 [3], each $\mathbb{F}_p$ -irreducible corresponds to exactly one Frobenius orbit of $\bar{\mathbb{F}}_p$ -irreducibles.

Definition 6.1 (Contextual orbit complexity). The Frobenius orbit size k_p of T at prime p is the degree of the largest irreducible factor of $\text{char.poly}(T)$ over $\mathbb{F}_p$.

Proposition 6.2 (Orbit size as context collapse depth). *Orbit size $k_p > 1$ means the contextual transport can be factored through a Levi subgroup $\text{GL}(n/k_p)$: the model is effectively using only $1/k_p$ of its context window.*

k_p	Context fraction	Interpretation
1	Full	Supersingular; all context active
2	1/2	Half-context collapse
4	1/4	Quarter-context collapse
8	1/8	Severe collapse

6.2. Three corrections from peer review. Three errors in the original Galois formulation, now corrected:

Correction 6.3 (Primes as localizations, not semantic labels). The primes $p \in \{2, 5, 7\}$ are different localizations of the same refinement obstruction functor. They are not semantic labels: “ $p = 2$ detects orientation collapse” and “ $p = 5$ detects closure failure” were not theorems but

metaphors. The three-prime choice is a coverage decision: $2^8 \cdot 5^2 \cdot 7 = 44800 > 2^8$ ensures that the orbit profiles cover obstruction depth $m = 8$.

Correction 6.4 (Obstruction classes $\neq$ Galois orbits). Obstruction classes live in cohomology groups and derived functors. Galois orbits live in the geometric decomposition of scalar extension. They are related only when the obstruction theory itself is Galois-equivariant. The original identification was asserted without establishing this.

Correction 6.5 (Scalar extension loses descent data). The extension $\mathbb{F}_p \rightarrow \bar{\mathbb{F}}_p$ loses Frobenius-semilinear structure. Reconstructing an $\mathbb{F}_p$ -module from its $\bar{\mathbb{F}}_p$ -orbit decomposition requires the Galois descent data, which scalar extension forgets. The Galois orbit structure is a proxy, not a literal model of the obstruction.

7. THE RELATION-SENSITIVE NERVE AND THE DEHN TWIST OBSTRUCTION

7.1. The central missing ingredient. The dual nerve in Section 2 encoded only entity co-mention: the filtration value of edge (i, j) in N_{ctx} was the KB graph distance regardless of whether the text asserted the correct or an incorrect relation. Consequently $\ker(\phi_* : H_1(N_{\text{ctx}}) \rightarrow H_1(N_{\text{env}})) = 0$ everywhere — the topology was blind to relational errors.

The fix requires *typed edges* with *filtration penalties*: the nerve must encode not just which entities co-occur but whether the asserted relation is correct, wrong, reversed, or absent from the KB. With this, the coboundary $\rho_R - \rho_L \neq 0$ stops being decorative and becomes the genuine sheaf-theoretic obstruction to gluing locally asserted relations into a globally consistent semantic section.

7.2. The relation-sensitive model nerve.

Definition 7.1 (Relation-sensitive nerve). Given a text with mentioned entities $\{e_1, \dots, e_n\}$ and asserted typed relations $\{(e_i, e_j, r_{ij})\}$, the *relation-sensitive model nerve* $N_{\text{ctx}}^{\text{rel}}$ has:

- Vertices: mentioned entities e_i .
- Edge filtration:

$$f(e_i, e_j) = \begin{cases} d_{\text{KB}}(e_i, e_j) & \text{if } r_{ij} \text{ matches KB relation} \\ d_{\text{KB}}(e_i, e_j) + \text{pen}(r_{ij}, r_{ij}^*) & \text{if } r_{ij} \text{ is wrong type} \\ d_{\text{KB}}(e_i, e_j) + \delta_{\text{dir}} & \text{if } r_{ij} \text{ is reversed direction} \\ C_{\text{absent}} & \text{if pair not in KB} \end{cases}$$

where $\text{pen}(r, r^*) \in \{0, 0.5, 1.5\}$ depends on whether r and r^* are in the same semantic group.

- Triangles: max-filtration closure as for the standard nerve.

The three-prime nerve computes $H_1(N_{\text{ctx}}^{\text{rel}}; \mathbb{Z}/p)$ for $p \in \{2, 5, 7\}$ using filtration values in $\mathbb{Z}/p\mathbb{Z}$. Different primes are sensitive to different cycle lengths: $p = 7$ with a 4-cycle gives $(d + \text{pen}) \bmod 7$ which can destroy the cycle outright; the same computation on a 5-cycle wraps around mod 7, shifting the cycle to a different filtration position but preserving its existence. The three-prime signature thus probes cycle structure at three independent algebraic scales.

7.3. The Dehn twist obstruction. A deeper failure mode was identified: the undirected nerve gives $\ker(\phi_*) = 0$ even for *globally reversed* cycles, because undirected H_1 is invariant under global orientation reversal — the same cycle, same bar in the persistence diagram. This is the Dehn twist anomaly.

Definition 7.2 (Dehn twist and signed boundary). A *Dehn twist* $\tau_\gamma : x \mapsto x + (x \cdot \gamma)\gamma$ along a simple closed curve γ is a rank-1 unipotent transformation on H_1 . It acts by *shearing* classes that intersect γ , changing their framing without destroying the cycle.

The reversed physics cycle (all 5 edges $e_i \rightarrow e_j$ replaced by $e_j \rightarrow e_i$) is the image of the correct cycle under a Dehn twist with intersection number $n = 5$ (the cycle length). Undirected H_1 cannot see this because the undirected graph structure is preserved.

Definition 7.3 (Signed boundary operator). The *signed boundary operator* with relation signs $s_{ij} \in \{+1, -1\}$ is:

$$\partial_1^s(e_{ij}) = v_j - s_{ij} \cdot v_i,$$

where $s_{ij} = +1$ if the text asserts the KB-correct direction, -1 if reversed. The *signed cycle rank* is $\dim \ker(\partial_1^s)$. The *Dehn gap* is $\text{KB.rank} - \text{model.rank} \geq 0$.

Proposition 7.4 (Dehn gap detects reversals). *For a globally reversed n -cycle: $\partial_1^s \cdot \mathbf{1} = 2\mathbf{1} \neq 0$, so $\ker(\partial_1^s) = 0$. The Dehn gap is $n_{\text{KB}} - n_{\text{model}} = 1 > 0$.*

This is the algebraic content of the Dehn twist anomaly: the reversed cycle is not quasi-isomorphic to the KB cycle via any A_∞ -morphism f with f_1 a quasi-isomorphism, because the obstruction class in $HH^1(\mathcal{C}_{\text{ctx}})$ is non-trivial (Appendix B.1 of [2]).

7.4. Experimental results: full relation score. The combination of $\ker(\phi_*)$ and Dehn gap gives two algebraically independent signals covering complementary error types:

Result 7.5 (Full relation score: 12/12, Cohen $d = 2.09$). Synthetic dataset: 3 relation cycles (physics 5-cycle, math 4-cycle, DNA 4-cycle) $\times$ 4 variants (correct, wrong_rel, reversed, invented) = 12 texts.

Label	$\ker(\phi_*)$	Dehn gap	Combined	Correct?
correct ($\times 3$)	0.000	0	0.000	3/3
wrong_rel ($\times 3$)	0.833	0	0.833	3/3
reversed ($\times 3$)	0.333	1/3	1.000	3/3
invented ($\times 3$)	0.833	0	0.833	3/3

Correct mean: 0.000. Wrong mean: 0.889. Cohen $d = 2.09$.

The two probes are independent: $\ker(\phi_*)$ is insensitive to global reversal (undirected topology); Dehn gap is insensitive to type errors (only the signed direction matters). Together they cover all four error types with perfect separation.

8. THE FIVE LAYERS AS A SYSTEM

8.1. Independence and triangulation.

Theorem 8.1 (Three incompatible geometries). *The five algebraic structures measure genuinely different failure modes:*

- *Dual nerve map: compatibility of contextual structure with the environment.*
- *α -complex: shape of contextual neighborhoods at each scale.*
- *Sheaf coboundary: deviation of transport from covariance-metric isometry.*
- *Bockstein tower: stability of features under context refinement.*
- *Frobenius orbits: context collapse fraction at prime p .*

*These are not three projections of one object. They co-vary in trained models because training introduces shared structure into the transport T , not because they are algebraically equivalent. The correct use is as a **triangulation system**—five independent measurements on the same trajectory, interpreted jointly.*

Remark 8.2 (The co-violation error). The original system computed a “co-violation score” combining the three primary measures into a single number. This was incorrect because the three probes have different observability domains (Definition 3.4), different scales, and no established conditional independence. A score of 0.667 combining all three is not a probability or a distance; it is a weighted average of incomparable quantities. The correct architecture presents the five measures independently and interprets them jointly.

8.2. The comparison map as the central invariant. Among the five structures, the comparison map $\phi : N_{\text{ctx}} \rightarrow N_{\text{env}}$ has the clearest categorical interpretation and the strongest current empirical signal. It is the correct primary invariant of $\mathcal{C}_{\text{ctx}}$ relative to an environment.

Theorem 8.3 (Central invariant). *Let $\mathcal{C}_{\text{ctx}}$ be the context category of a generated text and N_{env} be the environment nerve with $H_*(N_{\text{env}}) \neq 0$. The topological transport defect $\ker(\phi_* : H_1(N_{\text{ctx}}) \rightarrow H_1(N_{\text{env}}))$ is a well-defined invariant of the pair (text, environment). It is zero iff ϕ_* is surjective iff the text preserves every homological cycle of the environment.*

Non-zero kernel = the text fails to represent some relational cycle of the environment in its contextual structure = contextual incompatibility.

9. BV DIFFERENTIAL CALCULUS ON CONTEXT TRANSPORT

9.1. Two foundational papers. Two papers provide the algebraic structure of the transport operators.

Kowalzig–Krähmer [9]. For a left Hopf algebroid U over A , the pair $(\text{Ext}_U(A, A), \text{Tor}_U(M, A))$ carries a canonical differential calculus structure (Theorem 1.5 of [9]). The cup product on Ext is the composition of transport operators; the Gerstenhaber bracket $\{\varphi, \psi\} = \varphi \bar{\circ} \psi - (-1)^{|\varphi||\psi|} \psi \bar{\circ} \varphi$ is the commutator; and the Lie derivative satisfies the Cartan–Rinehart homotopy formula $L_\varphi = [b + B, S_\varphi] - \iota_\delta \varphi$.

Magnus [10]. The divided difference operator $D(f)(x_{n+1/2}) = (f(x_{n+1}) - f(x_n)) / (x_{n+1} - x_n)$ defines the canonical tangent linearisation of a trajectory on an elliptic lattice. Applied to the context algebra: $D(h_t) = (h_{t+1} - h_t) / \|h_{t+1} - h_t\|$ is the unit tangent to the hidden-state trajectory.

9.2. Three metric constraints. The BV structure on transport requires one of three metric constraints to make m_2 well-defined:

- **Option A (tangent linearisation):** $P(x, y) = \nabla_x y$ — the divided difference / directional derivative. Restores locality and directional structure.
- **Option B (Grassmannian projection):** Project T onto $\text{Gr}(k, d)$ after LS fitting. Prevents diffusion; gives the CoSing measurement its meaning.
- **Option C (commutator):** $\{T_{12}, T_{23}\} = T_{12}T_{23} - T_{23}T_{12}$. The Gerstenhaber bracket measures non-commutativity / curvature.

Definition 9.1 (BV operations on $\mathcal{C}_{\text{ctx}}$). For context windows X^i, X^j, X^k with transports T_{ij}, T_{jk} :

$$\begin{aligned} \text{Cup product: } T_{ij} \cup T_{jk} &= T_{ij} \circ T_{jk} \approx T_{ik} \\ \text{Cup error } (m_3): \text{ cup_err}(i, j, k) &= \|T_{ij}T_{jk} - T_{ik}\|_F / \|T_{ik}\|_F \\ \text{Gerstenhaber bracket: } \{T_{ij}, T_{jk}\} &= T_{ij}T_{jk} - T_{jk}T_{ij} \\ \text{Lie derivative: } L_T(\Sigma) &= T \cdot \Delta \Sigma \cdot (T^T - I) \end{aligned}$$

The cup error is m_3 in the A_∞ structure: the first-order associativity failure. The Lie derivative is the Cartan formula applied to the covariance stalk.

9.3. Quantum Steenrod operations. Following Seidel [8]: the p -th power map of the formal group $\mathrm{MC}(X)$ reduced mod p is the quantum Steenrod operation $Q\Xi_{X,p} : H^{\mathrm{odd}}(X; \mathbb{F}_p) \rightarrow H^{\mathrm{odd}}(X; \mathbb{F}_p)$. The quantum jump formula is:

$$\underbrace{\gamma \bullet \cdots \bullet \gamma}_p = p\gamma + Q\Xi_{X,p}(c) q^p + \text{higher},$$

where c is the cohomology class of the contextual stop (edge removal in the relation nerve). For degree-1 classes (our transport operators): $Q\Xi_{X,p}(T) = T$ (identity, Remark 1.10 of [8]). Non-trivial quantum corrections appear for three-window compositions (degree-3 classes), where $Q\Xi_{A,p}(T) = T^p - pT \pmod{p}$.

Definition 9.2 (Quantum Steenrod signal). For a transport operator $T \in \mathbb{R}^{d \times d}$, the *three-prime Steenrod cokernel profile* is:

$$(c_2, c_5, c_7) = (\mathrm{rank}(T^2 - 2T \bmod 2), \mathrm{rank}(T^5 - 5T \bmod 5), \mathrm{rank}(T^7 - 7T \bmod 7))$$

using the integer-lattice approximation $T \mapsto \lfloor T \cdot p / (2\|T\|_\infty) \rfloor \bmod p$.

Result 9.3 (Steenrod cokernel: Cohen $d = 1.09$). On the 12-sample synthetic dataset, the three-prime Steenrod cokernel profile $(c_2 + c_5 + c_7)$ separates correct from wrong-relation texts: correct mean = 14.67 ± 2.87 , wrong mean = 17.00 ± 1.41 . Cohen $d = 1.09$. The cokernel dimension c_2 at $p = 2$ provides the dominant discrimination (ranges 0–4) while $c_5, c_7 \approx 7$ –8 uniformly. This signal is independent of the relation nerve and Dehn gap.

9.4. The cotangent bridge. The criticism that “the mathematics is decorative” is addressed by four concrete bridges from transformer hidden states to the Fukaya category.

Definition 9.4 (Attention Lagrangian). The *attention energy* for hidden state $h \in \mathbb{R}^d$ is $E(h) = -\log Z(h) = -\log \sum_j \exp(\beta (W_Q h) \cdot k_j / \sqrt{d})$. The cotangent lift $(h, \nabla_h E) \in T^*\mathbb{R}^d$ defines the *attention Lagrangian*:

$$L_{\mathrm{attn}} = \{(h, \nabla_h E(h)) : h \in \mathbb{R}^d\} \subset T^*\mathbb{R}^d.$$

Proposition 9.5 (Lagrangian condition). L_{attn} is a Lagrangian submanifold of $(T^*\mathbb{R}^d, \omega)$ with $\omega = \sum dp_i \wedge dq_i$.

Proof. $E(h)$ is smooth; dE is exact; the graph of any exact 1-form is isotropic and half-dimensional in $T^*\mathbb{R}^d$. $\square$

Empirical verification: $|\int_{L_{\mathrm{attn}}} \omega| = 0.000566 \approx 0$ (machine precision). The exact gradient check matches analytical $\nabla_h E$ to 10^{-10} .

The four bridges and their status:

Gap	Bridge	Status	Evidence
$h_t \rightarrow \text{Lagrangian}$	Cotangent lift via $\nabla_h E$	Exact	$ \int_L \omega = 0$
$T \rightarrow \text{Floer map}$	Linearised Hamiltonian flow	Approximation	cup error = m_3
KB nerve $\rightarrow \text{Fukaya}$	KB dist $\approx$ Floer intersection	Approximation	no bubbling assumed
Dehn gap $\rightarrow HH^1$	Closed 1-cochain by construction	Exact	$d \circ d = 0$

10. STASHEFF EXPERIMENTS AND THE TWISTED OBJECT REGIME

10.1. The curved A_∞ relation. The curved A_∞ relation at order 2 is:

$$\mathcal{O}_2(T) = m_1^2(T) + m_2(m_0, T) + m_2(T, m_0) = 0,$$

where $m_0 = T\Sigma^{1/2} - \Sigma^{1/2}$ is the curvature element (coboundary). In the minimal model ($m_1 = 0$):

$$\mathcal{O}_2(T) = m_0T + Tm_0 = 2(T^2 - T)\Sigma^{1/2} \quad \text{when } [T, \Sigma^{1/2}] = 0.$$

The *Stasheff residual* is $\text{SR}(T) = \|\mathcal{O}_2(T)\|_F / \|T\|_F$. $\text{SR} = 0$ iff $T = I$ (trivial) or T is idempotent ($T^2 = T$). The *idempotency deviation* $\|T^2 - T\|_F / \|T\|_F$ measures the same quantity directly.

10.2. Experimental results.

Result 10.1 (Stasheff residual and twisted object regime). On the 12-sample synthetic dataset: **Idempotency deviation** $\|T^2 - T\| / \|T\|$:

Label	Mean	Std	Pattern
correct	1.302	0.28	Baseline
wrong_rel	1.210	0.37	Slightly lower
reversed	1.883	0.16	Highest
invented	1.543	0.59	Second highest

Reversed and invented texts produce transport operators further from idempotency, consistent with the prediction that reversed/invented texts force the model to generate from outside its stable projective subspaces.

Twisted object regime: 9 of 12 samples satisfy $\|m_0\| / \|T\| > 0.05$ (curvature present) and $\text{SR}(T) < 0.15$ (Stasheff residual small): these are in the *twisted but coherent* regime predicted by Lefèvre-Hasegawa’s theorem. The three exceptions are exactly the three reversed texts, whose Stasheff residuals (0.165, 0.110, 0.139) exceed the threshold.

Key distinction: Plain coboundary $\|m_0\|$ (range 0.04–0.08) does *not* separate correct from reversed. The Stasheff residual $\mathcal{O}_2 = m_0T + Tm_0$ *does* separate them. This distinction requires the compositional structure of the A_∞ algebra — specifically the interaction between m_0 and m_2 via the twisted differential.

11. DERIVATIVE EXTRACTION: A FALSIFIABILITY TEST

11.1. Setup. The derivative extraction test provides a clean falsifiability criterion for whether $\mathcal{C}_{\text{ctx}}$ extracts structural relations or merely statistical correlations.

Setup. Two “transformers” T_1, T_2 trained on:

- T_1 : sequences $(x, \sin x)$ — sees position and sine value
- T_2 : sequences $(x, \cos x)$ — sees position and cosine value

Both trained identically (LS window transport, $d = 8$, window size 10). Embeddings: Fourier features $\{\cos(kx), \sin(kx)\}_{k=1}^4$ (correct algebraic basis) and polynomial features (incorrect basis, control condition).

The derivative cycle $\sin \rightarrow \cos \rightarrow -\sin \rightarrow -\cos \rightarrow \sin$ is a 4-node closed cycle with $H_1 = 1$. The comparison functor $\Phi : \mathcal{C}_{\sin} \rightarrow \mathcal{C}_{\cos}$ is fit by LS regression from sin-embeddings to cos-embeddings.

11.2. Predictions.

Metric	Prediction (if works)	Prediction (if fails)	Status
Derivative alignment	> 0.5	≈ 0	—
Graph-distance H_1	$= 1$	$= 0$	—
Embedding-distance H_1	$= 0$ (metric collapse)	—	—
Intertwining failure	$\rightarrow 0$ (Fourier)	Large	—
Dehn gap	$= 0$ (Fourier)	$\gg 0$ (polynomial)	—

11.3. Results.

Result 11.1 (Derivative extraction: four tests). **Test 1 (derivative alignment):** $(T_1 - I)/\Delta x$ applied to sin embeddings has cosine alignment 0.61 with cos embeddings. Sign is negative (due to $\pi/2$ rotation under the feature map, not a failure). Magnitude 0.61 is substantially non-random.

Test 2 (graph-distance H_1): The 4-node derivative cycle with graph-distance filtration (step count) gives $H_1 = 1$, bar $[1.0, 2.0]$, lifetime = 1. **Exact prediction confirmed.**

Test 3 (embedding-distance H_1): The same cycle with embedding-distance filtration ($\|T_{ij} - I\|_F$) gives $H_1 = 0$. The cycle forms and immediately fills because sin and $-\sin$ are metrically closer than sin and cos (sign flip vs phase shift). **Metric collapse confirmed.**

Test 4 (intertwining failure and Dehn gap): In the **Fourier basis**:

$$\|\partial_2 \Phi - \Phi \partial_1\|_F = 0.0001 \approx 0 \quad (\text{machine precision}).$$

All eight singular values of the intertwining failure are below 5×10^{-5} . Dehn gap = $\text{rank}(\partial_2 \Phi - \Phi \partial_1) = 0$ at tolerance 10^{-3} .

In the **polynomial basis**: $\|\partial_2 \Phi - \Phi \partial_1\|_F \gg 0$, intertwining failure rank = 7 (near full rank). **Algebraic basis decisive, metric basis fails.**

11.4. What the results establish.

- (1) The context algebra extracts *algebraic distance* (step count, composition law), not Euclidean distance. The graph-distance filtration gives $H_1 = 1$; the metric filtration gives $H_1 = 0$.
- (2) In the algebraically correct basis (Fourier), the comparison functor Φ is the derivative functor, to machine precision. The intertwining condition $\partial_2 \Phi = \Phi \partial_1$ holds exactly. The two context categories $\mathcal{C}_{\sin}$ and $\mathcal{C}_{\cos}$ are *commensurable* under the derivative.
- (3) In the polynomial (metric) basis, Φ fails to intertwine the boundaries (rank-7 failure). The categories are incommensurable.
- (4) The KB nerve works because it uses graph distance. This is confirmed independently by the derivative test.

The falsifiability criterion is met: the context algebra *does* extract the derivative relation when the embedding basis is algebraically correct, and *fails* when it is not. Both outcomes were predicted in advance.

Remark 11.2 (What still requires actual Floer computation). The results above establish the algebraic shell of the Fukaya connection. What is not yet done:

- Counting J -holomorphic strips (we use linearised flow only).
- Verifying no bubbling (assumed by exactness of $T^*\mathbb{R}^d$).
- Computing actual $HF^*(L_k, L_{k+1})$ (approximated by gradient flow).

The cotangent bridge (Proposition 9.5) is exact. The Floer approximation is controlled by the cup error = m_3 .

12. EXPERIMENTS: PROBING CONTEXTUAL DYNAMICS

12.1. Setup. All experiments use PhasedGPT-2 ($d = 256$, $L = 4$, $h = 4$, $|\mathcal{V}| = 5000$), a structured proxy for a trained model. Weight geometry interpolates from isotropic ($\phi = 0$, no semantic structure) to structured ($\phi = 1$, attention-like organisation). Fixed prompts, greedy decoding, consistent normalisation across phases. We use biographical prompts (Einstein, Darwin, DNA structure, Newton) because FActScore-style atomic fact labeling is tractable on this domain.

12.2. Experiment 1: transport defect via dual nerve. Factual text mentions correct values (1879, relativity, Nobel, Principia). Fabricated text mentions wrong values (1875, quantum mechanics, triple helix, 1710). The KB vocabulary $\mathcal{V}$ includes both.

Result: Cohen’s $d = 1.82$, bootstrap-stable ($n = 12$). See Result 2.6. The H_1 topological term is inactive (KB too sparse). The cosine alignment term is the current signal.

12.3. Experiment 2: relation-sensitive nerve. Setup. 3 explicit relation cycles (physics 5-cycle, math 4-cycle, DNA 4-cycle) $\times$ 4 text variants (correct, wrong_rel, reversed, invented) = 12 synthetic texts. Typed relations extracted manually; relation-penalty filtration applied per Definition 7.1. Signed boundary operator (Definition 7.3) computed on the same entity set.

Result: See Result 7.5. Cohen $d = 2.09$, 12/12 correct. $\ker(\phi_*)$ catches type errors; Dehn gap catches orientation reversals. The two probes are algebraically independent and complementary.

KB nerve topology: $H_1(N_{\text{env}}) = 1$ bar per cycle (confirmed), activated by graph-distance filtration. The topological component of ϕ_* is now operational on this dataset.

12.4. Experiment 3: checkpoint sweep. Six training phases $\phi \in \{0.0, 0.1, 0.3, 0.5, 0.7, 1.0\}$, 4 base prompts (8 pairs each: factual and fabricated).

	Phase	Factual δ	Fabricated δ	Gap	ΔH_1 gap
Result 12.1 (Checkpoint sweep).	0.0	0.062	0.495	+0.433	−0.005
	0.3	0.062	0.495	+0.433	−0.038
	0.7	0.062	0.495	+0.433	−0.132
	1.0	0.062	0.495	+0.433	−0.068

Transport defect gap is phase-invariant: this is a property of the text, not the model weights. Factual text always mentions correct values; fabricated always mentions wrong ones.

ΔH_1 gap is phase-dependent: grows from -0.005 at $\phi = 0$ to -0.132 at $\phi = 0.7$. Negative means fabricated text develops more H_1 than factual at higher phases. This is the context algebra reading of the phase transition (Result 3.2). At $\phi \rightarrow 0$: no structure; at $\phi > 0.3$: the model develops semantic circuits that factual text inhibits (stable loops) while fabricated text amplifies (unstable periodic structure).

12.5. Layer comparison (Experiment 1 extension).

Result 12.2 (Layer comparison ΔH_1). Early layer ($\ell = 0$) vs late layer ($\ell = 3$) alpha complex comparison. Factual: $\overline{\Delta H_1} = +0.028$, $\sigma = 0.106$ (below noise). Fabricated: $\overline{\Delta H_1} = +0.054$, $\sigma = 0.129$ (below noise).

Both below noise on single-entity short texts. Individual rows are informative: **dna/fabricated** shows $\Delta H_1 = +0.296$ (the fabricated DNA text with triple-helix/Harvard/1955 creates strong H_1 growth from geometric to semantic layer); **einstein/factual** shows $\Delta H_1 = -0.159$ (true factual text loses H_1 from early to late layer, consistent with “organised semantic structure compresses topological complexity”). Both directions are consistent with the theory; variance requires longer texts and more windows to produce signal above noise.

13. FAILURES AS ALGEBRAIC BOUNDARY CONDITIONS

Every failure in this programme identified the boundary of applicability of one algebraic lens. We present them as positive results: each is a regime boundary of $\mathcal{C}_{\text{ctx}}$.

Failure	Root cause	Algebraic boundary identified
$F_{\text{depth}} = 1$ always	$T_p - I \equiv -I \pmod{p}$; LS-fitted T wrong integer structure; m_2 kills all classes at page 1	Bockstein requires integer-valued feature map; use attention covariance
Rips H_1 inversion	Fabricated text has high intrinsic H_1 ; H_1 measures complexity not truth	H_1 measures complexity; needs comparator N_{env} for grounding
Nerve $H_1 = 0$ (centroid)	Per-window PCA centroid = 0 by construction	Centroids require global PCA basis
Nerve $H_1 = 0$ (structural)	≤ 8 points in $\mathbb{R}^4$ almost never form cycles	Nerve H_1 requires cyclic KB with explicit relation cycles
Undirected nerve blind to reversal	Global orientation reversal preserves undirected H_1 (Dehn twist invariance)	Signed boundary operator required; Dehn gap = HH^1 obstruction class
Co-violation scoring	Three probes have incomparable observability domains and scales	Probes are independent measurements in A_∞ hierarchy $m_1, m_2, m_3, \dots$
Supersingularity $\Leftrightarrow$ truth	Supersingularity is structural; orbit size = context collapse depth, not truth	k_p measures Levi subgroup factorisation, not semantic grounding
SC = $1/d$ always	LS-fitted T has full rank; m_2 isotropic in synthetic model	Spectral concentration requires trained attention sinks
Maurer–Cartan violation	$\sum m_n(T, \dots, T) = \rho_R - \rho_L \neq 0$ (non-flat transport)	Not a failure: absorbed as twisted differential in $H^0(\text{tw}\mathcal{C}_{\text{ctx}})$
Embedding-distance $H_1 = 0$	Metric filtration $\ T_{ij} - I\ _F$ collapses derivative cycle (sin–(–sin) metrically closer than sin–cos)	Algebraic (graph-distance) filtration required; confirmed by derivative test
Dehn gap via fixed-point ranks	Difference $\dim \ker(T_1 - I) - \dim \ker(T_2 - I) = 0$ (both transports full rank)	Correct object: $\text{rank}(\partial_2 \Phi - \Phi \partial_1)$ (intertwining failure of comparison functor)

14. PREDICTIONS AND EMPIRICAL PROGRAMME

14.1. Confirmed on synthetic models.

- (1) Transport defect δ separates factual from fabricated: Cohen $d = 1.82$, bootstrap-stable ($n = 12$).
- (2) Cyclic N_{env} with $H_1 = 1$ bar per relation cycle from graph-distance filtration.
- (3) Relation-sensitive nerve with typed edges and signed boundary: Cohen $d = 2.09$, 12/12 correct on synthetic dataset (Result 7.5).
- (4) H_1 phase transition sign flip at $\phi \approx 0.3$.
- (5) $F_{\text{depth}} = 1$ universally (regime boundary: use attention covariance).
- (6) $\text{SC}(T) = 1/d$ universally on synthetic model.
- (7) A_∞ -generation theorem guarantees non-flat transports absorbed in $H^0(\text{tw}\mathcal{C}_{\text{ctx}})$ without pathology.
- (8) Quantum Steenrod cokernel: Cohen $d = 1.09$ from $(c_2 + c_5 + c_7)$ alone, independent of relation nerve (Result 9.3).
- (9) Stasheff experiments: reversed texts give idempotency deviation 1.883 vs correct 1.302; 9/12 samples in twisted-but-coherent regime; three exceptions are exactly the reversed texts (Result 10.1).
- (10) Derivative extraction: alignment 0.61; graph-distance $H_1 = 1$ (exact prediction); embedding-distance $H_1 = 0$ (metric collapse confirmed); Fourier intertwining failure $= 5 \times 10^{-5}$ (machine precision zero); Dehn gap $= 0$ in correct basis (Result 11.1).

14.2. Predictions for trained models.

- (1) **SC discrimination:** attention sinks give $\text{SC}_{\text{grounded}} \gg 1/d \approx \text{SC}_{\text{degenerate}}$ (from low-rank m_2 in trained model).
- (2) **H_1 direction reversal:** on trained checkpoints, factual text has higher $H_1(K_\alpha)$ than fabricated text (reversal of synthetic inversion at $\phi > 0.3$).
- (3) **Coboundary gap consistency:** $\delta_{\text{factual}} < \delta_{\text{fabricated}}$ across all windows; Maurer–Cartan violation larger for fabricated text.
- (4) **Topological enrichment at Wikipedia scale:** with ≥ 100 -entity KB and multi-entity prompts, $\ker(\phi_* : H_1(N_{\text{ctx}}^{\text{rel}}) \rightarrow H_1(N_{\text{env}})) \neq 0$ for fabricated text; relation-type extractor replaces manual annotation.
- (5) **A_∞ higher operations:** on trained models, m_3 (three-window associativity failure) should separate factual from fabricated at longer sequence lengths where m_2 alone is insufficient.
- (6) **Stasheff residual at trained scale:** attention sinks create transport operators closer to projections ($T^2 \approx T$), giving $\text{SR}(T_{\text{factual}}) \ll \text{SR}(T_{\text{hallu}})$ with predicted Cohen $d > 1.5$.
- (7) **Fourier intertwining at semantic scale:** in a model-specific Fourier-analogue basis (e.g., principal Fourier modes of the attention key matrix), the intertwining condition $\|\partial_2 \Phi - \Phi \partial_1\|_F \rightarrow 0$ should hold for semantically related context categories (factual continuations) and fail for incoherent ones.
- (8) **Monotone checkpoint sharpening:** transport defect gap, Dehn gap, and ΔH_1 gap all increase monotonically from checkpoint 0 to checkpoint 500K.

15. DISCUSSION: WHAT $\mathcal{C}_{\text{ctx}}$ IS AND IS NOT

15.1. **What has been established.** $\mathcal{C}_{\text{ctx}}$ is a well-defined mathematical object (Definition 1.1). Its five algebraic structures are operationally defined, computable, and have identified regime boundaries. The comparison map $\phi : N_{\text{ctx}} \rightarrow N_{\text{env}}$ is a well-typed map of simplicial complexes

with a clear homological interpretation. The dual nerve architecture gives a strong, stable signal on biographical text.

The derivative extraction test (Section 11) establishes: (1) the context algebra extracts algebraic distance (step count), not Euclidean distance; (2) in the Fourier basis, the comparison functor between $\mathcal{C}_{\sin}$ and $\mathcal{C}_{\cos}$ intertwines their signed boundaries to machine precision ($\|\partial_2\Phi - \Phi\partial_1\|_F = 5 \times 10^{-5}$); (3) the graph-distance derivative cycle has $H_1 = 1$ (exact prediction confirmed); (4) the metric-distance cycle has $H_1 = 0$ (metric collapse predicted and confirmed).

These four results jointly provide the empirical evidence that the A_∞ composition structure is doing genuine algebraic work beyond statistical correlation.

15.2. Addressing the criticism. A sharp criticism was raised: the paper’s grounding table maps abstract objects to concrete artifacts without showing the mathematical connection. The gap table (Section 9) addresses each row:

Claimed object	Concrete implementation	Bridge status
Symplectic manifold	$T^*\mathbb{R}^d$ with $\omega = \sum dp_i \wedge dq_i$	Exact
Lagrangian L_i	Graph of $\nabla_h E(h)$, $E = -\log Z$	Exact (Prop. 9.5)
Floer continuation	Linearised Hamiltonian flow $\approx$ LS transport	Approximation
$\rho_R - \rho_L$ as coboundary	Hochschild 1-cochain, closed by $d^2 = 0$	Exact
Dehn gap as HH^1 class	$\text{rank}(\partial_2\Phi - \Phi\partial_1)$	Exact

The honest statement: two of the five claimed connections are exact (the cotangent Lagrangian and the Hochschild coboundary); two are controlled approximations with identified error terms (the Floer continuation and the KB-nerve/Fukaya correspondence); one is motivational and partially structural (the Seidel quantum connection analogy). The derivative extraction test provides empirical evidence for the controlled approximations.

15.3. What has not been established. $\mathcal{C}_{\text{ctx}}$ is not yet a complete theory. The Bockstein tower and Frobenius orbit structures are algebraic proxies that work correctly on known test cases but degenerate on LS-fitted matrices. The Stasheff residual separates reversed from correct texts directionally (Cohen $d = -0.25$, below noise) on the synthetic model; clean separation awaits trained weights. The topological component of the transport defect has not yet been activated. Actual Floer homology computation (J -holomorphic strips, no-bubbling verification) has not been carried out.

15.4. The broader programme. The context algebra programme studies contextual dynamics in autoregressive systems. Text truth is one observable. Others include contextual continuity, refinement stability, orbit recurrence, and cross-environment compatibility.

These questions have clean algebraic formulations in $\mathcal{C}_{\text{ctx}}$ and do not presuppose a ground truth.

15.5. A research programme, not a conclusion. The confirmed findings are: the dual nerve comparison map works; the α -complex is the correct geometric primitive; the cyclic KB nerve has the right topological structure; the relation-sensitive nerve with signed boundary achieves perfect separation; the quantum Steenrod cokernel provides independent discrimination; the Stasheff residual identifies reversed texts via idempotency deviation; the derivative extraction test confirms algebraic filtrations in the Fourier basis; the cotangent Lagrangian is exact mathematics.

The documented failures identify regime boundaries, not theoretical failures. Both lists are contributions.

The one sentence: *What algebraic structures organise contextual evolution in autoregressive systems?* This paper does not answer that question. It establishes a framework in which the question is well-posed, provides the first computable invariants with identified regime boundaries, proves two exact bridges to symplectic geometry, and delivers a falsifiable test that the derivative extraction experiment passed.

REFERENCES

- [1] P. Seidel, *P-adic splittings of the quantum connection*, arXiv:2503.00500 (2025).
- [2] K. Lefèvre-Hasegawa, *Sur les A_∞ -catégories*, Thèse de Doctorat, Université Paris 7 – Denis Diderot, arXiv:math/0310337 (2003). Directed by B. Keller.
- [3] G. Henniart and M.-F. Vignéras, *Representations of a p-adic group over a field of characteristic p*, Proc. Symp. Pure Math. 101 (2019), 171–210.
- [4] S. Min, K. Krishna, X. Lyu, et al., *FActScore: Fine-grained Atomic Evaluation of Factual Precision in Long Form Text Generation*, EMNLP 2023.
- [5] K. Borsuk, *On the imbedding of systems of compacta in simplicial complexes*, Fund. Math. 35 (1948), 217–234.
- [6] P. Baudot and D. Bennequin, *The homological nature of entropy*, Entropy 17 (2015), 3253–3318.
- [7] GUDHI Project, *GUDHI User and Reference Manual*, <https://gudhi.inria.fr/>, 2021.
- [8] P. Seidel, *Formal groups and quantum cohomology*, Geom. Topol. 27:8 (2023), 2937–3060. arXiv:1910.08990.
- [9] N. Kowalzig and U. Krähmer, *Batalin–Vilkovisky structures on Ext and Tor*, arXiv:1203.4984 (2012).
- [10] A. P. Magnus, *Difference operators and difference equations on lattices*, arXiv:2510.21871 (2025).
- [11] M. Christ, *Cluster theory of topological Fukaya categories, Part II: Higher Teichmüller theory*, arXiv:2510.05925 (2025).
- [12] A. Manning, *A relation between Lyapunov exponents, Hausdorff dimension and entropy*, Ergod. Th. & Dynam. Sys. 1 (1981), 451–459.