

# Emittance preservation of an electron bunch in a loaded quasi-linear plasma wakefield

Veronica K. Berglyd Olsen<sup>\*</sup> and Erik Adli  
*University of Oslo, Oslo, Norway*

Patric Muggli  
*Max Planck Institute for Physics, Munich, Germany and  
CERN, Geneva, Switzerland*  
(Dated: July 7, 2017)

We investigate beam loading and emittance preservation for a high-charge electron beam being accelerated in quasi-linear plasma wakefield driven by a short proton beam. The structure of the wakefield is similar to that of a long, modulated proton beam. By selecting transverse and longitudinal electron beam parameters in order to appropriately load the wake, we show that the bulk of the electron beam can be accelerated without significant emittance growth.

## I. INTRODUCTION

The preliminary design of AWAKE Run 2 proposes to use two plasma sections. The first section of 4m is the SMI stage. The electron beam will be injected into the modulated proton beam before stage two, where acceleration will occur. As the  $e_z$  field will decrease due to the gap between the two cells, it is desirable to keep this as short as possible [1].

## II. METHOD

The main focus of this study has been on the beam loading of the electron beam. In order to eliminate other factors that may affect this, we have tried several approaches to create a stable drive beam structure based on previous SMI studies [citations].

Our first approach was to use a premodulated, short proton beam with the same structure as a section of the full AWAKE proton drive beam. These studies were done using the full PIC code Osiris [2] using 2D cylindrical-symmetric simulations. The proton beam was pre-modulated by a clipped cosine function to the longitudinal density profile, with a period matching the wavelength,  $\lambda_p$ , of the plasma. The length was limited to  $26 \cdot \lambda_p$ , and the electron beam injected after the 20th micro-bunch [3]. We performed several parameter scans with this setup, testing for optimal charge as well as beam length [1, 4].

[Add something about the optimal results]

In order to evaluate the quality of the beam, we also needed to study its emittance. Full PIC codes like Osiris are vulnerable to numerical growth of emittance caused by the “numerical Cherenkov effect” [5]. This is a known issue with the Yee EMF solver, which causes the phase velocity of electromagnetic fields to be lower than  $c$ , while the beam moves very close to  $c$ . The effect can be mitigated somewhat by the Lehe solver [6], but the effect

is still prominent in the high density regions of the electron beam.

In order to study the emittance evolution of the beam we used QuickPIC, a fully relativistic 3D PIC code [7, 8].

### A. Drive Beam Parameters

In these simulations we use a single proton drive bunch that sets up a wakefield comparable to that which we expect to see from the self-modulated SPS beam in AWAKE. The baseline AWAKE drive beam contains  $3 \times 10^{11}$  protons [9]. Only half of these are driving the wakefield, presuming the self-modulation is seeded in the middle of the unmodulated bunch. In addition, a significant portion of the protons are lost during self-modulation. The needed gap between the two plasma cells also contributes to a decreased density of protons near the axis, and some of the field is drained by other protons seeing an accelerating face within the drive beam. In total, the expected peak  $E_z$  field of 2 GV/m in the first plasma cell drops to 500 – 600 MV/m in the second cell [10]. A single proton beam of  $1.46 \times 10^{10}$ , or 2.34 nC and 7 kA, is needed to drive an  $E_z$  field of a comparable magnitude.

The single bunch approach was chosen to reduce simulation time for the 3D simulations, and to create a stable environment for the witness beam. We are not considering the evolution of the proton beam in this test setup, so to prevent the proton beam from evolving radially, we increased its mass.

The baseline AWAKE drive beam current is insufficient to produce a plasma bubble. The plasma electrons are depleted to around 65% of nominal plasma density at the injection point of the electron beam. This condition is replicated in our single bunch case. The single bunch setup also uses the baseline proton energy  $W_{pb} = 400$  GeV.

---

<sup>\*</sup> v.k.b.olsen@cern.ch

## B. Witness Beam Parameters

The witness beam in our simulation differs from AWAKE baseline parameters on several key points. Initial beam energy is set such that  $\gamma_{eb} = \gamma_{pb} = 426.3$ . This is to eliminate the problem of initial de-phasing of the witness beam. AWAKE baseline witness beam energy for Run 1 is  $W_{eb} = 10 - 20$  MeV [9]. Beam loading of a short witness beam is sensitive to initial position. AWAKE Run 2 will likely require a higher initial energy, but a  $W_{eb} = 30 - 50$  MeV is sufficient to minimise de-phasing [3]. For this case we have eliminated it entirely in order to reduce the number of variables in our parameter scans.

Earlier simulations with witness beam  $\sigma_r = 100 \mu\text{m}$  causes the beam radius to rapidly shrink as the beam enters the plasma [4]. This is due to a mismatch between beam emittance and the plasma density. The relation is given by

$$\beta = \frac{\sigma_r^2}{\epsilon_g} = \frac{\lambda_p}{2\pi} \sqrt{2\gamma_{rel}}, \quad (1)$$

where  $\lambda_p$  is the plasma wavelength.

## III. BEAM LOADING

The structure of the single drive beam setup behaves similarly to the self-modulated case. However, since the drive beam is prevented from significant evolution in this simulation setup, we are presented with an idealised case where the electron witness beam sees consistent fields.

## IV. PARAMETER OPTIMISATION

## V. DISCUSSION

## VI. CONCLUSION

- 
- [1] E. Adli and AWAKE Collaboration, in *Proceedings of IPAC 2016*, International Particle Accelerator Conference (JACoW, Busan, Korea, 2016) pp. 2557–2560.
  - [2] R. A. Fonseca, L. O. Silva, F. S. Tsung, V. K. Decyk, W. Lu, C. Ren, W. B. Mori, S. Deng, S. Lee, T. Katsouleas, and J. C. Adam, in *Computational Science ICCS 2002*, Lecture Notes in Computer Science No. 2331, edited by P. M. A. Sloot, A. G. Hoekstra, C. J. K. Tan, and J. J. Dongarra (Springer Berlin Heidelberg, 2002) pp. 342–351.
  - [3] V. K. Berglyd Olsen, E. Adli, P. Muggli, L. D. Amorim, and J. Vieira, in *Proceedings of IPAC 2015* (Richmond, VA, USA, 2015) pp. 2551–2554.
  - [4] V. K. Berglyd Olsen, E. Adli, P. Muggli, and J. Vieira, in *Proceedings of NAPAC 2016* (Chicago, IL, USA, 2016).
  - [5] B. B. Godfrey, *Journal of Computational Physics* **15**, 504 (1974).
  - [6] R. Lehe, A. Lifschitz, C. Thaury, V. Malka, and X. Davoine, *Physical Review Special Topics - Accelerators and Beams* **16**, 021301 (2013).
  - [7] C. Huang, V. K. Decyk, C. Ren, M. Zhou, W. Lu, W. B. Mori, J. H. Cooley, T. M. Antonsen, and T. Katsouleas, *Journal of Computational Physics* **217**, 658 (2006).
  - [8] W. An, V. K. Decyk, W. B. Mori, and T. M. Antonsen, *Journal of Computational Physics* **250**, 165 (2013).
  - [9] E. Gschwendtner, E. Adli, L. Amorim, R. Apsimon, R. Assmann, A. M. Bachmann, F. Batsch, J. Bauche, V. K. Berglyd Olsen, M. Bernardini, R. Bingham, B. Biskup, T. Bohl, C. Bracco, P. N. Burrows, G. Burt, B. Buttenschn, A. Butterworth, A. Caldwell, M. Cascella, E. Chevallay, S. Cipiccia, H. Damerau, L. Deacon, P. Dirksen, S. Doebert, U. Dorda, J. Farmer, V. Fedosseev, E. Feldbaumer, R. Fiorito, R. Fonseca, F. Friebel, A. A. Gorn, O. Grulke, J. Hansen, C. Hessler, W. Hoffe, J. Holloway, M. Hther, D. Jaroszynski, L. Jensen, S. Jolly, A. Joulaei, M. Kasim, F. Keeble, Y. Li, S. Liu, N. Lopes, K. V. Lotov, S. Mandry, R. Martorelli, M. Martyanov, S. Mazzoni, O. Mete, V. A. Minakov, J. Mitchell, J. Moody, P. Muggli, Z. Najmudin, P. Norreys, E. z, A. Pardons, K. Pepitone, A. Petrenko, G. Plyushchev, A. Pukhov, K. Rieger, H. Ruhl, F. Salveter, N. Savard, J. Schmidt, A. Seryi, E. Shaposhnikova, Z. M. Sheng, P. Sherwood, L. Silva, L. Soby, A. P. Sosedkin, R. I. Spitsyn, R. Trines, P. V. Tuv, M. Turner, V. Verzilov, J. Vieira, H. Vincke, Y. Wei, C. P. Welsch, M. Wing, G. Xia, and H. Zhang, *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment EAAC 2015*, **829**, 76 (2016).
  - [10] AWAKE Collaboration and A. Caldwell, *AWAKE Status Report, 2016*, Tech. Rep. CERN-SPSC-2016-033 (CERN, Geneva, 2016) sPSC-SR-194.