Experiment No : 05

Aim : Learn use of seaborn library as visualisation tool in data science pipeline.

Visualization with Seaborn Matplotlib has proven to be an incredibly useful and popular visualization tool, but even avid users will admit it often leaves much to be desired. There are several valid complaints about Matplotlib that often come up:

Prior to version 2.0, Matplotlib's defaults are not exactly the best choices. It was based off of MATLAB circa 1999, and this often shows. Matplotlib's API is relatively low level. Doing sophisticated statistical visualization is possible, but often requires a lot of boilerplate code. Matplotlib predated Pandas by more than a decade, and thus is not designed for use with Pandas DataFrames. In order to visualize data from a Pandas DataFrame, you must extract each Series and often concatenate them together into the right format. It would be nicer to have a plotting library that can intelligently use the DataFrame labels in a plot. An answer to these problems is Seaborn. Seaborn provides an API on top of Matplotlib that offers sane choices for plot style and color defaults, defines simple high-level functions for common statistical plot types, and integrates with the functionality provided by Pandas DataFrames.

To be fair, the Matplotlib team is addressing this: it has recently added the plt.style tools discussed in Customizing Matplotlib: Configurations and Style Sheets, and is starting to handle Pandas data more seamlessly. The 2.0 release of the library will include a new default stylesheet that will improve on the current status quo. But for all the reasons just discussed, Seaborn remains an extremely useful addon.

Seaborn Versus Matplotlib Here is an example of a simple random-walk plot in Matplotlib, using its classic plot formatting and colors. We start with the typical imports:

```
import matplotlib.pyplot as plt
plt.style.use('classic')
%matplotlib inline
import numpy as np
import pandas as pd
```

```
# Create some data
rng = np.random.RandomState(0)
x = np.linspace(0, 10, 500)
y = np.cumsum(rng.randn(500, 6), 0)
```


Scanned with OKEN Scanner

Scanned with OKEN Scanner

And do a simple plot:

```
# Plot the data with Matplotlib defaults
plt.plot(x, y)
plt.legend('ABCDEF', ncol=2, loc='upper left');
```



Although the result contains all the information we'd like it to convey, it does so in a way that is not all that aesthetically pleasing, and even looks a bit old-fashioned in the context of 21st-century data visualization.

Now let's take a look at how it works with Seaborn. As we will see, Seaborn has many of its own high-level plotting routines, but it can also overwrite Matplotlib's default parameters and in turn get even simple Matplotlib scripts to produce vastly superior output. We can set the style by calling Seaborn's set() method. By convention, Seaborn is imported as sns:

```
import seaborn as sns
sns.set()
```

```
# same plotting code as above!
plt.plot(x, y)
plt.legend('ABCDEF', ncol=2, loc='upper left');
```


Scanned with OKEN Scanner

Scanned with OKEN Scanner

Ah, much better!

Exploring Seaborn Plots The main idea of Seaborn is that it provides high-level commands to create a variety of plot types useful for statistical data exploration, and even some statistical model fitting.

Let's take a look at a few of the datasets and plot types available in Seaborn. Note that all of the following could be done using raw Matplotlib commands (this is, in fact, what Seaborn does under the hood) but the Seaborn API is much more convenient.

Histograms, KDE, and densities Often in statistical data visualization, all you want is to plot histograms and joint distributions of variables. We have seen that this is relatively straightforward in Matplotlib:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

# Generate data
data = np.random.multivariate_normal([0, 0], [[5, 2], [2, 2]], size=2000)
data = pd.DataFrame(data, columns=['x', 'y'])

# Plot histogram
for col in ['x', 'y']:
    plt.hist(data[col], density=True, alpha=0.5)
```


Scanned with OKEN Scanner

Scanned with OKEN Scanner

```
plt.xlabel('Values')
plt.ylabel('Density')
plt.title('Histogram of x and y')
plt.show()
```



Rather than a histogram, we can get a smooth estimate of the distribution using a kernel density estimation, which Seaborn does with sns.kdeplot:

```
for col in 'xy':
    sns.kdeplot(data[col], shade=True)
```


Scanned with OKEN Scanner
Scanned with OKEN Scanner

```
/tmp/ipykernel_215/4143655892.py:2: FutureWarning:

`shade` is now deprecated in favor of `fill`; setting `fill=True`.
This will become an error in seaborn v0.14.0; please update your code.

  sns.kdeplot(data[col], shade=True)
/tmp/ipykernel_215/4143655892.py:2: FutureWarning:

`shade` is now deprecated in favor of `fill`; setting `fill=True`.
This will become an error in seaborn v0.14.0; please update your code.

  sns.kdeplot(data[col], shade=True)
```



Histograms and KDE can be combined using distplot:

```
sns.distplot(data['x'])
sns.distplot(data['y']);
```


Scanned with OKEN Scanner

Scanned with OKEN Scanner

```
/tmp/ipykernel_215/923662334.py:1: UserWarning:

`distplot` is a deprecated function and will be removed in seaborn v0.14.0.

Please adapt your code to use either `displot` (a figure-level function with
similar flexibility) or `histplot` (an axes-level function for histograms).

For a guide to updating your code to use the new functions, please see
https://gist.github.com/mwaskom/de44147ed2974457ad6372750bbe5751

  sns.distplot(data['x'])
/tmp/ipykernel_215/923662334.py:2: UserWarning:

`distplot` is a deprecated function and will be removed in seaborn v0.14.0.

Please adapt your code to use either `displot` (a figure-level function with
similar flexibility) or `histplot` (an axes-level function for histograms).

For a guide to updating your code to use the new functions, please see
https://gist.github.com/mwaskom/de44147ed2974457ad6372750bbe5751

  sns.distplot(data['y']);
```



If we pass the full two-dimensional dataset to kdeplot, we will get a two-dimensional visualization of the data:

```
sns.kdeplot(data);
```


Scanned with OKEN Scanner
Scanned with OKEN Scanner



We can see the joint distribution and the marginal distributions together using sns.jointplot. For this plot, we'll set the style to a white background:

```
import seaborn as sns
import matplotlib.pyplot as plt

with sns.axes_style('white'):
    sns.jointplot(x="x", y="y", data=data, kind='kde')

plt.show()
```


Scanned with OKEN Scanner

Scanned with OKEN Scanner



There are other parameters that can be passed to jointplot—for example, we can use a hexagonally based histogram instead:

```
import seaborn as sns
import matplotlib.pyplot as plt

with sns.axes_style('white'):
    sns.jointplot(x="x", y="y", data=data, kind='hex')

plt.show()
```


Scanned with OKEN Scanner

Scanned with OKEN Scanner



Pair plots When you generalize joint plots to datasets of larger dimensions, you end up with pair plots. This is very useful for exploring correlations between multidimensional data, when you'd like to plot all pairs of values against each other.

We'll demo this with the well-known Iris dataset, which lists measurements of petals and sepals of three iris species:

```
iris = sns.load_dataset("iris")
iris.head()
```

	sepal_length	sepal_width	petal_length	petal_width	species
0	5.1	3.5	1.4	0.2	setosa
1	4.9	3.0	1.4	0.2	setosa
2	4.7	3.2	1.3	0.2	setosa
3	4.6	3.1	1.5	0.2	setosa
4	5.0	3.6	1.4	0.2	setosa

Next steps: Generate code with `iris` New interactive sheet

Scanned with OKEN Scanner

Scanned with OKEN Scanner

Visualizing the multidimensional relationships among the samples is as easy as calling sns.pairplot:

```
sns.pairplot(iris, hue='species', size=2.5);
```

```
/usr/local/lib/python3.12/dist-packages/seaborn/axisgrid.py:2100: UserWarning
  warnings.warn(msg, UserWarning)
```



Faceted histograms Sometimes the best way to view data is via histograms of subsets. Seaborn's FacetGrid makes this extremely simple. We'll take a look at some

Scanned with OKEN Scanner

Scanned with OKEN Scanner

data that shows the amount that restaurant staff receive in tips based on various indicator data:

```
tips = sns.load_dataset('tips')
tips.head()
```

	total_bill	tip	sex	smoker	day	time	size
0	16.99	1.01	Female	No	Sun	Dinner	2
1	10.34	1.66	Male	No	Sun	Dinner	3
2	21.01	3.50	Male	No	Sun	Dinner	3
3	23.68	3.31	Male	No	Sun	Dinner	2
4	24.59	3.61	Female	No	Sun	Dinner	4

Next steps: Generate code with tips New interactive sheet

```
tips['tip_pct'] = 100 * tips['tip'] / tips['total_bill']

grid = sns.FacetGrid(tips, row="sex", col="time", margin_titles=True)
grid.map(plt.hist, "tip_pct", bins=np.linspace(0, 40, 15));
```

Scanned with OKEN Scanner
Scanned with OKEN Scanner

```
import seaborn as sns
import matplotlib.pyplot as plt

with sns.axes_style('ticks'):
    g = sns.catplot(x="day", y="total_bill", hue="sex", data=tips, kind="box")

g.set_axis_labels("Day", "Total Bill")
plt.show()
```



Joint distributions Similar to the pairplot we saw earlier, we can use sns.jointplot to show the joint distribution between different datasets, along with the associated marginal distributions:

```
planets = sns.load_dataset('planets')
planets.head()
```

	method	number	orbital_period	mass	distance	year
0	Radial Velocity	1	269.300	7.10	77.40	2006
1	Radial Velocity	1	874.774	2.21	56.95	2008
2	Radial Velocity	1	763.000	2.60	19.84	2011
3	Radial Velocity	1	326.030	19.40	110.62	2007
4	Radial Velocity	1	516.220	10.50	119.47	2009

Next steps: Generate code with planets New interactive sheet

```
import seaborn as sns
import matplotlib.pyplot as plt

with sns.axes_style('white'):
    g = sns.catplot(x="year", data=planets, aspect=2,
                    kind="count", color='steelblue')

g.set_xticklabels(step=5)
plt.show()
```


Scanned with OKEN Scanner
Scanned with OKEN Scanner



We can learn more by looking at the method of discovery of each of these planets:

```
import seaborn as sns
import matplotlib.pyplot as plt

with sns.axes_style('white'):
    g = sns.catplot(x="year", data=planets, aspect=4.0, kind='count',
                    hue='method', order=list(range(2001, 2015)))

g.set_ylabels('Number of Planets Discovered')

plt.show()
```



For more information on plotting with Seaborn, see the Seaborn documentation, a [tutorial](http://seaborn.pydata.org/ tutorial.htm), and the Seaborn gallery.

Example: Exploring Marathon Finishing Times Here we'll look at using Seaborn to help visualize and understand finishing results from a marathon. I've scraped the data from sources on the Web, aggregated it and removed any identifying information, and put it on GitHub where it can be downloaded (if you are interested in using Python for web scraping, I would recommend Web Scraping with Python by Ryan Mitchell). We will start by downloading the data from the Web, and loading it into Pandas:

```
# !curl -O https://raw.githubusercontent.com/jakevdp/marathon-data/master/marathon-data.csv
```

```
data.dtypes
```

	0
x	float64
y	float64

dtype: object

```
data.dtypes
```


Scanned with OKEN Scanner
Scanned with OKEN Scanner

	0
x	float64
y	float64

dtype: object

The dotted line shows where someone's time would lie if they ran the marathon at a perfectly steady pace. The fact that the distribution lies above this indicates (as you might expect) that most people slow down over the course of the marathon. If you have run competitively, you'll know that those who do the opposite—run faster during the second half of the race—are said to have "negative-split" the race.

Let's create another column in the data, the split fraction, which measures the degree to which each runner negative-splits or positive-splits the race:

It looks like the split fraction does not correlate particularly with age, but does correlate with the final time: faster runners tend to have closer to even splits on their marathon time. (We see here that Seaborn is no panacea for Matplotlib's ills when it comes to plot styles: in particular, the x-axis labels overlap. Because the output is a simple Matplotlib plot, however, the methods in Customizing Ticks can be used to adjust such things if desired.)

The difference between men and women here is interesting. Let's look at the histogram of split fractions for these two groups:

Close

```
**Conclusion:**

Thus we have learned about seaborn python API used for graph plo
```

Conclusion:

Thus we have learned about seaborn python API used for graph ploting.

Scanned with OKEN Scanner

Scanned with OKEN Scanner