


# ***Experiment in Compiler Construction Scanner design***

Department of Computer Science  
School of ICT - Hanoi University of  
Science and Technology


# What is a scanner?

---



- The compiler's component/module that perform the job of lexical analysis (scanning) is called *scanner*.
- Compiler's first phase

# What is a scanner?



# Tasks of a scanner

---

- Skip meaningless characters: blank, tab, new line character, comment.
- Recognize illegal character and return error message
- Recognize different types of token
  - identifier
  - keyword
  - number
  - special character
  - ...

# Tasks of a scanner

---

- Recognize tokens of different types
  - identifier
  - keyword
  - number
  - special character
  - ...
- Pass recognized tokens to the *parser* (the module that perform the job of syntatic analysis)

## KPL's alphabet

---

- Letter: a b c ... x y z  
          A B C ... X Y Z
- Digit: 0 1 2 ... 8 9
- Special character:
  - + - \* /
  - > < ! =
  - [space] ,(comma) . : ; ' \_
  - ( )

# KPL's tokens

---

- Keywords

PROGRAM, CONST, TYPE, VAR, PROCEDURE,  
FUNCTION, BEGIN, END, ARRAY, OF, INTEGER,  
CHAR, CALL, IF, THEN, ELSE, WHILE, DO, FOR, TO

- Operators

**:=** (assign)

**+** (addition), **-** (subtraction), **\*** (multiplication), **/** (division)

**=** (comparison of equality), **!=** (comparison of difference),

**>** (comparison of greatness), **<** (comparison of lessness), **>=** (comparison of greatness or equality), **<=** (comparison of lessness or equality)

## KPL's tokens

---

- Special characters  
; (semicolon), . (period), : (colon), , (comma), (  
(left parenthesis), ) (right parenthesis), '  
(singlequote)
- Also  
(. and .) to mark the index of an array  
element  
(\* and \*) to mark the comment
- Others  
identifier, number, illegal charater



## Recognizing KPL's tokens

---

- All KPL's tokens make up a regular language.
- They can be described with regular grammar
- They can be recognized by a Deterministic Finite Automaton (DFA)
- The scanner is a big DFA

- After every token is recognized, the scanner starts in state 0 again
- If an illegal character is met, the scanner would change to the state -1 which tell the scanner to stop scanning and return error messages.



# KPL scanner - organization

---

#	Filename	Task
1	Makefile	Project
2	scanner.c	Main
3	reader.h, reader.c	Read the source code
4	charcode.h, charcode.c	Classify character
5	token.h, token.c	Classify and recognize token, keywords
6	error.h, error.c	Manage error types and messages

# KPL scanner – reader

---

```
// Read a character from input stream  
int readChar(void);
```

```
// Open input stream  
int openInputStream(char *fileName);
```

```
// Close input stream  
void closeInputStream(void);
```

```
// Current line number and column number  
int lineNo, colNo;
```

```
// Current character  
int currentChar;
```

# KPL scanner – charcode

---

```
typedef enum {  
    CHAR_SPACE,           // space  
    CHAR_LETTER,          // character  
    CHAR_DIGIT,           // digit  
    CHAR_PLUS,            // '+'  
    CHAR_MINUS,           // '-'  
    CHAR_TIMES,           // '*'  
    CHAR_SLASH,           // '/'  
    CHAR_LT,              // '<'  
    CHAR_GT,              // '>'  
    CHAR_EXCLAMATION,     // '!'  
    CHAR_EQ,              // '='  
    CHAR_COMMA,           // ','  
    CHAR_PERIOD,          // '.'  
    CHAR_COLON,           // ':'  
    CHAR_SEMICOLON,       // ';'   
    CHAR_SINGLEQUOTE,     // '\''  
    CHAR_LPAR,            // '('  
    CHAR_RPAR,            // ')'   
    CHAR_UNKNOWN          // invalid character  
} CharCode;
```

## KPL scanner – charcode

---

- In *charcode.c*, we define *charCodes* array that associates every ASCII character with an unique predefined *CharCode*.
- *getc()* function may return EOF (or -1) which is not an ASCII character.

# KPL scanner – token

---

```
typedef enum {
    TK_NONE,          // Invalid token - Error
    TK_IDENT,         // Identifier token
    TK_NUMBER,        // Number token
    TK_CHAR,          // Character constant token
    TK_EOF,           // End of program token
    // keywords
    KW_PROGRAM, KW_CONST, KW_TYPE, KW_VAR,
    KW_INTEGER, KW_CHAR, KW_ARRAY, KW_OF,
    KW_FUNCTION, KW_PROCEDURE,
    KW_BEGIN, KW_END, KW_CALL,
    KW_IF, KW_THEN, KW_ELSE,
    KW_WHILE, KW_DO, KW_FOR, KW_TO,
    // Special character
    SB_SEMICOLON, SB_COLON, SB_PERIOD, SB_COMMA,
    SB_ASSIGN, SB_EQ, SB_NEQ, SB_LT, SB_LE, SB_GT, SB_GE,
    SB_PLUS, SB_MINUS, SB_TIMES, SB_SLASH,
    SB_LPAR, SB_RPAR, SB_LSEL, SB_RSEL
} TokenType;
```

## KPL scanner – token

---

```
// Structure of a token
typedef struct {
    char string[MAX_IDENT_LEN + 1];
    int lineNo, colNo;
    TokenType tokenType;
    int value;
} Token;

// Check whether a string is a keyword or not
TokenType checkKeyword(char *string);

// Create new token, provided type of token and location
Token* makeToken(TokenType tokenType, int lineNo, int
colNo);
```



# KPL scanner – error management

---

```
// List of error may occur in lexical analysis
typedef enum {
    ERR_ENDOFCOMMENT,
    ERR_IDENTTOOLONG,
    ERR_INVALIDCHARCONSTANT,
    ERR_INVALIDSYMBOL
} ErrorCode;

// Error message
#define ERM_ENDOFCOMMENT "End of comment expected!"
#define ERM_IDENTTOOLONG "Identification too long!"
#define ERM_INVALIDCHARCONSTANT "Invalid const char!"
#define ERM_INVALIDSYMBOL "Invalid symbol!"

// Return error message
void error(ErrorCode err, int lineNo, int colNo);
```

# KPL scanner – scanner

---

```
// Get next token
Token* getToken(void) {
    Token *token;
    int ln, cn;

    if (currentChar == EOF)
        return makeToken(TK_EOF, lineNo, colNo);

    switch (charCodes[currentChar]) {
    case CHAR_SPACE:      skipBlank(); return getToken();
    case CHAR_LETTER:     return readIdentKeyword();
    case CHAR_DIGIT:      return readNumber();
    case CHAR_PLUS:
        token = makeToken(SB_PLUS, lineNo, colNo);
        readChar();
        return token;
    case ... // more cases
    }
}
```

# Assignment

---

- Complete following function in `scanner.c`
  - `void skipBlank();`
  - `void skipComment();`
  - `Token* readIdentKeyword(void);`
  - `Token* readNumber(void);`
  - `Token* readConstChar(void);`
  - `Token* getToken(void);`

(1)

- Program  $\Rightarrow$  getToken()  $\Rightarrow$  TokenType: token
  - digit readNumber()
  - letter readIdentKeyword()
  - blank skipBlank()
  - getToken();
  - (   |- . SB\_LSEL
  - |- \* skipComment()
  - |- other SB\_LPAR
  - ' readConstChar()
  - <   |- = SB\_LE
  - |- other SB\_LT

# getToken()

(2)

- Program  $\Rightarrow$  getToken()  $\Rightarrow$  TokenType: token

- >	- =	SB_GE
	- other	SB_GT
- !	- =	SB_NEQ
	- other	error: INVALIDSYMBOL
- .	- )	SB_RPAR
	- other	SB_PERIOD
- :	- =	SB_ASSIGN
	- other	SB_SEMICOLON
- + - * / = , ; )		SB_...
- other		error: INVALIDSYMBOL

# readNumber()

---

- **readNumber()  $\Rightarrow$  TokenType: token**
  - readChar()
    - digit readChar()
    - other TK\_NUMBER
- Use **atoi()** function to convert a string to an integer.

# readIdentKeyword()

---

- **readIdentKeyword()  $\Rightarrow$  TokenType: token**
  - readChar()
    - digit, letter                      readChar()
      - count ++
    - other
      - count > MAX\_IDENT\_LENT
        - error: IDEN\_TOO\_LONG
      - count  $\leq$  MAX\_IDENT\_LENT
        - $\equiv$  keywords              KW\_...
        - $\neq$  keywords              TK\_IDENT

# skipBlank()

---

- **skipBlank()**
    - |- blank
    - |- other
- readChar()  
return



# skipComment()

---

- **skipComment()**

<i>inside_comment</i>	- *	- )	return
		- other	<i>inside_comment</i>
		- EOF	error: END_OF_COMMENT
	- other		<i>inside_comment</i>
	- EOF		error: END_OF_COMMENT

# readConstChar()

---

- **readConstChar() ⇒ TokenType: token**
  - | - character
    - | - ' TK\_CHAR
    - | - other error: INVALID\_CONST\_CHAR
  - | - EOF error: INVALID\_CONST\_CHAR

```
case CHAR_COLON:
```

```
    ln = lineNo;
```

```
    cn = colNo;
```

---

```
    readChar();
```

```
    if ((currentChar != EOF) &&  
        (charCodes[currentChar] == CHAR_EQ)) {  
        readChar();  
        return makeToken(SB_ASSIGN, ln, cn);  
    } else return makeToken(SB_COLON, ln,  
cn);
```